


Global Groundwater

Australian Bore Consultants Pty. Ltd. Hydrogeological Division
ACN 077 734 153 ABN 66 077 734 153



**PO Box 174
Bassendean
Western Australia
6054**

Lake Disappointment

Hydrogeological Assessment of the Impact of Brine Extraction

for

Reward Minerals Limited

March, 2017

Superintendents

Reward Minerals Limited

PO Box 1104
Nedlands WA 6909

Global Groundwater

P.O. Box 174
Bassendean WA 6054
Tel: + 61 8 9386 4725
Fax: + 61 8 9386 1080

Australian Bore Consultants Pty LtdTrading As: **Global Groundwater**

ACN 077 734 153 ABN 66 077 734 153

PO Box 174 Bassendean, Western Australia 6054

Telephone: 61 8 9386 4725 Facsimile: 61 8 9386 1080 E-mail: office@globalgw.com.au







© 2017 Global Groundwater (Australian Bore Consultants Pty. Ltd. Hydrogeological Division)

No warranty or guarantee, whether expressed or implied, is made with respect to the data findings, observations and conclusions contained in this report.

The entire report was provided in digital form with the original bound copy. Use of the digital file is entirely at the risk of the user and no liability is accepted for damage caused by use of the digital file.

The Client has unlimited access to the information in this report but some of the data is the property of Global Groundwater or is under copyright licence agreement so the report may not be provided to a third party or cited without written permission.

Global Groundwater accepts no liability or responsibility whatsoever for and in the respect of any use or reliance on this report by any third party.

Document Status					
Rev No.	Author	Reviewer	Approved for Issue		
			Name	Signature	Date
Draft	R. Nixon	D. Skidmore	R. Nixon		03/11/2016
2 nd Draft	R. Nixon	B. Kinnell	R. Nixon		21/12/2016
Rev1	R. Nixon	B. Kinnell & L. Chandler	R. Nixon		21/03/2017
Rev2	R. Nixon	B. Kinnell & L. Chandler	R. Nixon		03/04/2017

CONTENTS

1	INTRODUCTION	1
2	SETTING	1
2.1	GEOLOGY	2
	Quaternary and Tertiary.....	2
	Neoproterozoic	4
2.2	CLIMATE	6
2.3	HYDROGRAPHY	6
3	HYDROGEOLOGICAL CONCEPTUALISATION	6
3.1	GENERAL.....	6
3.2	SURFACE WATER	6
3.3	RAINFALL.....	7
3.4	EVAPORATION	7
3.5	GROUNDWATER	7
	Hydrogeology	7
	Hydraulic Parameters	8
	Groundwater Inflow.....	8
3.6	Hydrologic System Overview.....	9
4	BRINE ABSTRACTION	9
4.1	TRENCHES	9
4.2	BORES	10
5	GROUNDWATER MODEL	10
5.1	DESIGN	10
5.2	RESULTS	11
6	CONCLUSIONS	13
6.1	IMPACT MITIGATION.....	13
7	REFERENCES	14

TABLE

Table 1	Geological Time Descriptions (in text)
Table 2	Summary of Hydraulic Parameters (in text)

FIGURES (After References)

Figure 1	Regional Location
Figure 2	Lake Disappointment Bore Locations
Figure 3	Basement Structure - Lake Disappointment
Figure 4	Hydrography - Lake Disappointment
Figure 5	Model Output – 10 years No Recharge

PLATES (After Figures)

Plate 1	Secondary Porosity Gypsiferous Sand (Qhs)
---------------	---

APPENDICES (After Plates)

Appendix A	Drilling Data
Appendix B	Detailed Log LDD1507
Appendix C	Monthly Monitoring of Lake Waterlevels
Appendix D	Test pumping Data
Appendix E	Model Design and Calibration

ENCLOSURES (After Appendices – pocket in rear cover or the bound report)

Enclosure 1	Lake Disappointment Sections Upper Lake Bed Sequence (A1 Plan)
-------------------	--

1 INTRODUCTION

Reward Minerals (RWD) plan to extract in the order of 2000 L/s (63 GL per year) of potash brine from Lake Disappointment located in the Sandy Desert east of Newman (Figure 1). Brine extraction is planned predominantly using trenches, with supplementation from bores. This report presents the hydrogeological conceptualisation of the lake and the parameters of a numerical model generated to assess potential impacts of brine extraction on the surrounding environment.

In 2007 Global Groundwater undertook an exploration drilling program on the Lake using a “Geoprobe” rig with shallow depth capability and presented the results of test trenches and core drilling (Nixon, 2007). That report presented a hydraulic conceptualisation and parameters to inform the resource assessment. Since 2007 RWD have expanded their exploration so that the data set now consists of 16 deep diamond core holes, 22 reverse circulation (RC) bores, several test production bores and 10 test trenches on the lake surface (Figure 2). Recent drilling results and testing data are presented in this report (Appendix A) and have resulted in an improved hydrogeological conceptualisation.

2 SETTING

In keeping with the previous report (Nixon, 2007), definitions for the various forms of evaporite minerals mentioned in this report are according to the Geological Survey of Western Australia (Jones, 1994). Strata presented by Nixon (2007), have also been reinterpreted based on recent drilling including deeper diamond core holes. In particular LDD1507 has been logged in detail and this is presented in Appendix B.

The genesis of the modern geological sequence was described by Heese (2009) who states:

“The topography and extensive palaeo-drainage network of the western half of the (Australian) continent date to the late Mesozoic to Early Cenozoic (Tertiary). It is thought that this relict landscape was the product of advancing aridity through the Neogene leading to loss of effective fluvial transport. Subsequent evolution towards an arid landscape saw the development of saline groundwater windows, playas and aeolian landforms by at least 1 million years ago (Fujioka et al. 2009). Because of this trend to aridity and reduction of sediment supply, most of the dunefields today receive little or no new supplies of sand from fluvial sources but rework old coastal, fluvial and lacustrine sediments from relict shorelines, terrestrial basin deposits, piedmonts and valley floors.

The repeated expansion of arid conditions in glacial stages of the Quaternary glacial cycles has left dunefields extending from the most arid parts of the continent into the semi-arid zone and isolated patches in presently humid areas. Growing geochronological evidence points to dune formation beginning in the mid-Pleistocene and accelerating as the climate has become increasingly arid in subsequent glacial cycles.

As geological times presented in this document are from differing sources they are summarised and correlated in Table 1.

Table 1 Geological Time Descriptions.

Era	Period		Epoch	Commenced years ago
Cenozoic	Neogene	Quaternary	Holocene	8000
			Pleistocene	1.8 million
		Palaeogene	Tertiary	Pliocene
	Miocene			23.8 million
	Oligocene			33.7 million
	Eocene			55.5 million
			Paleocene	65 million
Mesozoic	Cretaceous		Upper	100.5 million
			Lower	145 million
Geological periods not presented due to no identified strata				
Neo Proterozoic				1,000 million (up to 541 million)

2.1 GEOLOGY

The Gunanya 1:100,000 Geological Series Sheet (Bagas, 1998), the Blanche-Cronin 1:100,000 Geological Series Sheet (Bagas, 1999) and the Gunanya 1:250,000 Geological Series Sheet (Williams and Williams, 1980) indicate the following geological units occur in association with Lake Disappointment:

Quaternary and Tertiary

These deposits are comprised of; Lacustrine deposits within the lake; Kopi (flour gypsum) deposits present as stabilised dunes along the western margin the lake; Reworked aeolian deposits, also present along the western side of the lake; Aeolian deposits, present as flat to undulating sandplains and seif (longitudinal) dunes formed extensively adjacent to lake and as

discontinuous “islands” of shallow relief within the extent of Lake Disappointment; and calcrete deposits outside the lake.

For the purposes of this report the most relevant quaternary and tertiary sequences are those within and adjacent to the Lake. These are the Upper Lakebed Sequence, which are truncated by Aeolian Deposits and the underlying Lower Lakebed Sequence. A plan and cross sections of the Upper Lakebed Sequence is presented in Enclosure 1 (A1 map).

Upper Lakebed Sequence (Qh)

The playa lake surface typically comprises a thin crust (usually less than 5 cm in thickness) of evaporite mineral deposits (halite and gypsum). This layer is underlain by an interbedded sequence comprising two distinct forms:

- Reworked gypsiferous sand deposits (Qhs) comprising loose to very loose, orange, brown, green, fine to coarse grained silty to clayey sands and sandy to clayey gravels. The gypsum is present predominantly in seed (gypsarenite) form, the often rounded nature of which is considered indicative of aeolian reworking and accumulation. Crystalline gypsum (selenite) is also present.
- Lacustrine deposits (Qhl) comprising soft to firm, orange, brown, green, low to high plasticity clays to sandy clays, sandy silts and loose clayey sands with variable decomposed organic material content and minor gypsum in both crystalline and seed form as well as localised cellular form.

Interbedded gypsiferous sand materials (Qhs) are evident throughout the lake ranging up to 1.35 m in thickness (Nixon, 2007). The Qhs is truncated or underlain by cohesive lacustrine deposits (Qhl). The upper sequence forms a near continuous horizon of variable thickness across the lake and encompasses the significant development of “heaved earth” throughout the southeast portion of the lake. Together the Qhs and Qhl units are termed Qh or the upper lakebed sequence.

Aeolian Deposits (Qpe)

Both fringing and underlying the upper lakebed sequence locally throughout the extent of Lake Disappointment is a series of discontinuous aeolian deposits (Qpe) comprising orange, brown, fine to medium grained silty to clayey sands composed primarily of quartz with variable crystalline gypsum. These are described by Heese (2009) as dunes forming after the mid-Pleistocene Epoch and predate the Qhs units.

Lower Lakebed Sequence (Q/Tpl)

The upper lakebed sequence (Qhs) and aeolian deposits (Qpe) are underlain by an older more consolidated alluvial/lacustrine sequence (Q/Tpl) consisting of orange, red, brown, firm to stiff, medium to high plasticity sandy clays and clays with minor lenses and thin horizons of clayey to silty sands. This unit was named (Qpl) by Nixon (2007), but correlation with core from LDD1507 indicates that these sequences may be Tertiary in age and/or include weathered basement, which typically contains pale green clays. Gypsum, present in crystalline form and as localised cellular aggregates is present within Q/Tpl units. The interpreted base of the lower lake bed sequence is between 8 and 36 m bgl based on the diamond drilling carried out in 2015 (Appendix A).

Calcrete (Czk)

Extensive tracts of calcrete comprising massive, nodular and cavernous sandy limestone of Tertiary age are mapped by the Geological Survey (Williams and Williams, 1980) adjacent to Lake Disappointment where they formed as palaeo-drainage valley infill deposits. Secondary silicification of these deposits locally results in incomplete replacement by a vuggy, opaline silica caprock. Quaternary aeolian deposits often overlie the calcrete deposits. Calcrete deposits have not been identified within the lake.

Neoproterozoic

The superficial sequence is unconformably underlain by the Neoproterozoic Tarcunyah Group (Officer Basin), which comprises an interbedded sequence of sandstone, siltstone and shale deposited around 800 Ma. The upper Tarcunyah group consists of an unassigned sequence of sandstone (PUss), interbedded with siltstone and shales (PUs), which are collectively "PUsx". These are underlain by Gununya Sandstone (PUu), which outcrops 15 km north of the lake where the upper units have been eroded.

Bedrock Sequence - Weathered Bedrock (PUw)


Weathered bedrock occurs on the top of the bedrock sequence nominally between approximately 10 and 110 mbgl based on LDD1507. Weathering within the sandstone units can form unconsolidated sandy deposits, which are interpreted to be both structurally and stratigraphically controlled. These unconsolidated sands have relatively high porosity and are interpreted to be prevalent where folding locates the sandstone units within the weathering zone. The sandstone units occur from approximately 60 to 90 mbgl in LDD1507. It is believed that where folding results in these being deeper they will be consolidated, with lower porosity as evidenced where they outcrop adjacent to the lake.

Bedrock Sequence (PUsx) – Unassigned Units

Unassigned consolidated bedrock units outcrop immediately to the east and the south west of Lake Disappointment. The depth to consolidated bedrock is variable beneath the lake and recent drilling has penetrated these materials to depths of 156 mbgl.

The basal part of this sequence comprises massive medium to coarse grained, cross-bedded sandstone with local beds of quartz pebble conglomerate. The sandstone commonly contains clay and is interbedded with minor amounts of granular conglomerate containing intraformational mudstone clasts. The sequence fines upward through a 100 m interval to interbedded flaggy siltstone, shale and minor amounts of thin fine grained micaceous sandstone.

Sandstone units within the unassigned PU_{sx} are termed PU_{ss} and shale and siltstone PUs in the Gunanya 1:100 000 Geology sheet GSWA and Figure 3.



Units of the Tarcunyah Group after Gunanya 1:100 000 Geology sheet GSWA (Bagas, 1998)

Regional Structure

The major structural alignments are a number of west-northwesterly trending open folds formed throughout the Tarcunyah Group during the Paterson Orogeny (550 Ma). Mapped structure is presented over regional aeromagnetic data (GSWA, 2016) in Figure 3 to highlight potential basement structure beneath the lake. Folding results in interwoven west-northwesterly elongated and dipping sandstone PU_{ss} and siltstone PUs occurring beneath the lower lakebed sequence. The interwoven nature of sandstones and siltstones is evident on outcropping bedrock adjacent to the lake (Bagas, 1998 and Williams & Williams, 1980). It is interpreted that weathering within the sandstone units results in dipping unconsolidated and porous sandy sequences being connected to modern lake sediments (Q/Tpl) then plunging beneath weathered clayey strata derived from weathered siltstone and shale.

2.2 CLIMATE

The area is arid. Average annual rainfall is approximately 200 mm (Nixon, 2007 and Beard, 2005), with a recent estimate by Knight Piésold (2016) indicating 367 mm. Annual evaporation is in excess of 4000 mm. Most rainfall is from isolated local thunderstorms associated with low pressure systems as well as the passage of tropical cyclones and depressions or from the extension of the late summer-autumn rainfall regime of the Murchison region to the south. Prevailing winds are from the east and southeast.

2.3 HYDROGRAPHY

Lake Disappointment is part of a paleo-drainage system consisting of lakes and creeks, within the Sandy Desert Basin Surface Water Allocation Area (SWAA), which drains north to the coastline between the Pardoo and Shamrock Pastoral leases. The catchment of Lake Disappointment was mapped by Beard (2005) and this area was used by Knight Piésold (2016) for flood monitoring. Figure 4 presents the SWAA and the lake's catchment.

This interpretation is consistent with water flow direction arrows detailed on a map presented by Geoscience Australia (2011).

3 HYDROGEOLOGICAL CONCEPTUALISATION

3.1 GENERAL

Water enters the lake sediments from: surface water runoff, rainfall and groundwater discharge. Water is lost from the lake by evaporation. To provide context to the numerical groundwater model, the hydrologic system is also approximated below using first principles.

3.2 SURFACE WATER

Surface water is calculated to be intermittently the largest input to the lake and this is supported by the form of the lake, which displays large deltas in association with the creeks. Knight Piésold (2016) estimated that after Cyclone Rusty 271 644 407 m³ (271 GL) entered the lake by streamflow after approximately 256 mm of rainfall, which equates to approximately 2.1% runoff from the 50 654 km² catchment. Knight Piésold indicate that lower intensity rainfall produces less runoff and a 5% ARI event generates a peak flow of 13 GL over 30 hrs. Surface water inputs to the lake are highly variable.

3.3 RAINFALL

In addition to surface water runoff there is direct input from rainfall. The lake is approximately 40 km north to south and 30 km east to west with a calculated area of approximately 1178 km² based on Geoscience Australia 1:250 000 topographic data. As indicated above annual rainfall estimates range between 200 and 367 mm and are also highly variable and localised. A weather station has been ordered to collect site specific data. Direct inputs from 200 mm of rainfall are 236 GL annually. Recharge from rainfall to the salty surface is unknown, but likely very high due to the osmotic effect and as observed during field programs. The osmotic effect is the tendency of water to pass through a semipermeable membrane (the lake surface) into a solution where the concentration is higher, thus equalizing the concentrations (i.e. the salty sediments take up rainwater across an osmotic gradient).

3.4 EVAPORATION

Pan evaporation in the area is twenty times greater than rainfall at potentially 4712 GL and this is the mechanism for brine concentration. Recent monthly monitoring data (Appendix C) show that the groundwater levels across the lake are shallow (less than 0.5 mbl). During dry periods the levels remain relatively steady but following a rainfall event can respond quickly and rise 0.2 to 0.3m (Appendix C). The stability of the groundwater levels indicates that the depth to which evaporation can remove water from the lake is relatively shallow and likely extinguished at less than 1 mbl.

3.5 GROUNDWATER

Hydrogeology

The sediments have been divided into the following Hydrostratigraphic units:

- Upper lake bed unit – Groundwater in Qh. The unit is frequently highly permeable with permeability dominated by secondary interconnected porosity of thin gypsum beds.
- Aeolian sand unit - Groundwater in Qpe. An aquifer, when saturated, groundwater is held within primary porosity. Occurs as isolated sections within the upper lake bed sequence and surrounding the lake.
- Lower lake bed unit – Groundwater in the Q/Tpl. – Mostly low permeability clay with rare thin disconnected zones of gypsum with development of secondary porosity.
- Weathered basement rock unit – Groundwater in the PUw. Mostly clays and silts with some permeable sand sections where structure aligns sandstone units, within the weathering profile.

- Basement rock unit – Groundwater in the PUsx. Generally low permeability and regarded as the aquifer base.

Hydraulic Parameters

Hydraulic parameters from previous reports and recent testing are presented in Table 2. RWD have undertaken trench testing at 10 locations, with the longest being for 11.34 days in T11, which is used to calibrate the model (Appendix D) data presented in this report. Importantly there is a large range and discrepancy between hydraulic conductivity in the upper lake bed (Qh) derived from laboratory analysis compared to test pumping. It is evident from trench testing that groundwater flow in the upper bed sequence is dominated by secondary porosity (Plate 1). Laboratory analysis methods have likely provided data on the primary porosity component of the strata, which is significantly lower based on primary particle size.

Table 2 Summary of Hydraulic Parameters

Unit	Depths (m)		Storage		Conductivity (K)	Model Zone (zone colour)
	From	To	Sy	ss	(m/d)	
Aeolian sand (Qpe)	+10	2	15		[!] 1 to 5 (2)	1
Upper lake bed (Qh)	0	2	15		*0.11, \$10 to 360, (250)	2
Lower lake bed (Q/Tpl)	2	10	13	1.3×10^{-16}	*0.06 (0.06)	3
Sandy weathered basement (PUw after PUss)	10	90	12	1.3×10^{-16}	*0.02 to %2 (2)	4
Other weathered basement (PUw after PUs)	90	150	1	1.3×10^{-16}	*0.005 (0.005)	5
Basement rock (PUsx)	240	180	1	1.3×10^{-16}	[!] 0.001 to 1 (0.005)	5

Notes

- * Estimated from laboratory analysis of core (Skidmore, 2017)
- [!] Estimated from text book (Kruseman, & de Ridder, 1991) values of similar strata.
- \$ Estimated from Trench Testing (Xin Du & Lawrence, 2016)
- % Estimated from test pumping LDBH1603 (Skidmore, 2017)
- () Used in model

Model vertical hydraulic conductivities (K_z) are 10% of horizontal (K_x & K_y).

Groundwater Inflow

The Darcy equation ($Q=KiA$) can be used to estimate groundwater inflow (Q):.

- Based on a saturated sequence that is 150 m thick and a lakebed perimeter of 140 km, the cross sectional area (A) available for groundwater through-flow into the lake is 21 000 000 m².
- Groundwater levels form a subdued reflection of the ground surface contours, which nominally fall 20 m over 5 km towards the lake giving a hydraulic gradient (i) of around 0.004.
- Hydraulic conductivities (K) of the strata are variable (Table 2), but using the average of 0.57 m/day (adjusted for thickness and based on sandy weathered basement being 50% of the weathered basement sequence).

Using these parameters calculated inflow to the lake from groundwater (Q) is 17.5 GL/yr.

3.6 HYDROLOGIC SYSTEM OVERVIEW

This first principal hydrogeological conceptualisation indicates that recharge into the lake sequence is dominated by direct rainfall and surface water runoff rather than groundwater inflow. This recharge is then offset by the evaporation which concentrates the salts. The relationship between recharge and evaporation is one that exists in a form of equilibrium as evidenced by the consistent water levels below the surface (Appendix C).

4 BRINE ABSTRACTION

4.1 TRENCHES

Testing has been undertaken to derive bulk inflow and to measure the area of significant groundwater drawdown surrounding trenches. During brine abstraction testing for up to 11.3 days the area of significant (10 cm) groundwater drawdown laterally from a 2 m deep trench is limited to around 100 m. Hydraulic parameters calculated during these tests and calibrated to the early time outputs of the model have been used to simulate long term drawdown following brine extraction from the trenches.

Based on trench inflow testing and the requirement to access significant groundwater storage, it is likely the project will require in the order of 300 km of trenches up to 3 m deep. Similar calculations on trench inflow have been undertaken by Agrimin based on Lake Mackay, which is 600 km east of Lake Disappointment near the Northern Territory border. Agrimin in their ASX Release dated 6th April 2016 stated an abstraction of “2,150 litres per second (L/s) based on a 250 km trench design with an average 5.5m depth”.

4.2 BORES

Bores are being considered but they will likely contribute the smaller portion of 2000 L/s of brine extraction. There is currently little data on potential bore yields or aquifer hydraulic parameters at depth. However, average bore yields of less than 10 L/s are expected and on this basis the 2000 L/s brine requirement would require more than 200 bores. However a bore on the northern boundary of the Lake (LDRC1463) has reputed airlift yield of 25 L/s.

Test pumping of bore LDBH 1603 located on the Lake (Figure 2) shows a typically confined response after 17 hours of pumping at 3 L/s (Appendix D). The flow during the test was restricted by pump size, but test pumping analysis indicates that this bore could likely sustain around 10 L/s. This bore has similar strata to LDD 1414 (Appendix A) and the confined response correlates with a sandy aquifer beneath a clayey weathering profile, which forms a barrier to downward movement of groundwater and so is consistent with its geology. Therefore, where brine extraction occurs from bores within confined aquifers the impact on shallow groundwater will be absent. Additional testing and monitoring is required to confirm that this confined response continues during long term pumping.

It is interpreted that where a bores intersect a weathered sandstone sequence, comprising unconsolidated sand, there is the potential for a significant aquifer at depths of up to 100 mbgl. These aquifers are confined by overlying weathered clays with likely connection with the low permeability lower lakebed sequence up dip. A detailed log of LDDH 1507 is presented in Appendix B and describes this weathered bedrock sequence.

5 GROUNDWATER MODEL

5.1 DESIGN

The numerical groundwater model was generated in Visual Modflex 4.0 (2016). The extent of the model encompasses an area extending at least 20 km from the edge of the lake. The model extent is 450,000 to 510,000 mE (GDA94 zone 51), 7375,000 to 7445,000 mN (Figure 2). The boundaries of the model are of variable head with hydraulic conductivities of the adjacent cells. The model layout including boundary conditions and parameter zones are presented in Appendix E including cross sections of the layers. Layer boundaries in Appendix E are presented as relative to the Australian Height Datum (AHD). The lake surface in the model is set at 330 m AHD.

The model is a 4-layer system including:

1. the upper lakebed sequence from 0 to 2 m bgl (330 to 328 m AHD),
2. the lower lakebed sequence from 2 to 10 m bgl, (328 to 320 m AHD)
3. weathered basement from 10 to 90 bgl (320 to 240 m AHD) and
4. basement layer from 90 to 150 m bgl (240 to 180 m AHD).

The top of layer 1 is defined by surface elevations as presented in Figure 4. Within layer 1 the upper lakebed sequence has been broken into two zones; one for the Qh and; another for Qpe, which occurs as islands and surrounds the lake extending to the model boundaries. In layer 2 the lower bed sequence (Q/Tpl) is continuous beneath the lake, with Qpe characteristics extending to the model boundary. Layer 3 uses PUw-Pus characteristics in zones beneath the lake where sandier sequences have been identified in diamond drill holes (Figure 3) and lower permeability PUw-Puss parameters elsewhere. The base layer is continuous across the entire model, using bedrock parameters. Details are provided in Appendix E. Hydraulic parameters for each layer and zone are presented in Table 2.

Initial heads were applied across the model at 0.2 m below the lake bed surface (329.8 m AHD).

Trenches are modelled using the drain function with waterlevel in the trenches set at 1.9 mbgl (328.1 m AHD), which represents the anticipated lowest water level achievable during brine extraction. Pumping in bore LDBH 1603 was modelled at 10 L/s, screened only in Layer 3. The Kz of layer 2 was 0.006 m/day to simulate a semiconfined, rather than a fully confined aquifer to indicate the potential impact of pumping under a leaky aquitard scenario.

The model was run in a transient state for 10 years (3650 days) with no recharge to highlight the maximum potential impact of abstraction. This represents a period of no rain or inflow for 10 years, which is highly unlikely, but serves to simulate that worst case scenario.

5.2 RESULTS

The primary calibration of the model was against test pumping results from trenches, which are restricted to parameters in layer 1. When running calibration scenarios, layers 2, 3 and 4 were held constant retaining the parameters derived from previous work presented in Table 2. Transmission of water between the layers of the model is controlled by the vertical hydraulic conductivity (Kz), which were set at 10% of horizontal K values in Table 2). As a result of the Kz values used there was significant movement between layers so the head impacts are consistent across all layers (Appendix E).

Scenarios were run with hydraulic conductivities (K) in Zone 2 within layer 1 (Qh) of the model set at 5, 100 and 250 m/day. The outcome of these scenarios was then compared with the test pumping analysis from trench PT11, which is the longest test conducted on the lake. Pumping from PT11 was simulated in the model using the well package after generating cell dimensions to match the test trench and also enable sufficient granularity to suit the monitoring bores.

The scenario that used a K of 5 m/day for Qh removed orders of magnitude less brine through the drain package (trenches) than is required by the project. This K value was tested as it approximates the values derived from laboratory testing, which relate to the primary porosity of this sequence. This highlights the influence of secondary porosity, hosted by gypsum layers, on water movement within the upper lakebed sequence into the trenches. Hydraulic conductivities of this order also vary significantly from the hydraulic parameters derived from test pumping of PT11 (Appendix D).

The next scenario was run with a K of 100 m/day, which removed brine from the trenches in the order of the project requirement but did not provide a good calibration with test pumping of PT11 (Appendix E).

Scenarios using a further range of K values were run, with the best calibration against the PT11 analysis being achieved with a K of 250 m/day (Appendix E).

To simulate the greatest potential impact (worst case scenario) the transient simulation was run for 10 years without recharge with all water being sourced from storage within the model. This scenario represents a period of 10 years without significant rain or surface water inflow on, or into the lake, which based on recent observed weather patterns is considered highly unlikely. Impacts after 1 year of extraction without recharge are also presented in Appendix E representing an average year.

The maximum width that groundwater impacts extend from a trench is consistent across the model. After 1 year, drawdown of more than 0.3 m extends around 500 m from the trench. After 10 years this reaches around 1.7 Km (Figure 5). Brine abstracted from the trenches also significantly decreases over the 10 year period as the Qh aquifer thins.

Total drawdown at the end of the 10 year period from the trench design presented by Knight Piesold (2016) is presented in Figure 5, which indicates an impact of less than 0.3 m outside the confines of the lake under the worst case scenario modelled.

6 CONCLUSIONS

The purpose of this model is to assess potential impacts of brine extraction on the water levels within the lake and at the lake margins. The change in lake water levels are dominated by parameters applied to layer 1, which contains the abstraction trenches and the only unsaturated area with potential vegetative growth.

The following conclusions can be drawn from the development of the conceptual and numerical models:

- Although groundwater inflow contributes in the order of 17 GL to the lake annually (25% of the project abstraction), water inputs to the lake are dominated by surface water inflow and rainfall recharge, which on average exceed abstraction by an order of magnitude.
- The waterlevel in the lake is relatively stable with fluctuations in the order of half a metre indicating a quasi-equilibrium between inputs and evaporation at this depth.
- The model simulates an environment with no recharge over a period of 10 years, which is highly unlikely given recent rainfall and as such represents a worst case scenario. This scenario results in a change in water levels (drawdown) at the lake margins of between 10 cm and 30 cm, based on the trench design presented. This impact extends approximately 3.8 km from the nearest trench. Drawdown of between 30 and 70 cm extends approximately 1.7 km from the nearest trench. Restoration of water levels occurs after surface water inflow or significant rainfall, which based on recent weather is annually.
- The distance of drawdown from the trench increases with time between recharge events. Under recent weather conditions the extent of drawdown between rainfall recharge is significantly less and one year after a significant recharge event, drawdown of between 10 cm and 30 cm extends approximately 1 km from the nearest trench.
- Pumping from bores in the weathered basement shows a confined response to pumping indicating poor connection with the upper lake bed sequence. Modelling based on a leaky aquitard show the response to pumping in the upper lakebed sequence after one year is around 50 cm at a radius of 500 m from the bore.

6.1 IMPACT MITIGATION

Model results, which are supported by testing in the trenches, indicate that drawdown increases with time between recharge events, but even after 10 years without rainfall recharge this is restricted to 70 cm at a distance of 1.7 km from the nearest trench. The impact on fringe

vegetation, if any, of brine level changes is unknown, but natural changes in the order of 50 cm have been noted. The level of impact at the lake edge can be regulated by increasing the distance that the trenches are active from the lake edge to meet a prescribed brine level threshold.

Pumping from bores creates a pressure drop in the confined layer. The impact of this pumping will be insignificant on the water levels in the upper lakebed sequence including the fringing dunes (Qpe), subject to this confined response continuing with extended time. To test the impact of the unconfined response ceasing a leaky aquitard was modelled, which indicated minor impacts in the upper lakebed sequence. The impact of pumping from bores on areas outside the lake can be managed by their location and regulating flow rates.

A management plan should be developed for the management of water levels around the lake including the islands with trigger levels based on a negative response from fringing vegetation. Areas on the south eastern side of the lake where there is no modelled impact could be used as controls. The management response could include reduction in bore pumping rates and or placing bunds to shut off abstraction from trenches at prescribed distances from the edge.

Importantly the length and layout of trenches will vary throughout the development and will be subject to seasonal recharge.

7 REFERENCES

ASX release 2016, Insitu resource for Lake Mackay, Agrimin in their ASX Release dated 6th April 2016.

Ruane, M. 2007. Resource Estimate for Lake Disappointment, ASX RELEASE 13/03/2007.

Bagas, L., 1998, Geology of the Gunanya 1:100 000 sheet, Western Australian Geological Survey, 1:100 000 Geological Series Explanatory Notes.

Bagas, L., 1999, Geology of the Blanche-Cronin 1:100 000 sheet (part sheets 3551 and 3552), Western Australian Geological Survey, 1:100 000 Geological Series Explanatory Notes.

- Beard, J. S., 2005, Drainage Evolution in the Lake Disappointment Catchment, Western Australia - a discussion. Journal of the Royal Society of Western Australia, Vol88:57-64.
- Fujioka, T., Chappell, J., Fifield, L.K. & Rhodes, E.J. 2009. Australian desert dune fields initiated with Pliocene-Pleistocene global climatic shift. *Geology*, 37, 5154
- Geoscience Australia., 2011, Exploring for Calcrete-hosted Uranium Deposits in the Paterson Region, Western Australia presented in AusGeolIssue 103 Sept 2011.
- GSWA, 2016, WA State 40m grid merge of Total Magnetic Intensity (TMI) data.
- Heece, P.P. in press 2009. The Australian desert dunefields: formation and evolution in an old, flat, dry continent. In: Bishop, P. & Pillans, B. (eds), Australian landscapes. Special Publication. Geological Society, London.
- Jones, D. C. 1993, Gypsum deposits of Western Australia, Western Australia Geological Survey, Record 1993/5, ISBN 0 7309 4476 X.
- Knight Piésold Pty. Ltd., 2016. PE801-326 Flood Modelling Report for Rewards Minerals.
- Kruseman, G. P. and de Ridder, N. A., 1991, Analysis and evaluation of pumping test data: physical properties pp.19 – 25, International Institute For Land Reclamation and Improvement, Publication 47, Wageningen, The Netherlands, ISBN 90 70754 207.
- Nixon, R., 2007, Lake Disappointment, Bore Completion and Test Pumping, Report for Reward Minerals Limited. Global Groundwater Reference: \\Jobs\239gRewards\LakeDisappointmentReport.pdf.
- Skidmore, D., 2017, Lake Disappointment, Extractable Resource Estimation for Reward Minerals Limited. Reference: \\Jobs\1225g\\SpecificYieldReport.pdf.
- Williams, I. R. and Williams, S. J., 1980, Gunanya, W.A., Western Australian Geological Survey, 1:250 000 Geological Series Explanatory Notes.
- Xin Du, L. & Lawrence, R., 2016, Brief Summary of Updated Trench Pumping. Reference PES14017. Unpublished report for Dan Tenardi of Reward Minerals, June 2016.




Figure 1. Regional Location




Figure 3. Basement Structure - Lake Disappointment





Figure 4. Hydrography - Lake Disappointment



Legend

- Roads/Tracks (Geoscience Aust.)
- Bores (LDRC / LDD or LDBH)
- Surface drainage (river/creek/lake)
- Trench

Impact (waterlevel change)

- 0.1 to 0.3m drawdown (329.7 to 329.5mAHD)
- 0.3 to 0.7m drawdown (329.5 to 329.1mAHD)
- 0.7 to 1.1m drawdown (329.1 to 328.7mAHD)
- 1.1 to 1.7m drawdown (328.7 to 328.1 mAHD)

* initial head 329.8mAHD
base of drain 328.1mAHD



Figure 5. Model Output - 10 years No Recharge



Plate 1 Secondary Porosity Gypsiferous Sand (Qhs)

Appendix A

Drilling Data

GP & AGP

Hole ID	Drilling Method	Easting, Zone 51	Northing	RL (mAHD)	Stickup (m)	Drilled Depth (as per logs) (m)	Diameter (mm)	Casing Diameter (mm)	Casing Type	Blank Casing (m)		Slotted Casing (m)	
										Top	Bottom	Top	Bottom (+ end cap)
GP01	Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)	491135	7406417	329.9	0.30	4.00	55	20	Class 12 uPCV	-0.30	1.37	1.37	2.26
GP02	Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)	483694	7406478	329.6	0.49	5.00	55	20	Class 12 uPCV	-0.49	0.05	0.05	1.00
GP03	Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)	479431	7406620	330.7	0.43	2.85	55	20	Class 12 uPCV	-0.43	1.06	1.06	2.03
GP04	Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)	474148	7406413	330.2	0.42	3.94	55	20	Class 12 uPCV	-0.42	0.94	0.94	1.90
GP05	Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)	469186	7406505	329.7	0.36	6.00	55	20	Class 12 uPCV	-0.36	1.00	1.00	1.98
GP06	Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)	464236	7406358	330.6	0.34	4.23	55	20	Class 12 uPCV	-0.34	1.03	1.03	2.02
GP07	Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)	470683	7389823	329.3	0.34	6.00	55	20	Class 12 uPCV	-0.34	1.23	1.23	2.04
GP08	Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)	474264	7390056	330.6	0.35	2.70	55	20	Class 12 uPCV	-0.35	1.04	1.04	2.05
GP09	Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)	479448	7389909	330.6	1.03	2.70	55	20	Class 12 uPCV	-1.03	0.36	0.36	1.34
GP10	Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)	484638	7389332	330.1	0.30	3.40	55	20	Class 12 uPCV	-0.30	1.19	1.19	2.10

GP & AGP

Hole ID	Drilling Method	Easting, Zone 51	Northing	RL (mAHD)	Stickup (m)	Drilled Depth (as per logs) (m)	Diameter (mm)	Casing Diameter (mm)	Casing Type	Blank Casing (m)		Slotted Casing (m)	
										Top	Bottom	Top	Bottom (+ end cap)
GP11	Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)	489688	7389786	329.7	0.32	5.00	55	20	Class 12 uPCV	-0.32	0.91	0.91	1.92
GP12	Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)	474130	7423068	331	0.35	3.90	55	20	Class 12 uPCV	-0.35	1.01	1.01	2.00
GP13	Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)	479090	7423105	330.6	0.19	3.90	55	20	Class 12 uPCV	-0.19	1.18	1.18	2.18
GP14	Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)	474262	7417632	330.8	0.79	3.70	55	20	Class 12 uPCV	-0.79	0.54	0.54	1.53
GP15	Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)	476126	7419559	330.6	0.47	3.45	55	20	Class 12 uPCV	-0.47	0.88	0.88	2.17
GP16	Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)	482461	7417678	330.7	0.51	3.10	55	20	Class 12 uPCV	-0.51	0.88	0.88	2.16
GP17	Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)	489639	7417766	329.8	0.36	5.77	55	20	Class 12 uPCV	-0.36	0.96	0.96	2.26
GP18	Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)	484680	7412110	327.3	0.35	10.00	55	20	Class 12 uPCV	-0.35	0.89	0.89	2.12
GP19	Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)	479474	7412101	330.7	0.47	1.87	55	20	Class 12 uPCV	-0.47	0.82	0.82	1.80
GP20	Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)	468945	7412193	331.6	2.74	0.59	55	20	Class 12 uPCV	-0.59	0.82	0.82	1.91
GP21	Push Tube (hand auger)	474178	7412117	331.45	0.80	0.24	42	20	Class 12 uPCV	-0.74	-0.24	-0.24	0.61

Hole ID	Drilling Method	Easting, Zone 51	Northing	RL (mAHD)	Stickup (m)	Drilled Depth (as per logs) (m)	Diameter (mm)	Casing Diameter (mm)	Casing Type	Blank Casing (m)		Slotted Casing (m)	
										Top	Bottom	Top	Bottom (+ end cap)
GP22	Push Tube (hand auger)	479361	7401012	330.15	0.60	0.95	42	20	Class 12 uPCV	-0.60	0.00	0.00	0.92
GP23	Push Tube (hand auger)	474211	7401111	331.3	0.55	0.92	42	20	Class 12 uPCV	-0.55	-0.03	-0.03	0.90
GP24	Push Tube (hand auger)	469161	7401120	329.3	0.51	0.95	42	20	Class 12 uPCV	-0.51	0.05	0.05	0.97
GP25	Push Tube (hand auger)	464043	7400929	331.45	0.49	0.95	42	20	Class 12 uPCV	-0.49	0.06	0.06	1.01
GP26	Push Tube (hand auger)	470142	7395465	329.1	0.78	0.72	42	20	Class 12 uPCV	-0.78	-0.24	-0.24	0.68
GP27	Push Tube (hand auger)	474278	7395531	329.6	0.66	0.83	42	20	Class 12 uPCV	-0.66	-0.16	-0.16	0.75
GP28	Push Tube (hand auger)	479420	7395491	330.4	0.60	0.81	42	20	Class 12 uPCV	-0.60	-0.07	-0.07	0.83
GP29	Push Tube (hand auger)	474464	7385866	331.6	1.04	0.47	42	20	Class 12 uPCV	-1.04	-0.41	-0.41	0.52
GP30	Push Tube (hand auger)	479382	7384180	331.2	1.05	0.50	42	20	Class 12 uPCV	-1.05	-0.40	-0.40	0.52
AGP31		491627	7395377	331.5		1.00							
AGP32		494090	7389548	331.5		1.00							
AGP33		493589	7400909	331.5		1.00							
AGP34		486167	7423125	331.5		1.00							
AGP35		487505	7423125	331.5		1.00							
AGP36		491056	7423125	331.5		1.00							

Notes

	Artesian (18/12/2006)
	Groundwater at ground surface (18/12/2006)

This log version is a summary log; please refer to (Global Groundwater, 2007) bore logs for greater detail.

Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K2SO4) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007).

Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

Hole ID	Aperture (mm)	Gravel Pack Size (mm)	Well Development	Geology data available?	Status	Type	Purpose	Access	Comments
GP01	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP02	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP03	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP04	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP05	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP06	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP07	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP08	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP09	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP10	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods

Hole ID	Aperture (mm)	Gravel Pack Size (mm)	Well Development	Geology data available?	Status	Type	Purpose	Access	Comments
GP11	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP12	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP13	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP14	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP15	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP16	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP17	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP18	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP19	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP20	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP21	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods

Hole ID	Aperture (mm)	Gravel Pack Size (mm)	Well Development	Geology data available?	Status	Type	Purpose	Access	Comments
GP22	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP23	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP24	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP25	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP26	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP27	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP28	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP29	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
GP30	0.5	Backfill of hole through partial collapse of bore	None	Y		Monitoring Bore	Exploration/research	Helicopter	Drilling was conducted to refusal or to the limit of rods
AGP31			None	N		Monitoring Bore	Exploration/research		All data sourced from CoxsRocks Pty Ltd 2008 report
AGP32			None	N		Monitoring Bore	Exploration/research		All data sourced from CoxsRocks Pty Ltd 2008 report
AGP33			None	N		Monitoring Bore	Exploration/research		All data sourced from CoxsRocks Pty Ltd 2008 report
AGP34			None	N		Monitoring Bore	Exploration/research		All data sourced from CoxsRocks Pty Ltd 2008 report
AGP35			None	N		Monitoring Bore	Exploration/research		All data sourced from CoxsRocks Pty Ltd 2008 report
AGP36			None	N		Monitoring Bore	Exploration/research		All data sourced from CoxsRocks Pty Ltd 2008 report

Notes

Reward Minerals Ltd - Composite Log

Bore ID:
GP01


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73339

DATE COMMENCED: 12-Dec-2006
DATE COMPLETED: 12-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: EarthTEC Drilling
Tag ID: Not tagged.

Drilling Method: Driven Core
Bore Diameter: 55 mm

Northing: 7406417.000 m
Easting: 491135.000 m

Surface RL: 329.900 m
Scheme: GDA94 (Z51)



BORE NAME: GP01

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73339
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.367 m at 18-Dec-2006

LOCATION

North: 7406417.000 m
East: 491135.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 329.900 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006).

DRILLING DETAILS

Commenced: 12-Dec-2006
Completed: 12-Dec-2006
Drilled Depth: 4.0
Drilling Company: EarthTEC Drilling
Drilling Rig: Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 4.0	Driven core (55 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.300) - 1.370	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
1.370 - 2.260	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 2.3	Annulus fill, ID-OD: 20 mm to 55 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
2.3 - 4.0	Void fill, OD: 55 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.7	Sand with Silt and Clay	Upper Lake Bed Sequence
0.7 - 1.0	Clay with Sand	Upper Lake Bed Sequence
1.0 - 2.5	Clay with Sand	Lower Lake Bed Sequence
2.5 - 3.0	Clay	Lower Lake Bed Sequence
3.0 - 3.3	Clay with Sand	Lower Lake Bed Sequence
3.3 - 4.0	Clay	Lower Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 0.7 **Sand (with Silt and Clay)**: Orange-brown, fine sand - coarse sand, gypsum, subangular to rounded seed gypsum, trace clay.
- 0.7 - 1.0 **Clay (with Sand)**: Red-brown, gypsum-quartz, high plasticity clay, fine to medium grained seed gypsum sand, trace quartz sand.
- 1.0 - 2.5 **Clay (with Sand)**: Orange-brown, fine sand - medium sand, rounded, quartz-gypsum, medium-high plasticity, angular-subangular crystalline gypsum. **Sand**: Trace, dark green. **Sand**: Trace, black, heavy mineral sand from 2 m. **Clay (with Sand)**: Variable hard/soft layers approx. 100 mm thick from 2 m.
- 2.5 - 3.0 **Clay**: Orange-brown, quartz, high plasticity, with fine grained rounded quartz sand. **Sand**: Trace, black, heavy mineral sand.
- 3.0 - 3.3 **Clay (with Sand)**: Orange-brown, fine sand - medium sand, quartz, high plasticity.

Depth (m bgl)

3.3 - 4.0 **Clay:** Orange-brown, high plasticity, with green and black subrounded heavy mineral sand.

Reward Minerals Ltd - Composite Log

Bore ID:

GP02


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73340

DATE COMMENCED: 12-Dec-2006
DATE COMPLETED: 12-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: EarthTEC Drilling
Tag ID: Not tagged.

Drilling Method: Driven Core
Bore Diameter: 55 mm

Northing: 7406478.000 m
Easting: 483694.000 m

Surface RL: 329.600 m
Scheme: GDA94 (Z51)



BORE NAME: GP02

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73340
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.276 m at 18-Dec-2006

LOCATION

North: 7406478.000 m
East: 483694.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 329.600 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 12-Dec-2006
Completed: 12-Dec-2006
Drilled Depth: 5.0
Drilling Company: EarthTEC Drilling
Drilling Rig: Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 5.0	Driven core (55 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.490) - 0.050	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
0.050 - 1.020	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm, joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 1.0	Annulus fill, ID-OD: 20 mm to 55 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
0.0 - 5.0	Void fill, OD: 55 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 1.2	Sand with Silt	Upper Lake Bed Sequence
1.2 - 1.5	Silt with Sand	Upper Lake Bed Sequence
1.5 - 2.0	Clay with Sand	Upper Lake Bed Sequence
2.0 - 2.2	Sand with Silt and Clay	Lower Lake Bed Sequence
2.2 - 3.0	Clay with Sand	Lower Lake Bed Sequence
3.0 - 3.2	Sand with Clay	Lower Lake Bed Sequence
3.2 - 4.0	Clay	Lower Lake Bed Sequence
4.0 - 4.3	Clay with Sand	Lower Lake Bed Sequence
4.3 - 4.4	Sand with Clay	Lower Lake Bed Sequence
4.4 - 4.7	Clay with Sand	Lower Lake Bed Sequence
4.7 - 5.0	Clay	Lower Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 1.2 **Sand (with Silt):** Dominant, dark orange-brown, gypsum, fine to coarse grained seed gypsum sand, fine to medium from 1.0 m. **Sand:** Trace, black, fine sand, trace black, heavy mineral sand. **Sand (with Silt):** Gypsum, hard crust on surface with halite in depressions, 8 cm gypsum crystals.
- 1.2 - 1.5 **Silt (with Sand):** Orange-brown, gypsum, medium to high plasticity, fine to medium grained seed gypsum sand.

Depth (m bgl)

- 1.5 - 2.0 **Clay (with Sand)**: Dominant, pale orange-brown, fine sand - medium sand, sub-rounded to rounded, quartz-gypsum, high plasticity, crystalline gypsum sand. **Sand**: Trace, black-red, fine sand - medium sand, heavy mineral sand.
- 2.0 - 2.1 **Sand (with Silt)**: Fine sand - coarse sand, gypsum, sand is in reference to gypsum.
- 2.1 - 2.2 **Sand (with Clay)**: Orange-brown, fine sand.
- 2.2 - 3.0 **Clay (with Sand)**: Orange-brown, fine sand - medium sand, quartz-gypsum, high plasticity, also some pale orange, crystalline gypsum sand. **Gypsum (with Clay and Silt)**: Crystalline gypsum sand lenses.
- 3.0 - 3.2 **Sand (with Clay)**: Gypsum, fine to coarse grained gypsum.
- 3.2 - 4.0 **Clay**: Orange-brown, fine sand - medium sand, sub-rounded to rounded, quartz, high plasticity, trace fine grained heavy mineral sand.
- 4.0 - 4.3 **Clay (with Sand)**: Orange-brown, fine sand - medium sand, quartz-gypsum, medium to high plasticity, crystalline gypsum sand .
- 4.3 - 4.4 **Sand (with Clay)**: Fine sand - coarse sand, gypsum.
- 4.4 - 4.7 **Clay (with Sand)**: Pale orange-brown, medium to high plasticity.
- 4.7 - 5.0 **Clay**: Orange-brown, fine sand - medium sand, quartz, high plasticity, trace heavy mineral sand.

Reward Minerals Ltd - Composite Log

Bore ID:

GP03


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73341

DATE COMMENCED: 12-Dec-2006
DATE COMPLETED: 12-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: EarthTEC Drilling
Tag ID: Not tagged.

Drilling Method: Driven Core
Bore Diameter: 55 mm

Northing: 7406620.000 m
Easting: 479431.000 m

Surface RL: 330.700 m
Scheme: GDA94 (Z51)



BORE NAME: GP03

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73341
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.111 m at 18-Dec-2006

LOCATION

North: 7406620.000 m
East: 479431.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 330.700 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 12-Dec-2006
Completed: 12-Dec-2006
Drilled Depth: 2.8
Drilling Company: EarthTEC Drilling
Drilling Rig: Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 2.9	Driven core (55 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.430) - 1.055	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
1.055 - 2.025	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 2.0	Annulus fill, ID-OD: 20 mm to 55 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
2.0 - 2.9	Void fill, OD: 55 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.3	Sand with Silt	Upper Lake Bed Sequence
0.3 - 0.4	Clay with Sand	Upper Lake Bed Sequence
0.4 - 1.0	Sand with Clay	Upper Lake Bed Sequence
1.0 - 1.1	Clay	Lower Lake Bed Sequence
1.1 - 1.5	Clay with Sand	Lower Lake Bed Sequence
1.5 - 2.3	Clay with Sand	Lower Lake Bed Sequence
2.3 - 2.4	Sand with Silt	Lower Lake Bed Sequence
2.4 - 2.9	Clay with Sand	Lower Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 0.3 **Sand (with Silt):** Green-brown, gypsum, fine to course grained seed gypsum. Gypsum crystals to 12 mm, to 1.1 m .
- 0.3 - 0.4 **Clay (with Sand):** Green-brown, high plasticity.
- 0.4 - 1.0 **Sand (with Clay):** Orange-brown, fine sand - medium sand, sub-angular to sub-rounded, quartz-gypsum, rounded to subangular seed gypsum.
- 1.0 - 1.1 **Clay:** Orange-brown, high plasticity, with sand.
- 1.1 - 1.5 **Clay (with Sand):** Orange-brown, fine sand - medium sand, sub-rounded to rounded, quartz-gypsum-carbonate, medium-high plasticity, also pale orange, crystalline gypsum, trace carbonate.

Depth (m bgl)

- 1.5 - 1.7 **Clay**: Orange-brown, fine sand - medium sand, sub-angular to sub-rounded, quartz, high plasticity.
- 1.7 - 2.0 **Clay (with Sand)**: Orange-brown, medium to high plasticity.
- 2.0 - 2.3 **Clay**: Orange-brown, fine sand, sub-rounded to sub-angular, quartz-gypsum, high plasticity, trace crystalline gypsum.
- 2.3 - 2.4 **Sand (with Silt)**: Pale orange, gypsum, fine - course grained gypsum.
- 2.4 - 2.9 **Clay (with Sand)**: Orange-brown, gypsum, medium to high plasticity. **Clay (with Sand)**: Gypsum, fine-course grained crystalline gypsum, localised cellular gypsum aggregations.

Reward Minerals Ltd - Composite Log

Bore ID:
GP04


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73342

DATE COMMENCED: 13-Dec-2006
DATE COMPLETED: 13-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: EarthTEC Drilling
Tag ID: Not tagged.

Drilling Method: Driven Core
Bore Diameter: 55 mm

Northing: 7406413.000 m
Easting: 474148.000 m

Surface RL: 330.200 m
Scheme: GDA94 (Z51)



BORE NAME: GP04

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73342
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: -0.017 m at 18-Dec-2006

LOCATION

North: 7406413.000 m
East: 474148.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 330.200 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 13-Dec-2006
Completed: 13-Dec-2006
Drilled Depth: 3.9
Drilling Company: EarthTEC Drilling
Drilling Rig: Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 3.9	Driven core (55 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.420) - 0.940	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
0.940 - 1.915	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 1.9	Annulus fill, ID-OD: 20 mm to 55 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
1.9 - 3.9	Void fill, OD: 55 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.1	Sand with Silt	Upper Lake Bed Sequence
0.1 - 1.0	Sand with Clay	Upper Lake Bed Sequence
1.0 - 2.0	Clay with Sand	Lower Lake Bed Sequence
2.0 - 3.9	Clay	Lower Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 0.1 **Sand (with Silt)**: Pale green, gypsum, fine to coarse grained gypsum. Thin halite crust with organic material to 0.02m.
- 0.1 - 0.3 **Sand (with Clay)**: Green-brown, fine sand - medium sand, quartz-gypsum.
- 0.3 - 1.0 **Sand (with Clay)**: Dominant, orange-brown, fine sand - medium sand, sub-rounded to rounded, quartz-gypsum, with fine-coarse grained crystalline gypsum and fine-medium grained seed gypsum. **Sand (with Clay)**: Trace, black heavy mineral sand.
- 1.0 - 2.0 **Clay (with Sand)**: Dominant, orange-brown, fine sand - medium sand, sub-rounded, quartz-gypsum, high plasticity, fine-course grained crystalline gypsum. **Clay (with Sand)**: Trace, black heavy mineral sand.
- 2.0 - 3.9 **Clay**: Dominant, orange-brown, fine sand, rounded to sub-rounded, quartz, high plasticity. **Clay**: Trace, fine grained crystalline gypsum, with localised cellular gypsum aggregations. **Clay**: Trace, fine grained black heavy mineral sand.

Reward Minerals Ltd - Composite Log

Bore ID:

GP05


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73343

DATE COMMENCED: 13-Dec-2006
DATE COMPLETED: 13-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: EarthTEC Drilling
Tag ID: Not tagged.

Drilling Method: Driven Core
Bore Diameter: 55 mm

Northing: 7406505.000 m
Easting: 469186.000 m

Surface RL: 329.700 m
Scheme: GDA94 (Z51)



BORE NAME: GP05

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73343
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: -0.046 m at 18-Dec-2006

LOCATION

North: 7406505.000 m
East: 469186.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 329.700 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 13-Dec-2006
Completed: 13-Dec-2006
Drilled Depth: 6.0
Drilling Company: EarthTEC Drilling
Drilling Rig: Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 6.0	Driven core (55 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.360) - 1.000	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
1.000 - 1.980	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 2.0	Annulus fill, ID-OD: 20 mm to 55 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
2.0 - 6.0	Void fill, OD: 55 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.1	Sand with Silt	Upper Lake Bed Sequence
0.1 - 0.5	Clay with Sand	Upper Lake Bed Sequence
0.5 - 1.0	Sand with Clay	Upper Lake Bed Sequence
1.0 - 6.0	Clay	Lower Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 0.1 **Sand (with Silt):** Green-brown, gypsum, fine-medium grained gypsum. **Sand (with Silt):** Gypsum, White halite crust to 0.08 m with gypsum crystals to 3 cm to 0.9 m.
- 0.1 - 0.5 **Clay (with Sand):** Green-brown, fine sand - medium sand, sub-rounded to rounded, quartz-gypsum, medium to high plasticity, seed gypsum sand.
- 0.5 - 1.0 **Sand (with Clay):** Orange-red-brown, fine sand - coarse sand, rounded to sub-rounded, quartz-gypsum, seed gypsum.
- 1.0 - 4.6 **Clay:** Orange-brown, fine sand - medium sand, sub-rounded to rounded, quartz-gypsum, high plasticity, trace crystalline gypsum sand, trace black heavy mineral sand. **Clay:** 2 m: as above, red brown with crystalline gypsum to 1.5 cm. **Clay:** 2.7 m: as above but orange, red, brown. **Clay:** 3 - 3.6 m: as above but with trace black clay. **Clay:** 3.6 m: as above but pale green, with fibrous crystalline gypsum to 0.5 cm. **Clay:** 4 m: as above but red, brown. 4.1 m: pale green. **Clay:** 4.43 m: as above but red, brown.
- 4.6 - 5.0 **Clay:** Dominant, pale green-red, with fine to medium grained fibrous crystalline gypsum. **Sand:** Trace, black-red, fine sand - medium sand, rounded, ferruginous sand.

Depth (m bgl)

5.0 - 5.3	Clay: Pale orange-green, fine sand - medium sand, gypsum, medium to high plasticity, crystalline gypsum sand.
5.3 - 6.0	Clay: Pale green, fine sand, mostly medium sand, medium to high plasticity, crystalline gypsum sand.

Reward Minerals Ltd - Composite Log

Bore ID:
GP06


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73345

DATE COMMENCED: 13-Dec-2006
DATE COMPLETED: 13-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: EarthTEC Drilling
Tag ID: Not tagged.

Drilling Method: Driven Core
Bore Diameter: 55 mm

Northing: 7406358.000 m
Easting: 464236.000 m

Surface RL: 330.600 m
Scheme: GDA94 (Z51)



BORE NAME: GP06

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73345
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: -0.017 m at 18-Dec-2006

LOCATION

North: 7406358.000 m
East: 464236.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 330.600 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 13-Dec-2006
Completed: 13-Dec-2006
Drilled Depth: 4.2
Drilling Company: EarthTEC Drilling
Drilling Rig: Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 4.2	Driven core (55 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.340) - 1.030	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
1.030 - 2.020	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 2.0	Annulus fill, ID-OD: 20 mm to 55 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
2.0 - 4.2	Void fill, OD: 55 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.3	Sand with Silt	Upper Lake Bed Sequence
0.3 - 1.0	Clay with Sand	Upper Lake Bed Sequence
1.0 - 1.1	Sand with Clay	Upper Lake Bed Sequence
1.1 - 1.2	Clay with Sand	Upper Lake Bed Sequence
1.2 - 1.4	Sand with Clay	Aeolian Deposit
1.4 - 3.3	Clay with Sand	Lower Lake Bed Sequence
3.3 - 3.5	Sand with Clay	Lower Lake Bed Sequence
3.5 - 3.7	Clay with Sand	Lower Lake Bed Sequence
3.7 - 3.8	Sand with Clay	Lower Lake Bed Sequence
3.8 - 4.0	Clay with Sand	Lower Lake Bed Sequence
4.0 - 4.2	Sandstone	Weathered Basement

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

0.0 - 0.3 **Sand (with Silt and Clay):** Pale orange-brown, fine sand - medium sand, quartz-gypsum, coarse grained seed gypsum, crystalline gypsum, trace clay. **Sand (with Silt and Clay):** With black organic and white halite deposits to 0.02 m.

Depth (m bgl)

0.3 - 0.7	<u>Clay (with Sand)</u> : Green, fine sand, quartz-gypsum, high plasticity, fine grained seed gypsum sand, trace black heavy mineral sand.
0.7 - 1.0	<u>Clay (with Sand)</u> : Orange-brown, quartz-gypsum, medium to high plasticity, .
1.0 - 1.1	<u>Sand (with Clay)</u> : Orange-brown, fine sand - medium sand.
1.1 - 1.2	<u>Clay (with Sand)</u> : Orange-brown, high plasticity.
1.2 - 1.4	<u>Sand (with Clay)</u> : Orange-brown, fine sand - medium sand, rounded, quartz-gypsum, seed gypsum.
1.4 - 3.0	<u>Clay (with Sand)</u> : Red-brown, fine sand - medium sand, sub-rounded to rounded, quartz, high plasticity, trace black heavy mineral sand. <u>Clay (with Sand)</u> : Orange, red, brown from 2.0 m.
3.0 - 3.3	<u>Clay (with Sand)</u> : Orange-brown, medium to high plasticity.
3.3 - 3.5	<u>Sand (with Clay)</u> : Orange-brown, medium sand - coarse sand, gypsum.
3.5 - 3.7	<u>Clay (with Sand)</u> : Orange-brown, medium to high plasticity.
3.7 - 3.8	<u>Sand (with Clay)</u> : Orange-brown, fine sand - coarse sand.
3.8 - 4.0	<u>Clay (with Sand)</u> : Orange-brown-grey, medium to high plasticity.
4.0 - 4.2	<u>Sandstone</u> : Orange-brown-green, fine sand - coarse sand, quartz-gypsum, extremely weathered rock, crystalline gypsum.

Reward Minerals Ltd - Composite Log

Bore ID:
GP07


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73346

DATE COMMENCED: 13-Dec-2006
DATE COMPLETED: 14-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: EarthTEC Drilling
Tag ID: Not tagged.

Drilling Method: Driven Core
Bore Diameter: 55 mm

Northing: 7389823.000 m
Easting: 470683.000 m

Surface RL: 329.300 m
Scheme: GDA94 (Z51)



BORE NAME: GP07

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73346
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.007 m at 18-Dec-2006

LOCATION

North: 7389823.000 m
East: 470683.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 329.300 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 13-Dec-2006
Completed: 14-Dec-2006
Drilled Depth: 6.0
Drilling Company: EarthTEC Drilling
Drilling Rig: Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 6.0	Driven core (55 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.340) - 1.230	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
1.230 - 2.040	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 2.0	Annulus fill, ID-OD: 20 mm to 55 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
2.0 - 6.0	Void fill, OD: 55 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.1	Sand with Silt	Upper Lake Bed Sequence
0.1 - 0.4	Clay with Sand	Upper Lake Bed Sequence
0.4 - 1.0	Sand with Clay	Aeolian Deposit
1.0 - 2.0	Clay with Sand	Lower Lake Bed Sequence
2.0 - 2.2	Sand with Clay	Lower Lake Bed Sequence
2.2 - 6.0	Clay with Sand	Lower Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 0.1 **Sand (with Silt):** Green, fine sand - coarse sand, gypsum, Thin halite crust at surface.
- 0.1 - 0.4 **Clay (with Sand):** Pale green-brown, fine sand - medium sand, sub-rounded to rounded, quartz-gypsum, medium to high plasticity, seed gypsum sand, trace red, black heavy mineral sand.
- 0.4 - 1.0 **Sand (with Clay):** Orange-brown, fine sand - medium gravel, sub-rounded to rounded, quartz-gypsum, seed gypsum.
- 1.0 - 2.0 **Clay (with Sand):** Orange-brown, fine sand - medium sand, sub-rounded to rounded, quartz-gypsum, medium-high plasticity, crystalline gypsum sand, trace black heavy mineral sand.
- 2.0 - 2.2 **Sand (with Clay):** Orange-brown, fine sand - medium sand.
- 2.2 - 6.0 **Clay (with Sand):** Orange-brown, fine sand - medium sand, sub-rounded to rounded, quartz-gypsum, high plasticity, trace crystalline gypsum sand, trace black heavy mineral sand.

Reward Minerals Ltd - Composite Log

Bore ID:
GP08


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73347

DATE COMMENCED: 14-Dec-2006
DATE COMPLETED: 14-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: EarthTEC Drilling
Tag ID: Not tagged.

Drilling Method: Driven Core
Bore Diameter: 55 mm

Northing: 7390056.000 m
Easting: 474264.000 m

Surface RL: 330.600 m
Scheme: GDA94 (Z51)



BORE NAME: GP08

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73347
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.117 m at 18-Dec-2006

LOCATION

North: 7390056.000 m
East: 474264.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 330.600 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 14-Dec-2006
Completed: 14-Dec-2006
Drilled Depth: 2.7
Drilling Company: EarthTEC Drilling
Drilling Rig: Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 2.7	Driven core (55 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.350) - 1.040	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
1.040 - 2.050	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 2.1	Annulus fill, ID-OD: 20 mm to 55 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
2.1 - 2.7	Void fill, OD: 55 mm, spoil.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.2	Sand with Clay	Upper Lake Bed Sequence
0.2 - 2.2	Clay with Sand	Lower Lake Bed Sequence
2.2 - 2.3	Silt with Sand	Lower Lake Bed Sequence
2.3 - 2.7	Clay with Sand	Lower Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 0.2 **Sand (with Clay):** Orange-brown, fine sand - coarse sand, gypsum, with fine-coarse grained gypsum sand, dark brown-black organic material to 0.05m. **Sand (with Clay):** Minor halite crust at surface.
- 0.2 - 1.0 **Clay (with Sand):** Orange-brown, fine sand - medium sand, sub-rounded to rounded, quartz-gypsum, high plasticity, fine to coarse grained crystalline gypsum sand. **Clay (with Sand):** Trace fine grained heavy mineral sand.
- 1.0 - 1.2 **Clay (with Sand):** Red-brown, fine sand, quartz, high plasticity, trace black heavy mineral sand.
- 1.2 - 1.3 **Clay (with Sand):** Fine sand - coarse sand, gypsum.
- 1.3 - 2.2 **Clay (with Sand):** Pale orange-brown, fine sand - medium sand, sub-rounded to rounded, quartz-gypsum, medium-high plasticity, crystalline gypsum, minor cellular gypsum aggregations. **Clay (with Sand):** Trace black heavy mineral sand.
- 2.2 - 2.3 **Silt (with Sand):** Pale orange, medium to high plasticity, laminated.

Depth (m bgl)

2.3 - 2.7 **Clay (with Sand)**: Pale orange-red, fine sand - medium sand, gypsum, medium to high plasticity, crystalline gypsum sand. **Clay (with Sand)**: 2.53 - 2.56 m: pale orange, grey sandy silt layer. **Clay (with Sand)**: Refusal on extremely/highly weathered sandstone.

Reward Minerals Ltd - Composite Log

Bore ID:
GP09


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73348

DATE COMMENCED: 14-Dec-2006
DATE COMPLETED: 14-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: EarthTEC Drilling
Tag ID: Not tagged.

Drilling Method: Driven Core
Bore Diameter: 55 mm

Northing: 7389909.000 m
Easting: 479448.000 m

Surface RL: 330.600 m
Scheme: GDA94 (Z51)



BORE NAME: GP09

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73348
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.473 m at 18-Dec-2006

LOCATION

North: 7389909.000 m
East: 479448.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 330.600 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 14-Dec-2006
Completed: 14-Dec-2006
Drilled Depth: 2.7
Drilling Company: EarthTEC Drilling
Drilling Rig: Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 2.7	Driven core (55 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(1.030) - 0.360	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
0.360 - 1.340	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 1.3	Annulus fill, ID-OD: 20 mm to 55 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
1.3 - 2.7	Void fill, OD: 55 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 1.2	Sand with Silt	Upper Lake Bed Sequence
1.2 - 2.7	Clay with Sand	Lower Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 1.2 **Sand (with Silt)**: Pale orange-brown, fine sand - coarse sand, gypsum, seed and crystalline gypsum. Undulating heaved earth at surface. **Sand (with Silt)**: From 0.5 m pale green and green.
- 1.2 - 1.4 **Clay (with Sand)**: Pale orange-red-brown, fine sand - medium sand, quartz-gypsum, high plasticity, fine to coarse grained crystalline gypsum sand.
- 1.4 - 1.8 **Clay (with Sand)**: Red-grey-brown, fine sand, sub-rounded to rounded, quartz, high plasticity, trace black fine grained heavy mineral sand.
- 1.8 - 2.7 **Clay (with Sand)**: Dominant, pale orange, fine sand - medium sand, quartz-gypsum, medium to high plasticity, trace fine grained black, red heavy mineral sand. **Clay (with Sand)**: Minor, red-brown, gypsum, from 2.0 to 2.1 m: with fine to coarse grained crystalline gypsum sand. **Clay (with Sand)**: Trace, pale orange-brown, gypsum, from 2.1m: trace fine to coarse grained crystalline gypsum sand. **Clay (with Sand)**: Refusal on extremely/highly weathered sandstone.

Reward Minerals Ltd - Composite Log

Bore ID:

GP10


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73349

DATE COMMENCED: 14-Dec-2006
DATE COMPLETED: 14-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: EarthTEC Drilling
Tag ID: Not tagged.

Drilling Method: Driven Core
Bore Diameter: 55 mm

Northing: 7389332.000 m
Easting: 484638.000 m

Surface RL: 330.100 m
Scheme: GDA94 (Z51)



BORE NAME: GP10

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73349
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.456 m at 18-Dec-2006

LOCATION

North: 7389332.000 m
East: 484638.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 330.100 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 14-Dec-2006
Completed: 14-Dec-2006
Drilled Depth: 3.4
Drilling Company: EarthTEC Drilling
Drilling Rig: Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 3.4	Driven core (55 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.300) - 1.190	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
1.190 - 2.100	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 2.1	Annulus fill, ID-OD: 20 mm to 55 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
2.1 - 3.4	Void fill, OD: 55 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 1.1	Sand with Silt	Upper Lake Bed Sequence
1.1 - 2.0	Clay with Sand	Lower Lake Bed Sequence
2.0 - 2.1	Sand with Silt	Lower Lake Bed Sequence
2.1 - 3.4	Clay with Sand	Lower Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 1.1 **Sand (with Silt)**: Orange-brown, fine sand - coarse sand, gypsum, seed and crystalline gypsum. Fine-medium grained from 0.25 m. **Sand (with Silt)**: From 0.42 m: fine to coarse grained. **Sand (with Silt)**: From 0.54 m: green and brown. **Sand (with Silt)**: Undulating heaved earth at surface.
- 1.1 - 2.0 **Clay (with Sand)**: Orange-brown-grey, fine sand - medium sand, sub-rounded to rounded, quartz-gypsum, high plasticity, crystalline gypsum sand, trace red, black heavy mineral sand.
- 2.0 - 2.1 **Sand (with Silt)**: Pale orange-yellow-brown, fine sand - medium sand, quartz-gypsum.
- 2.1 - 2.5 **Clay (with Sand)**: Dominant, fine sand - medium sand, rounded to sub-rounded, quartz-gypsum, high plasticity. **Clay (with Sand)**: Minor cellular gypsum aggregations, trace crystalline gypsum sand. **Clay (with Sand)**: Trace, black, heavy mineral sand.
- 2.5 - 3.0 **Clay (with Sand)**: Pale orange-brown, fine sand, quartz-gypsum, medium to high plasticity. **Clay (with Sand)**: Crystalline gypsum sand, with fine grained cellular gypsum aggregations .
- 3.0 - 3.4 **Clay (with Sand)**: Pale orange-brown-grey, fine sand, quartz-gypsum, high plasticity, crystalline gypsum sand. **Clay (with Sand)**: Refusal on extremely/highly weathered sandstone.

Reward Minerals Ltd - Composite Log

Bore ID:

GP11


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73350

DATE COMMENCED: 15-Dec-2006
DATE COMPLETED: 15-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: EarthTEC Drilling
Tag ID: Not tagged.

Drilling Method: Driven Core
Bore Diameter: 55 mm

Northing: 7389786.000 m
Easting: 489688.000 m

Surface RL: 329.700 m
Scheme: GDA94 (Z51)



BORE NAME: GP11

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73350
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.101 m at 18-Dec-2006

LOCATION

North: 7389786.000 m
East: 489688.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 329.700 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 15-Dec-2006
Completed: 15-Dec-2006
Drilled Depth: 5.0
Drilling Company: EarthTEC Drilling
Drilling Rig: Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 5.0	Driven core (55 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.320) - 0.910	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
0.910 - 1.920	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 1.9	Annulus fill, ID-OD: 20 mm to 55 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
1.9 - 5.0	Void fill, OD: 55 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.6	Sand with Silt	Upper Lake Bed Sequence
0.6 - 0.6	Clay with Sand	Upper Lake Bed Sequence
0.6 - 1.2	Sand with Silt	Upper Lake Bed Sequence
1.2 - 1.4	Sand with Clay	Upper Lake Bed Sequence
1.4 - 2.0	Sand with Silt	Upper Lake Bed Sequence
2.0 - 5.0	Clay with Sand	Lower Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 0.6 **Sand (with Silt):** Orange-brown, fine sand - coarse sand, gypsum, seed and crystalline gypsum. **Sand (with Silt):** From 0.26 m: fine to medium grained . **Sand (with Silt):** From 0.35 m: fine to coarse grained . **Sand (with Silt):** From 0.44 m: green, brown . **Sand (with Silt):** Hard undulating halite/gypsum to 0.05 m depth.
- 0.6 - 0.6 **Clay (with Sand):** Green, medium to high plasticity.
- 0.6 - 1.2 **Sand (with Silt):** Pale green, fine sand - coarse sand, gypsum, seed and crystalline gypsum, trace black heavy mineral sand. **Sand (with Silt):** From 1.0 m: orange, brown .
- 1.2 - 1.4 **Sand (with Clay):** Grey-green, fine sand - medium sand, gypsum, with coarse grained gypsum sand.
- 1.4 - 2.0 **Sand (with Silt):** Orange-brown, fine sand - coarse sand, gypsum-quartz, seed and crystalline gypsum.

Depth (m bgl)

- 2.0 - 2.3 **Clay (with Sand)**: Pale green-orange-brown, fine sand, quartz-gypsum, high plasticity, crystalline gypsum sand.
- 2.3 - 5.0 **Clay (with Sand)**: Pale green, fine sand, sub-rounded to rounded, quartz, medium to high plasticity, with fine to medium grained crystalline gypsum sand. **Clay (with Sand)**: Trace black heavy mineral sand. **Clay (with Sand)**: Trace organic material (tree root) to 2.77 m. **Clay (with Sand)**: Refusal on extremely/highly weathered sandstone.

Reward Minerals Ltd - Composite Log

Bore ID:
GP12


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73351

DATE COMMENCED: 15-Dec-2006
DATE COMPLETED: 15-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: EarthTEC Drilling
Tag ID: Not tagged.

Drilling Method: Driven Core
Bore Diameter: 55 mm

Northing: 7423068.000 m
Easting: 474130.000 m

Surface RL: 331.000 m
Scheme: GDA94 (Z51)



BORE NAME: GP12

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73351
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.050 m at 18-Dec-2006

LOCATION

North: 7423068.000 m
East: 474130.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 331.000 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 15-Dec-2006
Completed: 15-Dec-2006
Drilled Depth: 3.9
Drilling Company: EarthTEC Drilling
Drilling Rig: Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 3.9	Driven core (55 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.350) - 1.010	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
1.010 - 2.000	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 2.0	Annulus fill, ID-OD: 20 mm to 55 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
2.0 - 3.9	Void fill, OD: 55 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 1.2	Clay with Sand	Upper Lake Bed Sequence
1.2 - 2.4	Clay with Sand	Lower Lake Bed Sequence
2.4 - 2.5	Sand with Silt	Lower Lake Bed Sequence
2.5 - 3.3	Clay with Sand	Lower Lake Bed Sequence
3.3 - 3.9	Sand with Silt	Lower Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 0.3 **Clay (with Sand):** Dominant, green, fine sand - medium sand, rounded, quartz-gypsum, medium plasticity, with organic material, seed gypsum sand. **Sand:** Trace, red-black, heavy mineral sand. **Clay (with Sand):** Halite crust (5mm) underlain by dark br spongy clay with high organics to 0.1m.
- 0.3 - 1.2 **Clay (with Sand):** Dominant, red-orange-brown, fine sand - medium sand, rounded to sub-rounded, quartz-gypsum, high plasticity, with fine to coarse grained crystalline gypsum sand. **Sand:** Trace, black, heavy mineral sand.
- 1.2 - 2.1 **Clay (with Sand):** Red-brown, fine sand, rounded to sub-rounded, quartz-gypsum, high plasticity, crystalline gypsum sand, trace black heavy mineral sand.
- 2.1 - 2.4 **Clay (with Sand):** Pale orange-red-brown, fine sand, gypsum, high plasticity, laminated, with medium grained gypsum sand.
- 2.4 - 2.5 **Sand (with Silt):** Orange-brown, fine sand - coarse sand, gypsum.
- 2.5 - 2.6 **Clay (with Sand):** Brown, fine sand - medium sand, high plasticity.

Depth (m bgl)

- 2.6 - 3.3 **Clay (with Sand)**: Pale orange-brown, fine sand - coarse sand, gypsum-quartz, high plasticity, crystalline gypsum sand & gravel, fine grained quartz.
- 3.3 - 3.9 **Sand (with Silt)**: Orange-brown, fine sand - medium sand, gypsum-quartz, crystalline gypsum/quartz sand. **Sand (with Silt)**: Refusal on highly weathered sandstone.

Reward Minerals Ltd - Composite Log

Bore ID:

GP13


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73352

DATE COMMENCED: 15-Dec-2006
DATE COMPLETED: 15-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: EarthTEC Drilling
Tag ID: Not tagged.

Drilling Method: Driven Core
Bore Diameter: 55 mm

Northing: 7423105.000 m
Easting: 479090.000 m

Surface RL: 330.600 m
Scheme: GDA94 (Z51)



BORE NAME: GP13

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73352
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.015 m at 18-Dec-2006

LOCATION

North: 7423105.000 m
East: 479090.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 330.600 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 15-Dec-2006
Completed: 15-Dec-2006
Drilled Depth: 3.9
Drilling Company: EarthTEC Drilling
Drilling Rig: Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 3.9	Driven core (55 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.190) - 1.180	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
1.180 - 2.180	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 2.2	Annulus fill, ID-OD: 20 mm to 55 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
2.2 - 3.9	Void fill, OD: 55 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.6	Clay with Sand	Upper Lake Bed Sequence
0.6 - 3.8	Clay with Sand	Lower Lake Bed Sequence
3.8 - 3.9	Sandstone	Weathered Basement

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 0.1 **Clay (with Sand)**: Green, high plasticity, with organic material. **Clay (with Sand)**: Thin halite crust at surface underlain by dark brown spongy organic clay.
- 0.1 - 0.6 **Clay (with Sand)**: Dominant, green, fine sand - coarse sand, sub-rounded to rounded, quartz-gypsum, medium to high plasticity, with organic material, seed gypsum sand. **Sand**: Trace, black, heavy mineral sand.
- 0.6 - 3.2 **Clay (with Sand)**: Dominant, red-brown, fine sand, quartz-gypsum, medium to high plasticity, fine to medium grained crystalline gypsum sand. **Sand**: Trace, black, heavy mineral sand. **Clay (with Sand)**: From 1.0 m: orange, brown, fine grained sand. **Clay (with Sand)**: From 1.27 m: pale green, red, brown mottled. **Clay (with Sand)**: From 1.32 m: orange, brown. **Clay (with Sand)**: Red-brown-orange-white, from 2.0-2.05 m: salt crystals to 0.5 cm across. **Clay (with Sand)**: Red-orange-brown, from 2.05 m: trace gypsum crystals to 0.3 cm across.
- 3.2 - 3.3 **Clay (with Sand)**: Pale orange-brown, medium plasticity.
- 3.3 - 3.7 **Clay (with Sand)**: Orange-brown, high plasticity.
- 3.7 - 3.8 **Clay (with Sand)**: Pale orange-brown, medium plasticity.

Depth (m bgl)

3.8 - 3.9 **Sandstone**: Pale orange, fine sand - coarse sand, quartz-gypsum, (refusal).

Reward Minerals Ltd - Composite Log

Bore ID:

GP14


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73353

DATE COMMENCED: 15-Dec-2006
DATE COMPLETED: 15-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: EarthTEC Drilling
Tag ID: Not tagged.

Drilling Method: Driven Core
Bore Diameter: 55 mm

Northing: 7417632.000 m
Easting: 474262.000 m

Surface RL: 330.800 m
Scheme: GDA94 (Z51)



BORE NAME: GP14

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73353
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: -0.032 m at 18-Dec-2006

LOCATION

North: 7417632.000 m
East: 474262.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 330.800 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 15-Dec-2006
Completed: 15-Dec-2006
Drilled Depth: 3.7
Drilling Company: EarthTEC Drilling
Drilling Rig: Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 3.7	Driven core (55 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.790) - 0.540	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
0.540 - 1.530	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 1.5	Annulus fill, ID-OD: 20 mm to 55 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
1.5 - 3.7	Void fill, OD: 55 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.2	Sand with Silt	Upper Lake Bed Sequence
0.2 - 0.3	Gravel with Silt	Upper Lake Bed Sequence
0.3 - 1.0	Clay with Sand	Upper Lake Bed Sequence
1.0 - 1.2	Gravel with Clay	Upper Lake Bed Sequence
1.2 - 2.0	Clay with Sand	Lower Lake Bed Sequence
2.0 - 2.1	Sand with Clay	Lower Lake Bed Sequence
2.1 - 2.3	Clay with Sand	Lower Lake Bed Sequence
2.3 - 2.4	Sand with Clay	Lower Lake Bed Sequence
2.4 - 3.1	Clay with Sand	Lower Lake Bed Sequence
3.1 - 3.2	Sand with Clay	Lower Lake Bed Sequence
3.2 - 3.5	Clay with Sand	Lower Lake Bed Sequence
3.5 - 3.6	Sand with Clay	Lower Lake Bed Sequence
3.6 - 3.7	Clay with Sand	Lower Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

0.0 - 0.2 **Sand (with Silt):** Green-brown, fine sand - coarse sand, gypsum. **Clay:** Black-brown, halite, halite crust at surface underlain by clay with organic material to 0.04 m depth.

Depth (m bgl)

0.2 - 0.3	<u>Gravel (with Silt and Sand)</u> : Green-brown, gypsum, gypsum to 2 cm.
0.3 - 1.0	<u>Clay (with Sand)</u> : Orange-brown, fine sand - medium sand, sub-rounded to rounded, quartz-gypsum, medium-high plasticity, seed gypsum, with fine-coarse grained crystalline gypsum.
1.0 - 1.2	<u>Gravel (with Clay)</u> : Pale orange-grey, fine sand - coarse sand, gypsum.
1.2 - 2.0	<u>Clay (with Sand)</u> : Orange-brown, fine sand - medium sand, sub-rounded to rounded, quartz-gypsum, high plasticity, crystalline gypsum.
2.0 - 2.1	<u>Sand (with Clay)</u> : Brown, fine sand - coarse sand, gypsum.
2.1 - 2.3	<u>Clay (with Sand)</u> : Orange-brown, fine sand - medium sand, high plasticity.
2.3 - 2.4	<u>Sand (with Clay)</u> : Orange-brown-grey, fine sand - coarse sand.
2.4 - 3.1	<u>Clay (with Sand)</u> : Red-brown, fine sand - medium sand, sub-rounded to rounded, quartz-gypsum, high plasticity, crystalline gypsum sand.
3.1 - 3.2	<u>Sand (with Clay)</u> : Fine sand - medium sand, gypsum.
3.2 - 3.5	<u>Clay (with Sand)</u> : Orange-brown, fine sand - coarse sand, gypsum, high plasticity.
3.5 - 3.6	<u>Sand (with Clay and Gravel)</u> : Fine sand - coarse sand, gypsum.
3.6 - 3.7	<u>Clay (with Sand)</u> : Red-brown, fine sand - medium sand, gypsum, medium to high plasticity. <u>Clay (with Sand)</u> : Refusal on highly weathered sandstone.

Reward Minerals Ltd - Composite Log

Bore ID:

GP15


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73354

DATE COMMENCED: 15-Dec-2006
DATE COMPLETED: 16-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: EarthTEC Drilling
Tag ID: Not tagged.

Drilling Method: Driven Core
Bore Diameter: 55 mm

Northing: 7419559.000 m
Easting: 476126.000 m

Surface RL: 330.600 m
Scheme: GDA94 (Z51)



BORE NAME: GP15

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73354
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.000 m at 18-Dec-2006

LOCATION

North: 7419559.000 m
East: 476126.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 330.600 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 15-Dec-2006
Completed: 16-Dec-2006
Drilled Depth: 3.4
Drilling Company: EarthTEC Drilling
Drilling Rig: Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 3.5	Driven core (55 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.470) - 0.880	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
0.880 - 2.170	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 2.2	Annulus fill, ID-OD: 20 mm to 55 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
2.2 - 3.5	Void fill, OD: 55 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.3	Sand with Clay	Upper Lake Bed Sequence
0.3 - 1.0	Clay with Sand	Upper Lake Bed Sequence
1.0 - 1.5	Sand with Clay	Upper Lake Bed Sequence
1.5 - 1.7	Gravel with Sand	Upper Lake Bed Sequence
1.7 - 1.8	Sand with Clay	Upper Lake Bed Sequence
1.8 - 2.0	Gravel with Clay	Upper Lake Bed Sequence
2.0 - 2.2	Sand with Silt	Upper Lake Bed Sequence
2.2 - 2.5	Clay with Sand	Lower Lake Bed Sequence
2.5 - 3.0	Sand with Clay	Lower Lake Bed Sequence
3.0 - 3.1	Sand with Gravel	Lower Lake Bed Sequence
3.1 - 3.5	Clay with Sand	Lower Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

0.0 - 0.3 **Sand (with Clay):** Green-brown, fine sand - medium sand, gypsum-quartz, seed and crystalline gypsum.
Sand (with Clay): From 0.2 m: orange, brown. **Clay:** Black-brown, thin halite crust at surface underlain by spongy clay.

Depth (m bgl)

0.3 - 1.0	<u>Clay (with Sand)</u> : Orange-brown, fine sand - medium sand, quartz-gypsum, high plasticity, crystalline gypsum, trace black heavy mineral sand.
1.0 - 1.5	<u>Sand (with Clay)</u> : Orange-brown, fine sand - coarse sand, crystalline gypsum.
1.5 - 1.7	<u>Gravel (with Sand and Clay)</u> : Orange-brown-grey, fine sand - coarse sand, gypsum, crystalline gypsum.
1.7 - 1.8	<u>Sand (with Clay)</u> : Red-brown, fine sand - coarse sand, gypsum.
1.8 - 2.0	<u>Gravel (with Clay)</u> : Red-brown, medium gravel, gypsum, gravel comprises crystalline gypsum to 1.2 cm .
2.0 - 2.2	<u>Sand (with Silt)</u> : Orange-brown, fine sand - coarse sand, gypsum.
2.2 - 2.5	<u>Clay (with Sand)</u> : Pale orange-brown, medium to high plasticity.
2.5 - 3.0	<u>Sand (with Clay)</u> : Pale orange-yellow-brown, fine sand - coarse sand, gypsum-quartz, seed and crystalline gypsum, subrounded to rounded quartz.
3.0 - 3.1	<u>Sand (with Gravel)</u> : Brown, fine sand - coarse sand, gypsum.
3.1 - 3.5	<u>Clay (with Sand)</u> : Pale orange-brown, medium to high plasticity, trace gypsum gravel. <u>Clay (with Sand)</u> : Refusal on highly weathered sandstone.

Reward Minerals Ltd - Composite Log

Bore ID:

GP16


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73355

DATE COMMENCED: 16-Dec-2006
DATE COMPLETED: 16-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: EarthTEC Drilling
Tag ID: Not tagged.

Drilling Method: Driven Core
Bore Diameter: 55 mm

Northing: 7417678.000 m
Easting: 482461.000 m

Surface RL: 330.700 m
Scheme: GDA94 (Z51)



BORE NAME: GP16

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73355
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.036 m at 18-Dec-2006

LOCATION

North: 7417678.000 m
East: 482461.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 330.700 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 16-Dec-2006
Completed: 16-Dec-2006
Drilled Depth: 3.1
Drilling Company: EarthTEC Drilling
Drilling Rig: Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 3.1	Driven core (55 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.510) - 0.880	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
0.880 - 2.160	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 2.2	Annulus fill, ID-OD: 20 mm to 55 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
2.2 - 3.1	Void fill, OD: 55 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.1	Sand with Clay	Upper Lake Bed Sequence
0.1 - 0.3	Clay	Upper Lake Bed Sequence
0.3 - 2.2	Clay with Sand	Lower Lake Bed Sequence
2.2 - 3.1	Silt with Sand	Lower Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 0.1 **Sand (with Clay):** Green, fine sand - coarse sand, gypsum. **Clay:** Black-brown, thin halite crust at surface underlain by spongy clay with organic material.
- 0.1 - 0.3 **Clay:** Green, high plasticity, with organic material.
- 0.3 - 2.1 **Clay (with Sand):** Dominant, red-orange-brown, fine sand - medium sand, sub-rounded to rounded, quartz-gypsum, high plasticity, crystalline gypsum sand. **Sand:** Trace, black, fine sand - medium sand, heavy mineral sand. **Clay:** Orange-brown, from 1.0 m: medium to high plasticity. **Clay:** Red-green-orange, from 2.0 m.
- 2.1 - 2.2 **Clay (with Sand):** Pale orange-brown, medium plasticity.
- 2.2 - 3.1 **Silt (with Sand):** Pale orange, fine sand - coarse sand, gypsum, medium to high plasticity, crystalline gypsum sand. **Silt (with Sand):** Refusal.

Reward Minerals Ltd - Composite Log

Bore ID:
GP17


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73356

DATE COMMENCED: 16-Dec-2006
DATE COMPLETED: 16-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: EarthTEC Drilling
Tag ID: Not tagged.

Drilling Method: Driven Core
Bore Diameter: 55 mm

Northing: 7417766.000 m
Easting: 489639.000 m

Surface RL: 329.800 m
Scheme: GDA94 (Z51)



BORE NAME: GP17

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73356
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.567 m at 18-Dec-2006

LOCATION

North: 7417766.000 m
East: 489639.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 329.800 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 16-Dec-2006
Completed: 16-Dec-2006
Drilled Depth: 5.8
Drilling Company: EarthTEC Drilling
Drilling Rig: Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 5.8	Driven core (55 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.360) - 0.960	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
0.960 - 2.260	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm, joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 2.3	Annulus fill, ID-OD: 20 mm to 55 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
2.3 - 5.8	Void fill, OD: 55 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.2	Sand with Silt	Upper Lake Bed Sequence
0.2 - 0.4	Clay with Sand	Upper Lake Bed Sequence
0.4 - 0.7	Sand with Silt	Upper Lake Bed Sequence
0.7 - 1.0	Clay with Sand	Upper Lake Bed Sequence
1.0 - 1.7	Sand with Clay	Upper Lake Bed Sequence
1.7 - 2.0	Clay with Sand	Upper Lake Bed Sequence
2.0 - 2.2	Sand with Clay	Upper Lake Bed Sequence
2.2 - 2.3	Clay with Sand	Upper Lake Bed Sequence
2.3 - 2.4	Sand with Clay	Upper Lake Bed Sequence
2.4 - 3.0	Clay with Sand	Lower Lake Bed Sequence
3.0 - 3.1	Sand with Clay	Lower Lake Bed Sequence
3.1 - 5.8	Clay with Sand	Lower Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

0.0 - 0.2 **Sand (with Silt and Clay):** Green-brown, fine sand - coarse sand, gypsum, seed and crystalline gypsum, trace clay. **Sand (with Silt and Clay):** Very hard heaved earth to 0.08 m depth, underlain by running gypsiferous layer.

Depth (m bgl)

0.2 - 0.4	<u>Clay (with Sand)</u> : Green, fine sand - medium sand, gypsum, medium to high plasticity, with organic material.
0.4 - 0.7	<u>Sand (with Silt)</u> : Pale orange, fine sand - coarse sand, gypsum-quartz, seed and crystalline gypsum, trace black heavy mineral sand.
0.7 - 1.0	<u>Clay (with Sand)</u> : Orange-brown, fine sand - medium sand, medium to high plasticity.
1.0 - 1.5	<u>Sand (with Clay)</u> : Orange-brown, fine sand - coarse sand, gypsum-quartz, crystalline gypsum.
1.5 - 2.0	<u>Clay (with Sand)</u> : Orange-brown, medium to high plasticity.
2.0 - 2.2	<u>Sand (with Clay)</u> : Orange-brown, fine sand - coarse sand, gypsum-quartz, crystalline gypsum.
2.2 - 2.3	<u>Clay (with Sand)</u> : Orange-brown, medium to high plasticity .
2.3 - 2.4	<u>Sand (with Clay)</u> : Orange, fine sand - coarse sand, gypsum.
2.4 - 3.0	<u>Clay (with Sand)</u> : Dominant, red-orange-brown, fine sand - medium sand, rounded to sub-rounded, quartz-gypsum, high plasticity, fine to coarse grained crystalline gypsum sand. <u>Sand</u> : Trace, black, heavy mineral sand.
3.0 - 3.1	<u>Sand (with Clay)</u> : Orange-brown, fine sand - coarse sand.
3.1 - 5.3	<u>Clay (with Sand)</u> : Dominant, red-orange-brown, fine sand - medium sand, rounded to sub-rounded, quartz, high plasticity, with fine to coarse grained crystalline gypsum sand. <u>Sand</u> : Trace, black, heavy mineral sand. <u>Clay (with Sand)</u> : From 4.0 m: laminated.
5.3 - 5.8	<u>Clay (with Sand)</u> : Red-orange-brown, fine sand - medium sand, rounded to sub-rounded, quartz-gypsum, medium to high plasticity, laminated, crystalline gypsum sand. <u>Clay (with Sand)</u> : Hole collapsing, abandoned.

Reward Minerals Ltd - Composite Log

Bore ID:
GP18


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73357

DATE COMMENCED: 16-Dec-2006
DATE COMPLETED: 17-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: EarthTEC Drilling
Tag ID: Not tagged.

Drilling Method: Driven Core
Bore Diameter: 55 mm

Northing: 7412110.000 m
Easting: 484680.000 m

Surface RL: 327.300 m
Scheme: GDA94 (Z51)



BORE NAME: GP18

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73357
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.426 m at 18-Dec-2006

LOCATION

North: 7412110.000 m
East: 484680.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 327.300 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 16-Dec-2006
Completed: 17-Dec-2006
Drilled Depth: 10.0
Drilling Company: EarthTEC Drilling
Drilling Rig: Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 10.0	Driven core (55 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.350) - 0.890	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
0.890 - 2.120	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 2.1	Annulus fill, ID-OD: 20 mm to 55 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
2.1 - 10.0	Void fill, OD: 55 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 1.4	Sand with Silt and Clay	Upper Lake Bed Sequence
1.4 - 2.0	Clay with Sand	Upper Lake Bed Sequence
2.0 - 2.2	Sand with Silt	Upper Lake Bed Sequence
2.2 - 2.6	Clay with Sand	Lower Lake Bed Sequence
2.6 - 2.7	Sand with Clay	Lower Lake Bed Sequence
2.7 - 5.0	Clay with Sand	Lower Lake Bed Sequence
5.0 - 5.3	Sand with Silt and Clay	Lower Lake Bed Sequence
5.3 - 8.0	Clay with Sand	Lower Lake Bed Sequence
8.0 - 8.6	Sand with Clay	Lower Lake Bed Sequence
8.6 - 10.0	Clay with Sand	Lower Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 1.0 **Sand (with Silt):** Dominant, pale orange-brown, fine sand - coarse sand, gypsum-quartz, seed and crystalline gypsum, subrounded to rounded quartz. **Sand:** Trace, black, heavy mineral sand. **Sand (with Silt):** Green-brown, from 0.5 - 0.6 m. **Sand (with Silt):** Hard heaved earth surface to 0.05 m depth underlain by running gypsiferous sand.
- 1.0 - 1.4 **Sand (with Clay):** Orange-brown, fine sand - coarse sand, gypsum-quartz.

Depth (m bgl)

1.4 - 2.0	Clay (with Sand): Dominant, red-orange-brown, fine sand - medium sand, rounded to sub-rounded, quartz-gypsum, medium to high plasticity, crystalline gypsum sand. Sand: Trace, red-black, heavy mineral sand.
2.0 - 2.2	Sand (with Silt): Pale orange-brown, fine sand - coarse sand, gypsum-quartz.
2.2 - 2.6	Clay (with Sand): Orange-red-brown, high plasticity.
2.6 - 2.7	Sand (with Clay): Orange, fine sand - coarse sand, gypsum.
2.7 - 5.0	Clay (with Sand): Dominant, orange-brown, fine sand - medium sand, gypsum-quartz, medium-high plasticity, crystalline gypsum, fine subrounded-rounded quartz. Sand: Trace, black, heavy mineral sand. Clay (with Sand): Red-orange-brown, from 3.0 m. Clay (with Sand): Orange-brown, from 4.0 m.
5.0 - 5.2	Sand (with Silt): Orange-brown, fine sand - coarse sand, gypsum.
5.2 - 5.3	Sand (with Clay): Fine sand - medium sand.
5.3 - 6.0	Clay (with Sand): Orange-brown, fine sand - medium sand, high plasticity.
6.0 - 6.2	Clay (with Sand): Orange-brown, fine sand - coarse sand, gypsum, medium to high plasticity, crystalline gypsum.
6.2 - 7.0	Clay (with Sand): Orange-brown, fine sand - medium sand, gypsum-quartz, high plasticity, crystalline gypsum.
7.0 - 8.0	Clay (with Sand): Pale orange-brown, fine sand - medium sand, gypsum, medium-high plasticity, crystalline gypsum, with cellular gypsum aggregations.
8.0 - 8.6	Sand (with Clay): Orange-brown, fine sand - medium sand, quartz-gypsum.
8.6 - 9.0	Clay (with Sand): Orange-brown, high plasticity.
9.0 - 9.2	Clay (with Sand): Orange-brown, fine sand - medium sand, medium to high plasticity.
9.2 - 9.4	Clay (with Sand): Orange-brown, high plasticity.
9.4 - 9.4	Clay (with Sand): Orange-brown, medium to high plasticity.
9.4 - 10.0	Clay (with Sand): Pale orange-brown, fine sand - medium sand, rounded to sub-rounded, quartz-gypsum, high plasticity, crystalline gypsum.

Reward Minerals Ltd - Composite Log

Bore ID:
GP19


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73358

DATE COMMENCED: 17-Dec-2006
DATE COMPLETED: 17-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: EarthTEC Drilling
Tag ID: Not tagged.

Drilling Method: Driven Core
Bore Diameter: 55 mm

Northing: 7412101.000 m
Easting: 479474.000 m

Surface RL: 330.700 m
Scheme: GDA94 (Z51)



BORE NAME: GP19

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73358
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.104 m at 18-Dec-2006

LOCATION

North: 7412101.000 m
East: 479474.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 330.700 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 17-Dec-2006
Completed: 17-Dec-2006
Drilled Depth: 1.9
Drilling Company: EarthTEC Drilling
Drilling Rig: Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 1.9	Driven core (55 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.470) - 0.820	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
0.820 - 1.800	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 1.8	Annulus fill, ID-OD: 20 mm to 55 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
1.8 - 1.9	Void fill, OD: 55 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.1	Sand with Clay	Upper Lake Bed Sequence
0.1 - 0.3	Clay with Silt	Upper Lake Bed Sequence
0.3 - 0.7	Silt with Sand	Upper Lake Bed Sequence
0.7 - 1.0	Clay with Sand	Lower Lake Bed Sequence
1.0 - 1.4	Silt with Sand	Lower Lake Bed Sequence
1.4 - 1.5	Sand	Lower Lake Bed Sequence
1.5 - 1.7	Clay with Sand	Lower Lake Bed Sequence
1.7 - 1.8	Sand with Clay	Lower Lake Bed Sequence
1.8 - 1.9	Silt with Sand	Lower Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

0.0 - 0.1	Sand (with Clay): Pale green, fine sand - coarse sand, gypsum, black, brown clay with organic material to 0.04 m depth.
0.1 - 0.3	Clay (with Sand): Green-brown, fine sand - medium sand, quartz, medium to high plasticity, with organic material.
0.3 - 0.7	Silt (with Sand): Orange-brown, fine sand - medium sand, rounded to sub-rounded, quartz-gypsum, medium plasticity, crystalline gypsum, trace black heavy mineral sand.
0.7 - 1.0	Clay (with Sand): Orange-brown, fine sand - medium sand, gypsum, medium to high plasticity.

Depth (m bgl)

- 1.0 - 1.4 **Silt (with Sand)**: Pale orange-brown, fine sand - medium sand, rounded to sub-rounded, quartz-gypsum, medium plasticity, crystalline gypsum with cellular gypsum sand.
- 1.4 - 1.5 **Sand**: Pale orange-grey, fine sand - coarse sand, gypsum.
- 1.5 - 1.7 **Clay (with Sand)**: Orange-brown, fine sand, quartz-gypsum, medium to high plasticity, crystalline gypsum sand.
- 1.7 - 1.8 **Sand (with Clay)**: Fine sand - coarse sand, gypsum.
- 1.8 - 1.9 **Silt (with Sand)**: Pale orange-brown, fine sand - coarse sand, gypsum. **Silt (with Sand)**: Refusal.

Reward Minerals Ltd - Composite Log

Bore ID:
GP20


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73359

DATE COMMENCED: 17-Dec-2006
DATE COMPLETED: 17-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: EarthTEC Drilling
Tag ID: Not tagged.

Drilling Method: Driven Core
Bore Diameter: 55 mm

Northing: 7412193.000 m
Easting: 468945.000 m

Surface RL: 331.600 m
Scheme: GDA94 (Z51)



BORE NAME: GP20

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73359
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: -0.006 m at 18-Dec-2006

LOCATION

North: 7412193.000 m
East: 468945.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 331.600 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 17-Dec-2006
Completed: 17-Dec-2006
Drilled Depth: 2.7
Drilling Company: EarthTEC Drilling
Drilling Rig: Geoprobe 540MT - Direct Push (dual tube Macro-Core closed piston sampling)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 2.7	Driven core (55 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.585) - 0.815	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
0.815 - 1.905	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 1.9	Annulus fill, ID-OD: 20 mm to 55 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
1.9 - 2.7	Void fill, OD: 55 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.1	Clay with Sand	Upper Lake Bed Sequence
0.1 - 0.2	Sand with Clay	Upper Lake Bed Sequence
0.2 - 0.6	Silt with Sand	Upper Lake Bed Sequence
0.6 - 1.3	Sand with Clay	Upper Lake Bed Sequence
1.3 - 2.0	Clay with Sand	Lower Lake Bed Sequence
2.0 - 2.3	Sand with Clay	Lower Lake Bed Sequence
2.3 - 2.7	Clay with Sand	Lower Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 0.1 **Clay (with Sand)**: Green-brown, trace gypsum gravel.
- 0.1 - 0.2 **Sand (with Clay)**: Green, fine sand - coarse sand, gypsum.
- 0.2 - 0.6 **Silt (with Sand)**: Orange-brown, fine sand - medium sand, rounded to sub-rounded, quartz-gypsum, low plasticity, seed and crystalline gypsum sand.
- 0.6 - 1.3 **Sand (with Clay)**: Orange-brown, fine sand - coarse sand, gypsum-quartz, seed and crystalline gypsum, fine grained subrounded to rounded quartz. **Sand (with Clay)**: Trace gypsum gravel. **Sand (with Clay)**: From 1.0 m: red, orange, brown, grey, with gypsum gravel .
- 1.3 - 2.0 **Clay (with Sand)**: Dominant, red-orange-brown, fine sand - coarse sand, gypsum-quartz, medium-high plasticity, crystalline gypsum, fine-medium grained quartz sand. **Sand**: Trace, black, heavy mineral sand.

Depth (m bgl)

2.0 - 2.3 **Sand (with Clay)**: Red-orange-brown-grey, fine sand - coarse sand, gypsum, crystalline gypsum.

2.3 - 2.7 **Clay (with Sand)**: Pale orange-brown-red, fine sand - medium sand, gypsum-quartz, medium to high plasticity, crystalline gypsum, trace cellular gypsum. **Clay (with Sand)**: Refusal.

Reward Minerals Ltd - Composite Log

Bore ID:

GP21


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73360

DATE COMMENCED: 17-Dec-2006
DATE COMPLETED: 17-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: Global Groundwater
Tag ID: Not tagged.

Drilling Method: Manually Excavated
Bore Diameter: 42 mm

Northing: 7412117.000 m
Easting: 474178.000 m

Surface RL: 331.450 m
Scheme: GDA94 (Z51)



BORE NAME: GP21

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73360
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.000 m at 18-Dec-2006

LOCATION

North: 7412117.000 m
East: 474178.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 331.450 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 17-Dec-2006
Completed: 17-Dec-2006
Drilled Depth: 0.8
Drilling Company: Global Groundwater
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 0.8	Hand drill (42 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.740) - (0.240)	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
(0.240) - 0.610	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 0.6	Annulus fill, ID-OD: 20 mm to 42 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
0.6 - 0.8	Void fill, OD: 42 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.4	Clay with Sand	Upper Lake Bed Sequence
0.4 - 0.6	Silt with Sand	Upper Lake Bed Sequence
0.6 - 0.8	Clay with Sand	Lower Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 0.4 **Clay (with Sand):** Green, fine sand - medium sand, gypsum, medium to high plasticity, seed and crystalline gypsum.
- 0.4 - 0.6 **Silt (with Sand):** Orange-brown, fine sand - medium sand, gypsum, high plasticity, seed and crystalline gypsum.
- 0.6 - 0.8 **Clay (with Sand):** Orange-brown, fine sand - medium sand, gypsum-quartz, high plasticity, crystalline gypsum. **Clay (with Sand):** Refusal.

Reward Minerals Ltd - Composite Log

Bore ID:
GP22


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73372

DATE COMMENCED: 17-Dec-2006
DATE COMPLETED: 17-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: Global Groundwater
Tag ID: Not tagged.

Drilling Method: Hand Drill
Bore Diameter: 42 mm

Northing: 7401012.000 m
Easting: 479361.000 m

Surface RL: 330.150 m
Scheme: GDA94 (Z51)

Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Construction Diagram
Qhs	0.0		Sand with Clay	 <p>1 Bore Casing: unplasticised polyvinylchloride uPVC, Class 12, 20.0 mm (nominal)</p> <p>2 Screen: slotted casing, 0.5 mm aperture, 20.0 mm (nominal), with end cap</p> <p>3 Annulus Fill: spoil</p> <p>4 Void Fill: spoil</p>
Qhl	0.0		Clay with Sand	
	1.0			
	2.0			
	3.0			
	4.0			
	5.0			
	6.0			
	7.0			
	8.0			
	9.0			
	10.0			

BORE NAME: GP22

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73372
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.100 m at 18-Dec-2006

LOCATION

North: 7401012.000 m
East: 479361.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 330.150 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 17-Dec-2006
Completed: 17-Dec-2006
Drilled Depth: 1.0
Drilling Company: Global Groundwater
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 1.0	Hand drill (42 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.600) - 0.000	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
0.000 - 0.920	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 0.9	Annulus fill, ID-OD: 20 mm to 42 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
0.9 - 1.0	Void fill, OD: 42 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.3	Sand with Clay	Upper Lake Bed Sequence
0.3 - 1.0	Clay with Sand	Upper Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

0.0 - 0.3 **Sand (with Clay):** Pale green, fine sand - coarse sand, gypsum, seed and crystalline gypsum.

0.3 - 1.0 **Clay (with Sand):** Pale orange-brown, fine sand - medium sand, gypsum, medium to high plasticity.

Clay (with Sand): Refusal.

Reward Minerals Ltd - Composite Log

Bore ID:
GP23


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73373

DATE COMMENCED: 17-Dec-2006
DATE COMPLETED: 17-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: Global Groundwater
Tag ID: Not tagged.

Drilling Method: Hand Drill
Bore Diameter: 42 mm

Northing: 7401111.000 m
Easting: 474211.000 m

Surface RL: 331.300 m
Scheme: GDA94 (Z51)



BORE NAME: GP23

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73373
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.000 m at 18-Dec-2006

LOCATION

North: 7401111.000 m
East: 474211.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 331.300 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 17-Dec-2006
Completed: 17-Dec-2006
Drilled Depth: 0.9
Drilling Company: Global Groundwater
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 0.9	Hand drill (42 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.545) - (0.025)	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
(0.025) - 0.895	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 0.9	Annulus fill, ID-OD: 20 mm to 42 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
0.9 - 0.9	Void fill, OD: 42 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.1	Clay with Sand	Upper Lake Bed Sequence
0.1 - 0.2	Sand with Clay	Upper Lake Bed Sequence
0.2 - 0.4	Clay with Sand	Aeolian Deposit
0.4 - 0.9	Sand with Silt	Aeolian Deposit

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 0.1 **Clay (with Sand)**: Green, quartz-gypsum, medium plasticity.
- 0.1 - 0.2 **Sand (with Clay)**: Green-brown, fine sand - coarse sand, gypsum.
- 0.2 - 0.4 **Clay (with Sand)**: Green, medium to high plasticity.
- 0.4 - 0.9 **Sand (with Silt)**: Orange-brown, fine sand - medium sand, quartz-gypsum, seed gypsum, trace black heavy mineral sand. **Sand (with Silt)**: Refusal.

Reward Minerals Ltd - Composite Log

Bore ID:
GP24




CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73374

DATE COMMENCED: 17-Dec-2006
DATE COMPLETED: 17-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: Global Groundwater
Tag ID: Not tagged.

Drilling Method: Hand Drill
Bore Diameter: 42 mm

Northing: 7401120.000 m
Easting: 469161.000 m

Surface RL: 329.300 m
Scheme: GDA94 (Z51)

Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Construction Diagram
QhI	0.0		Clay with Sand	 <p> 1 Bore Casing: unplasticised polyvinylchloride uPVC, Class 12, 20.0 mm (nominal) 2 Annulus Fill: spoil 3 Screen: slotted casing, 0.5 mm aperture, 20.0 mm (nominal), with end cap </p>
Qhs	1.0		Sand with Clay	
	2.0			
	3.0			
	4.0			
	5.0			
	6.0			
	7.0			
	8.0			
	9.0			
	10.0			

BORE NAME: GP24

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73374
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: -0.020 m at 18-Dec-2006

LOCATION

North: 7401120.000 m
East: 469161.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 329.300 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 17-Dec-2006
Completed: 17-Dec-2006
Drilled Depth: 0.9
Drilling Company: Global Groundwater
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 0.9	Hand drill (42 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.510) - 0.050	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
0.050 - 0.970	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 0.9	Annulus fill, ID-OD: 20 mm to 42 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.5	Clay with Sand	Upper Lake Bed Sequence
0.5 - 0.9	Sand with Clay	Upper Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 0.5 **Clay (with Sand):** Dominant, green-brown, fine sand - medium sand, quartz-gypsum, medium to high plasticity, fine to coarse crystalline and seed gypsum . **Sand:** Trace, black, heavy mineral sand.
- 0.5 - 0.9 **Sand (with Clay):** Green-brown, fine sand - coarse sand, gypsum-quartz, seed and crystalline gypsum, fine to medium grained quartz. **Sand (with Clay):** Refusal.

Reward Minerals Ltd - Composite Log

Bore ID:

GP25


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73375

DATE COMMENCED: 17-Dec-2006
DATE COMPLETED: 17-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: Global Groundwater
Tag ID: Not tagged.

Drilling Method: Hand Drill
Bore Diameter: 42 mm

Northing: 7400929.000 m
Easting: 464043.000 m

Surface RL: 331.450 m
Scheme: GDA94 (Z51)



BORE NAME: GP25

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73375
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: -0.005 m at 18-Dec-2006

LOCATION

North: 7400929.000 m
East: 464043.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 331.450 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 17-Dec-2006
Completed: 17-Dec-2006
Drilled Depth: 1.0
Drilling Company: Global Groundwater
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 1.0	Hand drill (42 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.490) - 0.060	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
0.060 - 1.010	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 1.0	Annulus fill, ID-OD: 20 mm to 42 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.7	Clay with Sand	Upper Lake Bed Sequence
0.7 - 1.0	Sand with Clay	Upper Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 0.7 **Clay (with Sand):** Green, fine sand - coarse sand, gypsum-quartz, medium plasticity, fine to medium grained quartz.
- 0.7 - 1.0 **Sand (with Clay):** Green, fine sand - coarse sand, gypsum.

Reward Minerals Ltd - Composite Log

Bore ID:
GP26


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73376

DATE COMMENCED: 17-Dec-2006
DATE COMPLETED: 17-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: Global Groundwater
Tag ID: Not tagged.

Drilling Method: Hand Drill
Bore Diameter: 42 mm

Northing: 7395465.000 m
Easting: 470142.000 m

Surface RL: 329.100 m
Scheme: GDA94 (Z51)



BORE NAME: GP26

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73376
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.000 m at 18-Dec-2006

LOCATION

North: 7395465.000 m
East: 470142.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 329.100 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006). Note the slotted casing sits above ground surface by 0.242 m

DRILLING DETAILS

Commenced: 17-Dec-2006
Completed: 17-Dec-2006
Drilled Depth: 0.7
Drilling Company: Global Groundwater
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 0.7	Hand drill (42 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.782) - (0.242)	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
(0.242) - 0.678	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 0.7	Annulus fill, ID-OD: 20 mm to 42 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
0.7 - 0.7	Void fill, OD: 42 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.1	Sand with Silt	Upper Lake Bed Sequence
0.1 - 0.3	Clay with Sand	Upper Lake Bed Sequence
0.3 - 0.7	Sand with Clay	Aeolian Deposit

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 0.1 **Sand (with Silt)**: Green, fine sand - coarse sand, gypsum.
- 0.1 - 0.3 **Clay (with Sand)**: Green-brown, high plasticity, with organic matter.
- 0.3 - 0.7 **Sand (with Clay)**: Fine sand, mostly medium sand, quartz-gypsum, seed gypsum, trace black heavy mineral sand. **Sand (with Clay)**: Refusal.

Reward Minerals Ltd - Composite Log

Bore ID:
GP27


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73377

DATE COMMENCED: 17-Dec-2006
DATE COMPLETED: 17-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: Global Groundwater
Tag ID: Not tagged.

Drilling Method: Hand Drill
Bore Diameter: 42 mm

Northing: 7395531.000 m
Easting: 474278.000 m

Surface RL: 329.600 m
Scheme: GDA94 (Z51)



BORE NAME: GP27

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73377
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.040 m at 18-Dec-2006

LOCATION

North: 7395531.000 m
East: 474278.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 329.600 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 17-Dec-2006
Completed: 17-Dec-2006
Drilled Depth: 0.8
Drilling Company: Global Groundwater
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 0.8	Hand drill (42 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.660) - (0.160)	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
(0.160) - 0.754	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 0.8	Annulus fill, ID-OD: 20 mm to 42 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

Depth (m bgl)	Construction
0.8 - 0.8	Void fill, OD: 42 mm, spoil. Backfill of hole through partial collapse of bore.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.1	Sand with Silt	Upper Lake Bed Sequence
0.1 - 0.2	Clay with Sand	Upper Lake Bed Sequence
0.2 - 0.4	Sand with Silt	Upper Lake Bed Sequence
0.4 - 0.8	Clay with Sand	Upper Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 0.1 **Sand (with Silt):** Green, fine sand - coarse sand, gypsum.
- 0.1 - 0.2 **Clay (with Sand):** Green, fine sand - coarse sand, gypsum, medium plasticity.
- 0.2 - 0.4 **Sand (with Silt):** Pale orange, fine sand - medium sand, quartz-gypsum.
- 0.4 - 0.8 **Clay (with Sand):** Orange-brown, fine sand - coarse sand, gypsum, medium to high plasticity, laminated. Refusal.

Reward Minerals Ltd - Composite Log

Bore ID:
GP28




CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73378

DATE COMMENCED: 17-Dec-2006
DATE COMPLETED: 17-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: Global Groundwater
Tag ID: Not tagged.

Drilling Method: Hand Drill
Bore Diameter: 42 mm

Northing: 7395491.000 m
Easting: 479420.000 m

Surface RL: 330.400 m
Scheme: GDA94 (Z51)

Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Construction Diagram
Qhs	0.0		Sand with Silt	 <p>1 Bore Casing: unplasticised polyvinylchloride uPVC, Class 12, 20.0 mm (nominal)</p> <p>2 Screen: slotted casing, 0.5 mm aperture, 20.0 mm (nominal), with end cap</p> <p>3 Annulus Fill: spoil</p>
Qhl			Clay with Sand	
	1.0			
	2.0			
	3.0			
	4.0			
	5.0			
	6.0			
	7.0			
	8.0			
	9.0			
	10.0			

BORE NAME: GP28

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73378
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.366 m at 18-Dec-2006

LOCATION

North: 7395491.000 m
East: 479420.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 330.400 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 17-Dec-2006
Completed: 17-Dec-2006
Drilled Depth: 0.8
Drilling Company: Global Groundwater
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 0.8	Hand drill (42 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.600) - (0.070)	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
(0.070) - 0.850	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 0.8	Annulus fill, ID-OD: 20 mm to 42 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.3	Sand with Silt	Upper Lake Bed Sequence
0.3 - 0.8	Clay with Sand	Upper Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

- 0.0 - 0.2 **Sand**: Orange-brown, fine sand - coarse sand, gypsum, with silt, white halite deposits at surface to 0.05 m depth.
- 0.2 - 0.3 **Sand (with Silt)**: Green, fine sand - coarse sand, gypsum.
- 0.3 - 0.4 **Clay (with Sand)**: Green, medium to high plasticity .
- 0.4 - 0.8 **Clay (with Sand)**: Red-brown, medium to high plasticity. **Clay (with Sand)**: Refusal.

Reward Minerals Ltd - Composite Log

Bore ID:
GP29


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73379

DATE COMMENCED: 17-Dec-2006
DATE COMPLETED: 17-Dec-2006
HYDROGEOLOGIST: K Bamblett
DRILLING COMPANY: Global Groundwater
Tag ID: Not tagged.

Drilling Method: Hand Drill
Bore Diameter: 42 mm

Northing: 7385866.000 m
Easting: 474464.000 m

Surface RL: 331.600 m
Scheme: GDA94 (Z51)



BORE NAME: GP29

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73379
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.234 m at 18-Dec-2006

LOCATION

North: 7385866.000 m
East: 474464.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 331.600 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 17-Dec-2006
Completed: 17-Dec-2006
Drilled Depth: 0.5
Drilling Company: Global Groundwater
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 0.5	Hand drill (42 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(1.035) - (0.405)	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
(0.405) - 0.515	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 0.5	Annulus fill, ID-OD: 20 mm to 42 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG



Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.5	Sand with Silt	Upper Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

0.0 - 0.5 **Sand (with Silt):** Pale orange-brown, fine sand - coarse sand, gypsum, seed gypsum, becomes coarse between 0.2 and 0.23 m. Refusal.

Reward Minerals Ltd - Composite Log						Bore ID: GP30
CLIENT: Reward Minerals Ltd		DATE COMMENCED: 17-Dec-2006				
PROJECT: Lake Disappointment Drilling		DATE COMPLETED: 17-Dec-2006				
LOCATION: Lake Disappointment		HYDROGEOLOGIST: K Bamblett				
SITE: Not recorded.		DRILLING COMPANY: Global Groundwater				
Database ID: 73380		Tag ID: Not tagged.				
Drilling Method: Hand Drill		Northing: 7384180.000 m		Surface RL: 331.200 m		
Bore Diameter: 42 mm		Easting: 479382.000 m		Scheme: GDA94 (Z51)		
Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Construction Diagram		
Qh1	0.0		Sand	 <p> 1 Bore Casing: unplasticised polyvinylchloride uPVC, Class 12, 20.0 mm (nominal) 2 Screen: slotted casing, 0.5 mm aperture, 20.0 mm (nominal), with end cap 3 Annulus Fill: spoil </p>		
	0.168		Clay with Sand			
	0.500					
	1.0					
	2.0					
	3.0					
	4.0					
	5.0					
	6.0					
	7.0					
	8.0					
	9.0					
	10.0					
	11.0					

BORE NAME: GP30

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73380
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: 0.168 m at 18-Dec-2006

LOCATION

North: 7384180.000 m
East: 479382.000 m
Coordinate System: GDA94 (Z51)
Method: GPS
Directions: None specified.
Elevation: 331.200 m (+/-0.050 m)

SUMMARY COMMENTS

This is a summary log; please refer to Global Groundwater's Lake Disappointment Bore Completion and Test Pumping Report (September, 2007) bore logs for greater detail. Elevation (assumed from ground) from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd, 2008); superseding elevations in Lake Disappointment Bore Completion and Test Pumping Report (Global Groundwater, 2007). Casing diameter and class sourced from Proposed Water Level Monitoring Piezometer Construction (EARTHtec Drilling Services, 2006)

DRILLING DETAILS

Commenced: 17-Dec-2006
Completed: 17-Dec-2006
Drilled Depth: 0.5
Drilling Company: Global Groundwater
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 0.5	Hand drill (42 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(1.050) - (0.400)	Casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	None.
(0.400) - 0.520	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 20 mm (nominal), joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 0.5	Annulus fill, ID-OD: 20 mm to 42 mm, spoil. Backfill of hole through partial collapse of bore.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 0.1	Sand	Upper Lake Bed Sequence
0.1 - 0.5	Clay with Sand	Upper Lake Bed Sequence

LITHOLOGICAL DESCRIPTIONS

Logged by: K Bamblett

Depth (m bgl)

0.0 - 0.1 **Sand**: Green-brown, fine sand - coarse sand, gypsum.

0.1 - 0.2 **Clay (with Sand)**: Green-brown, fine sand - coarse sand, gypsum, low plasticity .

0.2 - 0.5 **Clay (with Sand)**: Orange-brown, fine sand - coarse sand, gypsum-quartz, medium plasticity, seed and crystalline gypsum, more green with depth.

Reward Minerals Ltd - Composite Log					Bore ID: AGP31						
CLIENT:		Reward Minerals Ltd		DATE COMMENCED:		Not recorded.					
PROJECT:		Lake Disappointment Drilling		DATE COMPLETED:		Not recorded.					
LOCATION:		Lake Disappointment		HYDROGEOLOGIST:		Not recorded.					
SITE:		Not recorded.		DRILLING COMPANY:		Not recorded.					
Database ID:		73381		Tag ID:		Not tagged.					
Drilling Method:		Not recorded.		Northing:		7395377.000 m		Surface RL:		331.500 m	
Bore Diameter:		Not recorded.		Easting:		491627.000 m		Scheme:		GDA94 (Z51)	
Geological Unit	Depth (m)	Graphic Log	Summary Lithology				Construction Diagram				
None recorded	0.0		None recorded.				None recorded.				
	1.0										
	2.0										
	3.0										
	4.0										
	5.0										
	6.0										
	7.0										
	8.0										
	9.0										
	10.0										

BORE NAME: AGP31

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID:	73381
Tag ID:	Not tagged
Owner:	Reward Minerals Ltd
Status:	Functional
Purpose:	Exploration/research
Water level:	Not measured

LOCATION

North:	7395377.000 m
East:	491627.000 m
Coordinate System:	GDA94 (Z51)
Method:	GPS
Directions:	None specified.
Elevation:	331.500 m (+/-0.050 m)

SUMMARY COMMENTS

All data sourced from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd 2008) .
Elevation assumed from ground. Depth: 1 m

DRILLING DETAILS

Commenced:	Not specified.
Completed:	Not specified.
Drilled Depth:	
Drilling Company:	Not specified.
Drilling Rig:	Not specified.
Drilling Rods:	Not specified.
Drilling Collar:	Not specified.
Compressor:	Not specified.

Drillers

No drillers recorded.

Drilling Methods

No drilling methods recorded.

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS

No samples recorded.

Reward Minerals Ltd - Composite Log						Bore ID: AGP32	
CLIENT:		Reward Minerals Ltd		DATE COMMENCED:		Not recorded.	
PROJECT:		Lake Disappointment Drilling		DATE COMPLETED:		Not recorded.	
LOCATION:		Lake Disappointment		HYDROGEOLOGIST:		Not recorded.	
SITE:		Not recorded.		DRILLING COMPANY:		Not recorded.	
Database ID:		73382		Tag ID:		Not tagged.	
Drilling Method:		Not recorded.		Northing:		7389548.000 m	
Bore Diameter:		Not recorded.		Easting:		494090.000 m	
				Surface RL:		331.500 m	
				Scheme:		GDA94 (Z51)	
Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Construction Diagram			
None recorded	0.0						
	1.0						
	2.0						
	3.0						
	4.0						
	5.0		None recorded.	None recorded.			
	6.0						
	7.0						
	8.0						
	9.0						
	10.0						

BORE NAME: AGP32

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID:	73382
Tag ID:	Not tagged
Owner:	Reward Minerals Ltd
Status:	Indeterminate
Purpose:	Exploration/research
Water level:	Not measured

LOCATION

North:	7389548.000 m
East:	494090.000 m
Coordinate System:	GDA94 (Z51)
Method:	GPS
Directions:	None specified.
Elevation:	331.500 m (+/-0.050 m)

SUMMARY COMMENTS

All data sourced from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd 2008) .
Elevation assumed from ground. Depth: 1 m

DRILLING DETAILS

Commenced:	Not specified.
Completed:	Not specified.
Drilled Depth:	
Drilling Company:	Not specified.
Drilling Rig:	Not specified.
Drilling Rods:	Not specified.
Drilling Collar:	Not specified.
Compressor:	Not specified.

Drillers

No drillers recorded.

Drilling Methods

No drilling methods recorded.

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS

No samples recorded.

Reward Minerals Ltd - Composite Log					Bore ID: AGP33						
CLIENT:		Reward Minerals Ltd		DATE COMMENCED:		Not recorded.					
PROJECT:		Lake Disappointment Drilling		DATE COMPLETED:		Not recorded.					
LOCATION:		Lake Disappointment		HYDROGEOLOGIST:		Not recorded.					
SITE:		Not recorded.		DRILLING COMPANY:		Not recorded.					
Database ID:		73383		Tag ID:		Not tagged.					
Drilling Method:		Not recorded.		Northing:		7400909.000 m		Surface RL:		331.500 m	
Bore Diameter:		Not recorded.		Easting:		493589.000 m		Scheme:		GDA94 (Z51)	
Geological Unit	Depth (m)	Graphic Log	Summary Lithology				Construction Diagram				
None recorded	0.0		None recorded.				None recorded.				
	1.0										
	2.0										
	3.0										
	4.0										
	5.0										
	6.0										
	7.0										
	8.0										
	9.0										
	10.0										

BORE NAME: AGP33

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID:	73383
Tag ID:	Not tagged
Owner:	Reward Minerals Ltd
Status:	Indeterminate
Purpose:	Exploration/research
Water level:	Not measured

LOCATION

North:	7400909.000 m
East:	493589.000 m
Coordinate System:	GDA94 (Z51)
Method:	GPS
Directions:	None specified.
Elevation:	331.500 m (+/-0.050 m)

SUMMARY COMMENTS

All data sourced from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd 2008) .
Elevation assumed from ground. Depth: 1m

DRILLING DETAILS

Commenced:	Not specified.
Completed:	Not specified.
Drilled Depth:	
Drilling Company:	Not specified.
Drilling Rig:	Not specified.
Drilling Rods:	Not specified.
Drilling Collar:	Not specified.
Compressor:	Not specified.

Drillers

No drillers recorded.

Drilling Methods

No drilling methods recorded.

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS

No samples recorded.

Reward Minerals Ltd - Composite Log						Bore ID: AGP34
CLIENT:		Reward Minerals Ltd		DATE COMMENCED:		Not recorded.
PROJECT:		Lake Disappointment Drilling		DATE COMPLETED:		Not recorded.
LOCATION:		Lake Disappointment		HYDROGEOLOGIST:		Not recorded.
SITE:		Not recorded.		DRILLING COMPANY:		Not recorded.
Database ID:		73384		Tag ID:		Not tagged.
Drilling Method:		Not recorded.		Northing:		7423125.000 m
Bore Diameter:		Not recorded.		Easting:		486167.000 m
				Surface RL:		331.500 m
				Scheme:		GDA94 (Z51)
Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Construction Diagram		
None recorded	0.0					
	1.0					
	2.0					
	3.0					
	4.0					
	5.0		None recorded.	None recorded.		
	6.0					
	7.0					
	8.0					
	9.0					
	10.0					

BORE NAME: AGP34

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID:	73384
Tag ID:	Not tagged
Owner:	Reward Minerals Ltd
Status:	Indeterminate
Purpose:	Exploration/research
Water level:	Not measured

LOCATION

North:	7423125.000 m
East:	486167.000 m
Coordinate System:	GDA94 (Z51)
Method:	GPS
Directions:	None specified.
Elevation:	331.500 m (+/-0.050 m)

SUMMARY COMMENTS

All data sourced from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd 2008) .
Elevation assumed from ground. Depth: 1m

DRILLING DETAILS

Commenced:	Not specified.
Completed:	Not specified.
Drilled Depth:	
Drilling Company:	Not specified.
Drilling Rig:	Not specified.
Drilling Rods:	Not specified.
Drilling Collar:	Not specified.
Compressor:	Not specified.

Drillers

No drillers recorded.

Drilling Methods

No drilling methods recorded.

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS

No samples recorded.

Reward Minerals Ltd - Composite Log					Bore ID: AGP35						
CLIENT:		Reward Minerals Ltd		DATE COMMENCED:		Not recorded.					
PROJECT:		Lake Disappointment Drilling		DATE COMPLETED:		Not recorded.					
LOCATION:		Lake Disappointment		HYDROGEOLOGIST:		Not recorded.					
SITE:		Not recorded.		DRILLING COMPANY:		Not recorded.					
Database ID:		73385		Tag ID:		Not tagged.					
Drilling Method:		Not recorded.		Northing:		7423125.000 m		Surface RL:		331.500 m	
Bore Diameter:		Not recorded.		Easting:		487505.000 m		Scheme:		GDA94 (Z51)	
Geological Unit	Depth (m)	Graphic Log	Summary Lithology				Construction Diagram				
None recorded	0.0		None recorded.				None recorded.				
	1.0										
	2.0										
	3.0										
	4.0										
	5.0										
	6.0										
	7.0										
	8.0										
	9.0										
10.0											

BORE NAME: AGP35

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID:	73385
Tag ID:	Not tagged
Owner:	Reward Minerals Ltd
Status:	Indeterminate
Purpose:	Exploration/research
Water level:	Not measured

LOCATION

North:	7423125.000 m
East:	487505.000 m
Coordinate System:	GDA94 (Z51)
Method:	GPS
Directions:	None specified.
Elevation:	331.500 m (+/-0.050 m)

SUMMARY COMMENTS

All data sourced from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd 2008) .
Elevation assumed from ground. Depth: 1m

DRILLING DETAILS

Commenced:	Not specified.
Completed:	Not specified.
Drilled Depth:	
Drilling Company:	Not specified.
Drilling Rig:	Not specified.
Drilling Rods:	Not specified.
Drilling Collar:	Not specified.
Compressor:	Not specified.

Drillers

No drillers recorded.

Drilling Methods

No drilling methods recorded.

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS

No samples recorded.

Reward Minerals Ltd - Composite Log				Bore ID: AGP36	
CLIENT: Reward Minerals Ltd		DATE COMMENCED: Not recorded.			
PROJECT: Lake Disappointment Drilling		DATE COMPLETED: Not recorded.			
LOCATION: Lake Disappointment		HYDROGEOLOGIST: Not recorded.			
SITE: Not recorded.		DRILLING COMPANY: Not recorded.			
Database ID: 73386		Tag ID: Not tagged.			
Drilling Method: Not recorded.		Northing: 7423125.000 m		Surface RL: 331.500 m	
Bore Diameter: Not recorded.		Easting: 491056.000 m		Scheme: GDA94 (Z51)	
Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Construction Diagram	
None recorded	0.0				
	1.0				
	2.0				
	3.0				
	4.0				
	5.0		None recorded.	None recorded.	
	6.0				
	7.0				
	8.0				
	9.0				
	10.0				

BORE NAME: AGP36

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID:	73386
Tag ID:	Not tagged
Owner:	Reward Minerals Ltd
Status:	Indeterminate
Purpose:	Exploration/research
Water level:	Not measured

LOCATION

North:	7423125.000 m
East:	491056.000 m
Coordinate System:	GDA94 (Z51)
Method:	GPS
Directions:	None specified.
Elevation:	331.500 m (+/-0.050 m)

SUMMARY COMMENTS

All data sourced from Lake Disappointment Potassium Sulphate (K₂SO₄) Resource Report (CoxsRocks Pty Ltd 2008) .
Elevation assumed from ground. Depth: 1m

DRILLING DETAILS

Commenced:	Not specified.
Completed:	Not specified.
Drilled Depth:	
Drilling Company:	Not specified.
Drilling Rig:	Not specified.
Drilling Rods:	Not specified.
Drilling Collar:	Not specified.
Compressor:	Not specified.

Drillers

No drillers recorded.

Drilling Methods

No drilling methods recorded.

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS

No samples recorded.

Hole ID	Drilling Method	Easting, Zone 51	Northing	RL (ground) (mAHD)	Stickup (m)	Drilled Depth (m)	Diameter (mm)	Ream Diameter (mm)	Ream To (m)	Casing Diameter (mm)
LDRC1409	RC Rotary Air/Percussion	466980.00	7420740.00	-	-	101	100	-	-	50?
LDRC1410	RC Rotary Air/Percussion	466560.00	7425440.00	-	-	101	100	-	-	-
LDRC1411	RC Rotary Air/Percussion	469200.00	7427950.00	-	-	102	100	-	-	-
LDRC1412	RC Rotary Air/Percussion	472470.00	7430930.00	-	-	102	100	-	-	-
LDRC1413	RC Rotary Air/Percussion	475240.00	7434030.00	-	-	78	100	-	-	-
LDRC1414	RC Rotary Air/Percussion	476870.00	7436710.00	-	-	102	100	-	-	-
LDRC1416	RC Rotary Air/Percussion	480130.00	7436730.00	-	-	101	100	-	-	-
LDRC1417	RC Rotary Air/Percussion	483840.00	7437110.00	-	-	114	100	-	-	-
LDRC1418	RC Rotary Air/Percussion	488270.00	7436780.00	-	-	94	100	-	-	-
LDRC1419	RC Rotary Air/Percussion	492080.00	7437930.00	-	-	95	100	-	-	-
LDRC1420	RC Rotary Air/Percussion	496190.00	7438730.00	-	-	125	100	-	-	-
LDRC1421	RC Rotary Air/Percussion	501400.00	7438720.00	-	-	125	100	-	-	-
LDRC1459										
LDRC1460	RC Rotary Air/Percussion	481400.00	7429100.00	-	-	102	100	-	-	-
LDRC1461	RC Rotary Air/Percussion	481560.00	7425711.00	-	-	132	100	-	-	-
LDRC1462	Rotary Blade/Percussion	481132.00	7427547.00	-	-	156	108	-	-	50
LDRC1463	Conventional 650/350 PSI Reverse Circulation (blade and hammer)	481130.00	7427520.00	-	-	120	100	225.00	120.00	150
LDRC1601	Rotary Air/Percussion	482684.70	7441245.00	354.430	0.590	120	114	292	120	200
LDRC1602	Rotary Air/Percussion	483335.19	7441999.43	354.460	0.620	100	114	292	100	200
LDRC1603	Rotary Air/Percussion	482211.00	7443076.00	-	-	138	127	-	-	-
LDRC1604	Rotary Air/Percussion	483561.20	7442676.39	352.190	0.480	130	127	-	-	50
LDRC1605	Rotary Air/Percussion	481924.68	7440927.37	353.520	0.345	132	127	-	-	50

Notes

Aquifer test data available
Missing/assumed data

Hole ID	Casing Type	Blank Casing (m)		Slotted Casing (m)		Aperture (mm)	Gravel Pack Size (mm)	Flow Rate (L/s)	Completion
		Top	Bottom	Top	Bottom				
LDRC1409	uPVC	-	-	-	-	0.5?	1.5 - 3?	-	Concrete seal and cap?
LDRC1410	-	-	-	-	-	-	-	-	-
LDRC1411	-	-	-	-	-	-	-	-	-
LDRC1412	-	-	-	-	-	-	-	-	-
LDRC1413	-	-	-	-	-	-	-	-	-
LDRC1414	-	-	-	-	-	-	-	-	-
LDRC1416	-	-	-	-	-	-	-	-	-
LDRC1417	-	-	-	-	-	-	-	-	-
LDRC1418	-	-	-	-	-	-	-	-	-
LDRC1419	-	-	-	-	-	-	-	-	-
LDRC1420	-	-	-	-	-	-	-	-	-
LDRC1421	-	-	-	-	-	-	-	-	-
LDRC1459	-	-	-	-	-	-	-	-	-
LDRC1460	-	-	-	-	-	-	-	5.0	-
LDRC1461	-	-	-	-	-	-	-	5.0	-
LDRC1462	uPVC	-	-	0.00	46.00	0.5	1.5-3	8.0	-
LDRC1463	uPVC	-	-	0.00	120.00	1.0	-	25.0	-
LDRC1601	uPVC Class 12	0	6	6	12	1.0	>1.5 & >5	4.1	Cement seal to natural ground surface, concrete plinth, and cap
		12	24	24	108				
		108	120						
LDRC1602	uPVC Class 12	0	27	27	93	1.0	>1.5 & >5	18.0	Cement seal to natural ground surface, concrete plinth, and cap
		93	99						
LDRC1603	-	-	-	-	-	-	-	1.8	-
LDRC1604	uPVC Class 12	0	6	6	18	0.5	1.5-3	2.3	-
LDRC1605	uPVC Class 12	0	6	6	18	0.5	1.5-3	2.0	-

Notes

Hole ID	Well Development	Geology Data Avail.?	Status	Type	Tenements	Purpose
LDRC1409	Flushed with clean water and airlift 8 hrs?	N	Functional?	Monitoring Bore	ELs45/3285, 45/3286 and L45/302 (registered under Holocene Pty Ltd (Reward Minerals Ltd)	Investigate Palaeovalley system - prelim reconnaissance work
LDRC1410	-	N	-	Monitoring Bore	ELs45/3285, 45/3286 and L45/302 (registered under Holocene Pty Ltd (Reward Minerals Ltd)	Investigate Palaeovalley system - prelim reconnaissance work
LDRC1411	-	N	-	Monitoring Bore	ELs45/3285, 45/3286 and L45/302 (registered under Holocene Pty Ltd (Reward Minerals Ltd)	Investigate Palaeovalley system - prelim reconnaissance work
LDRC1412	-	N	-	Monitoring Bore	ELs45/3285, 45/3286 and L45/302 (registered under Holocene Pty Ltd (Reward Minerals Ltd)	Investigate Palaeovalley system - prelim reconnaissance work
LDRC1413	-	N	-	Monitoring Bore	ELs45/3285, 45/3286 and L45/302 (registered under Holocene Pty Ltd (Reward Minerals Ltd)	Investigate Palaeovalley system - prelim reconnaissance work
LDRC1414	-	N	-	Monitoring Bore	ELs45/3285, 45/3286 and L45/302 (registered under Holocene Pty Ltd (Reward Minerals Ltd)	Investigate Palaeovalley system - prelim reconnaissance work
LDRC1416	-	N	-	Monitoring Bore	ELs45/3285, 45/3286 and L45/302 (registered under Holocene Pty Ltd (Reward Minerals Ltd)	Investigate Palaeovalley system - prelim reconnaissance work
LDRC1417	-	N	-	Monitoring Bore	ELs45/3285, 45/3286 and L45/302 (registered under Holocene Pty Ltd (Reward Minerals Ltd)	Investigate Palaeovalley system - prelim reconnaissance work
LDRC1418	-	N	-	Monitoring Bore	ELs45/3285, 45/3286 and L45/302 (registered under Holocene Pty Ltd (Reward Minerals Ltd)	Investigate Palaeovalley system - prelim reconnaissance work
LDRC1419	-	N	-	Monitoring Bore	ELs45/3285, 45/3286 and L45/302 (registered under Holocene Pty Ltd (Reward Minerals Ltd)	Investigate Palaeovalley system - prelim reconnaissance work
LDRC1420	-	N	-	Monitoring Bore	ELs45/3285, 45/3286 and L45/302 (registered under Holocene Pty Ltd (Reward Minerals Ltd)	Investigate Palaeovalley system - prelim reconnaissance work
LDRC1421	-	N	-	Monitoring Bore	ELs45/3285, 45/3286 and L45/302 (registered under Holocene Pty Ltd (Reward Minerals Ltd)	Investigate Palaeovalley system - prelim reconnaissance work
LDRC1459		N		Monitoring Bore	-	-
LDRC1460	-	N	-	Monitoring Bore	ELs45/3285, 45/3286 and L45/302 (registered under Holocene Pty Ltd (Reward Minerals Ltd)	Investigate Palaeovalley system - prelim reconnaissance work
LDRC1461	-	N	-	Monitoring Bore	ELs45/3285 and L45/302 (registered under Holocene Pty Ltd (Reward Minerals Ltd)	Investigate Palaeovalley system - prelim reconnaissance work (last two holes of a 15 hole program after two failed)
LDRC1462	-	N	-	Monitoring Bore	ELs45/3285 and L45/302 (registered under Holocene Pty Ltd (Reward Minerals Ltd)	Investigate Palaeovalley system - prelim reconnaissance work (last two holes of a 15 hole program after two failed)
LDRC1463	-	N	-	Monitoring Bore	EL45/2801	-
LDRC1601	Airlift 96m @ 4.1l/s for 4 hours	Y	Functional	Production Bore	-	-
LDRC1602	Airlift 96m @ 18l/s for 4 hours	Y	Functional	Production Bore	-	-
LDRC1603	-	N	Not Functional	NA	-	-
LDRC1604	-	Y	-	Monitoring Bore	-	-
LDRC1605	-	Y	-	Monitoring Bore	-	-

Notes

Hole ID	Access	Comments
LDRC1409	Via Canning Stock Route	Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings. Basement not reached due to drilling difficulties.
LDRC1410	Via Canning Stock Route	Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings. Basement not reached due to drilling difficulties.
LDRC1411	Via Canning Stock Route	Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings
LDRC1412	Via Canning Stock Route	Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings
LDRC1413	Via Canning Stock Route	Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings
LDRC1414	Via Canning Stock Route	Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings
LDRC1416	Via Canning Stock Route	Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings
LDRC1417	Via Canning Stock Route	Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings
LDRC1418	Via Canning Stock Route	Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings
LDRC1419	Via Canning Stock Route	Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings. Basement not reached due to drilling difficulties.
LDRC1420	Via Canning Stock Route	Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings
LDRC1421	Via Canning Stock Route	Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings
LDRC1459	-	Failed? Collapsed due to high flow rates? See April 2014 ASX reports
LDRC1460	Via Canning Stock Route	Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings
LDRC1461	Via Wiljabu Track	LDDH1402 was drilled to twin this
LDRC1462	Via Wiljabu Track	LDDH1401 was drilled to twin this
LDRC1463	-	During airlifting, air and water discharged from LDDH1401 (~35 m away). Pump testing done in 2014 (as per ASX report 13 Oct 2014) but we have no data. >4L/s CRT.
LDRC1601	-	-
LDRC1602	-	-
LDRC1603	-	Abandoned. Why? Backfilled with what?
LDRC1604	-	-
LDRC1605	-	-

Notes

Reward Minerals Ltd - Composite Log

Bore ID:
LDRC1601


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73315

DATE COMMENCED: 12-Mar-2016
DATE COMPLETED: 12-Mar-2016
HYDROGEOLOGIST: Not recorded.
DRILLING COMPANY: NDRC Drilling Pty Ltd
Tag ID: Not tagged.

Drilling Method: Rotary Hammer
Bore Diameter: 292 mm

Northing: 7441245.000 m
Easting: 482684.700 m

Surface RL: 354.430 m
Scheme: GDA94 (Z51)



BORE NAME: LDRC1601

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73315
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Mining
Water level: 10.300 m at 12-Mar-2016

LOCATION

North: 7441245.000 m
East: 482684.700 m
Coordinate System: GDA94 (Z51)
Method: Differential GPS (+/-0.040 m)
Directions: None specified.
Elevation: 354.430 m (+/-0.040 m)

SUMMARY COMMENTS

Bore collars were reamed to 355mm; fitted with 300mm DIA UPVC Solid Casing; grouted and cemented in place to natural surface. Pilot hole was reamed to 290mm DIA and 200mm DIA UPVC solid casings and screens (1mm slot) were installed as required. Filter/washed gravels(> 5mmDIA) packs were installed to an average 3m above the screen. A bentonite seal was installed above the gravel pack and, where required, the bore annulus was backfilled using clean drilling cuttings. A concrete plinth and 250mm DIA 0.90m height steel riser with lockable cap were then installed to protect integrity of the bores. Drilling method; Rotary Air/Percussion.

DRILLING DETAILS

Commenced: 12-Mar-2016
Completed: 12-Mar-2016
Drilled Depth: 120.0
Drilling Company: NDRC Drilling Pty Ltd
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 120.0	Reverse circulation hammer (200 mm)	Air

CONSTRUCTION

Fixtures

Depth (m bgl)	Construction
(0.900) - 0.000	Lockable head cap, steel, circle, 250 mm (nominal).
(0.100) - 0.000	Concrete base, concrete, square, 500 mm (nominal).

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.590) - 6.000	Casing, unplasticised polyvinylchloride uPVC, Class 12, 200 mm (nominal), wall thickness 11.1 mm, joins: unknown.	None.
0.000 - 3.000	Casing, unplasticised polyvinylchloride uPVC, Class 12, 300 mm (nominal), wall thickness 11.1 mm, joins: unknown. Surface casing.	None.
6.000 - 12.000	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 200 mm (nominal), wall thickness 11.1 mm, joins: unknown.	1 mm aperture.
12.000 - 24.000	Casing, unplasticised polyvinylchloride uPVC, Class 12, 200 mm (nominal), wall thickness 11.1 mm, joins: unknown.	None.
24.000 - 108.000	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 200 mm (nominal), wall thickness 11.1 mm, joins: unknown.	1 mm aperture.
108.000 - 120.000	Casing, unplasticised polyvinylchloride uPVC, Class 12, 200 mm (nominal), wall thickness 11.1 mm, joins: unknown.	None.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 4.0	Gravel pack, ID-OD: 200 mm to 292 mm, spoil.
4.0 - 5.0	Seal, ID-OD: 200 mm to 292 mm, bentonite clay.
5.0 - 22.0	Gravel pack (1.5 mm to 5.0 mm), ID-OD: 200 mm to 290 mm, sand. Grain size estimate.
22.0 - 23.0	Seal, ID-OD: 200 mm to 290 mm, bentonite clay.
23.0 - 120.0	Gravel pack (1.5 mm to 5.0 mm), ID-OD: 200 mm to 290 mm, sand. Grain size estimate.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

Key: x - unspecified method

Date	Depth (m bgl)	Drill Rate (m/min)	Airlift Yield (L/s)	EC (uS/cm)	pH	Comment
12-Mar	9.0 - 9.0	-	0.50 ^x	-	-	
12-Mar	29.0 - 29.0	-	1.00 ^x	-	-	

Date	Depth (m bgl)	Drill Rate (m/min)	Airlift Yield (L/s)	EC (uS/cm)	pH	Comment
12-Mar	66.0 - 66.0	-	2.50 ^x	-	-	
12-Mar	88.0 - 88.0	-	4.10 ^x	-	-	Sample: No increase in water flow whilst drilling below.
12-Mar	96.0 - 96.0	-	4.10 ^x	-	-	Sample: No increase in water flow whilst drilling.

PARAMETERS MEASURED DURING DEVELOPMENT

Date	Time	Airlift Yield (L/s)	EC (uS/cm)	pH	Sediment	Water	Sediment
------	------	---------------------	------------	----	----------	-------	----------

12-Mar to 12-Mar: backwashing. Airlift 96m @ 4.1L/s for 4 hours.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 27.0	Sandstone	
27.0 - 29.0	Fractured sandstone	
29.0 - 65.0	Sandstone	
65.0 - 66.0	Fractured sandstone	
66.0 - 86.0	Sandstone	
86.0 - 88.0	Fractured sandstone	
88.0 - 120.0	Sandstone	

LITHOLOGICAL DESCRIPTIONS

Logged by:

Depth (m bgl)

- 0.0 - 1.0 **Unknown:** Topsoil (lithology not specified by logger). Comment: Dry
- 1.0 - 2.0 **Sandstone:** Extremely weathered rock.
- 2.0 - 3.0 **Sandstone:** Fresh rock.
- 3.0 - 5.0 **Sandstone:** Slightly weathered rock.
- 5.0 - 13.0 **Sandstone:** Fresh rock, with thin bands of weathering.
- 13.0 - 27.0 **Sandstone:** Fine sand - coarse sand, fresh rock. Comment: Dry
- 27.0 - 29.0 **Sandstone:** Fresh rock, Fractured.
- 29.0 - 65.0 **Sandstone:** Fine sand - coarse sand, fresh rock, with weathered bands.
- 65.0 - 66.0 **Sandstone:** Fresh rock, fractured.
- 66.0 - 86.0 **Sandstone:** Fine sand - coarse sand, fresh rock.
- 86.0 - 88.0 **Sandstone:** Fresh rock, fractured.
- 88.0 - 105.0 **Sandstone:** Fine sand - coarse sand, fresh rock.
- 105.0 - 120.0 **Sandstone:** Fresh rock, Fresh to weathered with depth.

Reward Minerals Ltd - Composite Log

Bore ID:
LDRC1602


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73316

DATE COMMENCED: 27-Mar-2016
DATE COMPLETED: 27-Mar-2016
HYDROGEOLOGIST: Not recorded.
DRILLING COMPANY: NDRC Drilling Pty Ltd
Tag ID: Not tagged.

Drilling Method: Rotary Hammer
Bore Diameter: 292 mm

Northing: 7441999.430 m
Easting: 483335.190 m

Surface RL: 354.460 m
Scheme: GDA94 (Z51)



BORE NAME: LDRC1602

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73316
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Mining
Water level: 10.050 m at 27-Mar-2016

LOCATION

North: 7441999.430 m
East: 483335.190 m
Coordinate System: GDA94 (Z51)
Method: Differential GPS (+/-0.050 m)
Directions: None specified.
Elevation: 354.460 m (+/-0.050 m)

SUMMARY COMMENTS

Bore collars were reamed to 355mm; fitted with 300mm DIA UPVC Solid Casing; grouted and cemented in place to natural surface. Pilot hole was reamed to 290mm DIA and 200mm DIA UPVC solid casings and screens (1mm slott) were installed as required. Filter/washed gravels(> 5mmDIA) packs were installed to an average 3m above the screen. A bentonite seal was installed above the gravel pack and, where required, the bore annulus was backfilled using clean drilling cuttings. A concrete plinth and 250mm DIA 0.90m height steel riser with lockable cap were then installed to protect integrity of the bores. Drilling method; Rotary Air/Percussion.

DRILLING DETAILS

Commenced: 27-Mar-2016
Completed: 27-Mar-2016
Drilled Depth: 100.0
Drilling Company: NDRC Drilling Pty Ltd
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 100.0	Reverse circulation hammer (292 mm)	Air

CONSTRUCTION

Fixtures

Depth (m bgl)	Construction
(0.900) - 0.000	Lockable head cap, steel, circle, 250 mm (nominal).
(0.100) - 0.000	Concrete base, concrete, square, 500 mm (nominal).

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.620) - 27.000	Casing, unplasticised polyvinylchloride uPVC, Class 12, 200 mm (nominal), wall thickness 11.1 mm, joins: unknown.	None.
0.000 - 3.000	Pipe, unplasticised polyvinylchloride uPVC, Class 12, 300 mm (nominal), wall thickness 11.1 mm, joins: unknown. Surface casing.	None.
27.000 - 93.000	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 200 mm (nominal), wall thickness 11.1 mm, joins: unknown.	1 mm aperture.
93.000 - 99.000	Casing, unplasticised polyvinylchloride uPVC, Class 12, 200 mm (nominal), wall thickness 11.1 mm, joins: unknown.	None.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 24.0	Annulus fill, ID-OD: 200 mm to 292 mm, spoil.
24.0 - 25.0	Seal, ID-OD: 200 mm to 292 mm, bentonite clay.
25.0 - 99.0	Gravel pack (1.5 mm to 5.0 mm), ID-OD: 200 mm to 292 mm, sand. Gravel pack size estimate.

Void Fill

Depth (m bgl)	Construction
99.0 - 100.0	Void fill (1.5 mm to 5.0 mm), OD: 292 mm, sand. Gravel size estimated.

PARAMETERS MEASURED DURING DRILLING

Key: x - unspecified method

Date	Depth (m bgl)	Drill Rate (m/min)	Airlift Yield (L/s)	EC (uS/cm)	pH	Comment
27-Mar	29.0 - 29.0	-	4.00 ^x	-	-	
27-Mar	68.0 - 68.0	-	10.00 ^x	-	-	Sample: Water flow increasing with depth beyond this point.
27-Mar	79.0 - 79.0	-	18.00 ^x	-	-	
27-Mar	96.0 - 96.0	-	18.00 ^x	-	-	

PARAMETERS MEASURED DURING DEVELOPMENT

Date	Time	Airlift Yield (L/s)	EC (uS/cm)	pH	Sediment	Water	Sediment
------	------	------------------------	---------------	----	----------	-------	----------

27-Mar to 27-Mar: backwashing. Airlift 96m @ 18L/s for 4 hours.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 1.0	Topsoil (lithology not specified)	
1.0 - 25.0	Sandstone	
25.0 - 29.0	Fractured sandstone	
29.0 - 67.0	Sandstone	
67.0 - 68.0	Fractured sandstone	
68.0 - 76.0	Sandstone	
76.0 - 79.0	Fractured sandstone	
79.0 - 88.0	Sandstone	
88.0 - 100.0	Fractured sandstone	

LITHOLOGICAL DESCRIPTIONS

Logged by:

Depth (m bgl)

0.0 - 1.0	Unknown: Topsoil (lithology not specified by logger). Comment: Dry
1.0 - 2.0	Sandstone: Extremely weathered rock.
2.0 - 3.0	Sandstone: Fresh rock.
3.0 - 10.0	Sandstone: Mostly fine sand, fresh rock, fresh to slightly weathered.
10.0 - 25.0	Sandstone: Fresh rock, with thin beds of weathering, <0.25m. Comment: Dry
25.0 - 29.0	Sandstone: Fresh rock, fractured. Comment: Moist
29.0 - 67.0	Sandstone: Fine sand - coarse sand, fresh rock, with small bands of weathering 33 - 66 m. Comment: Dry
67.0 - 68.0	Sandstone: Fresh rock, fractured.
68.0 - 76.0	Sandstone: Fine sand - coarse sand, fresh rock.
76.0 - 79.0	Sandstone: Fresh rock, fractured.
79.0 - 88.0	Sandstone: Mostly fine sand, fresh rock.
88.0 - 100.0	Sandstone: Slightly weathered rock, fractured.

Reward Minerals Ltd - Composite Log

Bore ID:
LDRC1603

CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73319

DATE COMMENCED: Mar-2016
DATE COMPLETED: Not recorded.
HYDROGEOLOGIST: Not recorded.
DRILLING COMPANY: Not recorded.
Tag ID: Not tagged.

Drilling Method: Rotary Hammer Northing: 7443076.000 m Surface RL: Not recorded
Bore Diameter: 127 mm Easting: 482211.000 m Scheme: GDA94 (Z51)

Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Airlift Yield (L/s)	Construction Diagram
None recorded	0.0				
	10.0				
None recorded	20.0				
	30.0				
None recorded	40.0				
	50.0				
None recorded	60.0				
	70.0		None recorded.		
None recorded	80.0				
	90.0				
None recorded	100.0				
	110.0				
None recorded	120.0				
	130.0				
None recorded	140.0			1.8	138.000

BORE NAME: LDRC1603

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73319
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Abandoned
Purpose: Monitoring
Water level: Not measured

LOCATION

North: 7443076.000 m
East: 482211.000 m
Coordinate System: GDA94 (Z51)
Method: Unknown
Directions: None specified.
Elevation: Not measured.

SUMMARY COMMENTS

Abandoned

DRILLING DETAILS

Commenced: Mar-2016
Completed: Not specified.
Drilled Depth: 138.0
Drilling Company: Not specified.
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 138.0	Reverse circulation hammer (127 mm)	Air

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

Key: x - unspecified method

Date	Depth (m bgl)	Drill Rate (m/min)	Airlift Yield (L/s)	EC (uS/cm)	pH	Comment
Mar	0.0 - 138.0	-	1.80 ^x	-	-	

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS

No samples recorded.

Reward Minerals Ltd - Composite Log

Bore ID:
LDRC1604


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73317

DATE COMMENCED: 31-Mar-2016 (estimate)
DATE COMPLETED: Not recorded.
HYDROGEOLOGIST: Not recorded.
DRILLING COMPANY: Not recorded.
Tag ID: Not tagged.

Drilling Method: Rotary Hammer
Bore Diameter: 127 mm

Northing: 7442676.390 m
Easting: 483561.200 m

Surface RL: 352.190 m
Scheme: GDA94 (Z51)



BORE NAME: LDRC1604

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73317
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Monitoring
Water level: 7.650 m at 31-Mar-2016 (estimate)

LOCATION

North: 7442676.390 m
East: 483561.200 m
Coordinate System: GDA94 (Z51)
Method: Differential GPS (+/-0.047 m)
Directions: None specified.
Elevation: 352.190 m (+/-0.047 m)

SUMMARY COMMENTS

Date of drilling unknown. Fresh water during drilling and airlift from fracture zones. Development: 4 V notch readings taken over 2.5 hrs at 130 m, measuring ~2.5 L/s (78 mm). Flow didn't change over time.

DRILLING DETAILS

Commenced: 31-Mar-2016 (estimate)
Completed: Not specified.
Drilled Depth: 130.0
Drilling Company: Not specified.
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 130.0	Reverse circulation hammer (127 mm)	Air

CONSTRUCTION

Fixtures

Depth (m bgl)	Construction
(0.100) - 0.000	Concrete base, concrete, square, 500 mm (nominal). Data estimated.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
(0.480) - 6.000	Casing, unplasticised polyvinylchloride uPVC, Class 12, 50 mm (nominal), wall thickness 11.1 mm, joins: glue. Casing details estimated.	None.
6.000 - 18.000	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 50 mm (nominal), wall thickness 11.1 mm, joins: glue. Casing details estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 18.0	Annulus fill (1.5 mm to 3.0 mm), ID-OD: 50 mm to 127 mm, sand. Gravel pack data estimated.

Void Fill

Depth (m bgl)	Construction
18.0 - 130.0	Void fill (1.5 mm to 3.0 mm), OD: 127 mm, sand. Gravel pack and depth estimated.

PARAMETERS MEASURED DURING DRILLING

Key: * - estimated, x - unspecified method

Date	Depth (m bgl)	Drill Rate (m/min)	Airlift Yield (L/s)	EC (uS/cm)	pH	Comment
31-Mar*	14.0 - 18.0	-	0.25 ^x	-	-	
31-Mar	18.0 - 23.0	-	0.25 ^x	-	-	
31-Mar	23.0 - 27.0	-	0.50 ^x	-	-	
31-Mar	27.0 - 39.0	-	1.00 ^x	-	-	
31-Mar	39.0 - 40.0	-	1.00 ^x	-	-	
31-Mar	40.0 - 54.0	-	2.00 ^x	-	-	
31-Mar	54.0 - 88.0	-	1.90 ^x	-	-	
31-Mar	88.0 - 101.0	-	1.90 ^x	-	-	
31-Mar	101.0 - 102.0	-	2.30 ^x	-	-	
31-Mar	102.0 - 130.0	-	2.30 ^x	-	-	

PARAMETERS MEASURED DURING DEVELOPMENT

Key: na - not available, * - estimated

Date	Time	Airlift Yield (L/s)	EC (uS/cm)	pH	Sediment	Water	Sediment
------	------	---------------------	------------	----	----------	-------	----------

31-Mar 08:00* to 31-Mar 10:30*: backwashing. Data estimated. .

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 1.0	Sand	

Depth (m bgl)	Geology	Stratigraphic Unit
1.0 - 2.0	Silcrete with Sand	
2.0 - 14.0	Fractured sandstone, Quartzite	
14.0 - 18.0	Fractured sandstone, Quartzite, Ironstone	
18.0 - 27.0	Sandstone with Quartzite and Ironstone	
27.0 - 39.0	Siltstone with Quartzite	
39.0 - 40.0	Sandstone	
40.0 - 54.0	Siltstone with Quartzite	
54.0 - 88.0	Sandstone with Quartzite and Ironstone	
88.0 - 101.0	Fractured sandstone, Quartzite, Ironstone	
101.0 - 102.0	Siltstone with Quartzite	
102.0 - 130.0	Sandstone with Quartzite and Ironstone	

LITHOLOGICAL DESCRIPTIONS

Logged by:

Depth (m bgl)

- 0.0 - 1.0 **Sand**: Alluvial.
- 1.0 - 2.0 **Silcrete (with Sand)**: Mostly fine sand.
- 2.0 - 8.0 **Sandstone (with Quartzite)**: Mostly fine sand, fractured, weak, oxidised.
- 8.0 - 14.0 **Sandstone (with Quartzite)**: Fractured, 40 - 100% quartz.
- 14.0 - 18.0 **Sandstone (with Quartzite and Ironstone)**: Mostly fine sand, fractured, with limonite (ironstone).
- 18.0 - 23.0 **Sandstone (with Quartzite and Ironstone)**: Mostly fine sand, rounded, with limonite (ironstone).
- 23.0 - 27.0 **Sandstone (with Quartzite and Ironstone)**: Mostly coarse sand, with minor limonite (ironstone).
- 27.0 - 39.0 **Siltstone (with Quartzite)**: Mostly fine silt, laminated ferrug siltstone, minor quartz.
- 39.0 - 40.0 **Sandstone**: Fine sand - medium sand, fresh rock, with muscovite.
- 40.0 - 54.0 **Siltstone (with Quartzite)**: Mostly fine sand, laminated ferrug siltstone, minor quartz.
- 54.0 - 88.0 **Sandstone (with Quartzite and Ironstone)**: Mostly fine sand, with muscovite, minor quartz, minor limonite.
- 88.0 - 101.0 **Sandstone (with Quartzite and Ironstone)**: Fine sand - medium sand, fractured, 2 - 60 % quartz, minor limonite.
- 101.0 - 102.0 **Siltstone (with Quartzite)**: Mostly fine silt, laminated ferrug siltstone, minor quartz.
- 102.0 - 130.0 **Sandstone (with Quartzite and Ironstone)**: Mostly fine sand, minor quartz and limonite.

Reward Minerals Ltd - Composite Log

Bore ID:
LDRC1605


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73318

DATE COMMENCED: 31-Mar-2016 (estimate)
DATE COMPLETED: Not recorded.
HYDROGEOLOGIST: Not recorded.
DRILLING COMPANY: Not recorded.
Tag ID: Not tagged.

Drilling Method: Rotary Hammer
Bore Diameter: 127 mm

Northing: 7440927.370 m
Easting: 481924.680 m

Surface RL: 353.520 m
Scheme: GDA94 (Z51)



BORE NAME: LDRC1605

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73318
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Monitoring
Water level: 9.550 m at 31-Mar-2016 (estimate)

LOCATION

North: 7440927.370 m
East: 481924.680 m
Coordinate System: GDA94 (Z51)
Method: Differential GPS (+/-0.038 m)
Directions: None specified.
Elevation: 353.520 m (+/-0.038 m)

SUMMARY COMMENTS

Date of drilling estimated. Fresh water during drilling and airlift from fracture zones. Development: 4 V notch readings measured over 2.5 hrs at 132 m, each reading 1.8 L/s (72mm).

DRILLING DETAILS

Commenced: 31-Mar-2016 (estimate)
Completed: Not specified.
Drilled Depth: 132.0
Drilling Company: Not specified.
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 132.0	Reverse circulation hammer (127 mm)	Air

CONSTRUCTION

Fixtures

Depth (m bgl)	Construction
(0.100) - 0.000	Concrete base, concrete, square, 500 mm (nominal).

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
0.345 - 6.000	Casing, unplasticised polyvinylchloride uPVC, Class 12, 50 mm (nominal), wall thickness 11.1 mm, joins: glue. Data estimated.	None.
6.000 - 18.000	Slotted casing, unplasticised polyvinylchloride uPVC, Class 12, 50 mm (nominal), wall thickness 11.1 mm, joins: glue. Data estimated.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 18.0	Annulus fill (1.5 mm to 3.0 mm), ID-OD: 50 mm to 127 mm, sand.

Void Fill

Depth (m bgl)	Construction
18.0 - 132.0	Void fill (1.5 mm to 3.0 mm), OD: 127 mm, sand. Data estimated.

PARAMETERS MEASURED DURING DRILLING

Key: * - estimated, x - unspecified method

Date	Depth (m bgl)	Drill Rate (m/min)	Airlift Yield (L/s)	EC (uS/cm)	pH	Comment
31-Mar*	31.0 - 32.0	-	0.25 ^x	-	-	
31-Mar	32.0 - 38.0	-	0.25 ^x	-	-	
31-Mar	38.0 - 42.0	-	0.25 ^x	-	-	
31-Mar	42.0 - 47.0	-	0.25 ^x	-	-	
31-Mar	47.0 - 49.0	-	0.25 ^x	-	-	
31-Mar	49.0 - 54.0	-	0.25 ^x	-	-	
31-Mar	54.0 - 55.0	-	0.25 ^x	-	-	
31-Mar	55.0 - 56.0	-	0.25 ^x	-	-	
31-Mar	56.0 - 57.0	-	0.25 ^x	-	-	
31-Mar	57.0 - 68.0	-	0.25 ^x	-	-	
31-Mar	68.0 - 69.0	-	0.50 ^x	-	-	
31-Mar	69.0 - 77.0	-	0.50 ^x	-	-	
31-Mar	77.0 - 97.0	-	0.50 ^x	-	-	
31-Mar	97.0 - 99.0	-	1.00 ^x	-	-	
31-Mar	99.0 - 105.0	-	2.00 ^x	-	-	
31-Mar	105.0 - 132.0	-	2.00 ^x	-	-	

PARAMETERS MEASURED DURING DEVELOPMENT

Key: na - not available, * - estimated

Date	Time	Airlift Yield (L/s)	EC (uS/cm)	pH	Sediment	Water	Sediment
------	------	------------------------	---------------	----	----------	-------	----------

31-Mar 08:00* to 31-Mar 10:30*: backwashing. Data estimated.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 4.0	Fractured sandstone, Quartzite	
4.0 - 7.0	Sandstone with Ironstone	
7.0 - 9.0	Siltstone	
9.0 - 10.0	Sandstone with Quartzite and Ironstone	
10.0 - 12.0	Fracture of quartzite	
12.0 - 13.0	Sandstone with Quartzite and Ironstone	
13.0 - 15.0	Siltstone with Ironstone	
15.0 - 16.0	Sandstone	
16.0 - 17.0	Siltstone	
17.0 - 24.0	Sandstone with Quartzite and Ironstone	
24.0 - 26.0	Siltstone	
26.0 - 29.0	Sandstone with Quartzite	
29.0 - 31.0	Fractured sandstone, Quartzite	
31.0 - 32.0	Siltstone	
32.0 - 47.0	Sandstone with Ironstone and Quartzite	
47.0 - 49.0	Siltstone with Quartzite and Ironstone	
49.0 - 54.0	Sandstone with Ironstone and Quartzite	
54.0 - 55.0	Siltstone with Ironstone	
55.0 - 56.0	Sandstone with Ironstone and Quartzite	
56.0 - 57.0	Siltstone with Ironstone	
57.0 - 68.0	Sandstone with Ironstone and Quartzite	
68.0 - 69.0	Fracture	
69.0 - 77.0	Sandstone with Ironstone and Quartzite	
77.0 - 97.0	Siltstone	
97.0 - 99.0	Sandstone with Quartzite and Ironstone	
99.0 - 105.0	Siltstone with Ironstone	
105.0 - 132.0	Sandstone with Quartzite and Ironstone	

LITHOLOGICAL DESCRIPTIONS

Logged by:

Depth (m bgl)

0.0 - 4.0 **Sandstone (with Quartzite):** Mostly medium sand, fractured, oxidised.

4.0 - 7.0 **Sandstone (with Ironstone):** Mostly medium sand, minor limonite (ironstone).

Depth (m bgl)

7.0 - 9.0	<u>Siltstone</u> : Mostly fine silt, laminated ferrug siltstone, muscovite.
9.0 - 10.0	<u>Sandstone (with Quartzite and Ironstone)</u> : Mostly medium sand, with limonite (ironstone).
10.0 - 12.0	<u>Quartzite</u> : Fractured/PC, quartz rounded pebbles. Comment: Lithology not clear
12.0 - 13.0	<u>Sandstone (with Quartzite and Ironstone)</u> : Medium sand - coarse sand.
13.0 - 15.0	<u>Siltstone (with Ironstone)</u> : Mostly fine silt, laminated ferrug siltstone, minor muscovite, limonite (ironstone).
15.0 - 16.0	<u>Sandstone</u> : Mostly medium sand, fresh rock.
16.0 - 17.0	<u>Siltstone</u> : Mostly fine silt, laminated ferrug .
17.0 - 24.0	<u>Sandstone (with Quartzite and Ironstone)</u> : Mostly medium sand, minor limonite (ironstone) and muscovite.
24.0 - 26.0	<u>Siltstone</u> : Mostly fine silt, laminated ferrug.
26.0 - 29.0	<u>Sandstone (with Quartzite)</u> : Mostly medium sand.
29.0 - 31.0	<u>Sandstone (with Quartzite)</u> : Mostly medium sand, fractured.
31.0 - 32.0	<u>Siltstone</u> : Mostly fine silt, laminated ferrug.
32.0 - 38.0	<u>Sandstone (with Ironstone and Quartzite)</u> : Mostly medium sand, limonite (ironstone), 2 - 10 % quartz.
38.0 - 42.0	<u>Sandstone (with Ironstone and Quartzite)</u> : Mostly medium sand, limonite (ironstone), 80 - 95 % quartz, weak chlorite.
42.0 - 47.0	<u>Sandstone (with Ironstone and Quartzite)</u> : Mostly medium sand.
47.0 - 49.0	<u>Siltstone (with Quartzite and Ironstone)</u> : Mostly fine silt, laminated ferrug siltstone, minor quartz and limonite (ironstone).
49.0 - 54.0	<u>Sandstone (with Ironstone and Quartzite)</u> : Mostly medium sand, limonite (ironstone), minor quartz.
54.0 - 55.0	<u>Siltstone (with Ironstone)</u> : Mostly fine silt, laminated ferrug siltstone, minor limonite (ironstone).
55.0 - 56.0	<u>Sandstone (with Ironstone and Quartzite)</u> : Mostly medium sand, limonite (ironstone).
56.0 - 57.0	<u>Siltstone (with Ironstone)</u> : Mostly fine silt, laminated ferrug siltstone, minor limonite (ironstone).
57.0 - 68.0	<u>Sandstone (with Ironstone and Quartzite)</u> : Mostly medium sand, limonite (ironstone).
68.0 - 69.0	<u>Sandstone</u> : Fracture bearing water.
69.0 - 77.0	<u>Sandstone (with Ironstone and Quartzite)</u> : Mostly medium sand, limonite (ironstone).
77.0 - 97.0	<u>Siltstone</u> : Mostly fine silt, laminated ferrug siltstone, minor muscovite.
97.0 - 99.0	<u>Sandstone (with Quartzite and Ironstone)</u> : Fine sand - medium sand, minor muscovite and limonite (ironstone).
99.0 - 105.0	<u>Siltstone (with Ironstone)</u> : Mostly fine silt, laminated ferrug siltstone, minor muscovite and limonite (ironstone).
105.0 - 132.0	<u>Sandstone (with Quartzite and Ironstone)</u> : Fine sand - medium sand, minor limonite (ironstone).

Reward Minerals Ltd - Composite Log

Bore ID:

LDRC1409

CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73323

DATE COMMENCED: 01-Jan-2014 (estimate)
DATE COMPLETED: Not recorded.
HYDROGEOLOGIST: Not recorded.
DRILLING COMPANY: Not recorded.
Tag ID: Not tagged.

Drilling Method:	Rotary
Bore Diameter:	100 mm

Northing: 7420740.000 m
 Easting: 466980.000 m

Surface RL: Not recorded
Scheme: GDA94 (Z51)

Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Airlift Yield (L/s)	Construction Diagram
None recorded	0.0		None recorded.	None recorded.	
	100.0				

BORE NAME: LDRC1409

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73323
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Indeterminate
Purpose: Exploration/research
Water level: Not measured

LOCATION

North: 7420740.000 m
East: 466980.000 m
Coordinate System: GDA94 (Z51)
Method: Unknown
Directions: Via Canning Stock Route
Elevation: Not measured.

SUMMARY COMMENTS

Limited details available. Purpose: Investigate Palaeovalley system - prelim reconnaissance work. Drilled as a sighter hole north of Lake Disappointment, drilled on ~4 km spacings. Basement not reached due to drilling difficulties.

DRILLING DETAILS

Commenced: 01-Jan-2014 (estimate)
Completed: Not specified.
Drilled Depth: 101.0
Drilling Company: Not specified.
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 101.0	Reverse circulation (100 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS

No samples recorded.

Reward Minerals Ltd - Composite Log

Bore ID:
LDRC1410

CLIENT:	Reward Minerals Ltd	DATE COMMENCED:	01-Jan-2014 (estimate)
PROJECT:	Lake Disappointment Drilling	DATE COMPLETED:	Not recorded.
LOCATION:	Lake Disappointment	HYDROGEOLOGIST:	Not recorded.
SITE:	Not recorded.	DRILLING COMPANY:	Not recorded.
Database ID:	73324	Tag ID:	Not tagged.

Drilling Method:	Rotary	Northing:	7425440.000 m	Surface RL:	Not recorded
Bore Diameter:	100 mm	Easting:	466560.000 m	Scheme:	GDA94 (Z51)

Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Airlift Yield (L/s)	Construction Diagram
None recorded	<div>0.0</div> <div>10.0</div> <div>20.0</div> <div>30.0</div> <div>40.0</div> <div>50.0</div> <div>60.0</div> <div>70.0</div> <div>80.0</div> <div>90.0</div> <div>100.0</div>		None recorded.	None recorded.	

BORE NAME: LDRC1410

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73324
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Exploration/research
Water level: Not measured

LOCATION

North: 7425440.000 m
East: 466560.000 m
Coordinate System: GDA94 (Z51)
Method: Unknown
Directions: Via Canning Stock Route
Elevation: Not measured.

SUMMARY COMMENTS

Limited details available. Purpose: Investigate Palaeovalley system - prelim reconnaissance work. Drilled as a sighter hole north of Lake Disappointment, drilled on ~4 km spacings. Basement not reached due to drilling difficulties.

DRILLING DETAILS

Commenced: 01-Jan-2014 (estimate)
Completed: Not specified.
Drilled Depth: 101.0
Drilling Company: Not specified.
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 101.0	Reverse circulation (100 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS

No samples recorded.

Reward Minerals Ltd - Composite Log

Bore ID:
LDRC1411

CLIENT:	Reward Minerals Ltd	DATE COMMENCED:	01-Jan-2014 (estimate)
PROJECT:	Lake Disappointment Drilling	DATE COMPLETED:	Not recorded.
LOCATION:	Lake Disappointment	HYDROGEOLOGIST:	Not recorded.
SITE:	Not recorded.	DRILLING COMPANY:	Not recorded.
Database ID:	73325	Tag ID:	Not tagged.

Drilling Method:	Rotary	Northing:	7427950.000 m	Surface RL:	Not recorded
Bore Diameter:	100 mm	Easting:	469200.000 m	Scheme:	GDA94 (Z51)

Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Airlift Yield (L/s)	Construction Diagram
None recorded	<div> <div></div> <div>0.0</div> <div>10.0</div> <div>20.0</div> <div>30.0</div> <div>40.0</div> <div>50.0</div> <div>60.0</div> <div>70.0</div> <div>80.0</div> <div>90.0</div> <div>100.0</div> </div>		None recorded.	None recorded.	<div> <div></div> <div>102.000</div> </div>

BORE NAME: LDRC1411

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73325
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Indeterminate
Purpose: Exploration/research
Water level: Not measured

LOCATION

North: 7427950.000 m
East: 469200.000 m
Coordinate System: GDA94 (Z51)
Method: Unknown
Directions: Via Canning Stock Route
Elevation: Not measured.

SUMMARY COMMENTS

Limited details available. Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings. Purpose: Investigate Palaeovalley system - prelim reconnaissance work.

DRILLING DETAILS

Commenced: 01-Jan-2014 (estimate)
Completed: Not specified.
Drilled Depth: 102.0
Drilling Company: Not specified.
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 102.0	Reverse circulation (100 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS

No samples recorded.

Reward Minerals Ltd - Composite Log

Bore ID:
LDRC1412

CLIENT:	Reward Minerals Ltd	DATE COMMENCED:	01-Jan-2014 (estimate)
PROJECT:	Lake Disappointment Drilling	DATE COMPLETED:	Not recorded.
LOCATION:	Lake Disappointment	HYDROGEOLOGIST:	Not recorded.
SITE:	Not recorded.	DRILLING COMPANY:	Not recorded.
Database ID:	73326	Tag ID:	Not tagged.

Drilling Method:	Rotary	Northing:	7430930.000 m	Surface RL:	Not recorded
Bore Diameter:	100 mm	Easting:	472470.000 m	Scheme:	GDA94 (Z51)

Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Airlift Yield (L/s)	Construction Diagram
None recorded	<div> <div></div> <div>0.0</div> <div>10.0</div> <div>20.0</div> <div>30.0</div> <div>40.0</div> <div>50.0</div> <div>60.0</div> <div>70.0</div> <div>80.0</div> <div>90.0</div> <div>100.0</div> </div>		None recorded.	None recorded.	<div> <div></div> <div>102.000</div> </div>

BORE NAME: LDRC1412

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73326
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Indeterminate
Purpose: Exploration/research
Water level: Not measured

LOCATION

North: 7430930.000 m
East: 472470.000 m
Coordinate System: GDA94 (Z51)
Method: Unknown
Directions: Via Canning Stock Route
Elevation: Not measured.

SUMMARY COMMENTS

Limited details available. Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings. Purpose: Investigate Palaeovalley system - prelim reconnaissance work.

DRILLING DETAILS

Commenced: 01-Jan-2014 (estimate)
Completed: Not specified.
Drilled Depth: 102.0
Drilling Company: Not specified.
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 102.0	Reverse circulation (100 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS


No samples recorded.

Reward Minerals Ltd - Composite Log

Bore ID:
LDRC1413

CLIENT:	Reward Minerals Ltd	DATE COMMENCED:	01-Jan-2014 (estimate)
PROJECT:	Lake Disappointment Drilling	DATE COMPLETED:	Not recorded.
LOCATION:	Lake Disappointment	HYDROGEOLOGIST:	Not recorded.
SITE:	Not recorded.	DRILLING COMPANY:	Not recorded.
Database ID:	73327	Tag ID:	Not tagged.

Drilling Method:	Rotary	Northing:	7434030.000 m	Surface RL:	Not recorded
Bore Diameter:	100 mm	Easting:	475240.000 m	Scheme:	GDA94 (Z51)

Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Airlift Yield (L/s)	Construction Diagram
None recorded	0.0		None recorded.	None recorded.	
	78.000				

BORE NAME: LDRC1413

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73327
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Indeterminate
Purpose: Exploration/research
Water level: Not measured

LOCATION

North: 7434030.000 m
East: 475240.000 m
Coordinate System: GDA94 (Z51)
Method: Unknown
Directions: Via Canning Stock Route
Elevation: Not measured.

SUMMARY COMMENTS

Limited details available. Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings. Purpose: Investigate Palaeovalley system - prelim reconnaissance work.

DRILLING DETAILS

Commenced: 01-Jan-2014 (estimate)
Completed: Not specified.
Drilled Depth: 78.0
Drilling Company: Not specified.
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 78.0	Reverse circulation (100 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS

No samples recorded.

Reward Minerals Ltd - Composite Log

Bore ID:
LDRC1414

CLIENT:	Reward Minerals Ltd	DATE COMMENCED:	01-Jan-2014 (estimate)
PROJECT:	Lake Disappointment Drilling	DATE COMPLETED:	Not recorded.
LOCATION:	Lake Disappointment	HYDROGEOLOGIST:	Not recorded.
SITE:	Not recorded.	DRILLING COMPANY:	Not recorded.
Database ID:	73328	Tag ID:	Not tagged.

Drilling Method:	Rotary	Northing:	7436710.000 m	Surface RL:	Not recorded
Bore Diameter:	100 mm	Easting:	476870.000 m	Scheme:	GDA94 (Z51)

Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Airlift Yield (L/s)	Construction Diagram
None recorded	0.0				
	10.0				
None recorded	20.0				
	30.0				
None recorded	40.0				
	50.0		None recorded.	None recorded.	
None recorded	60.0				
	70.0				
None recorded	80.0				
	90.0				
None recorded	100.0				
				102.000	

BORE NAME: LDRC1414

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73328
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Indeterminate
Purpose: Exploration/research
Water level: Not measured

LOCATION

North: 7436710.000 m
East: 476870.000 m
Coordinate System: GDA94 (Z51)
Method: Unknown
Directions: Via Canning Stock Route
Elevation: Not measured.

SUMMARY COMMENTS

Limited details available. Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings. Purpose: Investigate Palaeovalley system - prelim reconnaissance work.

DRILLING DETAILS

Commenced: 01-Jan-2014 (estimate)
Completed: Not specified.
Drilled Depth: 102.0
Drilling Company: Not specified.
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 102.0	Reverse circulation (100 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS

No samples recorded.

Reward Minerals Ltd - Composite Log

Bore ID:
LDRC1416

CLIENT:	Reward Minerals Ltd	DATE COMMENCED:	01-Jan-2014 (estimate)
PROJECT:	Lake Disappointment Drilling	DATE COMPLETED:	Not recorded.
LOCATION:	Lake Disappointment	HYDROGEOLOGIST:	Not recorded.
SITE:	Not recorded.	DRILLING COMPANY:	Not recorded.
Database ID:	73329	Tag ID:	Not tagged.

Drilling Method:	Rotary	Northing:	7436730.000 m	Surface RL:	Not recorded
Bore Diameter:	100 mm	Easting:	480130.000 m	Scheme:	GDA94 (Z51)

Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Airlift Yield (L/s)	Construction Diagram
None recorded	<div>0.0</div> <div>10.0</div> <div>20.0</div> <div>30.0</div> <div>40.0</div> <div>50.0</div> <div>60.0</div> <div>70.0</div> <div>80.0</div> <div>90.0</div> <div>100.0</div>		None recorded.	None recorded.	

BORE NAME: LDRC1416

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73329
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Indeterminate
Purpose: Exploration/research
Water level: Not measured

LOCATION

North: 7436730.000 m
East: 480130.000 m
Coordinate System: GDA94 (Z51)
Method: Unknown
Directions: Via Canning Stock Route
Elevation: Not measured.

SUMMARY COMMENTS

Limited details available. Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings. Purpose: Investigate Palaeovalley system - prelim reconnaissance work.

DRILLING DETAILS

Commenced: 01-Jan-2014 (estimate)
Completed: Not specified.
Drilled Depth: 101.0
Drilling Company: Not specified.
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 101.0	Reverse circulation (100 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS


No samples recorded.

Reward Minerals Ltd - Composite Log

Bore ID:
LDRC1417

CLIENT:	Reward Minerals Ltd	DATE COMMENCED:	01-Jan-2014 (estimate)
PROJECT:	Lake Disappointment Drilling	DATE COMPLETED:	Not recorded.
LOCATION:	Lake Disappointment	HYDROGEOLOGIST:	Not recorded.
SITE:	Not recorded.	DRILLING COMPANY:	Not recorded.
Database ID:	73330	Tag ID:	Not tagged.

Drilling Method:	Rotary	Northing:	7437110.000 m	Surface RL:	Not recorded
Bore Diameter:	100 mm	Easting:	483840.000 m	Scheme:	GDA94 (Z51)

Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Airlift Yield (L/s)	Construction Diagram
None recorded	0.0		None recorded.	None recorded.	
	114.000				

BORE NAME: LDRC1417

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73330
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Indeterminate
Purpose: Exploration/research
Water level: Not measured

LOCATION

North: 7437110.000 m
East: 483840.000 m
Coordinate System: GDA94 (Z51)
Method: Unknown
Directions: Via Canning Stock Route
Elevation: Not measured.

SUMMARY COMMENTS

Limited details available. Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings. Purpose: Investigate Palaeovalley system - prelim reconnaissance work.

DRILLING DETAILS

Commenced: 01-Jan-2014 (estimate)
Completed: Not specified.
Drilled Depth: 114.0
Drilling Company: Not specified.
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 114.0	Reverse circulation (100 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS

No samples recorded.

Reward Minerals Ltd - Composite Log

Bore ID:
LDRC1418

CLIENT:	Reward Minerals Ltd	DATE COMMENCED:	01-Jan-2014 (estimate)
PROJECT:	Lake Disappointment Drilling	DATE COMPLETED:	Not recorded.
LOCATION:	Lake Disappointment	HYDROGEOLOGIST:	Not recorded.
SITE:	Not recorded.	DRILLING COMPANY:	Not recorded.
Database ID:	73331	Tag ID:	Not tagged.

Drilling Method:	Rotary	Northing:	7436780.000 m	Surface RL:	Not recorded
Bore Diameter:	100 mm	Easting:	488270.000 m	Scheme:	GDA94 (Z51)

Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Airlift Yield (L/s)	Construction Diagram
None recorded	0.0				
	10.0				
None recorded	20.0				
	30.0				
None recorded	40.0				
	50.0				
None recorded	60.0				
	70.0				
None recorded	80.0				
	90.0				
None recorded	94.000				

BORE NAME: LDRC1418

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73331
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Indeterminate
Purpose: Exploration/research
Water level: Not measured

LOCATION

North: 7436780.000 m
East: 488270.000 m
Coordinate System: GDA94 (Z51)
Method: Unknown
Directions: Via Canning Stock Route
Elevation: Not measured.

SUMMARY COMMENTS

Limited details available. Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings. Purpose: Investigate Palaeovalley system - prelim reconnaissance work.

DRILLING DETAILS

Commenced: 01-Jan-2014 (estimate)
Completed: Not specified.
Drilled Depth: 94.0
Drilling Company: Not specified.
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 94.0	Reverse circulation (100 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS


No samples recorded.

Reward Minerals Ltd - Composite Log

Bore ID:
LDRC1419

CLIENT:	Reward Minerals Ltd	DATE COMMENCED:	01-Jan-2014 (estimate)
PROJECT:	Lake Disappointment Drilling	DATE COMPLETED:	Not recorded.
LOCATION:	Lake Disappointment	HYDROGEOLOGIST:	Not recorded.
SITE:	Not recorded.	DRILLING COMPANY:	Not recorded.
Database ID:	73332	Tag ID:	Not tagged.

Drilling Method:	Rotary	Northing:	7437930.000 m	Surface RL:	Not recorded
Bore Diameter:	100 mm	Easting:	492080.000 m	Scheme:	GDA94 (Z51)

Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Airlift Yield (L/s)	Construction Diagram
None recorded	<div>0.0</div> <div>10.0</div> <div>20.0</div> <div>30.0</div> <div>40.0</div> <div>50.0</div> <div>60.0</div> <div>70.0</div> <div>80.0</div> <div>90.0</div>		None recorded.	None recorded.	

BORE NAME: LDRC1419

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73332
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Indeterminate
Purpose: Exploration/research
Water level: Not measured

LOCATION

North: 7437930.000 m
East: 492080.000 m
Coordinate System: GDA94 (Z51)
Method: Unknown
Directions: Via Canning Stock Route
Elevation: Not measured.

SUMMARY COMMENTS

Limited information available. Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings. Basement not reached due to drilling difficulties. Purpose: Investigate Palaeovalley system - prelim reconnaissance work

DRILLING DETAILS

Commenced: 01-Jan-2014 (estimate)
Completed: Not specified.
Drilled Depth: 95.0
Drilling Company: Not specified.
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 95.0	Reverse circulation (100 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS

No samples recorded.

Reward Minerals Ltd - Composite Log

Bore ID:
LDRC1420

CLIENT:	Reward Minerals Ltd	DATE COMMENCED:	01-Jan-2014 (estimate)
PROJECT:	Lake Disappointment Drilling	DATE COMPLETED:	Not recorded.
LOCATION:	Lake Disappointment	HYDROGEOLOGIST:	Not recorded.
SITE:	Not recorded.	DRILLING COMPANY:	Not recorded.
Database ID:	73333	Tag ID:	Not tagged.

Drilling Method:	Rotary	Northing:	7438730.000 m	Surface RL:	Not recorded
Bore Diameter:	100 mm	Easting:	496190.000 m	Scheme:	GDA94 (Z51)

Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Airlift Yield (L/s)	Construction Diagram
None recorded	0.0				
	10.0				
None recorded	20.0				
	30.0				
None recorded	40.0				
	50.0				
None recorded	60.0		None recorded.	None recorded.	
	70.0				
None recorded	80.0				
	90.0				
None recorded	100.0				
	110.0				
None recorded	120.0				
	125.000				
None recorded	130.0				

BORE NAME: LDRC1420

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73333
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Indeterminate
Purpose: Exploration/research
Water level: Not measured

LOCATION

North: 7438730.000 m
East: 496190.000 m
Coordinate System: GDA94 (Z51)
Method: Unknown
Directions: Via Canning Stock Route
Elevation: Not measured.

SUMMARY COMMENTS

Limited data available. Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings. Purpose: Investigate Palaeovalley system - prelim reconnaissance work.

DRILLING DETAILS

Commenced: 01-Jan-2014 (estimate)
Completed: Not specified.
Drilled Depth: 125.0
Drilling Company: Not specified.
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 125.0	Reverse circulation (100 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS

No samples recorded.

Reward Minerals Ltd - Composite Log

Bore ID:
LDRC1421

CLIENT:	Reward Minerals Ltd	DATE COMMENCED:	01-Jan-2014 (estimate)
PROJECT:	Lake Disappointment Drilling	DATE COMPLETED:	Not recorded.
LOCATION:	Lake Disappointment	HYDROGEOLOGIST:	Not recorded.
SITE:	Not recorded.	DRILLING COMPANY:	Not recorded.
Database ID:	73334	Tag ID:	Not tagged.

Drilling Method:	Rotary	Northing:	7438720.000 m	Surface RL:	Not recorded
Bore Diameter:	100 mm	Easting:	501400.000 m	Scheme:	GDA94 (Z51)

Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Airlift Yield (L/s)	Construction Diagram
None recorded	0.0				
	10.0				
None recorded	20.0				
	30.0				
None recorded	40.0				
	50.0				
None recorded	60.0		None recorded.	None recorded.	
	70.0				
None recorded	80.0				
	90.0				
None recorded	100.0				
	110.0				
None recorded	120.0				
	125.000				
None recorded	130.0				

BORE NAME: LDRC1421

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73334
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Indeterminate
Purpose: Exploration/research
Water level: Not measured

LOCATION

North: 7438720.000 m
East: 501400.000 m
Coordinate System: GDA94 (Z51)
Method: Unknown
Directions: Via Canning Stock Route
Elevation: Not measured.

SUMMARY COMMENTS

Limited data available. Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings. Purpose: Investigate Palaeovalley system - prelim reconnaissance work.

DRILLING DETAILS

Commenced: 01-Jan-2014 (estimate)
Completed: Not specified.
Drilled Depth: 125.0
Drilling Company: Not specified.
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 125.0	Reverse circulation (100 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS

No samples recorded.

Reward Minerals Ltd - Composite Log					Bore ID: LDRC1459						
CLIENT:		Reward Minerals Ltd		DATE COMMENCED:		Not recorded.					
PROJECT:		Lake Disappointment Drilling		DATE COMPLETED:		Not recorded.					
LOCATION:		Not recorded.		HYDROGEOLOGIST:		Not recorded.					
SITE:		Not recorded.		DRILLING COMPANY:		Not recorded.					
Database ID:		73335		Tag ID:		Not tagged.					
Drilling Method:		Not recorded.		Latitude:		Not recorded.		Surface RL:		Not recorded	
Bore Diameter:		Not recorded.		Longitude:		Not recorded.		Scheme:		Not recorded.	
Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Airlift Yield (L/s)	Construction Diagram						
None recorded	0.0		None recorded.	None recorded.	None recorded.						
	1.0										
	2.0										
	3.0										
	4.0										
	5.0										
	6.0										
	7.0										
	8.0										
	9.0										
	10.0										

BORE NAME: LDRC1459

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID:	73335
Tag ID:	Not tagged
Owner:	Reward Minerals Ltd
Status:	Abandoned
Purpose:	Exploration/research
Water level:	Not measured

LOCATION

Latitude:	
Longitude	
Coordinate System:	
Method:	Not specified.
Directions:	None specified.
Elevation:	Not measured.

SUMMARY COMMENTS

No data available. Estimation: Failed; potentially collapsed due to high flow rates (see Reward Minerals Ltd April 2014 ASX reports).

DRILLING DETAILS

Commenced:	Not specified.
Completed:	Not specified.
Drilled Depth:	
Drilling Company:	Not specified.
Drilling Rig:	Not specified.
Drilling Rods:	Not specified.
Drilling Collar:	Not specified.
Compressor:	Not specified.

Drillers

No drillers recorded.

Drilling Methods

No drilling methods recorded.

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS

No samples recorded.

Reward Minerals Ltd - Composite Log

Bore ID:

LDR C1460

CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73336

DATE COMMENCED: 01-Jan-2014 (estimate)
DATE COMPLETED: Not recorded.
HYDROGEOLOGIST: Not recorded.
DRILLING COMPANY: Not recorded.
Tag ID: Not tagged.

Drilling Method:	Reverse Circulation Hammer
Bore Diameter:	100 mm

Northing: 7429100.000 m
 Easting: 481400.000 m

Surface RL:	Not recorded
Scheme:	GDA94 (Z51)

Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Airlift Yield (L/s)	Construction Diagram
None recorded	0.0		None recorded.	None recorded.	
	10.0				
	20.0				
	30.0				
	40.0				
	50.0				
	60.0				
	70.0				
	80.0				
	90.0				
	100.0			102.000	

BORE NAME: LDRC1460

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73336
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Indeterminate
Purpose: Exploration/research
Water level: Not measured

LOCATION

North: 7429100.000 m
East: 481400.000 m
Coordinate System: GDA94 (Z51)
Method: Unknown
Directions: Via Canning Stock Route
Elevation: Not measured.

SUMMARY COMMENTS

Limited data available. Drilled as a sighter hole north of Lake Disappointment, drilled on ~4km spacings. Purpose: Investigate Palaeovalley system - prelim reconnaissance work.

DRILLING DETAILS

Commenced: 01-Jan-2014 (estimate)
Completed: Not specified.
Drilled Depth: 102.0
Drilling Company: Not specified.
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 102.0	Reverse circulation (100 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS

No samples recorded.

Reward Minerals Ltd - Composite Log

Bore ID:
LDRC1461

CLIENT:	Reward Minerals Ltd	DATE COMMENCED:	01-Jan-2014 (estimate)
PROJECT:	Lake Disappointment Drilling	DATE COMPLETED:	Not recorded.
LOCATION:	Lake Disappointment	HYDROGEOLOGIST:	Not recorded.
SITE:	Not recorded.	DRILLING COMPANY:	Not recorded.
Database ID:	73337	Tag ID:	Not tagged.

Drilling Method:	Reverse Circulation	Northing:	7425711.000 m	Surface RL:	Not recorded
Bore Diameter:	100 mm	Easting:	481560.000 m	Scheme:	GDA94 (Z51)

Geological Unit	Depth (m)	Graphic Log	Summary Lithology	Airlift Yield (L/s)	Construction Diagram
None recorded	0.0				
	10.0				
None recorded	20.0				
	30.0				
None recorded	40.0				
	50.0				
None recorded	60.0				
	70.0				
None recorded	80.0				
	90.0				
None recorded	100.0				
	110.0				
None recorded	120.0				
	130.0				
None recorded					

BORE NAME: LDRC1461

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73337
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Indeterminate
Purpose: Exploration/research
Water level: Not measured

LOCATION

North: 7425711.000 m
East: 481560.000 m
Coordinate System: GDA94 (Z51)
Method: Unknown
Directions: Via Wiljabu Track
Elevation: Not measured.

SUMMARY COMMENTS

LDDH1402 was drilled to twin this hole. Limited data available. Purpose: Investigate Palaeovalley system - prelim reconnaissance work (part of a 15 hole program starting from LDRC1409)

DRILLING DETAILS

Commenced: 01-Jan-2014 (estimate)
Completed: Not specified.
Drilled Depth: 132.0
Drilling Company: Not specified.
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 132.0	Reverse circulation (100 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

No casing or slots/screens recorded.

Annulus Fill

No fill recorded.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS

No samples recorded.

Reward Minerals Ltd - Composite Log

Bore ID:
LDRC1462


CLIENT: Reward Minerals Ltd
PROJECT: Lake Disappointment Drilling
LOCATION: Lake Disappointment
SITE: Not recorded.
Database ID: 73320

DATE COMMENCED: Not recorded.
DATE COMPLETED: Not recorded.
HYDROGEOLOGIST: Not recorded.
DRILLING COMPANY: Not recorded.
Tag ID: Not tagged.

Drilling Method: Not recorded.
Bore Diameter: Not recorded.

Northing: 7427547.000 m
Easting: 481132.000 m

Surface RL: Not recorded
Scheme: GDA94 (Z51)



BORE NAME: LDRC1462

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73320
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Functional
Purpose: Monitoring
Water level: Not measured

LOCATION

North: 7427547.000 m
East: 481132.000 m
Coordinate System: GDA94 (Z51)
Method: Unknown
Directions: Via Wiljabu Track
Elevation: Not measured.

SUMMARY COMMENTS

Was initially incorrectly called LDRC1460 and corrected soon after. LDDH1401 was drilled to twin this hole. Geologist listed as 'Dot'. Drill Company personnel: Jason, Nigel, Dean (driller). Purpose: Investigate Palaeovalley system - prelim reconnaissance work (part of a 15 hole program starting from LDRC1409). Drilling parameters; V notch readings: 28-29 m:

DRILLING DETAILS

Commenced: Not specified.
Completed: Not specified.
Drilled Depth: 156.0
Drilling Company: Not specified.
Drilling Rig: Not specified.
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 79.0	Rotary blade (108 mm)	Air
79.0 - 156.0	Reverse circulation hammer (108 mm)	Air

CONSTRUCTION

Fixtures

Depth (m bgl)	Construction
(0.100) - 0.000	Concrete base, concrete, square, 500 mm (nominal). All anecdotal data and estimation.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
0.000 - 46.000	Slotted casing, unplasticised polyvinylchloride uPVC, 50 mm (nominal), wall thickness 11.1 mm, joins: glue. Casing details estimated. Use of blank casing unknown.	0.5 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 46.0	Annulus fill (1.5 mm to 3.0 mm), ID-OD: 50 mm to 108 mm, sand. All anecdotal data and estimations.

Void Fill

Depth (m bgl)	Construction
46.0 - 47.0	Void fill, OD: 108 mm, spoil. Blocked at 46 m (collapse) .
47.0 - 156.0	Void fill, OD: 108 mm, spoil. Unknown extent of collapse/open void.

PARAMETERS MEASURED DURING DRILLING

Key: x - unspecified method, y - 90 deg v-notch weir

Date	Depth (m bgl)	Drill Rate (m/min)	Airlift Yield (L/s)	EC (uS/cm)	pH	Comment
08-Apr	58.0 - 59.0	-	1.00 ^x	-	-	
08-Apr	65.0 - 66.0	-	1.50 ^x	-	-	
08-Apr	70.0 - 71.0	-	1.50 ^x	-	-	
08-Apr	76.0 - 77.0	-	2.00 ^x	-	-	
08-Apr	80.0 - 81.0	-	4.00 ^x	-	-	
08-Apr	89.0 - 90.0	-	4.50 ^x	-	-	
08-Apr	95.0 - 96.0	-	6.00 ^x	-	-	
08-Apr	103.0 - 104.0	-	5.00 ^x	-	-	
08-Apr	108.0 - 109.0	-	5.00 ^x	-	-	
08-Apr	113.0 - 114.0	-	5.00 ^x	-	-	
08-Apr	114.0 - 115.0	-	6.00 ^x	-	-	
08-Apr	117.0 - 118.0	-	5.00 ^x	-	-	
08-Apr	124.0 - 125.0	-	5.00 ^x	-	-	
08-Apr	128.0 - 129.0	-	6.00 ^x	-	-	
08-Apr	137.0 - 138.0	-	5.00 ^x	-	-	

Date	Depth (m bgl)	Drill Rate (m/min)	Airlift Yield (L/s)	EC (uS/cm)	pH	Comment
08-Apr	143.0 - 144.0	-	6.00 ^x	-	-	
08-Apr	145.0 - 146.0	-	7.00 ^x	-	-	
08-Apr	147.0 - 148.0	-	7.00 ^x	-	-	
08-Apr	150.0 - 151.0	-	8.00 ^x	-	-	
08-Apr	151.0 - 156.0	-	7.43 ^y	-	-	Sample: Depth estimated.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

Depth (m bgl)	Geology	Stratigraphic Unit
0.0 - 8.0	Sand	
8.0 - 54.0	Clay	
54.0 - 55.0	Silt with Clay and Sand	
55.0 - 81.0	clay rock	Permian
81.0 - 137.0	Siltstone	Proterozoic
137.0 - 138.0	Sandstone	Proterozoic
138.0 - 144.0	Siltstone	Proterozoic
144.0 - 156.0	Sandstone	Proterozoic

LITHOLOGICAL DESCRIPTIONS

Logged by:

Depth (m bgl)


- 0.0 - 8.0 **Sand**: Brown, (edge of dune).
- 8.0 - 18.0 **Clay**: Brown, gooey. H2O injected.
- 18.0 - 23.0 **Clay**: Brown, increase in plasticity, thick, gooey mud. No flow.
- 23.0 - 25.0 **Clay**: Pale cream-brown, gooey.
- 25.0 - 47.0 **Clay**: Brown, gooey.
- 47.0 - 53.0 **Clay**: Buff-brown, gooey, massive, minor clay chips.
- 53.0 - 56.0 **Silt (with Clay and Sand)**: Brown, gritty chips/mud.
- 56.0 - 77.0 **Claystone**: Brown, Permian rock/clay, gritty massive chips, cream-brown 72 - 22m.
- 77.0 - 81.0 **Sand (with Gravel and Clay)**: Brown, poorly sorted.
- 81.0 - 101.0 **Siltstone**: Khaki-grey, siliceous, gritty. Alternates between the two colours.
- 101.0 - 107.0 **Siltstone**: Dark grey, very fine silt, pyrite, laminated, very fine grained trace pyrite.
- 107.0 - 110.0 **Siltstone**: Grey, pyrite, lacks mineralised structures, disseminated pyrite.
- 110.0 - 113.0 **Siltstone**: Grey, conchoidal break, highly silicified.
- 113.0 - 137.0 **Siltstone**: Grey, pyrite, silicified bands, conchoidal break.
- 137.0 - 138.0 **Sandstone**: Grey, sandstone chips.
- 138.0 - 144.0 **Siltstone**: Grey-khaki, pyrite, Conchoidal break, silicified bands, grey to 139m.
- 144.0 - 156.0 **Sandstone**: Grey, mostly fine sand, vuggy at 149 m. Grey-dark grey. Estimated sandstone, lithology not specified.

Reward Minerals Ltd - Composite Log

Bore ID:
LDRC1463

CLIENT:	Reward Minerals Ltd	DATE COMMENCED:	01-Jan-2014 (estimate)
PROJECT:	Lake Disappointment Drilling	DATE COMPLETED:	Not recorded.
LOCATION:	Lake Disappointment	HYDROGEOLOGIST:	Not recorded.
SITE:	Not recorded.	DRILLING COMPANY:	Not recorded.
Database ID:	73338	Tag ID:	Not tagged.

Drilling Method:	Not recorded.	Northing:	7427520.000 m	Surface RL:	Not recorded
Bore Diameter:	225 mm	Easting:	481130.000 m	Scheme:	GDA94 (Z51)



BORE NAME: LDRC1463

Note: All depths in this report are in metres below ground level (bgl). Negative depths (in brackets) indicate above ground level.

BORE DETAILS

Database ID: 73338
Tag ID: Not tagged
Owner: Reward Minerals Ltd
Status: Unknown
Purpose: Exploration/research
Water level: Not measured

LOCATION

North: 7427520.000 m
East: 481130.000 m
Coordinate System: GDA94 (Z51)
Method: Unknown
Directions: None specified.
Elevation: Not measured.

SUMMARY COMMENTS

Majority of data sourced from Reward Minerals Ltd 2014 ASX reports. Flow rate during development reached ~25 L/s. During airlift, air and water discharged from LDDH1401 (~35 m away). Drilling: Conventional 650/350 PSI Reverse Circulation (blade and hammer)

DRILLING DETAILS

Commenced: 01-Jan-2014 (estimate)
Completed: Not specified.
Drilled Depth: 120.0
Drilling Company: Not specified.
Drilling Rig: Conventional 650/350 PSI Reverse Circulation (blade and hammer)
Drilling Rods: Not specified.
Drilling Collar: Not specified.
Compressor: Not specified.

Drillers

No drillers recorded.

Drilling Methods

Depth (m bgl)	Equipment (outside diameter)	Medium
0.0 - 120.0	Reverse circulation (225 mm)	

CONSTRUCTION

Fixtures

No fixtures recorded.

Bore Casing and Slots/Screens

Depth (m bgl)	Construction	Slots/Screens
0.000 - 120.000	Slotted casing, unplasticised polyvinylchloride uPVC, 150 mm (nominal), joins: unknown. Data estimated from 2014 Reward Minerals Ltd ASX reports.	1 mm aperture.

Annulus Fill

Depth (m bgl)	Construction
0.0 - 120.0	Annulus fill, ID-OD: 150 mm to 225 mm, rock. Data estimated from Reward Minerals Ltd 2014 ASX reports.

Void Fill

No fill recorded.

PARAMETERS MEASURED DURING DRILLING

No samples recorded.

PARAMETERS MEASURED DURING DEVELOPMENT

No samples recorded.

INTERPRETED SUMMARY LOG

No samples recorded.

LITHOLOGICAL DESCRIPTIONS

No samples recorded.

Hole ID	Drilling Method	Easting, Zone 51	Northing	RL (ground) (mAHD)	Stickup (m)	Collar width (mm)	Drilled Depth (m)	Diameter (mm)	Ream Diameter (mm)	Ream To (m)	Casing Diameter (mm)	Casing Type	Blank Casing (m)		Slotted Casing (m)		Aperture (mm)	Gravel Pack Size (mm)	Flow Rate (L/s)
													Top	Bottom	Top	Bottom			
LDDH1401	Diamond, Heliportable diesel drive rig	481128	7427555				123.6	75			50	uPVC			0	123.6	0.5	1.5-3	
LDDH1402	Diamond, Heliportable diesel drive rig	481564	7425722				121.0	75											
LDD1501		481263	7426547				130.9	96											
LDD1502		481565	7425422				85.9												
LDD1503		477902	7424577				135.5												
LDD1504		477743	7420598				110.0												
LDD1505		471903	7412645				119.0												
LDD1506		469922	7404587				39.5												
LDD1507		478079	7408745				128.0												
LDD1508		478056	7400534				126.5												
LDD1509		473920	7392593				116.0												
LDD1510		490520	7416773		0.08		122.0	152											
LDD1512		461903	7404603				144.5												
LDD1514		469903	7398591				99.5												
LDD1516		493356	7408920				113.0												

LDBH1601		478589	7414131				81?												
LDBH1602		479490	7401184				84?												
LDBH1603	?	469452	7401199				?												
LDBH1604	?	?	?			305	?				203	uPVC			90				

Notes

Aquifer test data available

Hole ID	Completion	Well Development	Geology data available?	Alias	Type	Status	Tenement	Comments
LDDH1401			Y	LDD1401	Monitoring Bore		EL45/2801	Drilled to twin LDRC1462. During airlifting of LDRC1463, air and water discharged from LDDH1401 (~35 m away).
LDDH1402			Y	LDD1402	Monitoring Bore		EL45/2801	Drilled to twin LDRC1461
LDD1501			Y		Monitoring Bore			
LDD1502			Y		Monitoring Bore			
LDD1503			Y		Monitoring Bore			
LDD1504			Y		Monitoring Bore			
LDD1505			Y		Monitoring Bore			
LDD1506			Y		Monitoring Bore			
LDD1507			Y		Monitoring Bore			
LDD1508			Y		Monitoring Bore			
LDD1509			Y		Monitoring Bore			
LDD1510			Y		Monitoring Bore	Functional		Last accessed 23/09/2016
LDD1512			Y		Monitoring Bore			
LDD1514			Y		Monitoring Bore			
LDD1516			Y		Monitoring Bore			

LDBH1601			N		Monitoring Bore			
LDBH1602			N		Monitoring Bore			
LDBH1603			N		Production Bore			
LDBH1604			N		Production Bore			<p>There is no geological log for this bore, however it is adjacent to LDDH1512.</p> <p>LDBH 1604-casing depth- 90 meters-8" PVC</p> <ul style="list-style-type: none"> • 12 " collar • Drilled through rock, sands and clays. • 6 tonnes of gravel pack • Flushed hole before casing off, then set up rig over collar and casing, ran in 84 meters off rods and flushed inside casing. Water coming out clean. Pictures taken . • Got sump/ trench water samples • Samples taken @ start of flushing inside casing then @ 10 o'clock then @ 12 o'clock • No discolouration at all whilst flushing inside of casing @ 84 meters • Flushed for 4 hours @ 50psi • Commenced drilling LDBH 1604 on 7/11/16 Finished hole completely on 19/11/16

Notes

Appendix B

Detailed Log LDD1507

Based on information contained in the original borehole log for Bore LDD 1507 (as received from Reward Minerals) and the assessment of (selected) representative samples viewed as part of this study the following material types and stratigraphic sequence is interpreted for this site, representative photographs of the various materials are attached.

Depth (m)	Geological Symbol	Stratigraphy	Material Types
0.0-2.0	Qhl	Upper Lakebed Sequence	Sandy Clay, orange brown with fine to coarse grained crystalline gypsum sand, uncemented.
2.0-6.5	Qpl	Lower Lakebed Sequence	Clay, red, brown, pale orange with fine grained crystalline gypsum sand, with interbedded fine to coarse grained subangular to angular gypsum sand (kopi gypsum) horizons, uncemented.
6.5-9.7	Qpl	Lower Lakebed Sequence	Sandstone, pale orange to white, Mwk-Mo silica and gypsum cemented gypsum & quartz sand, very fine to very coarse grained (<0.06 to 1.8mm) sub-rounded to sub-angular (detrital) gypsum sand & angular (crystalline) gypsum sand, very fine to coarse grained (<0.06 to 0.6mm) sub-rounded to rounded quartz sand, trace proportions of very coarse silt and very fine grained subrounded to rounded black heavy mineral sand.
9.7-13.5	Puw	Weathered Basement Mottled Zone	Clay, pale green, grey, pale orange, with 5-10% very fine to medium grained (<0.06 to 0.27mm) crystalline gypsum sand, with 5% very coarse silt to very fine sand (<0.05 to 0.1mm) comprising subrounded to well rounded brown ironstone, black heavy mineral and minor green lithic fragments. Localised crystalline gypsum veining.
13.5-14.0	Puw	Weathered Basement Mottled Zone (calcareous)	Sandy Clay, orange to pale green, calcareous, with 5% very fine to very coarse (0.1 to 1.5mm) crystalline gypsum sand, trace very coarse silt and very fine grained subrounded to rounded black heavy mineral sand.

14.0-29.0	Puw	Weathered Basement Mottled Zone (oxidised)	Clay, grey, pale green, with red, orange ferruginous alteration, trace very fine grained to coarse grained crystalline gypsum sand, trace coarse silt and very fine grained heavy mineral sand. Minor interbedded sandstone, grey, very fine to coarse quartz sand, Mwk silica cemented.
26.6-29.0	Puw	Weathered Basement Mottled Zone (oxidised, calcareous)	Weakly calcareous from 26.6m with minor carbonate veining from 27.7m.
29.0-34.6	Puw	Weathered Basement Mottled Zone (oxidised)	Clay, pale green, grey, to red, orange, brown with very fine to coarse grained crystalline gypsum sand and gravel, with coarse silt and very fine grained black heavy mineral sand.
34.6-34.7	Puw	Weathered Basement Mottled Zone (calcareous)	Calcrete, white, moderately carbonate cemented.
34.7-43.75	Puw	Weathered Basement Mottled Zone (oxidised)	Clay, grey, minor red, orange with very fine to coarse grained crystalline gypsum sand and minor crystalline gypsum gravel (<0.06 to 2.1mm).
39.5-43.75	Puw	Weathered Basement Mottled Zone	Clay, grey, minor red, pale orange with very fine to coarse grained crystalline gypsum sand.
43.75-59.0	Puw	Weathered Basement	Clay, grey, dark grey, black, minor green. XW claystone with relict crystalline gypsum infilled joints.
59.0-65.0	Puw	Weathered Basement	Siltstone, XW-HW, grey, Mwk-Mo siliceous cemented, sandy with 20% very fine to fine grained (<0.06 to 0.2mm) subrounded to rounded quartz sand and minor heavy mineral sand, clayey matrix. With very fine to fine grained crystalline gypsum sand and localised gypsum veining.
65.0-66.1	Puw	Weathered Basement	Sandstone, HW-MW, pale grey, pale brown, grey, very fine to medium grained subrounded quartz, Mwk-Mo siliceous cemented, clayey matrix with fine grained crystalline gypsum sand.

66.1-70.7	Puw	Weathered Basement	Sand and Sandstone, HW, pale brown, grey, Vwk siliceous cemented to uncemented very fine to fine grained (<0.06-0.2mm) subrounded to rounded quartz sand, with very fine to fine grained crystalline gypsum sand, minor very fine grained rounded black heavy mineral sand. Slight increase in grain size with depth to 0.3mm.
70.7-71.0	Puw	Weathered Basement	Clay, dark grey, XW claystone.
71.0-72.0	Puw	Weathered Basement	Sand and Sandstone, fine to medium grained subrounded to rounded quartz sand, minor fine grained rounded black heavy mineral sand, variably Mwk-Mo siliceous cemented HW sandstone and uncemented sand.
72.0-78.5	Puw	Weathered Basement	Sand and Sandstone, fine to medium grained subrounded to rounded quartz sand, with argillaceous clayey matrix, minor fine grained rounded black heavy mineral sand, variably Wk siliceous cemented HW argillaceous sandstone and uncemented clayey sand.
81.5-90.5	Puw	Weathered Basement	Siltstone with interbedded claystone, MW-HW, grey, dark grey, Mwk-Mo siliceous cemented, sandy with 15-20% very fine to fine grained (<0.06 to 0.2mm) subrounded to rounded quartz sand and minor heavy mineral sand, clayey matrix, with narrow interbedded fine laminae comprising silt and clay sized particles (fissile in places). With very fine to fine grained crystalline gypsum sand. Bedding at 30° dip.
90.5-91.0	Puw	Weathered Basement	Sand and Sandstone, grey, fine to medium grained subrounded to rounded quartz sand, minor fine grained rounded black heavy mineral sand, variably Mo-We siliceous cemented MW-HW sandstone and uncemented sand.
91.0-109.65	Puw	Weathered Basement	91.0-102.4m: Siltstone, MW-HW, grey, dark grey, Mwk-Mo siliceous cemented, sandy with 15% very fine to fine grained (<0.06 to 0.1mm)

			subrounded to rounded quartz sand and minor green mica & black heavy mineral sand, silty to clayey matrix, laminated. With interbedded sandstone, MW-HW, dark grey, argillaceous, very fine to fine grained (<0.06 to 0.15mm) subrounded to rounded quartz and minor heavy mineral sand, silty matrix. With narrow crystalline gypsum veining.
109.65-118.5	Pu	Basement	Siltstone, MW-SW, dark grey, Mo siliceous cemented, sandy with 10-15% very fine to fine grained (<0.06 to 0.1mm) subrounded to rounded quartz sand, subangular green to black mica (disseminated and as thin laminae) & black heavy mineral sand, silty to clayey matrix, laminated to finely bedded. Bedding dips at 25 to 30°.
118.5-128.0	Pu	Basement	Siltstone, SW, grey to black, Mo siliceous cemented, variably sandy with up to 15% very fine to fine grained (<0.06 to 0.15mm) subrounded to rounded quartz sand, subangular green to black mica (disseminated and as thin laminae) & black heavy mineral sand, silty to clayey matrix, laminated to finely bedded. Bedding dips at 25 to 30°.


Terms used to describe weathering of the material types encountered include:

Term	Symbol	Index Test
Residual Soil	RS	Soil derived from the weathering of rock, the mass structure and substance fabric are no longer evident, there is a large change in volume but the soil has not been significantly transported.
Extremely Weathered	XW	Material is weathered to such an extent that it has "soil" properties i.e. it either disintegrates or can be remoulded in water. Original fabric still evident.
Highly Weathered	HW	Rock is weathered to such an extent that it shows considerable change in appearance and loss in strength. Material is still a rock but of relatively low strength.
Moderately Weathered	MW	Rock is weathered to such an extent that it shows a visible change in appearance with significant loss in strength.
Slightly Weathered	SW	Rock is slightly discoloured but shows little or no change of strength from fresh rock.
Fresh	FR	Rock shows no sign of decomposition or staining.



Terms used to describe cementation of the material types encountered include:

Term	Symbol	Index Test
Uncemented	Uc	Clean grains, exhibiting soil properties.
Very Weakly Cemented	Vwk	Marginal soil-rock strengths, collapsing feel under light finger pressure, cement seen on some washed grains.
Weakly Cemented	Wk	Collapsing feel under light finger pressure, breaks down to individual grains or with some grains cemented together, cement seen on many washed grains.
Moderately Weakly Cemented	Mwk	Cement on nearly all grains, breaks downs to lumps and some individual grains under finger pressure, can crush to individual grains under knife blade.
Moderately Cemented	Mo	Cement on nearly all grains, can break fragments off by hand, can crush to small lumps under knife blade.
Well Cemented	We	Cement on all grains, cannot break fragments off by hand, dull sound under hammer.
Very Well Cemented	Vwe	Most primary pores filled with cement, requires firm blow with hammer to break off fragments, rings under hammer.



Sample Photographs

LDD1507 @ 8.3m Depth


LDD1507 @ 8.3m Depth




LDD1507 @ 10.44m Depth





LDD1507 @ 10.44m Depth




LDD1507 @ 10.44m Depth




LDD1507 @ 13.9m Depth





LDD1507 @ 15.1m Depth





LDD1507 @ 20.15m Depth





LDD1507 @ 27.0m Depth





LDD1507 @ 32.8m Depth





LDD1507 @ 39.75m Depth





LDD1507 @ 43.75m Depth




LDD1507 @ 43.75m Depth





LDD1507 @ 56.7m Depth




LDD1507 @ 61.6m Depth





LDD1507 @ 61.6m Depth




LDD1507 @ 66.15m Depth




LDD1507 @ 66.8m Depth





LDD1507 @ 69.3m Depth




LDD1507 @ 83.5m Depth





LDD1507 @ 86.1m Depth



LDD1507 @ 90.1m Depth




LDD1507 @ 94.9m Depth



LDD1507 @ 94.9m Depth





LDD1507 @ 97.9m Depth



LDD1507 @ 102.4m Depth





LDD1507 @ 104.3m Depth





LDD1507 @ 109.65m Depth




LDD1507 @ 116.5m Depth





LDD1507 @ 117.9m Depth





LDD1507 @ 117.9m Depth



LDD1507 @ 122.0m Depth




LDD1507 @ 122.0m Depth



Appendix C

Monthly Monitoring of Lake Waterlevels

Depth to groundwater beneath the lake



Appendix **D**

Test Pumping Data

Reward

Constant Rate Test - Data Sheet

Test Start:	<input type="text" value="15-Dec-16 09:09"/>	Test End:	<input type="text" value="15-Dec-16 09:09"/>
Job No.:	<input type="text" value="1257g"/>	Quicklogs Bore ID:	<input type="text" value="73389"/>
		Pumped Bore:	<input type="text" value="LDBH1603"/>
Client.:	<input type="text" value="Reward"/>	Tagged depth (m bTOC):	<input type="text" value="65"/>
Contractor:	<input type="text" value="Global Groundwater"/>	Supervisor:	<input type="text" value="JL Percival"/>
SWL (mbMP):	<input type="text" value="1.070"/>	Pump Inlet (mbmp):	<input type="text" value="60.0"/>
MP (maTOC):	<input type="text" value="1.060"/>	Available Drawdown (m):	<input type="text" value="58.9"/>
TOC (magl):	<input type="text" value="0.000"/>	Discharge Dist. & Direction:	<input type="text" value="250m NW"/>
SWL (mbgl):	<input type="text" value="0.010"/>	Bore Internal Diameter (mm):	<input type="text" value="228"/>
Pump Used:	<input type="text" value="Grundfow SP14A"/>	Flow (L/s):	<input type="text" value="3.00"/>
		Flow (m ³ /day):	<input type="text" value="259"/>
Flow device:	<input type="text" value="Volume estimation"/>		
		Number of other Bores Monitored:	<input type="text" value="0"/>

SWL = Static water level mbMP = Metres below measuring point mbgl = Metres below ground level
 MP = Measuring point magl = Metres above ground level ToC= Top of Casing (Bore)

Reading Taken Date (Hr:Min:Sec)	Elapsed Time (Min)	Water Level (m)	Drawdown (m)	Corrected Drawdown (m)	Comments
15-Dec-16 09:09:30	0.5	2.620	1.550	1.550	
15-Dec-16 09:10:00	1.0	3.520	2.450	2.450	
15-Dec-16 09:11:00	2.0	4.550	3.480	3.480	
15-Dec-16 09:12:00	3.0	4.850	3.780	3.780	
15-Dec-16 09:13:00	4.0	5.250	4.180	4.180	
15-Dec-16 09:14:00	5.0	5.600	4.530	4.530	
15-Dec-16 09:15:00	6.0	5.990	4.920	4.920	
15-Dec-16 09:16:00	7.0	6.330	5.260	5.260	
15-Dec-16 09:17:00	8.0	6.590	5.520	5.520	
15-Dec-16 09:18:00	9.0	7.030	5.960	5.960	
15-Dec-16 09:19:00	10.0	7.290	6.220	6.220	
15-Dec-16 09:21:00	12.0	7.770	6.700	6.700	
15-Dec-16 09:23:00	14.0	8.080	7.010	7.010	
15-Dec-16 09:25:00	16.0	8.300	7.230	7.230	
15-Dec-16 09:27:00	18.0	8.500	7.430	7.430	
15-Dec-16 09:29:00	20.0	8.640	7.570	7.570	
15-Dec-16 09:31:00	22.0	8.760	7.690	7.690	
15-Dec-16 09:33:00	24.0	8.880	7.810	7.810	
15-Dec-16 09:35:00	26.0	8.950	7.880	7.880	
15-Dec-16 09:37:00	28.0	9.030	7.960	7.960	
15-Dec-16 09:39:00	30.0	9.100	8.030	8.030	
15-Dec-16 09:44:00	35.0	9.220	8.150	8.150	
15-Dec-16 09:49:00	40.0	9.340	8.270	8.270	
15-Dec-16 09:54:00	45.0	9.390	8.320	8.320	
15-Dec-16 09:59:00	50.0	9.450	8.380	8.380	
15-Dec-16 10:04:00	55.0	9.500	8.430	8.430	
15-Dec-16 10:09:00	60.0	9.540	8.470	8.470	
15-Dec-16 10:24:00	75.0	9.630	8.560	8.560	
15-Dec-16 10:39:00	90.0	9.690	8.620	8.620	
15-Dec-16 10:54:00	105.0	9.750	8.680	8.680	
15-Dec-16 11:09:00	120.0	9.770	8.700	8.700	
15-Dec-16 11:39:00	150.0	9.840	8.770	8.770	
15-Dec-16 12:09:00	180.0	9.830	8.760	8.760	
15-Dec-16 12:39:00	210.0	9.840	8.770	8.770	
15-Dec-16 13:09:00	240.0	9.850	8.780	8.780	
15-Dec-16 13:39:00	270.0	9.860	8.790	8.790	

Reward

Constant Rate Test - Data Sheet

Test Start:	15-Dec-16 09:09	Test End:	15-Dec-16 09:09
Job No.:	1257g	Quicklogs Bore ID:	73389
		Pumped Bore:	LDBH1603
Client.:	Reward	Tagged depth (m bTOC):	65
Contractor:	Global Groundwater	Supervisor:	JL Percival
SWL (mbMP):	1.070	Pump Inlet (mbmp):	60.0
MP (maTOC):	1.060	Available Drawdown (m):	58.9
TOC (magl):	0.000	Discharge Dist. & Direction:	250m NW
SWL (mbgl):	0.010	Bore Internal Diameter (mm):	228
Pump Used:	Grundfow SP14A	Flow (L/s):	3.00
		Flow (m³/day):	259
Flow device:	Volume estimation		
		Number of other Bores Monitored:	0

SWL = Static water level

mbMP = Metres below measuring point

mbal = Metres below ground level


MP = Measuring point


magl = Metres above ground level

ToC= Top of Casing (Bore)

[illegible]

Constant Rate Test - Production Bore LDBH1603





LDBH1603 CONSTANT RATE TEST

Data Set: C:\...\LDBH1603ConstanrateTest2016.aqt

Date: 03/21/17

Time: 11:51:30

PROJECT INFORMATION

Company: Global Groundwater

Client: Reward Minerals

Project: 1256g

Location: Lake Disappointment

Test Well: LDBH1603

Test Date: 16 December, 2016

AQUIFER DATA

Saturated Thickness: 48.6 m

Anisotropy Ratio (Kz/Kr): 0.1

WELL DATA

Pumping Wells

Well Name	X (m)	Y (m)
LDBH1603	469348	7401120

Observation Wells

Well Name	X (m)	Y (m)
LDBH1603	469348	7401120

SOLUTION

Aquifer Model: Confined

Solution Method: Cooper-Jacob

T = 91.35 m²/day

S = 1.262E-16

Dataset: CRT		Trench ID: PT011	Trench LxWxH: 100mL x 6mW x 2mD
Prospect:		East:	North:



TRENCH PUMPING SPREADSHEET

Pump Flow Checks											Raw Brine Level from top of PVC Pipe								Actual Brine Level below Natural Surface Level (NSL)								Dipper Code : H = Heron (bagged unit), I - ITMSoil (bare end)		Comments	
Date	Time	Elapsed Time (mins)	Bucket Chk (litres)	Bucket Chk (sec)	Bucket Flow (l/sec)	Flow Meter (litres)	Flow Meter (sec)	F/Meter Flow (l/sec)	Flow Meter Totaliser (m³)	F/Meter Volume (m³)	Obs Bore 1 (m)	Obs Bore 2 (m)	Obs Bore 3 (m)	Obs Bore 4 (m)	Obs Bore 5 (m)	Obs Bore 6 (m)	Obs Bore 7 (m)	Obs Bore 8 (m)	Obs Bore 1 (m)	Obs Bore 2 (m)	Obs Bore 3 (m)	Obs Bore 4 (m)	Obs Bore 5 (m)	Obs Bore 6 (m)	Obs Bore 7 (m)	Obs Bore 8 (m)	Dipper Used 1-5	Dipper Used 6-8		
			Nom 20			Nom 100														0.560	0.280	0.250	0.220	0.250	0.150	0.220	0.230	H	I	Top of PVC to NSL ('Stick-up')
9/11/2016	7:10	0	20	7.0 & 8.4	5.2	Too unreliable (erratic, high or siezed). Suitable for hypersaline brines ??					0.760	0.450	0.424	0.378	0.435	0.340	0.410	0.418	0.200	0.170	0.174	0.158	0.185	0.190	0.190	0.188	H	I	Twin pumps being used so that each is running at lower speed and thus slowly using fuel in its tank. Single pump running fast may run out of fuel overnight. Flow meters erratic, or seized, unreliable - may not be suited to hypersaline duty - scaling.	
9/11/2016	7:25	15									0.760				0.440	0.350			0.200				0.190	0.200			H	I		
9/11/2016	7:35	25									0.762		0.432		0.438	0.350			0.202		0.182		0.188	0.200			H	I		
9/11/2016	7:45	35									0.773	0.460	0.435	0.388	0.441	0.350			0.213	0.180	0.185	0.168	0.191	0.200			H	I		
9/11/2016	7:55	45									0.766	0.464	0.438	0.390	0.441	0.355	0.415		0.206	0.184	0.188	0.170	0.191	0.205	0.195		H	I		
9/11/2016	8:05	55									0.769	0.466	0.442	0.392	0.443	0.355	0.415		0.209	0.186	0.192	0.172	0.193	0.205	0.195		H	I		
9/11/2016	8:15	65									0.773	0.469	0.445	0.393	0.444	0.355	0.415		0.213	0.189	0.195	0.173	0.194	0.205	0.195		H	I		
9/11/2016	8:25	75									0.781	0.474	0.449	0.396	0.446	0.355	0.415		0.221	0.194	0.199	0.176	0.196	0.205	0.195		H	I		
9/11/2016	8:35	85									0.793	0.475	0.456	0.396	0.448	0.355	0.415	0.420	0.233	0.195	0.206	0.176	0.198	0.205	0.195	0.190	H	I		
9/11/2016	8:45	95									0.792	0.481	0.459	0.398	0.453	0.357	0.425		0.232	0.201	0.209	0.178	0.203	0.207	0.205		H	I		
9/11/2016	8:55	105									0.795	0.480	0.460	0.399	0.457	0.357	0.418		0.235	0.200	0.210	0.179	0.207	0.207	0.198		H	I		
9/11/2016	9:05	115									0.797	0.482	0.464	0.400	0.459	0.357	0.418	0.420	0.237	0.202	0.214	0.180	0.209	0.207	0.198	0.190	H	I		
9/11/2016	9:15	125									0.798	0.485	0.465	0.402	0.459	0.363	0.418		0.238	0.205	0.215	0.182	0.209	0.213	0.198		H	I		
9/11/2016	9:25	135									0.800	0.486	0.467	0.403	0.458	0.368	0.425		0.240	0.206	0.217	0.183	0.208	0.218	0.205		H	I		
9/11/2016	9:45	155									0.805	0.490	0.474	0.405	0.472	0.368	0.425	0.420	0.245	0.210	0.224	0.185	0.222	0.218	0.205	0.190	H	I		
9/11/2016	10:05	175									0.816	0.494	0.476	0.408	0.468	0.370	0.423		0.256	0.214	0.226	0.188	0.218	0.220	0.203		H	I		
9/11/2016	10:25	195									0.819	0.497	0.480	0.409	0.470	0.380	0.423		0.259	0.217	0.230	0.189	0.220	0.230	0.203		H	I		
9/11/2016	11:30	260									0.824	0.500	0.486	0.412	0.473	0.380	0.425		0.264	0.220	0.236	0.192	0.223	0.230	0.205		H	I	Both pumps off briefly to clear severe coarse crystal blockages in NRV screens and to unseize NRVs. Coarse crystals either on floor of trench or raining down due to recharge flow. Stable after first cleaning.	
9/11/2016	11:50	280									0.824	0.504	0.490	0.414	0.472	0.383	0.425		0.264	0.224	0.240	0.194	0.222	0.233	0.205		H	I		
9/11/2016	12:10	300									0.825	0.507	0.494	0.415	0.474	0.383	0.425	0.422	0.265	0.227	0.244	0.195	0.224	0.233	0.205	0.192	H	I		
9/11/2016	12:30	320									0.833	0.510	0.500	0.416	0.475	0.384	0.427		0.273	0.230	0.250	0.196	0.225	0.234	0.207		H	I		
9/11/2016	13:00	350									0.839	0.515	0.506	0.419	0.483	0.390	0.430	0.422	0.279	0.235	0.256	0.199	0.233	0.240	0.210	0.192	H	I		
9/11/2016	13:30	380									0.847	0.519	0.512	0.423	0.485	0.395	0.432		0.287	0.239	0.262	0.203	0.235	0.245	0.212		H	I		
9/11/2016	14:00	410									0.862	0.525	0.523	0.429	0.496	0.398	0.430	0.424	0.302	0.245	0.273	0.209	0.246	0.248	0.210	0.194	H	I		
9/11/2016	14:30	440									0.864	0.529	0.524	0.429	0.494	0.400	0.435		0.304	0.249	0.274	0.209	0.244	0.250	0.215		H	I		
9/11/2016	15:00	470									0.866	0.534	0.532	0.432	0.498	0.405	0.435	0.427	0.306	0.254	0.282	0.212	0.248	0.255	0.215	0.197	H	I		
9/11/2016	15:30	500									0.874	0.538	0.539	0.434	0.501	0.408	0.438		0.314	0.258	0.289	0.214	0.251	0.258	0.218		H	I		
9/11/2016	16:00	530									0.875	0.542	0.542	0.437	0.510	0.411	0.440	0.431	0.315	0.262	0.292	0.217	0.260	0.261	0.220	0.201	H	I		
10/11/2016	7:10	1440									0.932	0.599	0.597	0.501	0.574	0.475	0.506	0.498	0.372	0.319	0.347	0.281	0.324	0.325	0.286	0.268	H	I	As anticipated, Pump 1 was not running on arrival, it had stalled just before pickup time previous day (restarted) and had been running very poorly (smokey also). New pump had been organised, swapped out quickly.	
10/11/2016	8:35	1525	20	8.9 & 8.0	4.7						0.940	0.608	0.609	0.509	0.583	0.483	0.513	0.500	0.380	0.328	0.359	0.289	0.333	0.333	0.293	0.270	H	I	Both pumps running fine.	
10/11/2016	16:30	2000									1.032	0.683	0.704	0.565	0.643	0.560	0.558	0.543	0.472	0.403	0.454	0.345	0.393	0.410	0.338	0.313	H	I	Both pumps running fine.	
11/11/2016	6:55	2865									1.090	0.738	0.768	0.624	0.713	0.628	0.622	0.603	0.530	0.458	0.518	0.404	0.463	0.478	0.402	0.373	H	I	Both pumps running fine. Trench brine level now just below main trench lip rather than higher on 'shallows'. All MBs dropped 50-70mm overnight.	
11/11/2016	15:15	3365									1.109	0.754	0.789	0.646	0.733	0.650	0.643	0.622	0.549	0.474	0.539	0.426	0.483	0.500	0.423	0.392	H	I	Unbelievably, we arrived to find Pump 2 now leaking fairly badly. Layflat pressure still very good. Appears to be a crack in housing, spray pattern is away from major worry items. Due to site circumstances (time of day and oil leak / chopper), will have to swap out tomorrow. Fuel use quite low so running out of fuel probably less of an issue.	
12/11/2016	9:30	4460									1.113	0.773	0.818	0.673	0.758	0.681	0.666	0.648	0.553	0.493	0.568	0.453	0.508	0.531	0.446	0.418	H	I	Pump 2 leak about the same, both pumps running, both layflats good. Patched over hole as best we could with rags and tape. We estimate leakage rate visually at 0.25 to 0.5 L/sec. Normal chopper has oil leak, replacement being flown in this arvo.	
12/11/2016	16:15	4865										0.785	0.825	0.681	0.769	0.686	0.674	0.657		0.505	0.575	0.461	0.519	0.536	0.454	0.427	H	I	Pump 2 leak about the same, again both pumps running and both layflats good. Leakage rate visually still around 0.25 to 0.5 L/sec. Can't replace pump as replacement chopper has no lifting capability (WTF).	
13/11/2016	6:10	5700									1.059	0.718	0.726	0.633	0.700	0.621	0.643	0.639	0.499	0.438	0.476	0.413	0.450	0.471	0.423	0.409	H	I	Arrived to find Pump 2 DEAD. Attempts to restart futile, plenty of fuel and motor spins over but just coughs smoke. Still can't replace pump. Normal chopper 'due' back on site noon, will replace pump as quickly as possible and resume test at around 4.7 L/sec. MBs and trench have all recharged somewhat due to lower pump flow (est 4.7 down to 2.2 L/sec). Hope resuming and am / pm checks OK togive useful results.	
13/11/2016	12:50	6100									1.044	0.701	0.708	0.617	0.684	0.602	0.634	0.630	0.484	0.421	0.458	0.397	0.434	0.452	0.414	0.400	H	I	Waiting on replacement 2nd pump.	

Dataset: CRT		Trench ID: PT011	Trench LxWxH: 100mL x 6mW x 2mD
Prospect:		East:	North:





TRENCH PUMPING SPREADSHEET

Pump Flow Checks										Raw Brine Level from top of PVC Pipe								Actual Brine Level below Natural Surface Level (NSL)								Dipper Code : H = Heron (bagged unit), I = ITMSoil (bare end)			
Date	Time	Elapsed Time (mins)	Bucket Chk (litres)	Bucket Chk (sec)	Bucket Flow (l/sec)	Flow Meter (litres)	Flow Meter (sec)	F/Meter Flow (l/sec)	Flow Meter Totaliser (m³)	F/Meter Volume (m³)	Obs Bore 1 (m)	Obs Bore 2 (m)	Obs Bore 3 (m)	Obs Bore 4 (m)	Obs Bore 5 (m)	Obs Bore 6 (m)	Obs Bore 7 (m)	Obs Bore 8 (m)	Obs Bore 1 (m)	Obs Bore 2 (m)	Obs Bore 3 (m)	Obs Bore 4 (m)	Obs Bore 5 (m)	Obs Bore 6 (m)	Obs Bore 7 (m)	Obs Bore 8 (m)	Dipper Used 1-5	Dipper Used 6-8	Comments
13/11/2016	14:00	6170	20	8.5 & 11.0	4.2						1.045	0.705	0.711	0.618	0.687	0.605	0.634	0.630	0.485	0.425	0.461	0.398	0.437	0.455	0.414	0.400	H	I	At 13:20, replacement pump started in Pump 2 position, back to 2 x pumps now. Flow adjusted aiming for low to mid 4 l/sec. Actual number = 4.2 l/sec. Monitored until just before 1600 hrs - all running well.
13/11/2016	14:30	6200									1.045	0.710	0.723	0.618	0.693	0.607	0.630	0.629	0.485	0.430	0.473	0.398	0.443	0.457	0.410	0.399	H	I	
13/11/2016	15:00	6230									1.046	0.714	0.727	0.623	0.693	0.612	0.632	0.625	0.486	0.434	0.477	0.403	0.443	0.462	0.412	0.395	H	I	
13/11/2016	15:30	6260									1.058	0.719	0.734	0.622	0.699	0.615	0.635	0.629	0.498	0.439	0.484	0.402	0.449	0.465	0.415	0.399	H	I	Both pumps running well, all good.
14/11/2016	6:50	7180									1.128	0.788	0.809	0.683	0.768	0.682	0.679	0.668	0.568	0.508	0.559	0.463	0.518	0.532	0.459	0.438	H	I	Both pumps running well, all good.
14/11/2016	16:10	7740									1.135	0.796	0.822	0.689	0.773	0.696	0.690	0.679	0.575	0.516	0.572	0.469	0.523	0.546	0.470	0.449	H	I	Both pumps running well, all good. Trench level quite stable at top of main trench channel.
15/11/2016	6:45	8615									1.135	0.809	0.839	0.699	0.786	0.705	0.700	0.688	0.575	0.529	0.589	0.479	0.536	0.555	0.480	0.458	H	I	Both pumps running well, all good. Trench level quite stable at top of main trench channel.
15/11/2016	17:05	9235									1.135	0.818	0.850	0.707	0.791	0.710	0.705	0.693	0.575	0.538	0.600	0.487	0.541	0.560	0.485	0.463	H	I	
16/11/2016	7:00	10070									1.135	0.825	0.858	0.716	0.798	0.720	0.713	0.700	0.575	0.545	0.608	0.496	0.548	0.570	0.493	0.470	H	I	
16/11/2016	16:10	10620	20	7.0 & 8.4	5.2						1.150	0.829	0.864	0.719	0.804	0.727	0.718	0.706	0.590	0.549	0.614	0.499	0.554	0.577	0.498	0.476	H	I	
17/11/2016	6:55	11505									1.150	0.839	0.863	0.726	0.801	0.731	0.725	0.715	0.590	0.559	0.613	0.506	0.551	0.581	0.505	0.485	I	I	Due to the need for dippers at both LDBH1603 and Trench 11 on 17/11/16, the two person twin dipper arrangement used to date had to become ITM only. Even though the dippers are physically similar and should read the same, dipping a test BH showed a 24mm variation against the Heron. Reason / logic = unknown. Correction applied BH 1-5.
17/11/2016	15:45	12035									1.150	0.841	0.867	0.731	0.806	0.737	0.730	0.720	0.590	0.561	0.617	0.511	0.556	0.587	0.510	0.490	I	I	Ditto.
18/11/2016	7:15	12965									1.150	0.852	0.886	0.745	0.825	0.745	0.738	0.727	0.590	0.572	0.636	0.525	0.575	0.595	0.518	0.497	H	I	Back to twin dipper / twin operator monitoring today.
18/11/2016	14:00	13370									1.150	0.856	0.889	0.749	0.829	0.752	0.744	0.734	0.590	0.576	0.639	0.529	0.579	0.602	0.524	0.504	H	I	Back to twin dipper / twin operator monitoring today.
19/11/2016	7:15	14405									1.150	0.866	0.900	0.758	0.840	0.761	0.751	0.740	0.590	0.586	0.650	0.538	0.590	0.611	0.531	0.510	H	I	
19/11/2016	15:40	14910									1.150	0.868	0.902	0.762	0.844	0.765	0.755	0.745	0.590	0.588	0.652	0.542	0.594	0.615	0.535	0.515	H	I	
20/11/2016	7:00	15830									1.150	0.869	0.906	0.764	0.846	0.769	0.758	0.747	0.590	0.589	0.656	0.544	0.596	0.619	0.538	0.517	H	I	
20/11/2016	15:25	16335	20	8.6 & 11.2	4.1						1.150	0.872	0.907	0.765	0.847	0.772	0.762	0.747	0.590	0.592	0.657	0.545	0.597	0.622	0.542	0.517	H	I	

Bore ID	stick up	depth	casing	geology	east	north
PT11 MB1	0.56	1.5	slotted 50mm	Qh	474684.6	7410316.5
PT11 MB2	0.28	1.5	slotted 50mm	Qh	474675.2	7410316.5
PT11 MB3	0.25	1.5	slotted 50mm	Qh	474680.2	7410338
PT11 MB4	0.22	1.5	slotted 50mm	Qh	474675.4	7410359.6
PT11 MB5	0.25	1.5	slotted 50mm	Qh	474684.4	7410359.6
PT11 MB6	0.15	1.5	slotted 50mm	Qh	474713.1	7410336.7
PT11 MB7	0.22	1.5	slotted 50mm	Qh	474721.4	7410336.7
PT11 MB8	0.23	1.5	slotted 50mm	Qh	474729.1	7410336.7

ULS upper lakebed sequence





WELL TEST ANALYSIS

Data Set: C:\...\PT11_MB8.aqt

Date: 03/14/17

Time: 11:41:28

PROJECT INFORMATION

Company: Reward Minerals

Client: Reward Minerals

Project: Lake Disappointment

Location: Lake Disappointment

Test Well: PT 11

AQUIFER DATA

Saturated Thickness: 1. m

Anisotropy Ratio (Kz/Kr): 1.

WELL DATA

Pumping Wells

Well Name	X (m)	Y (m)
PT11	474693	7410395

Observation Wells

Well Name	X (m)	Y (m)
□ MB8	474729.1	7410336.7


SOLUTION

Aquifer Model: Unconfined

Solution Method: Cooper-Jacob

T = 335.9 m²/day

S = 0.02183



WELL TEST ANALYSIS

Data Set: C:\...\PT11_MB7.aqt

Date: 03/14/17

Time: 11:40:44

PROJECT INFORMATION

Company: Reward Minerals

Client: Reward Minerals

Project: Lake Disappointment

Location: Lake Disappointment

Test Well: PT 11

AQUIFER DATA

Saturated Thickness: 1. m

Anisotropy Ratio (Kz/Kr): 1.

WELL DATA

Pumping Wells

Well Name	X (m)	Y (m)
PT11	474693	7410395

Observation Wells

Well Name	X (m)	Y (m)
□ MB7	474721.4	7410336.7


SOLUTION

Aquifer Model: Unconfined

Solution Method: Cooper-Jacob

T = 371. m²/day

S = 0.01206



WELL TEST ANALYSIS

Data Set: C:\...\PT11_MB6.aqt
 Date: 03/14/17

Time: 11:40:08

PROJECT INFORMATION

Company: Reward Minerals
 Client: Reward Minerals
 Project: Lake Disappointment
 Location: Lake Disappointment
 Test Well: PT 11

AQUIFER DATA

Saturated Thickness: 1. m

Anisotropy Ratio (Kz/Kr): 1.

WELL DATA

Pumping Wells

Well Name	X (m)	Y (m)
PT11	474693	7410395


Observation Wells

Well Name	X (m)	Y (m)
□ MB6	474713.1	7410336.7

SOLUTION

Aquifer Model: Unconfined
 T = 325.5 m²/day

Solution Method: Cooper-Jacob
 S = 0.01043



WELL TEST ANALYSIS

Data Set: C:\...\PT11_MB5.aqt

Date: 03/14/17

Time: 11:39:37

PROJECT INFORMATION

Company: Reward Minerals

Client: Reward Minerals

Project: Lake Disappointment

Location: Lake Disappointment

Test Well: PT 11

AQUIFER DATA

Saturated Thickness: 1. m

Anisotropy Ratio (Kz/Kr): 1.

WELL DATA

Pumping Wells

Well Name	X (m)	Y (m)
PT11	474693	7410395

Observation Wells

Well Name	X (m)	Y (m)
□ MB5	474684.4	7410359.6


SOLUTION

Aquifer Model: Unconfined

Solution Method: Cooper-Jacob

T = 352.9 m²/day

S = 0.02814



WELL TEST ANALYSIS

Data Set: C:\...\PT11_MB4.aqt

Date: 03/14/17

Time: 11:39:09

PROJECT INFORMATION

Company: Reward Minerals

Client: Reward Minerals

Project: Lake Disappointment

Location: Lake Disappointment

Test Well: PT 11

AQUIFER DATA

Saturated Thickness: 1. m

Anisotropy Ratio (K_z/K_r): 1.

WELL DATA

Pumping Wells

Well Name	X (m)	Y (m)
PT11	474693	7410395

Observation Wells

Well Name	X (m)	Y (m)
□ MB4	474675.4	7410359.6


SOLUTION

Aquifer Model: Unconfined

Solution Method: Cooper-Jacob

$T = \underline{359.} \text{ m}^2/\text{day}$

$S = \underline{0.02803}$



WELL TEST ANALYSIS

Data Set: C:\...\PT11_MB3.aqt

Date: 03/14/17

Time: 11:37:46

PROJECT INFORMATION

Company: Reward Minerals

Client: Reward Minerals

Project: Lake Disappointment

Location: Lake Disappointment

Test Well: PT 11

AQUIFER DATA

Saturated Thickness: 1. m

Anisotropy Ratio (Kz/Kr): 1.

WELL DATA

Pumping Wells

Well Name	X (m)	Y (m)
MB3	474693	7410395

Observation Wells

Well Name	X (m)	Y (m)
□ MB2	474680.2	7410338


SOLUTION

Aquifer Model: Unconfined

Solution Method: Cooper-Jacob

T = 324.1 m²/day

S = 0.007672



WELL TEST ANALYSIS

Data Set: C:\...\PT11_MB2.aqt

Date: 03/14/17

Time: 11:48:14

PROJECT INFORMATION

Company: Reward Minerals

Client: Reward Minerals

Project: Lake Disappointment

Location: Lake Disappointment

Test Well: PT 11

AQUIFER DATA

Saturated Thickness: 1. m

Anisotropy Ratio (Kz/Kr): 1.

WELL DATA

Pumping Wells

Well Name	X (m)	Y (m)
PT11	474693	7410395

Observation Wells

Well Name	X (m)	Y (m)
□ MB2	474675.2	7410316.5

SOLUTION

Aquifer Model: Unconfined

Solution Method: Cooper-Jacob

T = 359. m²/day

S = 0.004692

Appendix E

Model Parameters and Results

Summary of Model.

1) Hydraulic Parameters

Unit	Depths (m AHD)		Storage		Conductivity (Kx, Ky, Kz)	Model Zone (zone colour)
	From	To	Sy	ss	(m/d)	
Aeolian sand (Qpe)	340	328	15		2, 0.2	1
Upper lake bed (Qhs)	330	328	15		250, 25	2
Lower lake bed (Q/Tpl)	328	320	13	1.3×10^{-16}	0.06, .006	3
Sandy weathered basement (PUw after PUss)	320	240	12	1.3×10^{-16}	2, 0.2	4
Other weathered basement (PUw after PUs)	320	240	1	1.3×10^{-16}	0.005, 0.0005	5
Basement rock (PUsx)	240	180	1	1.3×10^{-16}	0.005, 0.0005	5

2) Model design

Model start date: 01/01/2018, 12:00

Grid

Coordinate system = WGS84 Zone 51

Length unit = m

Hydraulic Conductivity unit = m/d

Time unit = day

Pumping unit = m³/d

Recharge unit = mm/yr

Columns

Min X = 450000m

Max X = 510000m

Total of 120 columns, uniform grid spacing 500m.

Rows

Min Y = 7375000 m

Max Y = 7445000 m

Total of 140 rows with cell width 500m

Layers

Number of Layers = 4

Top Layer 1: GroundMin330mAHD


Bottom Layer 1: 328mAHD

Bottom Layer 2: 320mAHD


Bottom Layer 3: 240mAHD

Bottom Layer 4: 180mAHD


Layer 1




Layer 2




Layer 3




Layer 4



Row 75




Column 50




3) Model Calibration (Sensitivity to K in Zone 2)

a) Layer 1 K = 5, results in poor calibration


b) Layer 1 K = 100, results in reasonable calibration




c) Layer 1 K = 250, good correlation with PT11 (pumping rate to 430kL/day for 11.3days).




K=250 heads around T11 at day 11




4) Results



K=250 heads after 1yrs no recharge



K=250 heads after 10yrs no recharge



K=250 heads after 1yr no recharge pumping from bore LDBH1603 at 10L/s

