

Proposal content document CSBP Ammonia Expansion Project

Table 1: General proposal content description

- and - control proposal content accompany			
Proposal title	Ammonia Expansion Project		
Proponent name	CSBP Limited		
Short description	The Proposal is for the construction and operation of a new ammonia plant within the CSBP Kwinana Industrial Complex in the Kwinana Industrial Area (KIA), approximately 40 km south of the Perth Central Business District (CBD) (Figure 1.1).		
	The Proposal will use natural gas sourced from the Dampier to Bunbury Natural Gas Pipeline (DBNGP), integrated with hydrogen production from a 10 megawatt (MW) electrolyser manufacture ammonia, which will then be used by CSBP for the manufacture of other chemical products or sold externally to customers.		
	The Proposal will be a self-sustained facility with a production capacity of approximately 300,000 tonnes per annum (tpa) and will be integrated with a number of existing CSBP facilities located in the KIA (Figure 2.2).		

Table 2: Proposal content elements

Table 2. Proposal c		I
Proposal element	Location/description	Maximum extent, capacity, or range
Physical elements		
Overall extent of	Figure 2.1	Development Envelope of 27.52 ha, including less than 1 ha of clearing,
the Proposal		within the 138 ha CSBP Kwinana Industrial Complex.
Ammonia plant		300,000 tonnes per annum nominal capacity
Utilities		Including:
		10MW electrolyser for hydrogen production
		Natural gas fuelled steam boiler;
		Water treatment plant for boiler water supply to ammonia plant;
		Electrolyser for green hydrogen production;
		Cooling water tower;
		Flare; and
		Other utilities.
Infrastructure and	1	Including:
logistics buildings		Existing control room modification;
		Office and maintenance workshop relocation; and
		Ammonium nitrate storage dome shelter relocation.
Construction elemen	ts	•
Laydown area,	Figure 2.1	Approximately 7 ha of temporary facilities to support construction of
carpark, and roads		the Proposal.

Proposal element Location/description Maximum extent, capacity, or range	erient t t
Nominal 27 TJ per day via gas pipeline.	erient t t
Internal generation of up to 11 MW from process waste heat.	erient t t
Internal generation of up to 11 MW from process waste heat.	erient t t
Connection to the South West Interconnected System (SWIS) for so of up to 5.6 MW electricity and purchase of equivalent renewable energy certificates (REC) for the electrolyser. Approximately 1,610 ML per annum. Liquid effluent Liquid effluent will be collected and processed through existing nu stripping wetlands, or new water treatment plant, at CSBP Kwinan prior to being pumped offsite to the Sepia Depression Ocean Outle Landline (SDOOL), Cockburn sounds diffuser or emergency beach outflow. Conditions on effluent concentrations will be in line with existing licence conditions, with load limits to increase in line with volume increases. Solid waste Solid waste including water treatment residue and spent catalyst/directed to appropriate disposal site. Construction waste streams recycled by waste management contractors where available. Residuates to local landfill in accordance with landfill classification. Energy efficiency Finished product Transport of liquid ammonia by pipeline to existing storage tanks a distribution header. Emissions to air NO _X emissions to air: Approximately 150,000 kg per annum NO_X emissions to air: Approximately 150,000 kg per annum < 30 dB(A) cumulative at nearest noise sensitive premises. < 70 dB(A) at Proposal boundary. Greenhouse gas emissions Construction	erient t t
energy certificates (REC) for the electrolyser. Approximately 1,610 ML per annum. Liquid effluent Liquid effluent will be collected and processed through existing nu stripping wetlands, or new water treatment plant, at CSBP Kwinan prior to being pumped offsite to the Sepia Depression Ocean Outle Landline (SDOOL), Cockburn sounds diffuser or emergency beach outflow. Conditions on effluent concentrations will be in line with existing licence conditions, with load limits to increase in line with volume increases. Solid waste Solid waste including water treatment residue and spent catalyst/r directed to appropriate disposal site. Construction waste streams recycled by waste management contractors where available. Residuates to local landfill in accordance with landfill classification. Energy efficiency Finished product transport Emissions to air NO _X emissions to air: Approximately 150,000 kg per annum Noise	esins
energy certificates (REC) for the electrolyser. Approximately 1,610 ML per annum. Liquid effluent Liquid effluent will be collected and processed through existing nu stripping wetlands, or new water treatment plant, at CSBP Kwinan prior to being pumped offsite to the Sepia Depression Ocean Outle Landline (SDOOL), Cockburn sounds diffuser or emergency beach outflow. Conditions on effluent concentrations will be in line with existing licence conditions, with load limits to increase in line with volume increases. Solid waste Solid waste including water treatment residue and spent catalyst/r directed to appropriate disposal site. Construction waste streams recycled by waste management contractors where available. Residuates to local landfill in accordance with landfill classification. Energy efficiency Finished product transport Emissions to air NO _X emissions to air: Approximately 150,000 kg per annum Noise	esins
Approximately 1,610 ML per annum.	esins
Liquid effluent Liquid effluent will be collected and processed through existing nu stripping wetlands, or new water treatment plant, at CSBP Kwinan prior to being pumped offsite to the Sepia Depression Ocean Outle Landline (SDOOL), Cockburn sounds diffuser or emergency beach outflow. Conditions on effluent concentrations will be in line with existing licence conditions, with load limits to increase in line with volume increases. Solid waste Solid waste including water treatment residue and spent catalyst/s directed to appropriate disposal site. Construction waste streams recycled by waste management contractors where available. Residuates to local landfill in accordance with landfill classification. Energy efficiency Finished product Transport of liquid ammonia by pipeline to existing storage tanks at distribution header. Emissions to air NO _X emissions to air: Approximately 150,000 kg per annum < 30 dB(A) cumulative at nearest noise sensitive premises. < 70 dB(A) at Proposal boundary. Greenhouse gas emissions Construction	esins
prior to being pumped offsite to the Sepia Depression Ocean Outle Landline (SDOOL), Cockburn sounds diffuser or emergency beach outflow. Conditions on effluent concentrations will be in line with existing licence conditions, with load limits to increase in line with volume increases. Solid waste Solid waste including water treatment residue and spent catalyst/r directed to appropriate disposal site. Construction waste streams recycled by waste management contractors where available. Residuated by wastes to local landfill in accordance with landfill classification. Approximately 32 to 36 GJ per tonne ammonia. Transport of liquid ammonia by pipeline to existing storage tanks at distribution header. Emissions to air No _x emissions to air: Approximately 150,000 kg per annum < 30 dB(A) cumulative at nearest noise sensitive premises. < 70 dB(A) at Proposal boundary. Greenhouse gas emissions Construction	esins
Landline (SDOOL), Cockburn sounds diffuser or emergency beach outflow. Conditions on effluent concentrations will be in line with existing licence conditions, with load limits to increase in line with volume increases. Solid waste Solid waste including water treatment residue and spent catalyst/r directed to appropriate disposal site. Construction waste streams recycled by waste management contractors where available. Residuates to local landfill in accordance with landfill classification. Energy efficiency Finished product Transport of liquid ammonia by pipeline to existing storage tanks at distribution header. Emissions to air No _X emissions to air: Approximately 150,000 kg per annum NO_X emissions to ale (A) cumulative at nearest noise sensitive premises. 70 dB(A) at Proposal boundary . Greenhouse gas emissions Construction	esins to be
outflow. Conditions on effluent concentrations will be in line with existing licence conditions, with load limits to increase in line with volume increases. Solid waste Solid waste including water treatment residue and spent catalyst/directed to appropriate disposal site. Construction waste streams recycled by waste management contractors where available. Residuates to local landfill in accordance with landfill classification. Energy efficiency Finished product	to be
existing licence conditions, with load limits to increase in line with volume increases. Solid waste Solid waste including water treatment residue and spent catalyst/directed to appropriate disposal site. Construction waste streams recycled by waste management contractors where available. Residuates to local landfill in accordance with landfill classification. Energy efficiency Finished product Transport of liquid ammonia by pipeline to existing storage tanks a distribution header. Emissions to air NO _X emissions to air: Approximately 150,000 kg per annum Noise Solid waste including water treatment residue and spent catalyst/directed to appropriate disposal site. Construction waste streams recycled by waste management contractors where available. Residuates to local landfill in accordance with landfill classification. Transport of liquid ammonia by pipeline to existing storage tanks a distribution header. NO _X emissions to air: Approximately 150,000 kg per annum < 30 dB(A) cumulative at nearest noise sensitive premises. < 70 dB(A) at Proposal boundary. Greenhouse gas emissions Construction	to be
volume increases. Solid waste Solid waste including water treatment residue and spent catalyst/r directed to appropriate disposal site. Construction waste streams recycled by waste management contractors where available. Residuants to local landfill in accordance with landfill classification. Energy efficiency Approximately 32 to 36 GJ per tonne ammonia. Transport of liquid ammonia by pipeline to existing storage tanks at distribution header. Emissions to air NO _X emissions to air: Approximately 150,000 kg per annum Noise	to be
Solid waste including water treatment residue and spent catalyst/i directed to appropriate disposal site. Construction waste streams recycled by waste management contractors where available. Residuants to local landfill in accordance with landfill classification. Energy efficiency Approximately 32 to 36 GJ per tonne ammonia. Transport of liquid ammonia by pipeline to existing storage tanks at distribution header. Emissions to air NO _X emissions to air: Approximately 150,000 kg per annum Noise	to be
directed to appropriate disposal site. Construction waste streams recycled by waste management contractors where available. Residuates to local landfill in accordance with landfill classification. Energy efficiency Approximately 32 to 36 GJ per tonne ammonia. Transport of liquid ammonia by pipeline to existing storage tanks a distribution header. Emissions to air NO _X emissions to air: Approximately 150,000 kg per annum Noise	to be
recycled by waste management contractors where available. Residuates to local landfill in accordance with landfill classification. Approximately 32 to 36 GJ per tonne ammonia. Transport of liquid ammonia by pipeline to existing storage tanks a distribution header. Emissions to air No _x emissions to air: Approximately 150,000 kg per annum Noise 30 dB(A) cumulative at nearest noise sensitive premises. 70 dB(A) at Proposal boundary. Greenhouse gas emissions Construction	
wastes to local landfill in accordance with landfill classification. Approximately 32 to 36 GJ per tonne ammonia. Transport of liquid ammonia by pipeline to existing storage tanks a distribution header. Emissions to air NO _X emissions to air: Approximately 150,000 kg per annum NO_X emissions to air: Approximately 150,000 kg per annum < 30 dB(A) cumulative at nearest noise sensitive premises. < 70 dB(A) at Proposal boundary. Greenhouse gas emissions Construction	
Energy efficiency Finished product transport Emissions to air Noise Noise Greenhouse gas emissions Approximately 32 to 36 GJ per tonne ammonia. Transport of liquid ammonia by pipeline to existing storage tanks a distribution header. Noise Noise Solution Noise Noi	ual
Finished product transport Emissions to air Noise Transport of liquid ammonia by pipeline to existing storage tanks a distribution header. Noise No _X emissions to air: Approximately 150,000 kg per annum < 30 dB(A) cumulative at nearest noise sensitive premises. < 70 dB(A) at Proposal boundary. Greenhouse gas emissions Construction	
transport Emissions to air NO _X emissions to air: Approximately 150,000 kg per annum NO_X emissions to air: Approximately 150,000 kg per annum NOise < 30 dB(A) cumulative at nearest noise sensitive premises. < 70 dB(A) at Proposal boundary. Greenhouse gas emissions Construction	
Emissions to air NO _x emissions to air: Approximately 150,000 kg per annum < 30 dB(A) cumulative at nearest noise sensitive premises. < 70 dB(A) at Proposal boundary. Greenhouse gas emissions Construction	nd
Noise < 30 dB(A) cumulative at nearest noise sensitive premises. < 70 dB(A) at Proposal boundary. Greenhouse gas emissions Construction	
< 70 dB(A) at Proposal boundary. Greenhouse gas emissions Construction	
Greenhouse gas emissions Construction	
Construction	
Scope 1 Estimated 10 EOE tennes CO a	
Scope 1 Estimated 19,505 tonnes CO ₂ -e.	
Scope 2 Any occurring will displace Scope 1 emissions described above.	
Scope 3 Not determined.	
Operation	
Scope 1 Estimated maximum 539,003 tonnes CO ₂ -e per annum.	
Scope 2 Estimated 33,735 tCO ₂ -e per annum avoided via purchase of RECs	
Scope 3 Estimated 42,961 tonnes CO ₂ -e per annum.	
Rehabilitation	
Not applicable	
Commissioning	
Commissioning of the Proposal will be subject to operational limits above.	
Decommissioning	
Removal of all above surface infrastructure. Buried services will be decommissioned and left in-situ or removed.	
Elements which affect extent of effects on environment	
Proposal time Expected Project life 35 years	
Project Development Approximately 3 years	
Operation phase Approximately 30 years	
Decommissioning Approximately 2 years	