Hydrogeological Assessment

Calingiri Copper Project Caravel Minerals

Revision No 1 July 2018



Leaders in Environmental Practice



Pendragon Environmental Solutions

ABN: 92 147 485 416

Address and Contact Details

Suite 2, Level 1, 464 Murray Street

Perth WA 6000

Tel: +61 (8) 9382 8286

e-mail: info@pendragonenvironmental.com
Website: www.pendragonenvironmental.com

Limitations, Uses and Reliance

This document, once read in its entirety, may be relied upon for the purposes stated within the limits of:

Environmental investigations and assessments are undertaken in accordance with an agreed term of reference and timeframe and may involve intrusive investigations of subsurface conditions, generally at a few selected locations. Although due care, skill and professional judgement are applied in the interpretation and extrapolation of environmental conditions and factors to elsewhere, the potential for variances cannot be discounted. Therefore, the results, analyses and interpretations presented herein cannot be considered absolute or conclusive. Pendragon Environmental Solutions does not accept any responsibility for variances between the interpreted and extrapolated and those that are revealed by any means. Specific warning is given that many factors, natural or artificial, may render conditions different from those that prevailed at the time of investigation and should they be revealed at any time subsequently, they should be brought to our attention so that their significance may be assessed and appropriate advice may be offered. Users are also cautioned that fundamental assumptions made in this document may change with time and it is the responsibility of any user to ensure that assumptions made, remain valid.

The comments, findings, conclusions and recommendations contained in this document represent professional estimates and opinions and are not to be read as facts unless expressly stated to the contrary. In general, statements of fact are confined to statements as to what was done and/or what was observed; others have been based on professional judgement. The conclusions are based upon information and data, visual observations and the results of field and laboratory investigations and are therefore merely indicative of the environmental conditions at the time, including the presence or otherwise of contaminants or emissions. In addition, presentations in this document are based upon the extent of the terms of reference and/or on information supplied by the client, agents and third parties outside our control. To the extent that the statements, opinions, facts, conclusions and/or recommendations in this document are based in whole or part on this information, those are contingent upon the accuracy and completeness of the information which has not been verified unless stated otherwise. Pendragon Environmental Solutions does not accept responsibility for omissions and errors due to incorrect information or information not available at the time of preparation of this document and will not be liable in relation to incorrect conclusions should any information be incorrect or have been concealed, withheld, misrepresented or otherwise not fully disclosed. Neither will we be liable to update or revise the document to take into account any events, emergent circumstances or facts occurring or becoming apparent after the date of this document.

Within the limitations imposed by the terms of reference, the assessment of the study area and preparation of this document have been undertaken and performed in a professional manner, by suitably qualified and experienced personnel, in accordance with generally accepted practices and using a degree of skill and care ordinarily exercised by environmental consultants under similar circumstances. No other warranty, expressed or implied, is made.

This document has been prepared for the purposes stated herein. Every care was taken in the interpretation of environmental conditions and the nature and extent of impacts, presentation of findings and recommendations which are provided in good faith in the general belief that none of these are misleading. No responsibility or liability for the consequences of use and/or inference by others is accepted.

Intellectual and copyright in the information, data and representations such as drawings, figures, tabulations and text, included in this document remain the property of Pendragon Environmental Solutions. This document is for the exclusive use of the authorised recipient(s) and may not be used, copied or re-produced in whole, or in part, for any purpose(s) other than that for which it was prepared for. No responsibility or liability to any other party is accepted for any consequences and/or damages arising out of the use of this document without express and written consent.

The above conditions must be read as part of the document and must be reproduced where permitted. Acceptance of this document indicates acceptance of these terms and conditions.

Reference: PES18001 Page 2 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



Report

Title:	Hydrogeological Assessment Calingiri Copper Project
File:	PES18001
Author(s):	Ryan Lawrence, Fanie de Lange and Carel van der Westhuizen
Client:	Caravel Mineral
Contact:	Peter Pring
Synopsis:	This document details groundwater investigations at the Calingiri Copper Project, undertaken in accordance with Department of Water Operational Policy No. 5.12 – Hydrogeological Reporting associated with a Groundwater Well Licence. Although no level of assessment has been set yet, this document complies with a level H2 assessment.

Document Control

Revision No	Date	Author(s)	Reviewer(s)
1	25 July 2018	Ryan Lawrence, Fanie de Lange, Carel van der Westhuizen	Taryn Wren

Distribution

Revision No	Date	Approved	Recipient(s)	No of Copies
1	25 July 2018	Ryan Lawrence	Caravel Minerals	1

Revision

Revision No	Date	Description	Approved			
1	25 July 2018	Issued for Client review	Ryan Lawrence			
Recipients are responsible for eliminating all superseded documents in their possession.						

© Pendragon Environmental Solutions 2018

Reference: PES18001 Page 3 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



Table of Contents

EX	ecuti	ve Summary	7
1.	Intro	oduction	9
	1.1	Scope of Work	g
	1.2	Objectives	9
	1.3	Project Description	10
2.	Clin	nate	14
3.	Hyd	rogeology	16
	3.1	Geology	16
	3.2	Local and Regional Aquifers	16
	3.3	Groundwater Occurrences and Recharge Potential	
	3.4	Local Ground Water Trends	
	3.5	Bore Construction	20
4.	Exis	sting Ground Water Use	23
	4.1	Ground Water Licences	
	4.2	Ground Water Use	23
	4.3	Groundwater Dependent Ecosystems (GDEs)	23
5 .	Gro	und Water Investigations	
	5.1	Bore Drilling	
	5.2	Bore and Aquifer Testing	27
	5.3	Ground Water Chemistry	
		5.3.1 Ground Water Quality	33
		5.3.2 Stable Isotope Analysis	37
6.	Con	ceptual Ground Water Model	43
	6.1	Introduction	43
	6.2	The Calingiri Conceptual Model	43
7.	Ass	essment of Potential Impacts	45
	7.1	Ground Water Levels	45
	7.2	Ground Water Quality	46
	7.3	Ground Water Yields	46
	7.4	Potential AMD and Sediment/Salt Loads	46
	7.5	Aquifer/Ground Water Resource	46
	7.6	Beneficial Use and the Receiving Environment	46
	7.7	Summary of Impacts	47
8.	Gro	und Water Monitoring	49
9.	Man	agement Approach	51
10.	Con	clusions and Recommendations	52



10.1	Conclusions	52
10.2	Recommendations	53
Referen	ces	54
Figures		
Figure 1.1	: Location of the Calingiri Copper Project.	9
Figure 1.2	: Location of the Bindi, Dasher and Opie Prospects and Open Pits	11
Figure 1.3	: Location of the Bindi, Dasher and Opie Prospects and Open Pits	12
Figure 1.4	: Tenements and Mine Infrastructure	13
Figure 2.1	: Monthly Climatic Data.	14
Figure 3.1	: Water in Exploration Bores	19
Figure 3.2	: Proposed Bore Locations, Bindi Paleo Channel	21
Figure 4.1	: Aquatic Ecosystems.	25
Figure 4.2	: Terrestrial Ecosystems	25
Figure 5.1	: Bore Locations at Bindi (process plant in blue and TSF in yellow)	26
Figure 5.2	: Bore Locations at Opie (11km due south of Bindi).	26
Figure 5.3	: Bore Test 18CAWB001	30
Figure 5.4	: Bore Test 18CAWB002	31
Figure 5.5	: Bore Test 18CAWB005	32
Figure 5.6	: Bore Test 18CARC027.	33
Figure 5.7	: Piper Diagram	36
Figure 5.8	: Durov Diagram	36
Figure 5.9	: Stiff Diagram	37
Figure 5.1	0: General guide for ¹⁸ O and ² H Interpretation	39
Figure 5.1	1: Graphical Representation of Isotope Data vs the GMWL	40
Figure 5.1	2: Graphical Representation of Isotope Data vs the LMWL	40
Tables		
Table 1.1:	Calingiri Copper Project Tenements.	13
Table 2.1:	Climatic Data (Wongan Hills Weather Station 008137, Bureau of Meteorology, 2018)	14
Table 3.1:	Proposed Bore Locations.	20
Table 4.3:	Criteria for Discerning GDEs.	23
Table 5.1:	Summary of Bore Construction, Hydrogeological Details and Bore Testing	28
Table 5.5:	Field Measurements of Surface and Ground Water Quality.	34
Table 5.6:	Concentrations of Major Ions in Ground Water	34
Table 5.7:	Concentrations of Heavy Metals in Ground Water	35
Table 5.5:	Stable Isotope Analytical Data.	39
Table 5.6:	Summary of CI-Method Estimation of Recharge	41
Table 7.1:	Summary of Impact Assessment	48
Table 8.1:	Proposed Ground Water Monitoring Locations, Frequency and Analytes	49

Reference: PES18001 Page 5 of 55 Date: July 2018 Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



Appendices

Appendix A: Search Data.

Appendix B: Bore Drilling and Testing Completion Records.

Appendix C: Water Quality Data and Laboratory Certificates.

Reference: PES18001 Page 6 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



Executive Summary

Scope of Works

Pendragon Environmental Solutions was requested by Caravel Minerals to undertake a desk study assessment of groundwater at their Calingiri Copper Project. This brief was subsequently extended to include drilling into known paleo valleys near the proposed new processing plant to assess the water bearing potential of these paleo valleys. It was agreed that reporting will comply with a H2 level of hydrogeological assessment as outlined in Operational Policy No. 5.12 - Hydrogeological Reporting associated with a Groundwater Well Licence (Department of Water, 2009).

A license to drill exploratory bores under Section 26D of the Rights in Water and Irrigation Act 1914 was lodged with the Department of Water and Environmental Regulation (DWER). DWER subsequently advised that this application is not required as the property is in an unproclaimed water resource area.

Objectives

In addition to undertaking the preliminary investigation into the water bearing potential of the paleo valleys, this document details a hydrogeological assessment pertaining to the potential for impacts by mining on environmental factors including terrestrial environmental quality, hydrological processes, inland waters environmental quality and rehabilitation and decommissioning. The primary objectives are to ensure that the quality of land, soils, sediment and surface and ground water are maintained to protect environmental values and existing and potential future uses and to facilitate decommissioning and closure in an ecologically sustainable manner.

Salient Findings

The geology of the area comprises paleo channel sediments within and underlain by granite/gneiss bedrock which has been faulted and intruded by dykes of dolerite. The primary aquifers are:

- sediments confined to paleo channels or valleys; and
- weathered/fractured granite-gneiss bedrock, faulted in places and intruded by near-vertical dykes of dolerite.

Preliminary investigations were undertaken to assess the paleo valleys but the underlying faulted and intruded bedrock utilising the overlying paleo channels as a source for recharge has yet to be investigated. Ground water was encountered in paleo channel sediments between 5m and 45m with yields varying between 0.1L/s and 4.8L/s from 100mm diameter bores. Preliminary assessments suggest that larger yields in the range between 10L/s and 20L/s are possible and sustainable. Utilising the current range of hydraulic parameters (T values between 30m²/day and 900m²/day and a S value of 0.002), the cone of drawdown may extend between 7km and 10km from the plant site at an abstraction rate of 100L/s.

Recharge to the paleo channels was estimated at 6mm/a or 1.6% of the mean annual rainfall which may constrain groundwater exploitation as a large area will be required to sustain bore and aquifer yields over the long term.

Ground water has elevated concentrations of Total Dissolved Solids (between 1,900mg/L and 5,000mg/L), predominantly Chloride and Sodium, which often exceed the Australian Drinking Water Guidelines, and to a lesser extent Sulfate. The heavy metals Arsenic, Cadmium, Chromium, Lead, Selenium, Iron and Mercury are absent in groundwater. Concentrations of Aluminium, Copper, Nickel and Zinc generally exceed the

Reference: PES18001 Page 7 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



ANZECC Fresh Water guidelines for most if not all species protection levels but are well below the drinking water guideline.

With the current layout of mine infrastructure and provided that construction employs best practice, it seems unlikely that mining and processing at the Calingiri Copper Project will impact any GDE's and subterranean fauna seems to be absent.

The primary impacts of mining and processing pertain to:

- The potential for impacts to soils, sediment, surface and ground water resources.
- Potential seepage from mine impoundments such as ROM pads, stockpiles and plant water infrastructure, WRDs and the TSF: mounding underneath and downstream thereof impacting groundwater quality.
- Groundwater abstraction and mine influx: receding ground water levels across mining area and beyond may impact local and/or regional water supplies.
- Exposure of sulfide-bearing materials in open pit excavations during mining and subsequent rehabilitation and closure.
- Open pit sinks and/or lakes post closure.

Whilst the impacts appear to be acceptable and manageable, appropriate site specific management of mining, waste rock and tailings disposal and ground water abstraction will be required to ensure that there is no impact on the receiving environment.

More drilling, and testing and sampling are required across the area in order to develop the conceptual model to a level of higher confidence and higher resolution regarding geological heterogeneities. Piezometric heads need to be measured across the area to be able to determine the aquifer(s) within the system as well as their interaction and boundaries.

Recommendations

Consideration should be given to:

- Undertake a census of all available surface and ground water sources within the mine tenements.
- Refine the mine water requirement to define the extent of further groundwater supply investigations.
- Utilise geophysical techniques to delineate aquifers and locate future drilling targets.
- Groundwater monitoring in accordance with this document.
- Further drilling, testing and sampling to not only investigate the paleo channel aquifers but also the faulted/fractured and intruded underlying granite/gneiss.

Reference: PES18001 Page 8 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



1. Introduction

1.1 Scope of Work

Pendragon Environmental Solutions was requested by Caravel Minerals to undertake a desk study assessment of groundwater at their Calingiri Copper Project (Figure 1.1). This brief was subsequently extended to include drilling into known paleo valleys near the proposed new processing plant to assess the water bearing potential of these paleo valleys. It was agreed that reporting will comply with a H2 level of hydrogeological assessment as outlined in Operational Policy No. 5.12 - Hydrogeological Reporting associated with a Groundwater Well Licence (Department of Water, 2009).




Figure 1.1: Location of the Calingiri Copper Project.

A license to drill exploratory bores under Section 26D of the Rights in Water and Irrigation Act 1914 was lodged with the Department of Water and Environmental Regulation (DWER). DWER subsequently advised that this application is not required as the property is in an unproclaimed water resource area; the well can be drilled without a license (email dated 19/02/2018). Nevertheless, bores were constructed to the standards outlined in the Minimum Construction Requirements for Water Bores in Australia (National Uniform Drillers Licensing Committee, 2012).

1.2 Objectives

This document details the hydrogeological assessment pertaining to the potential for impacts by mining on environmental factors including Terrestrial Environmental Quality, Hydrological Processes, Inland Waters Environmental Quality and Rehabilitation and Decommissioning (EPA, 2015). The primary objectives are to ensure that the quality of land, soils, sediment and surface and ground water is maintained to protect environmental values and existing and potential future uses and to facilitate decommissioning and closure in an ecologically sustainable manner.

Reference: PES18001 Page 9 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



1.3 Project Description

The proposed Calingiri Copper Project is located some 120km north-east of Perth, 13km south-west of the township of Wongan Hills and some 3km south-west of Lake Ninan in the northern Wheatbelt of Western Australia. Lake Ninan, at the head of the Mortlock River (North), covers an area of almost 700ha of reserve land.



Lake Ninan (view from south to north).



Calingiri-Wongan Hills Road crossing Mortlock River east of Lake Ninan.

The Department of Parks and Wildlife (DPAW) manages the 259ha A Class Reserve for the conservation of fauna and flora (vested 1963) and the Recreation Reserve (245ha) is managed by the Shire of Wongan-Ballidu. The lake, along with many wetlands in Western Australia, was impacted by water logging and increased salinity. It is affected by the activities in the catchment which extends north as far as Bindi Bindi and consequently, the water in the lake can be up to six times more saltier than the sea, fish species once found are no longer consistently present and the numbers and variety of bird species are reduced due to the absence of food in the lake. There are no other potential ground water dependent ecosystems within the mining area.

Access to the Calingiri Copper Project is via the Calingiri-Wongan Hills road or the Great Eastern Highway and Goomalling Road. The project is accessible year round via the sealed road network with local access via gazetted gravel roads. Rail infrastructure, used for grain, provides access to the ports of Fremantle and Kwinana.

The project, currently the subject of a feasibility study, is considered a world class copper resource having a large resource (844kt Copper and 17kt Molybdenum, Caravel Minerals March 2018) and low (1:1) strip ratio with processing by means of conventional flotation. Environmental, social, tenure and infrastructure are low risk with low technical risk and no native title issues. Caravel Minerals intends employing an advanced bulk ore sorting technology to optimise mill feed grades with lower plant throughput and consequently markedly lower power and water consumption and tailings requirements. The project has an initial life of 21 years at 15Mtpa.

Conventional opencast mining will take place at three locations: Bindi, Dasher and Opie (Figure 1.2); these deposits all contain Copper (Cu), Molybdenum (Mo), Silver (Ag) and Gold (Au). Processing will be by means of crushing (with ore stockpiling), grinding and flotation to yield a concentrate for metal recovery. Waste rock will be placed in rock dumps near the open pits. The Calingiri mineralisation is characterised by a relatively simple mineralogy. All the copper is in the form of chalcopyrite with pyrite the only other significant sulphide (cpy: py variable 3:1 to 1:1). All sulphides, including molybdenite, are relatively coarse grained. The gangue is dominantly silicates (quartz, feldspar, epidote, chlorite and garnet) with minor magnetite

Reference: PES18001 Page 10 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1






Figure 1.2: Location of the Bindi, Dasher and Opie Prospects and Open Pits.

The Tailings Storage Facility (TSF) at Bindi, adjacent to the processing plant, will be progressively developed over the life of mine with conventional sub areal deposition forming long beaches with water returned to the process plant for reuse from a central decant. The final TSF will have 4 cells of 300ha each, each cell having a diameter of around 1,950m i.e. the final TSF will cover an area of 1,200ha, 3.9km by 3.9km. The cells will be operated in pairs.

Water supply options include the large paleo channel located close to the Bindi and Dasher Prospects (refer Figure 1.2). Additional supplies are further afield.

The Bindi mineral resource has a cumulative strike of 3,700m, a plan width of 200m (Bindi West) and 350m (Bindi East) and depth extent of 360m below surface. The resource has an overall flat lying geometry, except in the west where it dips to the west under a hanging wall fault zone. The Dasher Mineral Resource has a strike extent of 1,500m, a plan width of 170m and depth extent of 490m below surface with an average dip of 45 degrees to the east. The Opie Mineral Resource has a strike extent of 250m, a plan width of 400m and depth extent of 250m below surface with a shallow northerly dip.

There is a saprolitic weathering layer between 5m and 50m thick (at Bindi and 45m and 35m respectively at Dasher and Opie), immediately below which the mineralisation is developed. All of the reported resources relate to sulphide mineralisation which is developed within a very consistent gneissic unit. All the resources remain open in a number of directions (Figure 1.3).

Reference: PES18001 Page 11 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1






Figure 1.3: Location of the Bindi, Dasher and Opie Prospects and Open Pits.



Caravel Minerals (Quadrio Resources Pty Ltd) holds twelve Exploration Licences and one Prospecting Licence and owns 80% of Tenement E70/2343 held by Geodex Resources Pty Ltd Table 1.1 and Figure 1.4). All tenements are on privately owned land (excluded from this assessment).

Table 1.1: Calingiri Copper Project Tenements.

Tenement Number	Holder	Tenement Area (ha)	Legal Area [Blocks]	Status	Grant Date
E70/2788	Bindi and Dasher Open Pits and Waste Rock Dumps; Processing Plant and Tailings Storage Facility	27,616	70	Live	6/03/2007
E70/2789	Opie Open Pit and Waste Rock Dump	14,070	35	Live	11/08/2006
E70/3680	Exploration	4,018	10	Live	23/11/2009
E70/3755	Exploration	2,009	5	Live	15/04/2010
P70/1593	Exploration	157	116	Live	10/02/2011
E70/3674	Bindi Open Pits and Waste Rock Dumps	2,277	6	Live	15/11/2010
E70/4517	Exploration	802	2	Live	26/08/2013
E70/4476	Exploration	2,140	6	Live	19/08/2013
E70/4675	Exploration	799	2	Live	12/01/2015
E70/4674	Exploration	22,993	58	Live	14/01/2015
E70/4676	Exploration	803	3	Live	11/03/2015
E70/4732	Exploration	3,215	8	Live	11/08/2015
E70/4746	Exploration	4,024	10	Live	31/08/2015
E70/2343	Exploration	2,407	6	Live	30/05/2001




Figure 1.4: Tenements and Mine Infrastructure.

Reference: PES18001 Page 13 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



2. Climate

The area has a Mediterranean warm and temperate climate with dry hot summers and mild winters. Rain falls (Table 2.1 and Figure 2.1) mostly in the winter and average 388mm/a. It is the most important variable that impacts productivity and land degradation and arises from two general climatic systems: southern frontal systems, which pass from west to east; and rain from tropical air with a general pattern that tends to be a mosaic of wet and dry localities, which shifts from year to year. The growing season rainfall from April to October accounts for 75% of the average annual rainfall.

Table 2.1: Climatic Data (Wongan Hills Weather Station 008137, Bureau of Meteorology, 2018).

	•												
Statistics	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Annual
Mean Temperature (°C)													
Maximum	34.6	34.1	30.9	26.5	21.6	18.2	17.0	17.9	20.7	25.2	29.2	32.5	25.7
Minimum	17.9	18.2	16.4	13.4	9.9	7.7	6.6	6.7	7.6	10.1	13.2	15.8	12.0
Mean Rainfall and Evaporati	on (mm)												
Mean Rainfall (mm)	15.5	15.4	20.7	22.4	51.6	69.4	69.3	51.6	29.8	19.6	12.4	10.0	388.2
Highest rainfall (mm)	134.6	110.5	165.8	81.3	187.9	220.2	174.4	131.1	97.3	121.6	60.3	71.4	675.4
Highest daily rainfall (mm)	71.6	79.8	81.3	61.7	63.5	69.6	86.2	34.3	37.1	53.2	38.6	57.2	86.2
Mean number of rain days	2.1	2.3	2.9	4.9	8.8	12.3	13.5	12.2	8.6	5.9	3.4	2.0	78.9
Days of rain ≥ 25mm	0.2	0.2	0.2	0.1	0.3	0.4	0.3	0.1	0.0	0.0	0.0	0.1	1.9
Daily Evaporation	11.6	10.6	8.6	5.5	3.4	2.3	2.1	2.6	3.8	5.9	8.4	10.3	6.3
Daily Evaporation obtained from	the Wong	an Hills Re	s. Station	008138; 4 ⁻	1 years, 19	65 to 2013							




Figure 2.1: Monthly Climatic Data.

Since evaporation (averaging at about 2,276mm/a) exceeds rainfall (averaging at about 388mm/a) by



almost six times, there is a water deficit across the region (Table 2.1). December, January and February are the hottest months with average maximum temperatures around 34°C. The lowest temperatures occur in winter, between June and September, when average maximum temperatures are below 20°C and average minimum temperatures are around 7°C (Table 2.1 and Figure 2.1).

Reference: PES18001 Page 15 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



3. Hydrogeology

3.1 Geology

The Calingiri Project is located in the south-western corner of the Archaen Yilgarn craton comprising granitic, volcanic and sedimentary rocks. The Calingiri mineralised trend extends south of the Wongan Hills Greenstone Belt (host to the Ninan mineralisation) into an area dominated by granite and granite-gneiss (hosts to the Bindi, Dasher and Opie deposits).

The mineralisation at Bindi, Dasher and Opie is of a common style: it comprises chalcopyrite, pyrite, Molybdenite and magnetite, disseminated within coarse-grained quartz-feldspar-garnet-biotite gneiss of granitic origin. The garnet-biotite gneiss and associated mineralisation typically forms tabular zones in the order of 50m to 150m thick, up to 200m, through the core of the main prospects. The sulphide mineralisation is developed in fresh bedrock generally at depths between 5m and 50m beneath a regolith cover of *in situ* saprolitic clays blanketed by a variable 1m to 10m layer of sand and gravel beneath a thin soil horizon.

The mineralised zones at Dasher and Opie dip moderately to the east and north respectively, while the Bindi mineralisation appears to be folded resulting in the Bindi West (west dipping) and Bindi East (dip currently uncertain) components. Drilling identified lenses of amphibolite at all prospects and some post-mineralisation granite and pegmatite intrusions. Post-mineralisation dykes of dolerite are common.

3.2 Local and Regional Aquifers

Local aquifers comprise relatively shallow paleo-channels between 5m and 50m thick. Faults, fracture systems and dykes of dolerite intruded into the host gneiss and granite bedrock, usually considered impermeable, form weathered and fractured rock aquifers at depth. Alluvial streambed aquifers are generally absent, sediments in creeks and drainage lines are thin, less than 2m thick.


Regional aquifer assessments include the groundwater investigations at West Midlands/Koojan-Gillingarra (Capitela) by the Agriculture and Food Division of the Department of Primary Industries and Regional Development, The Mapping and Water Management Project, funded through the Royalties for Regions program, identified groundwater resources for irrigated agriculture or livestock water supplies in the Capitela Valley (Department of Agriculture and Food Western Australia, DAFWA, 2008) and discovered a 10km long surficial paleo channel in the Perth Basin about 20km west of the Midlands Road. In 2009 DAFWA investigated spreading salinity in the Gillingarra-Koojan Catchment 30km south of Moora: significant increases in salinity at some locations, causing loss of agricultural land, death of eucalypt woodlands and damage to the Midlands Road and rail line, might be caused by groundwater discharge from a paleo channel extending east towards New Norcia. To some extent, the paleo channel sediments discovered west of the Darling Fault in 2008 in the Capitela Valley aligned with the surmised paleo channel from New Norcia to Gillingarra. However, it was not clear whether the eastern and western sections of those separate channels were connected and one of the aims of the project was to investigate that possibility by means of airborne electromagnetic geophysical surveys (AEM) followed by drilling (mud rotary) to install a system of monitoring bores and a production bore and aquifer test pumping to determine the hydraulic parameters of the aquifer.


The AEM survey across a rectangular area about 50km long and 7km wide, extending from New Norcia in the east to Yathroo in the west, located a paleo channel 125m to 130m below ground in granite bedrock. Whilst it was presumed that the paleo channel continues westward, it is possible the

Reference: PES18001 Page 16 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



paleo channel sediments in the west are not linked to the paleo channel in the east (DAFWA, 2018).





Paleo channel sediments extend to 197m below surface some 6km north-west of New Norcia, significantly deeper than other paleo channels in the vicinity (generally no deeper than 100m below surface and more typically between 40m and 50m deep). Further to the west where the paleo channel crosses the Gillingarra-Glentromie Road, the paleo channel sediments extend to a depth of 192m. Aquifer testing at a constant discharge rate of 8L/s resulted in water level drawdown to 32m with subsequent recovery to more than 90% within 5 minutes. The bore yielded water with an Electrical Conductivity of 300mS/m or Total Dissolved Solids less than 1,700mg/L. DAFWA indicated that whilst water in the upper parts of the palaeochannel aquifer is very fresh, further analysis is needed to determine how far the fresh water extends.

3.3 Groundwater Occurrences and Recharge Potential

Most of the eastern Wheatbelt is situated on an Archaean craton with a flat landscape underlain by predominantly igneous rocks. Intrusions by dolerite dykes and more recent deformation by major faults, minor faults, and shear zones, have resulted in a strongly structurally controlled basement-aquifer complex. Aeolian, colluvial, fluviatile and lacustrine sediments overlie deeply weathered saprolite. The groundwater regime is a complex fractured-rock and regolith system through which water is transported slowly (DAFWA, 2007) with three main aquifer types: sedimentary (paleo channels), saprolite and fractured crystalline basement. Owing to the costs of drilling and high salinity of most groundwater, few bores were drilled to determine the hydraulic properties of the fractured basement aquifer system; the potential of these aquifers depends on the density of fractures, degree of connectivity and whether the fractures are open or filled with clay minerals but is likely to possess low porosity and high permeability.

Bedrock is generally overlain by alluvial deposits (soil) and regolith of markedly variable thicknesses, developed *in situ* by weathering of the underlying granite. The transition zone between unweathered bedrock and the overlying saprolite is often more permeable than the bulk of the saprolite.

The salt-river system and salt lakes of the Wheatbelt are dominated by chains of salt lakes, generally following the paths of the older paleo drainage system. They rarely flow as an interconnected system due to low seasonal rainfall, high evaporation rates and shallow lake profiles but rather act as a series of evaporation sumps to surface run-off.

Groundwater levels have risen following clearing of native vegetation; fluctuations characterised by a few distinct patterns (DAFWA, 2007):

Reference: PES18001 Page 17 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



- Seasonal fluctuation in the lower reaches of catchments where aquifers have direct hydraulic contact with creeks: water levels rise during winter and fall during summer in response to rainfall.
- Monotonically rising water levels in the upper reaches of catchments where water levels are relatively deep and rates of recharge are high. The rate of rise ranges from 0.2m/a to 0.5m/a.
- Continuously rising water levels with seasonal fluctuations in mid-slope areas; the water levels normally exhibit a sinusoidal pattern with a rising trend.
- Continuously falling water levels with seasonal fluctuations in catchments where re-vegetation occurred; in the Merredin catchment water levels declined by about 2m over five years.

Very little is known about the hydraulic and yield characteristics of the aquifers in close proximity to and underlying the Calingiri Copper Project. Detailed assessments of exploration drilling data (Caravel Minerals, 2018) revealed that groundwater was encountered in sands (paleo channels), fractures and in dolerite. Comments recorded by Caravel during exploratory drilling included:

- Bores abandoned/terminated due to water ingress, or too much water to continue or too wet or excess water.
- Water at (depth)m and very wet sample.
- Strong water flow and significant water.
- Hit groundwater/aquifer/paleo channel sands (running, collapsing), fresh/saline/salty water.
- Hit (small) fracture, abundant water flow and/or massive water.
- Water from fracture in dolerite.

The exploration database (refer Figure 3.1) indicated that some 44 of the 132 bores encountered groundwater between 100m and 250m depth. The remaining 88 bores encountered groundwater between 3m and 100m below surface averaging 42m with a standard deviation of 26m.

It seems that interconnectivity between aquifers, ground water storage and recharge potential would be limited (in quantity and also in lateral extent), controlled by irregular paleo and weathering/fracture/fault systems and intrusions, low and predominantly determined by secondary porosity and hydraulic conductivity coupled with the presence of and constraints by geological barriers. The depth

to ground water excludes ground water discharge into drainage lines and creeks (interconnectivity between ground and surface water) and consequently ground water dependent ecosystems.

Preliminary estimates of the hydraulic parameters of the sediments in the paleo channels and fractured/intruded bedrock aquifers are:

Aquifer Transmissivity T (m²/day):

less than 1 and between 10 and 100

Aquifer Storativity S (dimensionless):

less than 0.0005

Recharge (% of mean annual precipitation, MAP):

<3, if any, up to 6 in high rainfall years

Since the area has low rainfall with erratic seasonal distribution and high potential evaporation, recharge will be limited to a few events exceeding 25mm each year (Table 2.1).

3.4 Local Ground Water Trends

There are no hydrographs for bores at the Calingiri Copper Project; local ground water trends are therefore unknown.

Reference: PES18001 Page 18 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1






Figure 3.1: Water in Exploration Bores.



3.5 Bore Construction

A bore drilling program, primarily aimed at the paleo channel south of the proposed new plant at Bindi, including bore testing and water quality sampling, was to be implemented between March 2018 and April 2018. The objectives and scope of work for these preliminary hydrogeological investigations, constraint by both budget and time (availability of land prior to the planting season), included:

- Drill and construct small diameter (165mm drilling with 100mm solid casings and screens across the water bearing zones) ground water bores in accordance with the Minimum Construction Requirements for Water Bores in Australia (National Water Commission, 2012).
- Implement bore tests in accordance with Australian Standard AS 2368-1990 Test Pumping of Water Wells to ascertain the extent of aquifers and their characterization in terms of their hydraulic parameters and consequently the extent of the zone that may be impacted by mining. Undertake short-term 12-hour constant-rate discharge tests followed by recovery once the bores were constructed and fully developed:
 - The duration of discharge pump tests may vary between 12 hours and a maximum of 24 hours depending on the preliminary estimated bore yields attained during bore drilling/development.
 - The final number of bores to be tested will be decided upon following estimations of airlift yields on completion of drilling/development.
 - If airlift yields are low (<0.50L/s), falling/rising head tests will be undertaken by either pump-out and/or injection of water into the bore whilst the water level drawdown or rise is measured.
 Conventional slug tests by inserting a slug of known volume may also be undertaken.
- Undertake surveys of ground water levels to ascertain regional and local flow directions and velocities.
- Obtain ground water samples to ascertain the ambient quality of ground water.
- Obtain ground water samples for determining recharge characteristics by means of natural isotopes.
- Interpret and assess field and laboratory data gathered during the above programs to ascertain potential preferential pathways and enable a prediction of the potential impacts of mining and processing on the surrounding and downstream environments.

Indicative bore locations and details pertaining to construction/development of bores and subsequent testing appear in Table 3.1 and Figure 3.2.

Table 3.1: Proposed Bore Locations.

Site ID	Zone Coordinates		rdinates	Indicative Depth	Anticipated Ground Water Level			
Site ib	20116	Easting	Northing	(m)	(mbgl)			
Bindi Paleo	Channel (F	Refer Program o	of Work: 72163); Te	nement E70/2788				
PWB001		465,835	6,572,235					
PWB002		465,670	6,571,760					
PWB003		466,170	6,571,710					
PWB004		466,070	6,571,190					
PWB005		465,595	6,570,555					
PWB006	50J	466,465	6,570,475	up to 50	5 - 10			
PWB007		466,700	6,571,190					
PWB008		467,595	6,571,140					
PWB009		468,675	6,571,230					
PWB010		469,415	6,571,295					
PWB011		469,445	6,570,535					

Reference: PES18001 Page 20 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



Site ID	Zone		rdinates	Indicative Depth	Anticipated Ground Water Level
Site ib	Zone	Easting	Northing	(m)	(mbgl)
PWB012		468,620	6,570,345		
PWB013		467,585	6,570,340		
PWB014	50J	467,565	6,569,820	up to 50	
PWB015		468,500	6,569,815		
PWB016		469,475	6,569,825		
Opie (Refer	Program of	Work: 71063);	Tenement E70/278	9	
PDH096		468,450	6,560,680		
PDH098		468,900	6,560,520		
PDH099		468,520	6,560,520		
PDH100	50J	467,890	6,560,000	up to 50	5 - 10
PDH104		467,100	6,560,400		
PDH106		467,000	6,560,400		
PDH108		467,000	6,560,300		




Figure 3.2: Proposed Bore Locations, Bindi Paleo Channel.

The final number of bores, locations, depths, construction/development and completion requirements, pump testing and sampling will be determined during the drilling program. Key geological and hydrogeological parameters to be collected during the drilling and pump testing programs include:

- Drilling logs to record the geological formations. The soils and geological formations encountered, changes in lithology and mineralogy, evidence of structural formations, water strike depths and approximate water yields, etc. will be recorded on a simple but accurate drill log. Where possible soil/rock samples would be taken at regular depths (e.g. every meter) and described during the drilling process. If needed, some of the solid samples will be tested for their mineralogical and geochemical properties.
- Depth and nature of water strikes, pending drilling method (RC or mud rotary).
- Approximate airlift yields.
- Details of well installation (length of casings, well-screen, thickness of gravel pack and seal materials such as bentonite, etc.) and bore development.
- Samples for water quality assessment. In situ (field) measurements will include: pH, EC, TDS,
 Salinity, Temperature, Dissolved Oxygen, Oxidation Reduction Potential including observations



such as odour, colour, etc.). NATA accredited laboratory analytical assessments of the water samples will include:

- o Total Alkalinity (Talk, mg/L).
- Total Acidity (TAc, mg/L).
- Major anions (CI, SO₄, CO₃/HCO₃, NO₃-N; mg/L).
- Major cations (Ca, Mg, Na and K; mg/L).
- o Dissolved metals (Al, As, B, Cd, Cr, Cu, Fe, Mn, Ni, Pb, Zn, Fe; μg/L).
- o Nutrients (Ammonia, Nitrite, Nitrate, Total Kjeldahl Nitrogen, Total Nitrogen, Reactive Phosphorus and Total Phosphorus).
- Samples for isotope assessment.



4. Existing Ground Water Use

4.1 Ground Water Licences

The Calingiri Copper Project falls within an unproclaimed groundwater area in which licences in terms of Section 26D (constructing a well and/or taking of water) of the Rights in Water and Irrigation Act 1914 are not required.

4.2 Ground Water Use

Large proportions of dryland farms in Western Australia receiving less than 600mm average rain suffer from water supply problems in the form of shortages, poor quality or combinations of these two factors (DAFWA, 2007). The Farm Water Plan of 1994 (Farm Water Strategy Group, 1994) indicated that the north-eastern and eastern wheatbelt is where the greatest difficulty for development of reliable on-farm water supplies is experienced.

Water supplies are described as either low quality (livestock) or high quality (domestic) sources. Low quality water from dams and bores is generally used for livestock and gardens as well as laundry and toilet facilities. High quality water from rain water harvesting (tanks or excavated earth tanks or dams) and bores is used for drinking, domestic purposes (roughly 150L/person/day including amenities) and for specific needs such as crop spraying. Domestic water constitutes less than 15% of that used in agriculture.

There are at many unlicensed ground water bores across the project area (WIR Database search dated 28th February 2018, Appendix A). However, the data is old and contain no information on aquifer types, bore depths and yields and/or groundwater quality. Nevertheless, groundwater levels are between the surface and 27.43m deep averaging 5.35m.

4.3 Groundwater Dependent Ecosystems (GDEs)

Ground water dependant ecosystems (GDEs) are ecosystems which have their species composition and their natural ecological processes determined by ground water (ARMCANZ and ANZECC, 1996). This also refers to ecosystems that may vary in the degree of their dependency on ground water, from having no apparent dependency through to being entirely dependent on it.

The decision making criteria (Table 4.3) for assessing the presence or absence of GDEs for this investigation are:

Table 4.1: Criteria for Discerning GDEs.

Environmental Aspect	Criteria	Indicators of Ground Water Dependence						
Level 1. Locate zones with potentials for ground water dependence								
Potential for ground water fed systems	Status of inundation, submergence, seeps and springs, ground water aquifers, geology and topography	j ,						

Reference: PES18001 Page 23 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



Environmental Aspect	Criteria	Indicators of Ground Water Dependence						
Level 2. Assess specific areas where ground water dependence potential is high								
Indications of water: (inundation/ submergence/seeps/ springs) or close (dampness) to the surface	Soil moisture Expression of ground water Source of surface water Refer to vegetation criteria	Greater than 15% following at least 7 days of no rain. Shallow ground water levels, extent of ponding or flowing (frequency, rainfall relationship) Drainage/topographic characteristics Surface/ground water quality characteristics Refer to vegetation structure						
Vegetation Characteristics	Vegetation structure Plant species composition	Structure (large trees) suggests reliance on a long term available water source. Species composition suggests a dependence on a shallow ground water table. Presence of species dependent on (near) permanent water.						

GDEs are defined as natural ecosystems that require access to ground water to meet all or some of their water requirements so as to maintain their ecological functions. A time dimension (Smith et al., 2006) may be added to then define GDEs as ecosystems that rely wholly or partially on ground water to maintain an adequate level of ecosystem function and maintenance of community composition over multiple generations of the longest lived species within the community.

Six types of GDEs are conventionally recognised in Australia:

- Terrestrial vegetation that relies on the availability of shallow groundwater.
- Wetlands such as paperbark swamp forests and mound springs ecosystems.
- River base flow systems where ground water discharge adds to stream flow.
- Aquifer and cave ecosystems where life exists independent of sunlight.
- Terrestrial fauna, both native and introduced, that rely on ground water as a source of drinking water.
- Estuarine and near shore marine systems, such as some coastal mangroves, salt marshes and sea grass beds, which rely on the submarine discharge of ground water.

A preliminary assessment suggests that none of these are present at the Calingiri Copper Project. Base flow is not readily evident and riparian and terrestrial vegetation which may have some form of reliance on ground water appears to be absent. Field observations revealed open expressions of the groundwater level (with excessive salinity) and an ephemeral surface water regime in which streams dry out completely each year early in the dry season.

GDEs in proximity to Wongan Hills include (GDE Atlas, 15th June 2018):

- Aquatic ecosystems that rely on the surface expression of groundwater which includes surface water ecosystems which may have a groundwater component, such as rivers, wetlands and springs: unclassified potential GDEs (national assessment), refer Figure 4.1 overleaf.
- Terrestrial ecosystems that rely on the subsurface presence of groundwater which includes all vegetation ecosystems: unclassified potential GDEs (national assessment), refer Figure 4.2.
- Subterranean ecosystems, including cave and aquifer ecosystems were not mapped.

Reference: PES18001 Page 24 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1






Figure 4.1: Aquatic Ecosystems.




Figure 4.2: Terrestrial Ecosystems.

With the current layout of mine infrastructure and provided that construction employs best practice, it seems unlikely that mining and processing at the Calingiri Copper Project will impact any of the GDE's.



5. Ground Water Investigations

5.1 Bore Drilling

Several groundwater investigative bores were constructed between March 2018 and April 2018 to obtain information pertaining to the ground water bearing and hydraulic characteristics of the paleo channels west of the proposed Bindi processing plant (Figure 5.1) and at Opie (Figure 5.2).



Figure 5.1: Bore Locations at Bindi (process plant in blue and TSF in yellow).



Figure 5.2: Bore Locations at Opie (11km due south of Bindi).



The bores were constructed in accordance with the Minimum Construction Requirements for Water Bores in Australia (National Uniform Drillers Licensing Committee, 2012). Drilling employed reverse circulation and mud rotary techniques followed by installing PVC solid casings and slotted screens across the primary water bearing zones. The bore annulus between the PVC screen and bore wall were filled with coarse sand (gravel pack) and a polymer grout to ground level to prevent surface water entering the bore. Bores were developed subsequently by airlift and Wellclean (which is used in the development and cleanup of water bores to break down the viscosity of the bentonite mud and disperses cake that was formed on the walls of the drill hole, promoting rapid and effective clean up).

During drilling, samples of the drill cuttings were obtained, where possible, at 1m intervals, washed, sieved and used to prepare detailed lithological descriptions and bore construction logs. Detailed bore completion reports with details of casings and screens, surveyed coordinates and elevations, and, where possible, lithological descriptions, changes in moisture content and the depths at which water was encountered, ground water levels, airlift yields and observations made during drilling and construction appear in Appendix B. A summary of the more pertinent construction and hydrogeological details appear in Table 5.1.

Drilling encountered fine to medium and coarse gravels and sand, often interspersed in clays. Since the investigation aimed at determining the yield and hydraulic characteristics of the paleo channel sediments, drilling was stopped once bedrock was encountered. Earlier exploratory drilling encountered little, if any, groundwater in the underlying gneissic/granitic bedrock.

5.2 Bore and Aquifer Testing

Bore test pumping, constant rate discharge tests up to 12 hours in duration, was undertaken to ascertain the yield characteristics of the paleo channel sediments and to estimate their hydraulic parameters to undertake preliminary assessments of the potential long-term impacts of mine influx and ground water abstraction on the aquifer, receiving environment and surrounding users. It also allows a preliminary assessment of the availability and supply of water for mining and processing.

The test program was devised taking cognisance of bore construction and airlift yields, if available, measured on completion after bore development to obtain water qualities and to facilitate interpretation of aquifer properties, specifically hydraulic conductivity (K, m/d), transmissivity (T, m²/d) and storativity (S, no dimensions). Bore test data (Appendix B) was provided by Orbit Drilling and interpreted by Pendragon Environmental Solutions making use of the FC Method software developed by the Institute for Groundwater Studies at the University of the Free State and the Department of Water Affairs in South Africa. These criteria and parameters contribute in determining the subsurface ground water environment and predicting its possible behaviour in future under different stresses and influences to construct a conceptual model (or numerical model) of the prevailing ground water flow regime including the presence of impermeable or recharge boundaries.

Bore testing involved monitoring the drawdown of the ground water level whilst keeping the abstraction rate constant. Drawdown and recovery data from constant rate tests are evaluated by making use of suitable interpretation methods (Kruseman and De Ridder, 1994 and Van Tonder, et al., 2013) depending on knowledge regarding unconfined or confined aquifer conditions and whether the bore is situated in a porous or fractured medium. The duration of the constant rate test may be determined by the information and level of reliability required. It is common practice to run the test for a minimum of about eight hours for bores to be equipped with hand, solar or wind driven pumps, and for forty-eight to seventy-two hours for bores to be equipped with electricity or diesel driven pumps which are to be operated on a daily basis.

Reference: PES18001 Page 27 of 55 Date: July 2018 Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



Table 5.1: Summary of Bore Construction, Hydrogeological Details and Bore Testing.

	Summary of Bore Data														
Site/Location: Calingiri Copper Project															
Location															
Bore	Latitude Longitude		Elevation (mAHD)	Bore Depth	Casings/ Screens	Screen	Interval	Yield (Bore Test)	Duration	Drawdown	Recovery	TDS	Lithology/Aquifer Type	Groundwater Level	
Number	Zone 50J		(IIIAND)	Deptil	Screens	from	to	(Bore rest)							
	(m E)	(m N)	(mAHD)	(m)	(mbgl)	(mbgl)	(mbgl)	(L/s)	(hrs)	(m) - (%)	(%) (mg/L) -		-	(mbgl)	(mAHD)
New Investigative Bores															
Bindi Paleo Ch	nannel - To	enement													
18CAWB001	465,180	6,571,750	259	45.0	0 - 45	0.0	41.0	4.8	12	1.90m - (4.4%)	100% - 1min (residual s = 0)	2,890 - 3,050	Gravel.	2.00	257.00
18CAWB002	465,670	6,571,700	255	40.0	0 - 34	0.0	34.0	4.5	12	5.80m - (16.7%)	100% - 2min (residual s = 0)	984 - 1,610	Gravel.	5.20	249.80
18CAWB003	466,170	6,571,710	245	36.0	0 - 36	0.0	36.0	2.0	1 min	31.70m - (100%)	-	pumped dry	Gravel.	4.30	240.70
18CAWB004	467,595	6,571,140	256	24.0	-	-	-	-	-	-	-	-	Thin dry sand/gravel; bedrock.	-	-
18CAWB005	467,585	6,570,340	235	46.0	0 - 46	0.0	46.0	1.0	5	26.85m - (60.2%	55% - 150min (residual s = 1.15m)	-	Clayey gravel.	1.40	233.60
18CAWB006	467,565	6,569,820	231	34.0	0 - 21	0.0	21.0	1.0	1	9.59m - (31.0%)	76% - 60min (residual s = 1.00m)	-	Clayey gravel.	3.10	227.90
Opie Paleo Ch	annel - Te	enement													
18CARC027	467,734	6,560,805	229	132.0	0-24	18.0	24.0	1.8	8	18.35m - (93.1%	80% - 120min (residual s = 2.80m)	-	Sandy clay.	4.30	224.70
18CARC028	467,906	6,560,782	246	66.0	0-42	30.0	42.0	2.0	1 min	42.00m - (100%)	-	-	Sand and sandy clay	0.00	246.00
Notes	All bores	(except B00	6 at 144mm [DIA) drille	d at 203mm	DIA and f	itted with	100mm DIA Cla	ss 9 PVC s	creens (9mm w	allthickness).				
	Screens:	100mm DIA u	PVC Class 1	12 with 8 r	ows around	d screen,	37 banks	on each row ar	nd 22 0.51m	m slots on each	ı bank.				

Bore Number	Construction	Bore Testing								
Bindi Paleo Cha	Bindi Paleo Channel - Tenement									
18CAWB001	Drilled at 150mm to 48m, then cased with 100mm to 41mbgl; rounded gravel noted in drill cuttings.	-								
18CAWB002	Drilled at 150mm to 40m, then cased with 100mm to 40mbgl; one length of 150mm solid PVC could not be removed; therefore slotted 100mm PVC to 36mbgl; rounded gravel noted in drill cuttings.	-								
18CAWB003	Bore collapsing; site relocated 5m, drilled at 150mm and cased with 100mm slotted casing to 36m.	White foam affected water level measurements; pumped dry in <1min at 2L/s.								
18CAWB004	Water encountered for 2m directly above solid rock.	Not tested; penetrated thin dry paleo sediments.								
18CAWB005	Drilled to 41mm with 150mm, cased with 100mm to 32mbgl.	Bore was full of white foam which affected water level measurements; pumped dry in <1min at 2L/s; after redevelopment sustained 2L/s for 5hours.								
18CAWB006	Drilled to 34 mm with 150mm, cased with 100mm to 21mbgl.	Bore was full of white foam which affected water level measurements; pumped dry in <1min at 2L/s; after redevelopment sustained 0.6L/s for 1hour; test abandoned due to drawdown.								

Opie Paleo Cha	Opie Paleo Channel - Tenement								
18CARC027	Bore drilled to 140m+, drillers noted good water at 40mbgl maybe in a void; Asked to be cased to 60mbgl and left open with eth ambition of pumping at a depth of 40-50mbgl. Hole only cased to a depth of 28m; 4 tonnes of gravel added to bore to back fill.	Pumped at 2L/s.							
18CARC028	Drilled to 64mbgl. The aim was to install slotted pvc at 52-64m and 12-18m to target sandier materials. Casing only installed to 42m, comprised of slotted from 30-42 as bore collapsed. This meant that slotted casing was not located on the targeted zone; Bore was particularly heavy in clay.	Very small yield.							



18CAWB001

The very small drawdown measured during the test on Bore 18CAWB001, coupled with the almost immediate recovery of the water level after discharge testing, renders a reliable interpretation of the data difficult due to the predominant horizontal nature of the drawdown curves.




Figure 5.3: Bore Test 18CAWB001.

Approximate hydraulic parameters are: T value 889m²/day with S 1.6 x 10⁻³. It is clearly evident from the test data that this bore is capable of yielding far in excess of the 4.8L/s attained during testing considering the very small drawdown during testing. Using a radial flow model based on the Jacob Equation illustrates (Figure 5.3) that utilising the above hydraulic parameters and the available



drawdown, may yield as much as 100L/s with a drawdown of 5m some 10km away after 5 years. However, it is unlikely that the paleo channels would extend radially for such large distances which would limit yield as a direct consequence of barriers which in turn would result in larger drawdowns. Nevertheless, it seems that yields in the order between 10L/s and 20 L/s could be more sustainable; the FC Method predicted a sustainable yield around 18 L/s.

18CAWB002

The test on Bore 18CAWB002 resulted in larger drawdowns but again almost immediate recovery of the water level after discharge testing.




Figure 5.4: Bore Test 18CAWB002.

Approximate hydraulic parameters are: T value between 30m²/day and 100m²/day with an average S of 2.2 x 10⁻³; barrier boundaries are evident on the drawdown curves. Albeit lower hydraulic parameters at this location, it remains clearly evident from the test data that this bore is capable of yielding in excess of the 4.0L/s attained during testing. The radial flow model indicates that this bore may yield as much as 13L/s with a cone of dewatering of 7.5km after 5 years.

Bores 18CAWB003, 18CAWB004 and 18CARC0028

Bore 18CAWB003 yielded very little water and was pumped dry almost immediately. Inspection of the lithological descriptions reveals that the bore penetrated some 30m of gravel (the same as Bores 1

Reference: PES18001 Page 31 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



and 2). Whilst the bore was redeveloped, it seems that construction and development remained problematic and potentially did not result in breaking down the bentonite wall cake.

Bore 18CAWB004 encountered only 10m of sand and gravel which appeared to be dry.

Bore 18CARC0028 encountered thin gravels overlying sand with clay increasing in content with depth. Bore construction was problematic and potentially did not achieve the desired outcome.

18CAWB005

The test on Bore 18CAWB005 resulted in larger drawdowns but again almost immediate recovery of the water level after discharge testing.




Figure 5.5: Bore Test 18CAWB005.

Approximate hydraulic parameters are: T value 8m²/day with an average S of 2.2 x 10⁻³; barrier boundaries are evident on the drawdown curves. These much lower hydraulic parameters reflect the clayey gravels encountered at this location which impacted bore yields and consequently caused significant drawdown.

18CAWB006

The test on Bore 18CAWB006 yielded similar results than for Bore 5 and also encountered clayey



gravels. The yield in this bore decreased from 1.0L/s at the start of the test to about 0.6L/s after 30 minutes.

It seems that the paleo channel across bores 4, 5 and 6 have a much higher clay content and thus do not contain sufficient groundwater to sustain discharge.

18CARC027

The test on Bore 18CARC027 resulted in larger drawdowns but again almost immediate recovery of the water level after discharge testing.




Figure 5.6: Bore Test 18CARC027.

Approximate hydraulic parameters for the sandy clays at this location are: T value 10m²/day with an average S of 2.2 x 10³; barrier boundaries are evident on the drawdown curves and consequently caused significant drawdown towards the end of the test.

5.3 Ground Water Chemistry

5.3.1 Ground Water Quality

Samples of water were obtained subsequent to the drilling and testing program. A tabulated summary of the results and the detailed laboratory certificates may be found in Appendix C.

Reference: PES18001 Page 33 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



Field measurements of ground water quality reveal that pH is generally acidic and well below the Australian Drinking Water Guidelines. Total Dissolved Solids exceed the Australian Drinking Water Guidelines in all instances.

Table 5.2: Field Measurements of Surface and Ground Water Quality.

		Ground Water Level	Hd	Temperature	Electrical Conductivity @ 25°C	Salinity	Total Dissolved Solids @ 25°C	Dissolved Oxygen	Oxidation Reduction Potential (ORP)	
	Units	mbgl	pH Unit	°C	μS/cm	ppt	mg/L	%	mV	
ANZECC (2000)	Fresh Water (95%)	-	6.5-8.5	-	-	-	-	-	-	
ADWG (2015, V3)	Aesthetic Value (AV)	-	6.5-8.5	-	-	-	600	>5	-	
Date	Ground Water									
13/04/18	CAWB001	2.00	4.77	24.3	5,980	-	3,887	7.5	-	
13/04/18	CAWB002	5.30	5.15	24.1	2,950	-	1,918	7.5	-	
13/04/18	CAWB003	4.27	4.71	23.7	8,950	-	5,818	5.0	-	
13/04/18	CAWB005	1.40	5.72	23.5	8,120	-	5,278	5.8	-	
13/04/18	CAWB006	3.01	5.58	24.1	8,560	-	5,564	4.9	-	
13/04/18	CARC027	1.72	5.44	24.3	6,750	-	4,388	6.7	-	
13/04/18	CARC028	0.00	6.01	23.8	7,650	-	4,973	6.7	-	
	Minimum			23.5	2,950	-	1,700	4.9	-	
	Maximum	5.30	6.01	24.3	8,950	-	4,850	7.5	-	
	Average	2.53	5.34	24.0	6,994	-	3,964	6.2	-	
Note: Highlighted va	Note: Highlighted values exceed relevant guideline or trigger.									

Ground water has elevated concentrations of Total Dissolved Solids (generally well in excess of 600mg/L) and predominantly Chloride and Sodium, which often exceed the Australian Drinking Water Guidelines, and to a lesser extent Sulfate.

Table 5.3: Concentrations of Major Ions in Ground Water.

		Total Dissolved Solids @ 180°C	Total Hardness as CaCO ₃	Total Alkalinity as CaCO3	Acidity as CaCO3	Silicon as SiO2	Sulfate as SO4	Chloride	Calcium	Magnesium	Sodium	Potassium
	Units		(mg/L)									
ADWO (0045 NO)	Health Value (HV)	-	-	-	-	-	500	-	-	-	-	-
ADWG (2015, V3)	Aesthetic Value (AV)	600	200	-	-	-	250	250	-	-	180	•
DoH (2014)	Non-Potable Use	-	-	-	-	-	1,000	250	-	•	-	•
Date	Surface Water											
13/06/15	Lake (pond)	13,400	2,100	315	-	-	185	7,400	57	476	3,570	128
Date	Ground Water			-	-	-	104					
13/04/18	CAWB001	3,820	569	32	-	-	315	1,700	20	126	874	35
13/04/18	CAWB002	1,830	270	17	-	-	282	795	9	60	385	14
13/04/18	CAWB003	5,660	1,120	5	-	-	299	2,720	15	263	1,180	46
13/04/18	CAWB005	5,150	985	5	-	-	198	2,460	12	232	1,180	41
13/04/18	CAWB006	5,470	918	7	-	-	258	2,720	10	217	1,160	39
13/04/18	CARC027	4,110	393	70	-	-	185	1,870	22	82	1,030	31
13/04/18	CARC028	5,050	956	30	-	-	104	2,420	20	220	1,290	47
	Minimum			5	-	-	104	795	9	60	385	14
	Maximum			70	-	-	315	2,720	22	263	1,290	47
	Average			24	-	-	234	2,098	15	171	1,014	36
Note: Highlighted va	alues exceed relevant guid	deline or trig	ger.									

Reference: PES18001 Page 34 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



The heavy metals Arsenic, Cadmium, Chromium (except two small detections), Lead, Selenium, Iron (except two small detections) and Mercury are absent in groundwater. Concentrations of Aluminium, Copper, Nickel and Zinc generally exceed the ANZECC Fresh Water guidelines for most if not all species protection levels but are well below the drinking water guideline.

Table 5.4: Concentrations of Heavy Metals in Ground Water.

		Aluminium	Copper	Nickel	Zinc					
	Units	mg/L								
400 NEDM 4000	GILs: Fresh water (95%)	0.055	0.0014	0.011	0.008					
ASC NEPM 1999	GILs: Drinking Water	-	2	0.020	-					
	Fresh Water (80%)	0.15	0.0025	0.017	0.031					
ANZECC (2000)	Fresh Water (90%)	0.08	0.0018	0.013	0.015					
	Fresh Water (95%)	0.055	0.0014	0.011	0.008					
ADMO (0045 MO)	Health Value (HV)		2	0.02	-					
ADWG (2015, V3)	Aesthetic Value (AV)	0.2	1	<u>-</u>	3					
DoH (2014)	Non-Potable Use	0.2	20	0.2	3					
Date	Ground Water									
13/04/18	CAWB001	<0.01	0.003	0.002	<0.005					
13/04/18	CAWB002	<0.01	0.002	<0.001	<0.005					
13/04/18	CAWB003	1.17	0.005	0.015	0.065					
13/04/18	CAWB005	0.35	0.026	0.007	0.036					
13/04/18	CAWB006	0.02	0.030	0.004	0.029					
13/04/18	CARC027	<0.01	0.017	0.005	0.008					
13/04/18	CARC028	<0.01	0.015	0.006	0.011					
	Minimum	0.02	0.002	0.002	0.008					
	Maximum	1.17	0.030	0.015	0.065					
	Average	0.51	0.014	0.007	0.030					

Ground water is deficient in nutrients:

- Ammonia (as N) varies between 0.03mg/L and 0.06mg/L.
- Nitrite is absent and Nitrate (as N) varies between <0.01mg/L and 12.30mg/L averaging 3.53mg/L.
- Total Nitrogen (as N) varies between 1.0mg/L and 15.1mg/L averaging 3.99mg/L.
- Total Phosphorous varies between <0.05mg/L and 18.60mg/L averaging 6.35mg/L whilst Reactive Phosphorous varies between 0.02mg/L and 12.50mg/L averaging 2.31mg/L.

Excluding the elevated Nitrate in Bore B002, these concentrations are well below their respective assessment levels.

Graphical illustrations of surface and ground water chemistry indicate that:

Piper Diagram

The Piper Diagram (Figure 5.7) allows for the graphical illustration of both anion and cation compositions on a single graph as percentages and is convenient for showing the mixing of waters from different sources and for visually describing the differences in major ion chemistry in groundwater flow systems. They also reveal similarities and differences among groundwater samples; those samples with similar qualities will tend to plot together as groups.

Reference: PES18001 Page 35 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



Figure 5.7 indicates that the surface and groundwater samples fall within the Na-Cl zone (water type) typical of marine or deep old stagnant ground waters receiving little if any recharge. There appears to be slight separations between the surface water sample and the groundwater samples with an additional separation with sample CARC027. Spatially sample CARC027 is approximately 11 km to the south of all the other samples (except CARC028 which is about 175 m to the east of CARC027). Although on a macro scale the differences could be considered negligible, reaching conclusions regarding recharge interactions might be with less confidence due to these minor discrepancies.




Figure 5.7: Piper Diagram.

Expanded Durov Diagram

A Durov Diagram is similar to a Piper Diagram in that relative percentages of the major ions (macro chemistry) are illustrated in nine different fields (Figure 5.8) each representing a different classification. All the samples at the Calingiri Project fall within the lowermost right corner indicative of a very old, stagnant water that has reached the end of the hydrogeological cycle (deserts, salty pans, etc.) or water that has moved a long time and/or distance through the aquifer and has undergone significant ion exchange during its migration to the surface. Too little information is currently available to make any comment with regard to the distance and duration.




Figure 5.8: Durov Diagram.

Reference: PES18001 Page 36 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



Stiff Diagram

Stiff diagrams illustrate individual samples as a means to graphically compare the concentrations of selected anions and cations. The shapes of the diagrams quickly identify samples with similar compositions and are particularly useful when used for mapping to show the geographic locations of different water facies. In a Stiff Diagram, data is plotted as a polygon, with cations to the left and anions to the right. From Figure 5.9 it is evident that all the samples have a similar signature albeit at different scales; the surface water sample exhibits a more pronounced signature, while sample CAWB002 has the least pronounced signature although it is located closest to the surface water sample.




Figure 5.9: Stiff Diagram.

Taking due cognisance of the graphical illustrations it seems that the surface water sample is an expression of groundwater and that the larger salt content is due to evaporation.

5.3.2 Stable Isotope Analysis

Isotopes are atoms that have the same number of protons but a different number of neutrons. They can be divided into radioactive and stable isotopes. Radioactive isotopes undergo spontaneous breakdown of their nuclei to form other isotopes whilst stable isotopes do not break down spontaneously. Isotopes have a wide range of applications in physical as well as biological sciences. For the purpose of this investigation, the focus will be on stable isotopes and a way to interpret the results from analysis of these stable isotopes to assist us in describing and characterising the surface and near-surface groundwater regimes.

By making use of stable isotope fractionation, stable isotopes can be applied in environmental and geological studies due to changes in their isotopic ratios as part of their physical, chemical and biological interaction with their environment. Deuterium (²H) and Oxygen 18 (¹⁸O) are the two most common stable isotopes in the field of hydrogeology and are frequently used to determine the origin of a specific water sample or the residence time of a groundwater sample. It can also be used to compare different water samples to understand different processes involved and to assist in grouping samples together due to their specific characteristics.

Owing to a linear relationship between the $\delta^{18}O$ and $\delta^{2}H$ in precipitation that has not been evaporated



(Craig, 1961) a standard for comparison, the *Global Meteoric Water Line* (GMWL) can be described by the equation:

 $\delta D = 8\delta^{18}O + 10$ Equation 1

Equation 1 has been derived from precipitation data across the globe with an R^2 value of better than 0.95. This implies that the stable oxygen and hydrogen isotopes in water molecules are closely related and therefore the isotopic ratios and fractionations of the two elements are most often evaluated and reported together. It needs to be noted that if data is available, it is more appropriate to establish a *Local Meteoric Water Line* (LMWL) for comparison as in some instances this site-specific standard can vary significantly from the GMWL. In most cases the slope of the LMWL is in the range of 8 ± 0.5 but slopes between 5 and 9 are not that uncommon.

Deviations from the GMWL are caused by natural processes; therefore, water that has been subjected to evaporation or that has mixed with evaporated water will typically plot below the GMWL along lines that intersects it at the location of the original unevaporated composition of the water; evaporation lines with slopes in the range of 2 to 5 are common. Low temperature diagenetic reactions involving silicate hydrolysis can sometimes cause increases in the δ^{18} O and δ D values of waters.

At any given location, two primary factors control the isotopic signature of precipitation:

- the temperature of condensation of the precipitation; and
- the degree of rainout of the air mass (the ratio of water vapor that has already condensed into precipitation to the initial amount of water vapor in the air mass).

Evaporation from low-altitude oceans contributes most of the vapor in the atmosphere and consequently precipitation derived from this vapor is always enriched in D and 18 O relative to the vapor with the fractionation between the rain and vapor a function of condensation temperature. When clouds move inland, they become increasingly isotopically lighter as successive rain storms along its path cause the heavier isotopes to be depleted resulting in more negative δ values.

As groundwater is essentially recharged from precipitation in most systems, knowledge of the factors that control the isotopic compositions of precipitation before and after recharge makes it possible to use hydrogen and oxygen isotopes as tracers to identify water sources (origin) and processes. Regionally, isotopic compositions are controlled by several factors:

- **Altitude effect**: on the windward side of a mountain, the δ^{18} O and δ D values of precipitation decrease with increasing altitude. Typical gradients are -0.15‰ to -0.5‰ per 100m for 18 O, and -1.5‰ to -4‰ per 100m for D. This pattern is often not observed in interior mountains, for snow, or on the leeward side of mountains.
- Latitude effect: The δ^{18} O and δ D values decrease with increasing latitude because of the increasing degree of *rain-out*.
- Continental effect: Isotopic ratios decrease inland from the coast.
- Amount effect: The greater the amount of rainfall, the lower the $\delta^{18}O$ and δD values of the rainfall; this effect is not seen in snow.

At a given location, the seasonal variations in $\delta^{18}O$ and δD values of precipitation and the weighted average annual $\delta^{18}O$ and δD values of precipitation remain fairly constant from year to year. This is because the annual sequence of climatic conditions (temperatures, vapor source, direction of air mass movement, etc.) and range thereof remain more or less constant from one year to the other. Generally summer rain is isotopically heavier (more positive δ values) than winter rainfall. This is

Reference: PES18001 Page 38 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



primarily caused by seasonal temperature differences but changes in moisture sources and storm tracks can also contribute to this observation.

Shallow groundwater usually reflects the local average of $\delta^{18}O$ and δD values of precipitation but is modified to some extent by selective recharge and fractionation processes that may alter the $\delta^{18}O$ and δD values of the precipitation before the water reaches the saturated zone (Gat and Tzur, 1967). Some of these processes include:

- Evaporation of rain during infiltration.
- Selective recharge.
- Interception of precipitation by the tree canopy.
- Exchange of infiltrating water with atmospheric vapor.

In the case of snow, various post-depositional processes, such as melting and subsequent infiltration of surface layers and evaporation, may alter the isotopic content of the snowpack, often leading to meltwater δ values that become progressively enriched (Stichler, 1987).

Table 5.5 summarises the stable isotope analysis on a surface and groundwater samples from the preliminary exploration bores. Figure 5.10 provides a general guide with regard to interpretation of stable water isotopes.

Table 5.5: Stable Isotope Analytical Data.

Sample ID	Sample date	δD (‰)	δ ¹⁸ O (‰)
18CAWB001	2018/04/27	-25.7	-4.73
18CAWB002	2018/04/27	-24.9	-4.27
18CAWB003	2018/04/27	-26.1	-4.78
18CAWB004	2018/04/26	-25.5	-4.61
18CAWB005	2018/04/26	-26.9	-4.96
18CAWB006	2018/04/26	-25.0	-4.17
18CARC026	2018/04/27	-24.8	-4.58
18CARC027	2018/04/27	-25.3	-4.70




Figure 5.10: General guide for ¹⁸O and ²H Interpretation.

Reference: PES18001 Page 39 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



Figure 5.11 depicts the graphical representation of the isotope data against the GMWL, while Figure 5.12 represents the same data set against the LMWL (generated from information gleaned from Crosbie *et. al.*, 2012).




Figure 5.11: Graphical Representation of Isotope Data vs the GMWL.




Figure 5.12: Graphical Representation of Isotope Data vs the LMWL.

The δD values range between -24.8% and -26.9% whilst the $\delta^{18}O$ values range between -4.17% and -4.96%. It is evident that the values plot quite close to the standard (GMWL) which indicates that the relationship between the two parameters did not change significantly from where precipitation formed over the ocean to where recharge is occurring. Using the LMWL however, a distinct deviation to below the LMWL at a mean slope of 2.1 is apparent which fits within the acceptable range for evaporation. This evaporation effect could be indicative of slow infiltration rates that will in turn have an effect on the rate of recharge to the underlying aquifer(s).

The use of chloride as an environmental hydrologic tracer was first introduced in 1969 where groundwater recharge was determined in arid regions characterized by low relief and deep unsaturated zones. The chloride mass balance method (CMB method) involves quantifying the mass

Reference: PES18001 Page 40 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



of chloride derived from precipitation to the aquifer system based on measuring the chloride concentration in precipitation and groundwater or estimating the amount of precipitation received from which an annual volume of groundwater recharge could be calculated (Aishlin, 2006). The use of the CMB method provides a practical low cost means for estimating groundwater recharge (van Tonder and Bean, 2003). In addition, the method for the saturated zone may be particularly useful in areas where groundwater levels do not fluctuate or data on groundwater levels are lacking (Adams, *et. al.*, 2004).

The use of CMB method to estimate groundwater recharge at the Calingiri Project is subject to the following assumptions (applicable to the methodology in general):

- Chloride concentration in the system and mean rainfall did not change over time i.e. it is assumed that the climate is stable (Kirchner, 2003).
- Chloride in the system is conservative (Aishlin, 2006) thereby assuming that the increase in chloride concentration is due to evapotranspiration losses only and that no additional chloride has been added by contamination from or leaching of overburden/bedrock (Woodford and Chevallier, 2002) and that bulk wet and dry fall are the only inputs of chloride to the system.
- The system is at steady state and no external surface and/or ground water inflows occur.
- No unmeasured runoff from the system occurs (Aishlin, 2006).
- Recharge moves vertically through the unsaturated zone (van Tonder and Bean, 2003), except where shallow sandy soils overlie less permeable sedimentary sequences on gently sloping terrain (Beekman and Xu, 2003).

In addition to the above assumptions, several limitations apply to the CMB method:

- The method should not be applied to areas underlain by evaporates or areas where up-coning or mixing of saline ground waters occurs.
- Use in fractured rock systems (Beekman and Xu, 2003). Groundwater flow in fractured rock aquifers tends to concentrate in the permeable fracture zones usually located in the bottoms of valleys (Sami, 2003).
- The method should be applied with great caution in areas close to the sea where rainfall chloride contents are highly variable (Beekman and Xu, 2003).
- The absence of long-term rainfall quality data (van Tonder and Bean, 2003).

Using the CMB method, recharge at the Calingiri Project is estimated at 6mm/a or 1.6% of the mean annual rainfall:

Table 5.6: Summary of CI-Method Estimation of Recharge.

Average rainfall (mm/a)	388
CI in rain (mg/L)	10.6
Dry deposition CI (mg/L)	17.9
CI in groundwater or the unsaturated zone (mg/L)	1,779
Average recharge (mm/a):	6
Recharge (% of mean annual rainfall):	1.6

In conclusion:



- Macro element analyses indicate a large concentration of salts in groundwater with larger concentrations in surface water (groundwater expressions) due to evaporation.
- The Piper Diagram indicates both surface and groundwater samples exhibit characteristics consistent with deep ancient waters. The mechanisms of interaction between surface and ground water could not be clearly established.
- The Durov Diagram confirms the above observations and indicates a water type that represent very old, stagnant water that has reached the end of the hydrogeological cycle or water that has moved a long time and/or distance through the aquifer and has undergone significant ion exchange.
- Stiff Diagrams indicate water types with the same characteristics but with a much more pronounced signature for surface water attributed to evaporation.
- Stable isotope data is consistent with vapor above the ocean when compared to the GMWL; however, when compared with the LMWL the samples, grouped in a narrow cluster, deviate with a trend line with a slope of just above 2, indicative of evaporation, consistent with what is observed with the chemical diagrams of the macro elements.
- Recharge is estimated using the CMB method at 1.6% of the average annual rainfall.
- A single data set is never ideal to reach conclusive results but the consistency in the results from all the different methods that was applied during this analysis, all indicate very low recharge probabilities with a definite evaporation component across the area.
- Although recharge to the paleo-channel is obvious, indications are that it does not occur at an advanced rate and precipitation undergoes evaporation impacted upon by chemical reactions along the pathway(s) towards the underlying aquifer(s).

Reference: PES18001 Page 42 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



6. Conceptual Ground Water Model

6.1 Introduction

This section presents a preliminary simplistic conceptual model of the aquifers at the Calingiri Copper Project. Numerical modelling has not been attempted due to a lack of sufficient data.

A conceptual model consists of a set of assumptions that describe the composition of the aquifer or ground water flow regime, based on field observations, measurement and interpretation of data. It can be regarded as a pictorial representation of the ground water flow regime and is frequently in the form of a simplified diagram or hydrogeological cross section. It defines the dimensions of a numerical model, how the grid is designed and how the grid is oriented and is an evolving hypothesis identifying important features, processes and events controlling fluid flow in a specific location. Assumptions that constitute a conceptual model should relate to the following:

- The flow regime.
- The matrix of the aquifer with reference to its homogeneity, heterogeneity, anisotropy and isotropy.

Homogeneity refers to if the hydraulic conductivity (K) is independent of position within a geologic formation. If K is dependent on position within a geologic formation, which is always the case in ground water systems, the formation is heterogeneous. In a homogeneous formation, $K_{(x, y, z)} = C$, C being a constant; whereas in a heterogeneous formation $K_{(x, y, z)} \neq C$. If the hydraulic conductivity (K) is independent of the direction of measurement at a point in a geologic formation, the formation is isotropic at that point. If K varies with the direction of measurement at a point in a geologic formation, the formation is anisotropic at that point.

Constructing a representative conceptual model and the degree of simplification in any particular case depends on available resources and information. Elements of a comprehensive conceptual model development process include:

- Geological formation and aquifer type.
- Boundary conditions.
- Ground water quality.
- Geometric structure of the system.

Although a conceptual model is by necessity a simplification of information, it should relate to the problem being addressed. The context in which the model is developed constrains the applicability of the model.

6.2 The Calingiri Conceptual Model

A simplified interpretation from bore completion records includes:

- The primary aquifers are:
 - sediments confined to paleo channels or valleys;
 - within and underlain by weathered/fractured granite-gneiss bedrock, faulted in places and intruded by near-vertical dykes of dolerite.

Preliminary investigations were undertaken to assess the paleo valleys but the underlying faulted and intruded bedrock utilising the overlying paleo channels as a source for recharge has yet to be

Reference: PES18001 Page 43 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



investigated.

Ground water was encountered in paleo channel sediments between 5m and 45m with yields varying between 0.1L/s and 4.8L/s from 100mm diameter bores. Preliminary assessments suggest that larger yields in the range between 10L/s and 20L/s are possible.

The hydraulic conductivities, K_h , of the paleo channel sediments fall within the range semi-permeable to permeable in the range between 1m/day and 10m/day. Vertical permeabilities, K_v , due to the near horizontally bedded nature of the strata, are considered to be one order of magnitude lower. The estimated T values vary between ~10m²/day and ~889m²/day with a storativity value around 0.002.

Recharge to the paleo channels was estimated at 6mm/a or 1.6% of the mean annual rainfall which may constrain groundwater exploitation as a large area will be required to sustain bore and aquifer yields over the long term.

Ground water has elevated concentrations of Total Dissolved Solids (between 1,900mg/L and 5,000mg/L), predominantly Chloride and Sodium, which often exceed the Australian Drinking Water Guidelines, and to a lesser extent Sulfate. The heavy metals Arsenic, Cadmium, Chromium, Lead, Selenium, Iron and Mercury are absent in groundwater. Concentrations of Aluminium, Copper, Nickel and Zinc generally exceed the ANZECC Fresh Water guidelines for most if not all species protection levels but are well below the drinking water guideline.

More drilling, and testing and sampling are required across the area in order to develop the conceptual model to a level of higher confidence and higher resolution regarding geological heterogeneities. Piezometric heads need to be measured across the area to be able to determine the aquifer(s) within the system as well as their interaction. Boundaries need to be investigated in more detail.



7. Assessment of Potential Impacts

This section details a preliminary identification of potential impacts to the aquifer, environment or other groundwater users, that may be caused by the proposed mining and processing, particularly disposal of waste rocks and tailings, mine influx and ground water abstraction. It is generally required to provide an evaluation of the potential extent of the cone of depression (impact of the proposed ground water abstraction and influx into the open pits) taking due cognizance of the aquifer parameters obtained from test pumping investigations or from other factual information.

Based on the results of limited groundwater investigation and assessment to date, the potential impacts of mining and processing, including abstraction of groundwater/mine influx, include:

- Receding ground water levels, deteriorating ground water quality and declining bore/aquifer yields.
- Potential acid mine drainage and sediment/salt loads.
- The aquifer/ground water resource including leakage from other aquifers.
- Other users (private and public) including GDEs and subterranean fauna, where and if present.
- The receiving environment.

The environmental factors (EPA, 2015) with reference to ground water include Hydrological Processes, Inland Waters Environmental Quality and Rehabilitation and Decommissioning. The primary objectives are to ensure that the quality of surface and ground water is maintained to protect environmental values, ecological and social, and existing and potential uses to facilitate decommissioning and closure in an ecologically sustainable manner. To achieve these objectives, appropriate management of mining, waste rock and tailings disposal and ground water abstraction/mine influx will be required.

The key risks for mining and processing pertain to:

- The potential for impacts to soils, sediment, surface and ground water resources by seepages, leachates and/or runoff from the process plant ROM pad and stockpiles, WRDs and the TSF containing potentially acid producing materials.
- Open pit mining: ground water influx, exposing sulfide-bearing materials in pit walls, water quality and pit lakes.
- Over exploitation of ground water resources by groundwater abstraction and mine influx.

7.1 Ground Water Levels

Ground water levels may be impacted by:

- Seepage from mine impoundments such as ROM pad, stockpiles and plant water infrastructure, WRDs and the TSF: mounding underneath and downstream thereof will cause a local rise in ground water levels and may impact groundwater quality.
- Open pit sinks and/or lakes post closure.
- Mine influx: receding ground water levels across mining area and beyond may impact local and/or regional water supplies.
- Ground water supply abstraction: receding ground water levels and declining yields across mining area and beyond may impact local and/or regional water supplies.

Reference: PES18001 Page 45 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



7.2 Ground Water Quality

Ground water quality may be impacted by:

- Infiltration/seepage from surface impoundments, the WRD's and TSF may impact on the quality of ground water beneath and within the vicinity of these structures.
- Open pit sinks and/or lakes post closure.
- Ground water abstraction: increasing acidity and salinity across mining area and beyond.

Receding groundwater levels may have a positive impact on soil salinity and groundwater quality.

7.3 Ground Water Yields

The impact of seepage and increased infiltration on ground water yields are considered negligible.

Ground water abstraction and mine influx will decrease ground water yields within the cone of influence due to mine influx/dewatering of the fractured bedrock.

7.4 Potential AMD and Sediment/Salt Loads

The key risks for mining and processing pertain to:

- The potential for impacts to soils, sediment, surface and ground water resources by seepages, leachates and/or runoff from the ROM pad and stockpiles, waste rock and tailings containing potentially acid producing materials. Whilst this risk is currently considered low, further investigation and assessment pertaining to soil and waste characterisation is required (Pendragon Environmental Solutions, 2018).
- Exposure of sulfide-bearing materials in open pit excavations during mining and subsequent remaining exposures as groundwater sinks and/or pit lakes.

7.5 Aquifer/Ground Water Resource

Ground water abstraction will cause rapidly declining ground water levels and consequently bore/aquifer yields.

Whilst ground water abstraction will retain potential water quality impacts within the cone of drawdown/mine influx, ground water qualities may deteriorate when ground water levels return to their pre-mining levels following rehabilitation and closure. Seepages of leachates from mining infrastructure may migrate downstream once ground water levels returned to their pre-mining levels.

7.6 Beneficial Use and the Receiving Environment

Beneficial uses and the receiving environment within the zone impacted by mining and processing include other groundwater users and GDEs and subterranean fauna if present.

Further isotope/water quality sampling will be required to ascertain whether the shallow paleo channel aquifers are interconnected with the underlying deep fractured aquifers. The underlying deep fractured aquifers may receive limited recharge, if any.

Reference: PES18001 Page 46 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



There seems to be no GDEs within the areas earmarked for mining and processing (to be confirmed by further investigation and assessment); hence the likely zone of impact of mining and processing is to be ascertained.

A desktop study assessment of stygofauna (EPA, 2013) to consider impacts of ground water abstraction/mine influx in a regional context and make conclusions about whether the area is likely to provide habitat for subterranean fauna indicated and/or to determine the level of survey and whether sampling is necessary, if any, indicated that stygofauna is unlikely to be present due to the salinity of groundwater within the area.

7.7 Summary of Impacts

A summary of the impacts, proposed management measures and controls and actions appear overleaf.

Reference: PES18001 Page 47 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



Table 7.1: Summary of Impact Assessment.

Immedia during Mining and Operations		Potenti	al Risk	Drawaged Management Management and Control	Residual	Action			
Impacts during Mining and Operations	L	С	R	Proposed Management Measure and Control	Risk	Action			
Surface Water and GDE's									
Infiltration/recharge, reduction in volume of surface water	L	Mi	Medium	Minimise disturbances/footprint, divert clean runoff.		Incorporate in design.			
Deterioration of water quality in drainage lines	L	Мо	High	No discharge, contain dirty runoff, infiltration and seepage by design; provide pollution control measures including sufficient storage capacity.	Low	Monitor water quality.			
Base flow, increase/decrease flow to potential GDEs, impact on biota	U	Мо	Medium	No discharge, contain dirty runoff, infiltration and seepage by design; provide pollution control measures including sufficient storage capacity.	Low	Incorporate in design. Monitor water quality downstream of mine infrastructure.			
Ground Water Abstraction/Mine Influx									
Ground water level drawdown	Α	Мо	High	Infiltration of mine influx to offset regional drawdown,		Incorporate in design.			
Bore/aquifer yield, mine influx	Α	Мо	High	abstraction at safe long term sustainable yields, spread		Provide additional monitoring bores.			
Ground water quality	A Mo High production bores across mining area and manage				Low	Ground water monitoring: rates of influx/abstraction, water level			
Subterranean Fauna		Abs	ent	abstraction to prevent over exploitation.		drawdown and water quality			
Mine Infrastructure	,								
Infiltration/seepage from mining disturbances: potential AMD	L Mi Medium		Medium	Minimise disturbance areas; contain runoff.		Incorporate in design. Monitor surface and ground water quality			
Seepage from WRDs, stockpiles, surface impoundments and tailings storage facility	L Mo High		High	Relative impermeable soils/formations, encapsulate and contain by design and engineering.	Low	Incorporate in design. Monitor surface and ground water quality			
Residual Impact following Rehabilitation and	Closure	: Ground	d Water						
Ground water level drawdown	Р	I	Low	Ground water levels will return to pre-mining levels.	Low	Ground water level monitoring until			
Bore/Aquifer yield	U	I	Low	Cease abstraction and remove equipment.	Low	pre-mining levels are achieved			
Ground water quality	L	L Mi		Contain seepage in a downstream direction in closure design.	Low	Remove abstraction equipment Incorporate measures to curtail/ contain seepage from residual mine infrastructure such as waste rock dumps and tailings storage facility			
Consequence: I - İnsignificant, Mi – Minor, Mo – Likelihood: R – Rare, U – Unlikely, P – Probable									



8. Ground Water Monitoring

The proposed preliminary groundwater monitoring program aims at ascertaining pre-mining/ambient base-line groundwater levels and water quality for the subsequent determining the extent and severity of the subsequent impacts of mining and processing particularly with regard to mine influx, groundwater abstraction and disposal of wastes.

The bores drilled for investigative purposes thus far are suitable for ongoing monitoring (Figures 5.1 and 5.2). However, additional dedicated monitoring bores are to be provided during further ongoing investigations and upon completion of construction of mine infrastructure such as at the open pits, stockpiles at the process plant, waste rock dumps and the tailings storage facility.

The monitoring program is designed to adequately assess aquifer performance and determine any impact on surface and ground water quality, other users and/or the receiving environment. It is likely that several of the current locations will be relocated and/or discarded following further assessment on completion of the mining plan and schedule. The monitoring program will be expanded to also reflect relevant conditions of any pollution control license under the *Environmental Protection Act 1986*, if required and once available.

The proposed ground water monitoring frequency and analytes required to establish a sound environment baseline appears in Table 8.1.

Table 8.1: Proposed Ground Water Monitoring Locations, Frequency and Analytes.

Monitoring Locations	Frequency	Measurements/Analytes
Ground Water Monitoring Locations:	Continuous, when required	Abstraction and influx rates and volumes, if any. Rainfall.
Figures 5.1 and 5.2. Additional locations are to be provided for:		Discharges from mining infrastructure, if any.
■ Open Pit Mining.	Quarterly	Field measurements:
■ Process Plant.		Depth to ground water level.
■ Waste Rock Dumps.		General field <i>in situ</i> (field) water quality measurements: pH, EC, TDS, Salinity, Temperature, Dissolved Oxygen, Oxidation
Tailings Storage Facility.		Reduction Potential including observations such as appearance, odour, colour, etc.)
■ Groundwater Abstraction.		Laboratory analyses:
		Total Alkalinity (T _{alk} , mg/L).
		Total Acidity (T _{ac} , mg/L).
		Major anions (CI, SO ₄ , CO ₃ /HCO ₃ , NO ₃ -N; mg/L).
		Major cations (Ca, Mg, Na and K; mg/L).
		Dissolved metals (Al, As, B, Cd, Cr, Cu, Fe, Mn, Ni, Pb, Zn, Fe; µg/L).

A full metal scan analysis will be undertaken for at least three sampling events and then periodically (e.g. annual) to confirm the proposed metal suite is appropriate for ongoing monitoring. Total metals analyses will also be undertaken at one monitoring site per sampling event as a quality control measure.

Water discharged, if any, shall have no visible surface films, oils and greases, Total Petroleum Hydrocarbons, litter or suspended matter.

Water quality data will be entered into an appropriate database and assessed against relevant water quality criteria and trigger values in order to immediately identify any potential impact as a consequence of mining and processing. Further investigation, if required, and remedial action will be

Reference: PES18001 Page 49 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1

undertaken promptly to address any potential water level and/or quality issues.

It is proposed that for ground water, the default Ground Water Investigation Levels (GILs) Schedule B1 National Environment Protection (Assessment of Site Contamination) Measure 1999 (amended in 2013) which combines the Australian Drinking Water Guidelines (NHMRC and NRMMC 2011) and the guidelines for 95 % species protection levels (hardness modified; ANZECC and ARMCANZ 2000) be adopted as trigger values for ground water quality (refer tabulations in Section 5.3: Ground Water Chemistry and Appendix C). Site-specific trigger values (and possibly for individual monitoring locations) are to be developed when there is sufficient data available from baseline monitoring and reference sites.

Monitoring data will be reported on and raw data provided at the required intervals and in agreed formats and will include an analysis of trends and comparisons with ambient water quality established prior to mining and appropriate water quality criteria and trigger values.

Reference: PES18001 Page 50 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



9. Management Approach

Whilst a preliminary impact assessment reveals that the potential risks appear to be acceptable and manageable, appropriate further site investigation and assessment are required to derive at specific management measures for mining and processing, waste rock and tailings disposal, mine influx into the open pits and well field ground water abstraction to ensure that there is no impact on the surrounding receiving environment. Caravel Minerals should prepare a Groundwater Management Plan.

Reference: PES18001 Page 51 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



10. Conclusions and Recommendations

10.1 Conclusions

The geology of the area comprises paleo channel sediments within and underlain by granite/gneiss bedrock which has been faulted and intruded by dykes of dolerite. The primary aquifers are:

- sediments confined to paleo channels or valleys; and
- weathered/fractured granite-gneiss bedrock, faulted in places and intruded by near-vertical dykes of dolerite.

Preliminary investigations were undertaken to assess the paleo valleys but the underlying faulted and intruded bedrock utilising the overlying paleo channels as a source for recharge has yet to be investigated. Ground water was encountered in paleo channel sediments between 5m and 45m with yields varying between 0.1L/s and 4.8L/s from 100mm diameter bores. Preliminary assessments suggest that larger yields in the range between 10L/s and 20L/s are possible and sustainable. Utilising the current range of hydraulic parameters (T values between 30m2/day and 900m2/day and a S value of 0.002), the cone of drawdown may extend between 7km and 10km from the plant site at an abstraction rate of 100L/s.

Recharge to the paleo channels was estimated at 6mm/a or 1.6% of the mean annual rainfall which may constrain groundwater exploitation as a large area will be required to sustain bore and aquifer yields over the long term.

Ground water has elevated concentrations of Total Dissolved Solids (between 1,900mg/L and 5,000mg/L), predominantly Chloride and Sodium, which often exceed the Australian Drinking Water Guidelines, and to a lesser extent Sulfate. The heavy metals Arsenic, Cadmium, Chromium, Lead, Selenium, Iron and Mercury are absent in groundwater. Concentrations of Aluminium, Copper, Nickel and Zinc generally exceed the ANZECC Fresh Water guidelines for most if not all species protection levels but are well below the drinking water guideline.

With the current layout of mine infrastructure and provided that construction employs best practice, it seems unlikely that mining and processing at the Calingiri Copper Project will impact any GDE's and subterranean fauna seems to be absent.

The primary impacts of mining and processing pertain to:

- The potential for impacts to soils, sediment, surface and ground water resources.
- Potential seepage from mine impoundments such as ROM pads, stockpiles and plant water infrastructure, WRDs and the TSF: mounding underneath and downstream thereof impacting groundwater quality.
- Groundwater abstraction and mine influx: receding ground water levels across mining area and beyond may impact local and/or regional water supplies.
- Exposure of sulfide-bearing materials in open pit excavations during mining and subsequent rehabilitation and closure.
- Open pit sinks and/or lakes post closure.

Whilst the impacts appear to be acceptable and manageable, appropriate site specific management of mining, waste rock and tailings disposal and ground water abstraction will be required to ensure that there is no impact on the receiving environment.

Reference: PES18001 Page 52 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1

More drilling, and testing and sampling are required across the area in order to develop the conceptual model to a level of higher confidence and higher resolution regarding geological heterogeneities. Piezometric heads need to be measured across the area to be able to determine the aquifer(s) within the system as well as their interaction. Boundaries need to be investigated in more detail.

10.2 Recommendations

Consideration should be given to:

- Undertake a census of all available surface and ground water sources within the mine tenements.
- Refine the mine water requirement to define the extent of further groundwater supply investigations.
- Utilise geophysical techniques to delineate aquifers and locate future drilling targets.
- Groundwater monitoring in accordance with this document.
- Further drilling, testing and sampling to not only investigate the paleo channel aquifers but also the faulted/fractured and intruded underlying granite/gneiss.

Reference: PES18001 Page 53 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



References

Australian and New Zealand Environment Conservation Council (ANZECC) (2000): *Australian and New Zealand Guidelines for Fresh and Marine Water Quality.* Volume 1, Chapters 1 to 7, National Water Quality Management Strategy. Canberra, ACT.

Agriculture and Resource Management Council of Australia and New Zealand and Australian and New Zealand Environment and Conservation Council, ARMCANZ and ANZECC, 1996: National Principles for the Provision of Water for Ecosystems.

Australian/New Zealand Standard (1998): Water Quality – Sampling Part 1: Guidance on the design of sampling programs, sampling techniques and the preservation and handling of samples. AS/NZS 5667.1-1998. NSW, Australia and Wellington, New Zealand.

Australian Standard (1993): Geotechnical Site Investigations (Including Amendments 1 and 2 – 1994). AS 1726-1993.

Australian Standard, 1990: Test Pumping of Water Wells . AS 2368-1990.

Caravel Minerals, 2018: Presentation (including several earlier presentations, fact sheets and the 2016 Scoping Study).

Craig, H., 1961: Isotopic Variations in Meteoric Waters. Science, 133, 1702-1703.

Crosbie RS, Morrow D, Cresswell RG, Leaney FW, Lamontagne S and Lefournour M, 2012: New Insights into the Chemical and Isotopic Composition of Rainfall across Australia. CSIRO Water for a Healthy Country Flagship, Australia.

Department of Primary Industries and Regional Development, Agriculture and Food Division, 2018: https://www.agric.wa.gov.au/r4r/west-midlandskoojan-gillingarra-capitela-groundwater-investigations.

Department of Primary Industries and Regional Development, Agriculture and Food Division, 2007: Farm Water for the North-Eastern and Eastern Wheatlbelt of Western Australia, Resource Management Technical Report 318.

Department of Water and Environmental Regulation, DWER, 2014: Assessment and Management of Contaminated Sites, Contaminated Sites Guidelines.

Department of Water, Western Australia, 2009: Operational Policy No. 5.12 - *Hydrogeological Reporting associated with a Groundwater Well Licence*, Department of Water, Perth.

EPA Western Australia, 2015: Environmental Assessment Guidelines for Environmental Principles, Factors and Objectives (EAG 8).

EPA Western Australia, 2013: Environmental Assessment Guideline for Consideration of Subterranean Fauna in Environmental Impact Assessment in Western Australia (EAG 12).

Gat, J.R., and Tzur, Y., 1967: Modification of the Isotopic Composition of Rainwater by Processes which occur before Groundwater Recharge, Isotope Hydrology, Proc. Symp. Vienna 1966, IAEA, Vienna, pp. 49-60.

Kruseman and de Ridder, 1994: Analysis and Evaluation of Pumping Test Data.



National Environment Protection (Assessment of Site Contamination) Measure 1999.

National Health and Medical Research Council (NHMRC) and Natural Resource Management Ministerial Council (NRMMC) 2011: Australian Drinking Water Guidelines 6 Version 3.1, updated March 2015.

National Uniform Drillers Licensing Committee, 2012: Minimum Construction Requirements for Water Bores in Australia, Edition 3.

Pendragon Environmental Solutions, 2018: Soil and Waste Characterisation, Calingiri Copper Project.

Renard, 2005: Understanding Diagnostic Plots for Well-Test Interpretation.

Stichler, W, 1987: Snowcover and Snowmelt Process Studies by means of Environmental Isotopes, in: H.G. Jones and W.J. Orville-Thomas (Eds.), Seasonal Snowcovers: Physics, Chemistry, Hydrology D. Reidel Publishers, pp. 673-726.

Van Tonder, De Lange and Gomo, 2013: FC-Method, Version 2013.

Water Research Commission South Africa, 2002: Manual on Pump Test Analysis in Fractured-Rock Aquifers WRC Report No.: 1116/1/02.

Reference: PES18001 Page 55 of 55 Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



Appendices

Appendix A: Search Data.

Appendix B: Bore Drilling and Testing Completion Records.


Appendix C: Water Quality Data and Laboratory Certificates.

Reference: PES18011 Appendices Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1




Appendix A: Search Data.

Reference: PES18011 Appendices Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1



Search radius 5km Calingiri town centre



					Static Water	Level m
Site Ref	Collected Date Time	Sample ID	Project Code	Project Site Ref	Reading Value	Quality
61510390	1/06/1979 00:00:00	20048662	WA-G-<1996AQWADATA	2135-1-SE-0002	1.00	
61510392	1/01/1900 00:00:00	20048672	WA-G-<1996AQWADATA	2135-1-SE-0012	3.66	
61510395	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2135-1-SE-0020	0.00	
61510397 61510400	30/06/1979 00:00:00 1/01/1900 00:00:00		WA-G-<1996AQWADATA WA-G-<1996AQWADATA	2135-1-SE-0025 2135-1-SE-0029	0.00	
61510400	30/06/1979 00:00:00		WA-G-<1996AQWADATA	2135-1-SE-0029 2135-1-SE-0031	4.60	
61510413	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2135-1-SE-0051	3.40	
61510427	1/01/1900 00:00:00	20048731	WA-G-<1996AQWADATA	2135-1-SE-0070	1.70	
61510428	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2135-1-SE-0071	5.40	
61510526	30/06/1974 00:00:00		WA-G-<1996AQWADATA	2136-2-SE-0069	2.00	
61510527 61511239	1/01/1900 00:00:00 15/03/1978 00:00:00		WA-G-<1996AQWADATA WA-G-<1996AQWADATA	2136-2-SE-0072 2235-4-NE-0001	2.29 7.90	
61511240	30/06/1977 00:00:00		WA-G-<1996AQWADATA	2235-4-NE-0001	2.70	
61511242	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2235-4-NE-0004	8.20	
61511243	1/01/1900 00:00:00	20061225	WA-G-<1996AQWADATA	2235-4-NE-0005	15.00	
61511244	30/06/1951 00:00:00		WA-G-<1996AQWADATA	2235-4-NE-0006	6.70	
61511245	30/06/1950 00:00:00		WA-G-<1996AQWADATA	2235-4-NE-0007	3.50	
61511246 61511247	1/01/1900 00:00:00 30/06/1950 00:00:00		WA-G-<1996AQWADATA WA-G-<1996AQWADATA	2235-4-NE-0008 2235-4-NE-0010	0.60 4.57	
61511248	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2235-4-NE-0013	1.00	
61511249	30/06/1981 00:00:00		WA-G-<1996AQWADATA	2235-4-NE-0014	1.70	
61511250	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2235-4-NE-0015	7.20	
61511251	30/06/1977 00:00:00		WA-G-<1996AQWADATA	2235-4-NE-0016	4.27	
61511252 61511253	1/01/1900 00:00:00 30/06/1951 00:00:00		WA-G-<1996AQWADATA WA-G-<1996AQWADATA	2235-4-NE-0017 2235-4-NE-0018	1.00 3.40	
61511254	30/06/1951 00:00:00		WA-G-<1996AQWADATA	2235-4-NE-0019	0.00	
61511255	30/06/1959 00:00:00		WA-G-<1996AQWADATA	2235-4-NE-0020	6.10	
61511256	1/01/1900 00:00:00	20061245	WA-G-<1996AQWADATA	2235-4-NE-0021	7.62	
61511257	1/01/1900 00:00:00	·	WA-G-<1996AQWADATA	2235-4-NE-0022	5.20	
61511258	30/06/1981 00:00:00		WA-G-<1996AQWADATA	2235-4-NE-0023	3.20	
61511261 61511266	30/06/1920 00:00:00 30/06/1961 00:00:00		WA-G-<1996AQWADATA WA-G-<1996AQWADATA	2235-4-NE-0026 2235-4-NW-0011	9.14 6.10	
61511267	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0012	6.90	
61511268	1/01/1900 00:00:00	20061272	WA-G-<1996AQWADATA	2235-4-NW-0017	1.30	
61511269	30/06/1977 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0018	3.05	
61511270	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0019	4.00	
61511271 61511272	30/06/1971 00:00:00 30/06/1975 00:00:00		WA-G-<1996AQWADATA WA-G-<1996AQWADATA	2235-4-NW-0020 2235-4-NW-0021	1.83 12.60	
61511273	1/01/1900 00:00:00	·	WA-G-<1996AQWADATA	2235-4-NW-0021	1.50	
61511274	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0023	3.30	
61511275	30/06/1976 00:00:00	20061279	WA-G-<1996AQWADATA	2235-4-NW-0024	1.40	
61511276	30/06/1939 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0025	3.30	
61511277	30/06/1979 00:00:00 30/06/1980 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0026	2.44	
61511278 61511279	30/06/1960 00:00:00		WA-G-<1996AQWADATA WA-G-<1996AQWADATA	2235-4-NW-0027 2235-4-NW-0028	1.40 12.19	
61511280	30/06/1978 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0029	7.50	
61511282	30/06/1972 00:00:00	20061286	WA-G-<1996AQWADATA	2235-4-NW-0031	3.05	
61511283	30/06/1980 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0032	6.10	
61511284	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0033	10.00	
61511287 61511289	1/01/1900 00:00:00 30/06/1975 00:00:00	·	WA-G-<1996AQWADATA WA-G-<1996AQWADATA	2235-4-NW-0036 2235-4-NW-0038	7.30 8.40	
61511290	30/06/1979 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0039	2.40	
61511291	30/06/1979 00:00:00	20061295	WA-G-<1996AQWADATA	2235-4-NW-0040	1.30	
61511292	30/06/1978 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0041	5.80	
61511296	30/06/1972 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0045	2.90	
61511297 61511298	1/01/1900 00:00:00 30/06/1979 00:00:00		WA-G-<1996AQWADATA WA-G-<1996AQWADATA	2235-4-NW-0046 2235-4-NW-0047	10.20 6.20	
61511299	30/06/1974 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0047	3.90	
61511300	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0049	3.20	
61511301	30/06/1980 00:00:00	·	WA-G-<1996AQWADATA	2235-4-NW-0050	1.00	
61511302	1/01/1900 00:00:00	·	WA-G-<1996AQWADATA	2235-4-NW-0051	23.30	
61511303	30/06/1980 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0052	12.30 21.34	
61511305 61511306	30/06/1951 00:00:00 30/06/1950 00:00:00		WA-G-<1996AQWADATA WA-G-<1996AQWADATA	2235-4-NW-0054 2235-4-NW-0055	21.34 8.90	
61511307	30/06/1950 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0057	25.91	
61511308	30/06/1975 00:00:00	·	WA-G-<1996AQWADATA	2235-4-NW-0058	18.29	
61511309	30/06/1955 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0059	27.43	
61511310	30/06/1975 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0060	7.00	
61511311	30/06/1980 00:00:00 30/06/1941 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0061	6.10 6.80	
61511312	30/00/1941 00:00:00	20001319	WA-G-<1996AQWADATA	2235-4-SE-0001	6.80	

	1	[222222222			[<u></u>	,
61511313	30/06/1974 00:00:00	20061320	WA-G-<1996AQWADATA	2235-4-SE-0002	2.44	
61511314	30/06/1976 00:00:00	20061321	WA-G-<1996AQWADATA	2235-4-SE-0003	4.60	
61511316	1/01/1900 00:00:00	20061323	WA-G-<1996AQWADATA	2235-4-SE-0005	6.00	
61511317	1/01/1900 00:00:00	20061324	WA-G-<1996AQWADATA	2235-4-SE-0006	0.00	
61511318	30/06/1950 00:00:00		WA-G-<1996AQWADATA	2235-4-SE-0007	3.05	
		 				
61511319	30/06/1979 00:00:00		WA-G-<1996AQWADATA	2235-4-SE-0008	4.57	
61511320	1/01/1900 00:00:00	20061328	WA-G-<1996AQWADATA	2235-4-SE-0009	1.83	
61511321	30/06/1949 00:00:00	20061329	WA-G-<1996AQWADATA	2235-4-SE-0010	7.62	
61511322	30/06/1979 00:00:00	20061330	WA-G-<1996AQWADATA	2235-4-SE-0011	6.10	
61511323	30/06/1969 00:00:00	20061331	WA-G-<1996AQWADATA	2235-4-SE-0012	6.10	
61511324	30/06/1956 00:00:00	 	WA-G-<1996AQWADATA	2235-4-SE-0013	4.40	
			WA-G-<1996AQWADATA	2235-4-SE-0014		
61511325	30/06/1970 00:00:00				17.50	
61511326	30/06/1981 00:00:00	20061335	WA-G-<1996AQWADATA	2235-4-SE-0015	1.40	
61511327	30/06/1977 00:00:00	20061336	WA-G-<1996AQWADATA	2235-4-SE-0016	5.00	
61511328	30/06/1949 00:00:00	20061337	WA-G-<1996AQWADATA	2235-4-SE-0017	0.90	
61511329	30/06/1979 00:00:00	20061338	WA-G-<1996AQWADATA	2235-4-SE-0018	21.50	
61511330	1/01/1900 00:00:00	20061340	WA-G-<1996AQWADATA	2235-4-SE-0020	6.40	
61511331	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2235-4-SE-0021	8.80	
						
61511333	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2235-4-SE-0023	14.00	
61511335	1/01/1900 00:00:00	20061345	WA-G-<1996AQWADATA	2235-4-SE-0025	0.00	
61511336	30/06/1979 00:00:00	20061346	WA-G-<1996AQWADATA	2235-4-SE-0026	6.10	
61511337	1/01/1900 00:00:00	20061347	WA-G-<1996AQWADATA	2235-4-SE-0027	9.14	
61511338	1/01/1900 00:00:00	20061348	WA-G-<1996AQWADATA	2235-4-SE-0028	3.10	
61511341	30/06/1950 00:00:00		WA-G-<1996AQWADATA	2235-4-SE-0032	10.67	
			WA-G-<1996AQWADATA	2235-4-SE-0032	 	
61511342	30/06/1959 00:00:00				18.29	
61511343	30/06/1960 00:00:00		WA-G-<1996AQWADATA	2235-4-SE-0034	0.50	
61511363	1/01/1900 00:00:00	20061375	WA-G-<1996AQWADATA	2235-4-SW-0004	2.30	
61511364	1/01/1900 00:00:00	20061376	WA-G-<1996AQWADATA	2235-4-SW-0005	4.88	
61511365	1/01/1900 00:00:00	20061377	WA-G-<1996AQWADATA	2235-4-SW-0006	5.20	
61511366		20061378	WA-G-<1996AQWADATA	2235-4-SW-0007	2.13	
61511367	30/06/1948 00:00:00	 	WA-G-<1996AQWADATA	2235-4-SW-0008	4.40	
61511368	30/06/1979 00:00:00		WA-G-<1996AQWADATA	2235-4-SW-0009	4.80	
61511369	30/06/1977 00:00:00	20061381	WA-G-<1996AQWADATA	2235-4-SW-0010	4.90	
61511370	30/06/1948 00:00:00	20061382	WA-G-<1996AQWADATA	2235-4-SW-0011	0.00	
61511373	30/06/1979 00:00:00	20061387	WA-G-<1996AQWADATA	2235-4-SW-0016	5.80	
61511375	1/01/1900 00:00:00	20061388	WA-G-<1996AQWADATA	2235-4-SW-0018	0.00	
61511377	1/01/1900 00:00:00	20061390	WA-G-<1996AQWADATA	2235-4-SW-0020	0.00	
61511378	30/06/1948 00:00:00		WA-G-<1996AQWADATA	2235-4-SW-0021	2.50	
						
61511382	30/06/1940 00:00:00		WA-G-<1996AQWADATA	2235-4-SW-0025	4.00	
61511389	1/01/1900 00:00:00	20061403	WA-G-<1996AQWADATA	2235-4-SW-0032	5.50	
61511390	30/06/1952 00:00:00	20061404	WA-G-<1996AQWADATA	2235-4-SW-0033	8.60	
61511391	1/01/1900 00:00:00	20061406	WA-G-<1996AQWADATA	2235-4-SW-0035	7.40	
61511392	1/01/1900 00:00:00	20061407	WA-G-<1996AQWADATA	2235-4-SW-0036	1.00	
61511398	30/06/1950 00:00:00		WA-G-<1996AQWADATA	2235-4-SW-0046	3.50	
61511399	30/06/1945 00:00:00		WA-G-<1996AQWADATA	2235-4-SW-0047	4.90	
61511400	30/06/1965 00:00:00	20061420	WA-G-<1996AQWADATA	2235-4-SW-0048	2.70	
61511401	30/06/1945 00:00:00	20061422	WA-G-<1996AQWADATA	2235-4-SW-0050	3.50	
61511402	1/01/1900 00:00:00	20061423	WA-G-<1996AQWADATA	2235-4-SW-0051	3.80	
61511443	1/01/1900 00:00:00	20061558	WA-G-<1996AQWADATA	2236-3-SE-0047	9.14	
61511445	30/06/1950 00:00:00	 	WA-G-<1996AQWADATA	2236-3-SE-0049	5.47	
61511447	30/06/1977 00:00:00		WA-G-<1996AQWADATA	2236-3-SW-0001	10.70	
						
61511450	30/06/1976 00:00:00	 	WA-G-<1996AQWADATA	2236-3-SW-0005	6.10	
61511451	30/06/1970 00:00:00		WA-G-<1996AQWADATA	2236-3-SW-0007	0.00	
61511452	30/06/1980 00:00:00	20061569	WA-G-<1996AQWADATA	2236-3-SW-0008	3.30	
61511453	30/06/1950 00:00:00	20061570	WA-G-<1996AQWADATA	2236-3-SW-0009	7.62	
61511454	30/06/1978 00:00:00	20061571	WA-G-<1996AQWADATA	2236-3-SW-0010	5.00	
61511455	30/06/1952 00:00:00	20061572	WA-G-<1996AQWADATA	2236-3-SW-0011	13.72	
61511456	30/06/1950 00:00:00		WA-G-<1996AQWADATA	2236-3-SW-0012	2.70	
61511458	30/06/1976 00:00:00		WA-G-<1996AQWADATA	2236-3-SW-0012	16.00	
		 				
61512976	1/01/1900 00:00:00	 	WA-G-<1996AQWADATA	2135-1-SE-0058	3.05	
61513006	30/06/1977 00:00:00		WA-G-<1996AQWADATA	2235-4-SW-0049	1.22	
61513008	1/01/1900 00:00:00	20061560	WA-G-<1996AQWADATA	2236-3-SE-0050	1.00	
61513009	1/01/1900 00:00:00	20061561	WA-G-<1996AQWADATA	2236-3-SE-0052	1.00	
61513103	1/01/1900 00:00:00	20048722	WA-G-<1996AQWADATA	2135-1-SE-0060	1.90	
61513107	1/01/1900 00:00:00	·	WA-G-<1996AQWADATA	2136-2-SE-0070	0.34	
	30/06/1969 00:00:00	 				
61513119			WA-G-<1996AQWADATA	2235-4-NE-0009	0.00	
61513120	30/06/1969 00:00:00		WA-G-<1996AQWADATA	2235-4-NE-0011	0.50	
61513121	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2235-4-NE-0012	1.00	
61513122	30/06/1981 00:00:00	20061339	WA-G-<1996AQWADATA	2235-4-SE-0019	0.00	
61513124	30/06/1981 00:00:00	20061383	WA-G-<1996AQWADATA	2235-4-SW-0012	0.91	
61513125	30/06/1977 00:00:00	20061384	WA-G-<1996AQWADATA	2235-4-SW-0013	0.61	
	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2235-4-SW-0034	0.80	
61513126						

61513143	1/01/1900 00:00:00	20048677	WA-G-<1996AQWADATA	2135-1-SE-0017	0.00	
61513145	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2135-1-SE-0019	1.00	
61513647	1/01/1900 00:00:00	20061562	WA-G-<1996AQWADATA	2236-3-SE-0053	1.00	
61712891	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0011	13.20	
61712900	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0020	2.90	
61712907	30/06/1978 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0027	3.80	
61712918	30/06/1980 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0038	7.50	
61712923	30/06/1950 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0043	5.40	
61712924	30/06/1974 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0044	4.20	
61712928	30/06/1945 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0048	3.00	
61712930	30/06/1937 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0050	6.50	
61712931	30/06/1976 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0051	6.70	
61712932	30/06/1950 00:00:00	20048624	WA-G-<1996AQWADATA	2135-1-NE-0052	0.70	
61712933	30/06/1977 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0053	5.60	
61712934	30/06/1976 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0054	10.00	
61712935	30/06/1976 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0055	6.71	
61712936	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0056	0.90	
61712937	30/06/1966 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0057	3.05	
61712938	30/06/1950 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0058	0.00	
61712939	30/06/1950 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0060	5.50	
61712940	30/06/1980 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0061	6.00	
61712941	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0062	3.70	
61712956	30/06/1980 00:00:00		WA-G-<1996AQWADATA	2135-1-SE-0028	0.00	
61712957	30/06/1971 00:00:00		WA-G-<1996AQWADATA	2135-1-SE-0034	26.52	
61712958	30/06/1956 00:00:00		WA-G-<1996AQWADATA	2135-1-SE-0035	10.67	
61712959	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2135-1-SE-0036	3.40	
61712960	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2135-1-SE-0037	0.00	
61713076	30/06/1965 00:00:00		WA-G-<1996AQWADATA	2136-2-SE-0021	0.30	
61713077	30/06/1965 00:00:00		WA-G-<1996AQWADATA	2136-2-SE-0022	2.03	
61713081	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2136-2-SE-0044	10.00	
61713086	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2136-2-SE-0049	12.19	
61713098	30/06/1980 00:00:00		WA-G-<1996AQWADATA	2136-2-SE-0061	3.40	
61713099	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2136-2-SE-0062	1.30	
61713102	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2136-2-SE-0066	2.30	
61713103	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2136-2-SE-0067	10.00	
61713104	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2136-2-SE-0068	8.70	
61713106	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2136-2-SE-0075	6.40	
61713107	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2136-2-SE-0076	4.20	
61713108	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2136-2-SE-0077	2.80	
61714258	30/06/1972 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0008	9.30	
61714259	30/06/1977 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0010	6.10	
61714260	30/06/1980 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0013	6.10	
61714261	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0015	1.70	
61714262	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0016	7.62	
61714263	30/06/1975 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0056	6.10	
61714844	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2136-2-SE-0071	4.00	
61714852	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0009	2.20	
61714853	1/01/1900 00:00:00		WA-G-<1996AQWADATA	2235-4-NW-0014	0.90	
61716299	30/06/1916 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0001	10.36	
61716300	30/06/1916 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0002	9.45	
61716301	30/06/1916 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0003	16.76	
61716302	30/06/1916 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0004	16.76	
61716304	30/06/1912 00:00:00		WA-G-<1996AQWADATA	2135-1-NE-0006	0.00	
61716462	30/06/1965 00:00:00		WA-G-<1996AQWADATA	2136-2-SE-0023	2.82	
61716463	30/06/1965 00:00:00		WA-G-<1996AQWADATA	2136-2-SE-0024	2.74	
61716464	30/06/1965 00:00:00		WA-G-<1996AQWADATA	2136-2-SE-0025	0.51	
61719226	15/07/1988 10:30:00		WA-S-SWRISHIST	61719226		
70210054	30/06/1988 00:00:00		WA-G-<1996AQWADATA	1742-4-SE-0087	6.09	
70210056	30/06/1975 00:00:00		WA-G-<1996AQWADATA	1742-4-SE-0089	0.80	
70212130	1/01/1900 00:00:00		WA-G-<1996AQWADATA	1742-4-SE-0024	0.00	
70212131	1/01/1900 00:00:00		WA-G-<1996AQWADATA	1742-4-SE-0025	3.35	
70270009	3/09/2008 00:00:00		WA-G-WFFEXTREP	70270009	4.58	
	2.00,20000000			Minimum	0.00	0
				Maximum	27.43	0
				Average	5.35	ŭ
					5.55	



Appendix B: Bore Drilling and Testing Completion Records.

Reference: PES18011 Appendices Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1

pen	dragon	2	/	Suite 2, Level 1, 464 Perth WA 6000		Northing (mN): 465,180.00 Easting (mE): 6,571,750.00	Bore ID: 18CAWB001
www.pendra	mental solutions agonenvironmenta	l.com		Tel No: (08) 9382-82 email: info@pendrag		Elevation (mAHD): 259.00 Zone: 50J	
Project:	Calingiri Proj			Driller:	Orbit Drilling	Elevation (ToC, mAHD):	259.00
Reference:	PES18011			Method:	RC/Mud Rotary	Top of Casing (ToC, agl):	-
Client:	Caravel Mine	rals		Date Started:	13-March-2018	Depth to Ground Water (GWL, mbToC):	-
				Date Completed:	13-March-2018	Depth to Ground Water (GWL, mbgl):	2.00
	D : : (1)			Logged:	RL	Ground Water Level (GWL, mAHD):	257.00
mbgl	Depth RL (m)	Well	Construc	tion Moisture Content Water Strike	Lithological Description		Observations and Remarks
1.0	259.00 258.0			Dry to moist			
2.0	257.0		▼	Moist to wet			
3.0	256.0						
4.0 5.0	255.0 254.0				Gravelly SAND.		
6.0	253.0						
7.0 8.0	252.0 251.0						
9.0	250.0						
10.0	249.0						
11.0 12.0	248.0 247.0						
13.0	246.0						
14.0 15.0	245.0 244.0						
16.0	243.0						
17.0	242.0						
18.0 19.0	241.0						
20.0	239.0				GRAVEL.		
21.0	238.0						
22.0 23.0	237.0 236.0						
24.0	235.0						
25.0	234.0						
26.0 27.0	233.0 232.0						
28.0	231.0						
29.0 30.0	230.0						
31.0	228.0				Brown/red GRAVEL.		
32.0	227.0						
33.0 34.0	226.0 225.0						
35.0	224.0						
36.0 37.0	223.0 222.0				Clayey GRAVEL		
38.0	221.0						
39.0	220.0						
40.0 41.0	219.0 218.0						-nalificial and medical substitution
42.0	217.0				CLAY.		CARRIADES TRUBBLES
43.0 44.0	216.0				Bore Construction Notes:		
45.0	215.0 214.0				Pilot hole drilled using RC to fina	al depth.	+ add NOS
46.0	213.0			End of Hole	†	fitted with 100mmDIA UPVC casings/screens.	Bedrock
47.0 48.0	212.0 211.0				-	A uPVC Class 9, 9mm wall thickness. ss 12 with 8 rows around screen, 37 banks on each	
49.0	210.0				row and 22 0.51mm slots on ear	ch bank.	
50.0	209.0 Bore Comple	tion		Lockable Steel Riser	Filter/gravel (> 5mmDIA) packs	to surface top 0.5m grouted with foam.	12 April 2019
	Bore Comple Bore Construc			Cement		Date: pH:	13-April-2018 4.77
				Bentonite/Cement Grout		Temperature (°C):	24.3
				Gravel Pack Filter Sock	Type: Washed gravel >5mm	Electrical Conductivity (dS/cm): Total Dissolved Solids (mg/L):	5,980 3,300
	Bore Cas	sing:		Solid	Type: 100mm UPV	Salinity (ppt):	
	Bore Scr	reen:		Screen Ground Water Level	Type: 100mm UPV	Dissolved Oxygen (%): Dissolved Oxygen (mg/L)	7.50
			•	Cidulia Waler Level		Oxidation Reduction Potential (ORP, mV):	7.50 -

15 5.5		* /	Suite 2, Level 1, 464	Murray Street	Northing (mN): 465,180.00	1
pen	dragon 7		Perth WA 6000		Easting (mE): 6,571,750.00	I BOILE ID. IOCHVIDUZ
environ	mental solutions		Tel No: (08) 9382-828		Elevation (mAHD): 259.00	
Project:	agonenvironmental. Calingiri Proje		email: info@pendrage Driller:	Orbit Drilling	Zone: 50J Elevation (ToC, mAHD):	255.00
Reference:	PES18011		Method:	RC/Mud Rotary		
					Top of Casing (ToC, agl):	·
Client:	Caravel Miner	als	Date Started:	14-March-2018	Depth to Ground Water (GWL, mbToC):	-
			Date Completed:	14-March-2018	Depth to Ground Water (GWL, mbgl):	5.30
			Logged:	RL	Ground Water Level (GWL, mAHD):	249.70
mbgl	Depth RL (m)	Well Constru		Lithological Description		Observations and Remarks
0.0	259.00		Water Strike			
1.0	258.0		Dry to moist			
2.0	257.0					
3.0	256.0			sandy GRAVEL.		
4.0 5.0	255.0 254.0	_	Moist to wet			
6.0	253.0					
7.0	252.0					
8.0	251.0					
9.0	250.0					
10.0	249.0					
11.0	248.0					
12.0 13.0	247.0 246.0					
14.0	245.0					
15.0	244.0					
16.0	243.0					
17.0	242.0					
18.0	241.0			Grey/light brown GRAVEL.		
19.0	240.0					
20.0	239.0 238.0					
22.0	237.0					
23.0	236.0					
24.0	235.0					
25.0	234.0					
26.0	233.0					
27.0 28.0	232.0					
29.0	230.0					
30.0	229.0					
31.0	228.0					
32.0	227.0			Brown GRAVEL.		
33.0	226.0					
34.0 35.0	225.0 224.0					
36.0	223.0					MINISTRAL PROPERTY WHEN THE REAL PROPERTY AND INC.
37.0	222.0			Bedrock.		Street Street
38.0	221.0					
39.0	220.0			End of Hole.		EREE SEES SEES SEES SEES SEES SEES SEES
40.0 41.0	219.0 218.0			End of Flore.		
42.0	217.0					
43.0	216.0					
44.0	215.0			Bore Construction Notes:		
45.0	214.0			Pilot hole drilled using RC to fina		
46.0	213.0				. fitted with 100mmDIA UPVC casings/screens.	
47.0 48.0	212.0 211.0			-	A uPVC Class 9, 9mm wall thickness. ss 12 with 8 rows around screen, 37 banks on each	
49.0	210.0			row and 22 0.51mm slots on ea		
50.0	209.0			Filter/gravel (> 5mmDIA) packs	to surface top 0.5m grouted with foam.	
	Bore Complet	tion:	Lockable Steel Riser		Date:	13-April-2018
	Bore Construct	tion:	Cement		pH:	5.50
			Bentonite/Cement Grout	Times Week a large 1	Temperature (°C):	24.1
			Gravel Pack Filter Sock	Type: Washed gravel >5mm	Electrical Conductivity (dS/cm): Total Dissolved Solids (mg/L):	2,950
	Bore Cas		Solid	Type: 100mm UPV	Salinity (ppt):	1,700 -
	Bore Scre		Screen	Type: 100mm UPV	Dissolved Oxygen (%):	-
		▼	Ground Water Level		Dissolved Oxygen (mg/L)	7.50
					Oxidation Reduction Potential (ORP, mV):	-

						1	
		4	/	Suite 2, Level 1, 464	Murray Street	Northing (mN): 466,170.0	
pen	mental solutions	6		Perth WA 6000 Tel No: (08) 9382-82	86	Easting (mE): 6,571,710.0 Elevation (mAHD): 245.0	I DOIGID. IOCAVIDUUS
	gonenvironmental.	.com		, ,	onenvironmental.com	Elevation (mAHD): 245.0 Zone: 50	"'
Project:	Calingiri Proje	ect		Driller:	Orbit Drilling	Elevation (ToC, mAHD):	245.00
Reference:	PES18011			Method:	RC/Mud Rotary	Top of Casing (ToC, agl):	
Client:	Caravel Miner	als		Date Started:	15-March-2018	Depth to Ground Water (GWL, mbToC):	
				Date Completed:	18-March-2018	Depth to Ground Water (GWL, mbgl):	4.27
	Logged				RL	Ground Water Level (GWL, mAHD):	240.73
	Depth	Well	Construc			(
mbgl 0.0	RL (m) 245.00	ı		Water Strike	Lithological Description		Observations and Remarks
1.0	244.0			Dry to moist			
2.0	243.0				sandy CLAY.		
3.0	242.0			Moist to wet			
4.0 5.0	241.0 240.0			Woist to wet			1
6.0	239.0						
7.0	238.0						Chips of rock.
8.0	237.0						
9.0 10.0	236.0 235.0						
11.0	234.0				Grey/cream GRAVEL.		
12.0	233.0						
13.0	232.0						
14.0	231.0						
15.0 16.0	230.0 229.0						
17.0	228.0						
18.0	227.0						
19.0	226.0						
20.0	225.0 224.0						
21.0	223.0						
23.0	222.0						
24.0	221.0						
25.0	220.0				GRAVEL.		Increasing presenc of quartz.
26.0 27.0	219.0 218.0						
28.0	217.0						
29.0	216.0						
30.0	215.0						
31.0 32.0	214.0 213.0						oz sochung,
33.0	212.0						
34.0	211.0						· 1-1 # 2 表 表 名 的 2 表 经 条 图 & 图 B 是 图 L L L
35.0	210.0				Weathered Bedrock.		11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
36.0 37.0	209.0	-			End of Hole.		
38.0	207.0						
39.0	206.0						
40.0	205.0						
41.0 42.0	204.0						
43.0	203.0						
44.0	201.0				Bore Construction Notes:		
45.0	200.0				Pilot hole drilled using RC to fin		
46.0	199.0					A fitted with 100mmDIA UPVC casings/screens. A uPVC Class 9, 9mm wall thickness.	
47.0 48.0	198.0 197.0				_	ss 12 with 8 rows around screen, 37 banks on each	
49.0	196.0				row and 22 0.51mm slots on ea		
50.0	195.0				Filter/gravel (> 5mmDIA) packs	to surface top 0.5m grouted with foam.	
	Bore Complet			Lockable Steel Riser		Date:	13-April-2018
	Bore Construct	JUII:		Cement Bentonite/Cement Grout		pH: Temperature (°C):	5.50 24.1
				Gravel Pack	Type: Washed gravel >5mm	Electrical Conductivity (dS/cm):	2,950
				Filter Sock		Total Dissolved Solids (mg/L):	1,700
	Bore Cas	- 1		Solid	Type: 100mm UPV	Salinity (ppt):	-
	Bore Scre	ееп:	V	Screen Ground Water Level	Type: 100mm UPV	Dissolved Oxygen (%): Dissolved Oxygen (mg/L)	7.50
						Oxidation Reduction Potential (ORP, mV):	-

					Suite 2, Level 1, 464 I	Murray Stroot	Northing (mN): 46	7,595.00		
nene	dragon	3	1		Perth WA 6000	wurray Street		1,140.00		400 414/0004
pen	mental solutions	6			Tel No: (08) 9382-828	36	Elevation (mAHD):	256.00	Bore ID:	18CAWB004
www.pendra	gonenvironmenta	l.com	1		email: info@pendrago	nenvironmental.com	Zone:	50J		
Project:	Calingiri Proj	ect			Driller:	Orbit Drilling	Elevation (ToC, mAHD):			256.00
Reference:	PES18011				Method:	RC/Mud Rotary	Top of Casing (ToC, agl):			<u>-</u>
Client:	Caravel Mine	rals			Date Started:	18-March-2018	Depth to Ground Water (GWL, mbToC):			<u> </u>
					Date Completed:	19-March-2018	Depth to Ground Water (GWL, mbgl):			12.00
					Logged:	RL	Ground Water Level (GWL, mAHD):			244.00
	Pepth RL (m)	We	II Constru	ction	Moisture Content	Lithological Description			Observations and Re	omarke
mbgl 0.0	256.00				Water Strike	Ethiological Description			observations and ite	silidi ko
1.0	255.0	_			Dry to moist					
2.0	254.0	-				Brown GRAVEL.				
3.0 4.0	253.0 252.0									
5.0	251.0					Madison to leave and the court of) A \ / \			
6.0	250.0					Medium to large, grey/brown GF	AVEL.			
7.0	249.0									
8.0 9.0	248.0 247.0	-				Sandy GRAVEL.				
10.0	247.0	-								
11.0	245.0					Weathered bedrock.				
12.0	244.0				Moist to wet					
13.0	243.0									
14.0 15.0	242.0 241.0									
16.0	240.0									
17.0	239.0	-								
18.0	238.0	-						0	181	PN 500H
19.0 20.0	237.0 236.0	-				End of Hole				A SACRE
21.0	235.0									
22.0	234.0	_								
23.0 24.0	233.0									
25.0	231.0									
26.0	230.0									
27.0	229.0									
28.0 29.0	228.0 227.0	-								
30.0	226.0									
31.0	225.0									
32.0	224.0	-								
33.0 34.0	223.0 222.0									
35.0	221.0									
36.0	220.0									
37.0 38.0	219.0 218.0									
39.0	217.0									
40.0	216.0									
41.0	215.0									
42.0 43.0	214.0 213.0									
44.0	212.0					Bore Construction Notes:				
45.0	211.0					Pilot hole drilled using RC to fina				
46.0 47.0	210.0 209.0						fitted with 100mmDIA UPVC casings/screen A uPVC Class 9, 9mm wall thickness.	ns.		
47.0 48.0	209.0					-	ss 12 with 8 rows around screen, 37 banks of	on each		
49.0	207.0					row and 22 0.51mm slots on each	ch bank.			
50.0	206.0	tion		1 ~ - '	kable Steel Riser	Filter/gravel (> 5mmDIA) packs	to surface top 0.5m grouted with foam.			12 April 2019
	Bore Comple Bore Construc			8	nent		Date: pH:			3-April-2018 -
					tonite/Cement Grout		Temperature (⁰ C):			-
				8	vel Pack	Type: Washed gravel >5mm	Electrical Conductivity (dS/cm):			-
	Bore Ca	ein-		Filte Solid	er Sock	Type: 100mm UPV	Total Dissolved Solids (mg/L):			-
	Bore Sci			Scre		Type: 100mm UPV	Salinity (ppt): Dissolved Oxygen (%):			-
			V	Gro	und Water Level		Dissolved Oxygen (mg/L)			-
							Oxidation Reduction Potential (ORP, mV	/):		-

non	dragon	3	1		Suite 2, Level 1, 464 I Perth WA 6000	Murray Street	Northing (mN): 467,585.00 Easting (mE): 6,570,340.00	
pen	imental solutions	G along			Tel No: (08) 9382-828		Elevation (mAHD): 235.00	Bore ID: 18CAWB005
Project:	agonenvironment Calingiri Pro		m		email: info@pendrago Driller:	Orbit Drilling	Zone: 50J Elevation (ToC, mAHD):	235.00
Reference:	PES18011				Method:	RC/Mud Rotary	Top of Casing (ToC, agl):	-
Client:	Caravel Min	erals	i		Date Started:	19-March-2018	Depth to Ground Water (GWL, mbToC):	-
					Date Completed:	19-March-2018	Depth to Ground Water (GWL, mbgl):	1.40
					Logged:	 RL	Ground Water Level (GWL, mAHD):	233.60
mbgl	Depth RL (m)	We	ell Constru	ction		Lithological Description		Observations and Remarks
0.0	235.00				Water Strike			
1.0 2.0	234.0 233.0	-	<u> </u>		Dry to moist Moist to wet			
3.0	232.0					Brown GRAVEL.		
4.0	231.0							
5.0 6.0	230.0 229.0							
7.0	228.0							
8.0	227.0							
9.0 10.0	226.0 225.0							
11.0	224.0							
12.0	223.0							Alternating layers of clay and gravel.
13.0 14.0	222.0 221.0							Alternating layers of day and graver.
15.0	220.0							
16.0 17.0	219.0 218.0							
18.0	217.0							
19.0	216.0	_						
20.0	215.0 214.0	_				Clayey GRAVEL.		
22.0	213.0							
23.0 24.0	212.0 211.0							
25.0	210.0							Increasing clay content below.
26.0	209.0							
27.0 28.0	208.0							
29.0	206.0							
30.0 31.0	205.0 204.0							
32.0	203.0							
33.0	202.0	_						
34.0 35.0	201.0	-						
36.0	199.0							
37.0 39.0	198.0					Clayey weathered bedrock.		The same of the sa
38.0 39.0	197.0 196.0					Bedrock.		Minuton
40.0	195.0							THE PROPERTY OF THE PARTY OF TH
41.0 42.0	194.0 193.0							A SAN BRANCH STATE OF THE SAN BEAUTY
43.0	192.0							THE REPORT OF THE PARTY OF THE
44.0 45.0	191.0 190.0					Bore Construction Notes: Pilot hole drilled using RC to fine	al denth	TO THE REPORT OF THE PARTY OF T
45.0 46.0	189.0	_			End of Hole.	-	a fitted with 100mmDIA UPVC casings/screens.	A STATE OF THE STA
47.0	188.0					_	A uPVC Class 9, 9mm wall thickness.	
48.0 49.0	187.0 186.0					Screens: 100mmDIA uPVC Cla row and 22 0.51mm slots on ea	ss 12 with 8 rows around screen, 37 banks on each ch bank.	
50.0	185.0					Filter/gravel (> 5mmDIA) packs	to surface top 0.5m grouted with foam.	
	Bore Compl Bore Constru			1	kable Steel Riser nent		Date:	13-April-2018
	Dore Constru	cuon			nent ntonite/Cement Grout		pH: Temperature (⁰ C):	5.72 23.5
				8	vel Pack	Type: Washed gravel >5mm	Electrical Conductivity (dS/cm):	8,120
	Filter Bore Casing: Solid			er Sock d	Type: 100mm UPV	Total Dissolved Solids (mg/L): Salinity (ppt):	4,600 -	
	Bore Se			Scr	een	Type: 100mm UPV	Dissolved Oxygen (%):	-
				Gro	und Water Level		Dissolved Oxygen (mg/L) Oxidation Reduction Potential (ORP, mV):	5.80
							CARAGON ROGACION I Otential (ORF, IIIV).	

			Suite 2, Level 1, 464 I	Murray Street	Northing (mN): 467,565.00	
pen	dragon 🐔	5/	Perth WA 6000	viuriay Street	Northing (mN): 467,565.00 Easting (mE): 6,569,820.00	
	mental solutions		Tel No: (08) 9382-828	36	Elevation (mAHD): 231.00	
www.pendra	igonenvironmental.c	om	email: info@pendrago	onenvironmental.com	Zone: 50.	J
Project:	Calingiri Projec	t	Driller:	Orbit Drilling	Elevation (ToC, mAHD):	231.00
Reference:	PES18011		Method:	RC/Mud Rotary	Top of Casing (ToC, agl):	- -
Client:	Caravel Minera	ls	Date Started:	20-March-2018	Depth to Ground Water (GWL, mbToC):	
			Date Completed:	20-March-2018	Depth to Ground Water (GWL, mbgl):	3.01
	Depth	Vell Constructi	Logged: ion Moisture Content	RL	Ground Water Level (GWL, mAHD):	227.99
mbgl 0.0	RL (m) 231.00	veii constructi	Water Strike	Lithological Description		Observations and Remarks
1.0	230.0		Dry to moist			
2.0	229.0		Moist to wet	Brown GRAVEL.		
3.0 4.0	228.0		Worst to wet			
5.0	226.0					
6.0	225.0					
7.0 8.0	224.0					
9.0	222.0					
10.0	221.0					
11.0 12.0	220.0					
13.0	218.0					
14.0	217.0			Clayey GRAVEL.		Observation leaves of also and arrows
15.0 16.0	216.0 215.0					Alternating layers of clay and gravel.
17.0	214.0					
18.0	213.0					
19.0 20.0	212.0					
21.0	210.0					
22.0	209.0					
23.0 24.0	208.0					
25.0	206.0					Increasing clay content.
26.0	205.0					
27.0 28.0	204.0					
29.0	202.0			Clayey GRAVEL.		
30.0	201.0					200 (14)41
31.0 32.0	200.0 199.0					
33.0	198.0					
34.0	197.0			End of Hole.		Section (de la Jacob
35.0 36.0	196.0 195.0					
37.0	194.0					
38.0	193.0					
39.0 40.0	192.0 191.0					
41.0	190.0					
42.0	189.0					
43.0 44.0	188.0 187.0			Bore Construction Notes:		
45.0	186.0			Pilot hole drilled using RC to final	al depth.	
46.0	185.0				fitted with 100mmDIA UPVC casings/screens.	
47.0 48.0	184.0 183.0			_	A uPVC Class 9, 9mm wall thickness. ss 12 with 8 rows around screen, 37 banks on each	
49.0	182.0			row and 22 0.51mm slots on ea		
50.0	181.0			Filter/gravel (> 5mmDIA) packs	to surface top 0.5m grouted with foam.	
	Bore Completion		Lockable Steel Riser Dement		Date: pH:	13-April-2018 5.58
	20.0 001101110110		Bentonite/Cement Grout		Temperature (⁰ C):	24.1
			Gravel Pack	Type: Washed gravel >5mm	Electrical Conductivity (dS/cm):	8,560
	Bore Casin		Filter Sock Solid	Type: 100mm UPV	Total Dissolved Solids (mg/L): Salinity (ppt):	4,750 -
	Bore Scree		Screen	Type: 100mm UPV	Dissolved Oxygen (%):	-
		V	Ground Water Level		Dissolved Oxygen (mg/L)	4.90
					Oxidation Reduction Potential (ORP, mV):	

peno	dra mental s	gon olutions	3	/		Suite 2, Level 1, 464 M Perth WA 6000 Tel No: (08) 9382-828		Northing (mN): 467,734.00 Easting (mE): 6,560,805.00 Elevation (mAHD): 229.00	Bore ID: 18CARC27			
www.pendra	gonenv	ironmenta	l.com	n		email: info@pendrago	nenvironmental.com	Zone: 50J				
Project:	Cali	ngiri Proj	ect			Driller:	Orbit Drilling	Elevation (ToC, mAHD):	229.00			
Reference: PES18011						Method:	RC/Mud Rotary	Top of Casing (ToC, agl):	-			
Client: Caravel Minerals						Date Started:	12-March-2018	Depth to Ground Water (GWL, mbToC):				
						Date Completed:	13-March-2018	Depth to Ground Water (GWL, mbgl):	1.72			
Depth						Logged:	RL	Ground Water Level (GWL, mAHD):	227.28			
mbgl RL (m) Well Construction					ction	Moisture Content Water Strike	Lithological Description		Observations and Remarks			
1.0		229.00				Dry to moist						
2.0		27.0		▼		Moist to wet			Dolerite present.			
3.0		26.0										
4.0		25.0										
5.0 6.0		23.0										
7.0		22.0										
8.0		21.0										
9.0 10.0		20.0										
11.0		18.0					Day to maint and	W CLAY				
12.0	2	17.0					Dry to moist and wet, grey sand	y OLAT.				
13.0		16.0										
14.0 15.0		15.0 14.0	-									
16.0		13.0										
17.0	2	12.0										
18.0		11.0	-									
19.0 20.0		10.0 209.0										
21.0		0.80										
22.0		207.0										
23.0 24.0		06.0 05.0					End of Hole.					
25.0		04.0					End of Flore.					
26.0		03.0										
27.0		202.0										
28.0 29.0		201.0										
30.0		99.0										
31.0	1	98.0										
32.0		97.0										
33.0 34.0		96.0 95.0	-									
35.0		94.0										
36.0		93.0										
37.0 38.0		92.0 91.0										
39.0		90.0										
40.0		89.0										
41.0		88.0										
42.0 43.0		87.0 86.0										
44.0		85.0					Bore Construction Notes:					
45.0		84.0					Pilot hole drilled using RC to fina					
46.0 47.0		83.0 82.0						A titted with 100mmDIA UPVC casings/screens. A uPVC Class 9, 9mm wall thickness.				
48.0		81.0					-	ss 12 with 8 rows around screen, 37 banks on each				
49.0		80.0					row and 22 0.51mm slots on each					
50.0		79.0	tic		100	kahla Steel Bisse	Filter/gravel (> 5mmDIA) packs	to surface top 0.5m grouted with foam.	42 April 2049			
		e Comple Construc			8	kable Steel Riser nent		Date: pH:	13-April-2018 5.44			
						tonite/Cement Grout		Temperature (⁰ C):	24.3			
					8	vel Pack	Type: Washed gravel >5mm	Electrical Conductivity (dS/cm):	6.7			
		Bore Cas	sina.		Filte Solid	er Sock d	Type: 100mm UPV	Total Dissolved Solids (mg/L): Salinity (ppt):	3,950 -			
		Bore Scr			Scre		Type: 100mm UPV	Dissolved Oxygen (%):	-			
				V	Gro	und Water Level		Dissolved Oxygen (mg/L)	6.70			
								Oxidation Reduction Potential (ORP, mV):				

pen	dra	gon solutions	Z		Suite 2, Level 1 Perth WA 6000 Tel No: (08) 938)		Northing (mN): 467,906.0 Easting (mE): 6,560,782.0 Elevation (mAHD): 246.0	Bore ID: 18CARC28				
www.pendra	agonen	vironmenta	al.com	n	email: info@per	ndragor	nenvironmental.com	Zone: 50	J				
Project:	Ca	lingiri Proj	ject		Driller:		Orbit Drilling	Elevation (ToC, mAHD):	246.00				
Reference:	PE	S18011			Method:		RC/Mud Rotary	Top of Casing (ToC, agl):	-				
Client: Caravel Minerals					Date Started:		13-March-2018	Depth to Ground Water (GWL, mbToC):					
					Date Complete	ed:	13-March-2018	Depth to Ground Water (GWL, mbgl):	0.00				
	Depth						RL	Ground Water Level (GWL, mAHD):	L, mAHD): 246.00				
mbgl RL (m) Well Construction					ction Moisture Con Water Strik		Lithological Description		Observations and Remarks				
1.0	T	246.00 245.0		_	Moist to we	et							
2.0		244.0			-				Dolerite present.				
3.0		243.0	_										
4.0 5.0		242.0 241.0	-										
6.0		240.0	-				Dry to moist and wet, brown san	dy GRAVEL.					
7.0		239.0											
8.0		238.0	_										
9.0 10.0	\vdash	237.0 236.0	-										
11.0	++-	235.0							_				
12.0		234.0	_										
13.0 14.0		233.0 232.0											
15.0	++-	231.0											
16.0		230.0	_				Fine, yellow/orange SAND.						
17.0 18.0		229.0 228.0											
19.0		227.0	-										
20.0		226.0											
21.0		225.0	-										
22.0		224.0 223.0	-										
24.0		222.0											
25.0		221.0											
26.0 27.0		220.0 219.0	-										
28.0		218.0					Orange SAND, increasing grey	clay content.					
29.0		217.0	-										
30.0 31.0		216.0 215.0	-										
32.0		214.0											
33.0		213.0	-										
34.0		212.0 211.0	-										
35.0 36.0		210.0							1				
37.0		209.0											
38.0 39.0		208.0 207.0					Grey CLAY.						
39.0 40.0		206.0											
41.0	++-	205.0											
42.0		204.0					End of Casing/Screen.		Bore drilled to bedrock at 66.0m.				
43.0 44.0		203.0 202.0					Bore Construction Notes:		(CV-MATURE)				
45.0	++-	201.0					Pilot hole drilled using RC to fina	al depth.	等自己是可是是自己创始了。 1000年日日本日日初始了				
46.0	++-	200.0						fitted with 100mmDIA UPVC casings/screens.	FERENCE CONTRACTOR				
47.0 48.0		199.0 198.0						A uPVC Class 9, 9mm wall thickness. ss 12 with 8 rows around screen, 37 banks on each	/ SOME DESIGNATION OF THE PARTY				
49.0		197.0					row and 22 0.51mm slots on each		ADDODES - DECEMBER 1995				
50.0		196.0					Filter/gravel (> 5mmDIA) packs	to surface top 0.5m grouted with foam.					
		re Comple Construc			Lockable Steel Riser Cement	r		Date: pH:	13-April-2018 6.01				
	_0.0				Bentonite/Cement G	Grout		Temperature (⁰ C):	6.01 23.8				
					Gravel Pack		Type: Washed gravel >5mm	Electrical Conductivity (dS/cm):	7,650				
		Bore Cas	eina.		Filter Sock Solid		Type: 100mm UPV	Total Dissolved Solids (mg/L): Salinity (ppt):	4,600				
		Bore Sci			Screen		Type: 100mm UPV	Dissolved Oxygen (%):	-				
					Ground Water Level	I		Dissolved Oxygen (mg/L)	6.30				
								Oxidation Reduction Potential (ORP, mV):	•				

CONTINUIOS PUMPING RATE

	TO A TUBE O.C. 2 (C)
NAME	DATE 26.3.19
ADDRESS	TO COME CONTROL
SUBURB	CALINGIR

		WATER LEV		2		tres				LET: Δ		ometre	es 	
PUI	MPIN	G RATE: 4-8	5Lt/s	sec OR	288L	om	PU	MPIN	GRA	TE: 0.0	000			
Tin		Actual Pumping Level		ime	Actua Pump Level	1	Ti	me	P	Actual umping Level		Time	Pur	ctual npin Leve
1	Min	38 60 m	4 1/4	Hr	3800	o m	R	ecove	ry R	eadings				
2	Min	. 3900 m	4 1/2	Hr	380		1	Min		2	m			
3	Min	3900 m	4 3/4	Hr	3900		2	Min			m			
4	Min	3900 m	5	Hr	390	o m	3	Min			m			
<u>.</u>	Min	3900 m	5 1/4	Hr	3900		4	Min			m			
6	Min	3900 m	5 ½	Hr	390	o m	5	Min	_		m			
7	Min	3900 m	5 3/4	Hr	390		6	Min			m			
8	Min	3900 m	6	Hr	3900	2 m	7	Min			m			
9	Min	3900 m	6 1/4	Hr	3900		8	Min			m			
10	Min	3900 m	6 1/2	Hr	390		9	Min			m			
15	Min	3900m	6 3/4	Hr	390		10	Min			m			
20	Min	3900m	7	Hr	390		15	Min			m			
25	Min	3900 m	7 1/4	Hr	390		20	Min			m			
30	Min	3900m	7 1/2	Hr	890		25	Min			m			
35	Min	3900m	7 3/4	Hr	390		30	Min			m			
40	Min	13900m	8	Hr	390		35	Min			m			
50	Min	390 am	9		390		40	Min			m			
1	Hr	3900m	10		399		50	Min			m			
1 1/	4 Hr	3900 m	11		39	00	1	Hr			m			
1 1	4 Hr	3000m	12		39	00	Veg	e						
1 3	4 Hr					·	100	::						,
2	Hr	3860 m					ļ		3 4					
	4 Hr	3800 m	ļ				-	T 00 X 7		CIDE A TOV	- Tr	0000	<u> </u>	PIV
2 3										STAR		2899		PPM
	4 Hr		ļ				SA	لللال	E V E 3	FINIS		3050	<u></u>	1 1V
3	Hr													
3 1	4 Hr													
3 !							-			SA.	VL	2 0	00 M	
3 3							-			34	¥ #1	2.0	(() 113	
4	Hr	3900m					-	TOO	ת מ	CODE	ואויה	<u> </u>	M	
							 	10	rui	SCRE	DIA		147	1
			-					T	OTA	L DEP	TH	45.	80 av	I
	S	TART TIME		1300	PH				FIN	ISH TI	ME	1.00	AM	
	e	COMMENTS	Bo	7 E S	No	1								- 11

NAME		DATE 27.3.18
ADDRESS		
SUBURB	Calhairi	POST CODE

STATIC	WATER LEV	/EI: 5 20	o metres	PUMPING INLET: 36 000 metres					
1	G RATE 45					G RATE: 0.000			
	Actual	Time	Actual		ime	Actual	Time	Actual	
Time 7.00 am	Pumping	111120	Pumping			Pumping		Pumpins	
/.00 am	Level		Level			Level		Level	
7.7		41/ 13-	<u> </u>	E	lecover				
1 Min		4 1/4 Hr	10.800 m	1	Min				
2 Min		4 ½ Hr 4 ¾ Hr	10.900 m	2	Min	5.600 m 5.200 m			
3 Min		5 Hr	11.000 m	3	Min	m			
4 Min		5 Hr		4	Min	m			
5 Min			11000 m	5	Min	m			
6 Min		5 ½ Hr 5 ¾ Hr	1	6	Min	m			
7 Min		6 Hr		7	Min	no			
8 Min		6 1/4 Hr	10950 m	8	Min	m			
9 Min		6 ½ Hr	11050 m	9	Min	m			
10 Min		6¾ Hr		10	Min	m			
15 Min			11250 m	15	Min				
20 Min		7 Hr 7 ¼ Hr	11000 m	20	Min	m			
25 Min		<u></u>	11050 m	25	Min	m m			
30 Min		7½ Hr 7¾ Hr	11000 m	30	Min	m	<u> </u>		
35 Min		8 Hr	11050 m	35	Min	m ·			
40 Min			<u> </u>	40	Min				
50 Min		844 HV	1000	50	Min	m			
1 Hr		81/2 HV		1	Hr	m m			
1 1/4 Hr			00011	1	111	<u> </u>			
1 ½ Hr		9 HL	11000						
1 34 Hr		91/4 HV		-					
2 Hr 2 1/4 Hr		91/2 44		<u> </u>					
		9314 HV		EA.	TTTE	VEL START	984	PPM	
						VEL START VEL FINISH	1610	PPM	
2 ³ / ₄ Hr			10900	BA	ىدىد دىد	VEL VIIVISII	1670		
3 Hr 3 ¼ Hr	10	1013/4 H		 			-	4	
	1,7-6/1			-			 		
3 ½ Hr		II HV		-		SWL	50	M	
3 ¾ Hr		11114 144	11000	 		TAAT	5 200	112	
4 Hr	10.800m	111/2 40	11000		TAI	OF CODEEN	<u> </u>	M	
		113/4 HV	11.000	 	101	OF SCREEN	 	TAN	
		112 HL	. 11.000	+	TIT'A	TAL TERRIT	40.00	M	
		<u> </u>		+	1 4	OTAL DEPTH	40.00	JOHE	
CM - THE THE		1700		 		THAT ETOPIATE	10.20		
S	TART TIME	1/.30				FINISH TIME	19.30		
	~~ ~			<u></u>	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				
	COMMENTS					***************************************			
		BORE NO	2	democratical	-				

NAME	DATE 28.3./8
ADDRESS	
SUBURB	CALINGIR! POST CODE

BORE NO. 3.

STA	TIC	WATER LEV	ÆL:	4.300	metres	PU	MPINO	GINLET: 35	metres	<u></u>
		GRATE:1.5				PU	MPIN(G RATE: 0.000		
Tin 7.00	1	Actual Pumping	T	ime	Actual Pumping	T	ime	Actual Pumping Level	Time	Actual Pumpin Leve
		Level			Level					LEVE
1	Min	RUN AUT III	4 1/4	Hr	l m		Recover			
2	Min	. m	4 1/2	Hr	m	1	Min Min	n		
3	Min	m	4 3/4	Hr Hr	m	3	Min	m		
4	Min	m	5		m	4	Min			
5	Min	m	5 1/4	Hr	m	!	Min	m		
6	Min	m	5 1/2	Hr	m	5	Min	m		
7	Min	m	5 3/4	Hr	m	7	Min	m		
8	Min	m	6	Hr	m	8	Min	m		
9	Min		6 1/4	Hr Hr	m	9	Min	m m		
10	Min	m	6 3/4	Hr	m	10	Min	m		
15	Min	m	7		m	15	Min			
20	Min	m m	7 1/4	Hr Hr	m	20	Min	m		
25	Min	m —	7 1/2	Hr	m	25	Min	m		
30	Min Min	m	7 3/4	Hr	m	30	Min	m m		
$\frac{35}{40}$	Min	m m	8	Hr	m	35	Min	m		
50	Min	m	0	111	111	40	Min	m		
$\frac{30}{1}$	Hr	m	 			50	Min	m		
$\frac{1}{1^{1/2}}$		m				1	Hr	m		
1 1/		m	-		-	 ^				
	4 Hr	m	 			1		***************************************		
2	Hr	m				<u> </u>				
2 1/2		m								
2 1/2		m				SA	LTLE	VEL START		PPM
2 3/		TIS.				SA	LT LE	VEL FINISH		PPM
3	Hr	m				1				
	4 Hr	m				1		, , , , , , , , , , , , , , , , , , ,		
3 1/		m		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,						
	4 Hr	m						SWL	4.300	M
4	Hr	m								
						<u> </u>	TOF	OF SCREEN		<u>M</u>
		.,				-	T(OTAL DEPTH	36:000	M
	S	TART TIME]	FINISH TIME		
				,						
	(COMMENTS		<u> </u>	O WATE	15				

	NAME		DATE 448
	ADDRESS		
Ì	SUBURB	CALINGIRI	POST CODE

BORE NO 18 CARC 027

STA	ATIC	WATER LEV	ÆL:	1.43	0	metr	es	PUMPING INLET: 24,000 metres						
PU	MPIN	GRATE: 1.8	Lt/	sec O	RIC	8Lpr	n	PU	MPIN(G RAT	E: 0.000)		
Time 7.00 am		Actual Pumping Level	Ţ			Actual Pumping Level		Time		Pun	ctual nping evel	Time	I	Actua Pumpir Lev
1	Min	6.200 m	4 1/4	Hr	24€	500	m	R	ecover	ry Rea	dings			
2	Min	7.200 m	4 1/2	Hr	41	360	m	1	Min	22	.000m			
3	Min	7.400 m	4 3/4	Hr	21	500	m	2	Min		600 m	7.AM	1.7	00
4	Min	8.800 m	5	Hr	21	650	m	3	Min	21.4	400 m			
5	Min	9.500 m	5 1/4	Hr	2	500	ш	4	Min	21.~	200m			
6	Min	10.400 m	5 1/2	Hr	2	1600	m	5	Min	21.0	うらのm			
7	Min	10.700 m	5 3/4	Hr		1730		6	Min	20.	900 m			
8	Min	11.000 m	6	Hr	2	1900	m	7	Min	20,	Sor m			
9	Min	11.00 m	6 1/4	Hr		2100		8	Min	20	.200 m			
10	Min	10.950 m		Hr	12	244e	m	9	Min		50 cm			
15	Min	10.950 m	6 3/4	Hr		2430		10	Min	18	80 m			
20	Min	10.950 m	7	Hr		5 40		13	Min	17.	30 cm			
25	Min	10 900 m	7 1/4	Hr		2700		102	Min		300m	15		
30	Min	10,900 m	7 1/2	Hr		2700		253	Min		40 cm			
35	Min	10.900 m	7 3/4	Hr		2706		304	Min		900m	14		
40	Min	10,900 m	8	Hr		2650		337	Min		200m	15		
50	Min	10.900 m						40	Min	12.	900 m	204		
1	Hr	10.950 m	l					50	Min		<u>စ်စ္</u> က	304		
1 1/2		10.950m			· · · · · · · · · · · · · · · · · · ·			$\frac{30}{1}$	Hr		プロジ m			
1 1/2		// 000m									300	50H		
	4 Hr	11 150 m	 								300 300	THN	l	
2	4 111 Hr	11. 200 m	 								500	1.30	1/1-	
2 1/		11 450 m	 					6 P1			500 500	2 46	14 8	
2 1/2				.,							TART			PPM
2 3/		11 600 m	 								INISH		***************************************	PPM
3	4 Hr	11850 m						DCT	نوبد د د	יצ וציינו א	RIVADAR	<u> </u>		1 2 112
		11950 m									<u>`</u>	1	·····	
3 1/		12 200m							~~~	***************************************	······································	 		
	4 Hr	1.3900 m	-								C3373	1 2 12 1		M
3 3/		16 250 m	 								SWL	1430	<i>y</i> •	IVA
	Hr	17. F60 m							70.AX	NOTE O		 		n ø
3.4	B H	17090	1792	<u> 20</u>					TOP	OFS	CREEN	ļ		M
4	<u> Hr</u>	18570	-											3.7
40	5 Hr	19510	ļ						T	DTAL	DEPTH	27.60	0_	M
4.1	OHI	20100										<u> </u>		
	ST	ART TIME	<u> </u>		····]	FINISI	HTIME			
	C	OMMENTS	1				_	-						

1.8 ALT. / SEC. -

NAME		DATE 4.4.18
ADDRESS		,
SUBURB	CALINGIRI	POST CODE

0430310085 BORE NO 18CARC 028

		WATER LEV				PUMPING INLET: 40 metres PUMPING RATE: 0.000						
PU	MPIN	GRATE: 2,										
Tin 7.00	ne am	Actual Pumping Level	T	ime	Actual Pumping Level		ime	Actual Pumping Level	Time	Actual Pumpin Leve		
-	3.σ:	RUV AUT M	4 1/4	Hr	m	E	ecover	y Readings				
$\frac{1}{2}$	Min Min		4 1/2	Hr	m	1	Min	m				
3	Min	m	4 3/4	Hr	m	2	Min	m				
4	Min	m	5	Hr	m	3	Min	m				
5	Min	m	5 1/4	Hr	m	4	Min	m				
6	Min	m	5 1/2	Hr	m	5	Min	m				
7	Min	m	5 3/4	Hr	m	6	Min	m				
8	Min	m	6	Hr	m	7	Min	m				
9	Min	m	6 1/4	Hr	m	8	Min	m				
10	Min	m	6 1/2	Hr	m	9	Min	m				
15	Min	m	6 3/4	Hr	m	10	Min	m				
20	Min	m	7	Hr	m	15	Min	m				
25	Min	m	71/4	Hr	m	20	Min	m				
30	Min	m	7 1/2	Hr	m	25	Min	m m				
35	Min	m	7 3/4	Hr	m	30	Min	m				
40	Min	m	8	Hr	m	35	Min	m				
50	Min	m				40	Min	m				
1	Hr	m				50	Min	m				
1 1/		m				1	Hr	l m				
	4 Hr 4 Hr	m				-						
$\frac{1^{-3}}{2}$	4 Hr	m m	 			 						
	4 Hr	m	 			 						
$\frac{2}{2}$		m				SA	LTLE	ÆL START		PPM		
$\frac{2}{2}$		m				<u> </u>		EL FINISH		PPM		
 3	Hr	m										
	4 Hr	m										
	4 Hr	m										
3 3/		m					(0.00 SWL	(C) (C) (C)	M		
4	Hr	m		•								
						ļ	TOP	OF SCREEN		M		
					41.03		ТО	TAL DEPTH	4.03	M		
START TIME						F	INISH TIME					
		COMMENTS		Va	WATER		***************************************					

NAME		DATE 64.8
ADDRESS		
SUBURB	CACINGIA	POST CODE

BORE NO: 6

				TOTEL VENEZA	C TAIL EVE		
	WATER LEV			1	G INLET: 19 De		
PUMPIN	G RATE: I	Lt/sec OR	60 Lpm		G RATE: 0.000		
Time	Actual	Time	Actual	Time	Actual	Time	Actual
7.00 am	Pumping	Thursday as a	Pumping		Pumping		Pumping
	Level		Level		Level		Level
1 Min	11.30cm	4 1/4 Hr	m	Recove	ry Readings		
2 Min	17.70 cm	4½ Hr	m	1 Min	9.500 m		
3 Min	18.000m		m	2 Min	8.600 m		
4 Min	18.30 m		m	3 Min	7500 m		
5 Min			· m	4 Min	6.500 m		
6 Min	17.9 vom	5½ Hr	m	5 Min	6.000 m		
7 Min	17,800m	5¾ Hr	m	6 Min	5 700 m		
8 Min	17. 800m	6 Hr	m	7 Min	5.500 m		
9 Min			m	8 Min	5.300 m		
10 Min	77805 m	6½ Hr	m	9 Min	. 5.200 m		
15 Min	17805 m	6¾ Hr	m	10 Min	5100 m		
20 Min	17805 m	7 Hr	m	15 Min	4,800 m		
25 Min	17905 m	7 1/4 Hr	m	20 Min	4.700 m	- J	
30 Min	13.3cem	7½ Hr	m	25 Min		*	
35 Min	13,000 m	7% Hr	m	30 Min			
40 Min		8 Hr	m	35 Min	et a		
50 Min				40 Min			
1 Hr	12.7.50m			50 Min			
1 ¼ Hr		•		1 Hr	4.100 m		
1 ½ Hr							
1 3/4 Hr							
2 Hr		<u> </u>			37	1	
2 1/4 Hr				CITOTT	TENT CON LINE		DDA/
2 ½ Hr					EVEL START		PPM
2 3/4 Hr		<u> </u>		SALTLE	EVEL FINISH		PPM
3 Hr				ļ			
3 1/4 Hr							
3 ½ Hr					CRITI	1	M
3 ¾ Hr					SWL	3100	111
4 Hr	l m	1		Tr.A.	ואינונו פורע אינו אינו		M
				10.	P OF SCREEN		
		<u> </u>		- n-	OTAL DEPTH	20.500	M
		-		1	VIAL DEFIR	140.300	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	TO A TOUTH CONTRACTOR	-			FINISH TIME	-	
5	TART TIME	<u> </u>			CIVILI INCEPTED		
	TANK AN ANNIES C				The shade being		
(COMMENTS	1					

(3)

117/sic 0.6.17/ssc

NAME		DATE 6.4.18
ADDRESS		
SUBURB	CALINGIRI	POST CODE

BORE NO. 5

		BURE	, ,	• • •						
STA	TIC	WATER LEV	ÆL:	1.400	metres	PUi	MPIN	G INLET: 3/5	metres	
1		GRATE: 2				PUi	MPIN	G RATE: 0.000		
Tim		Actual		ime	Actual	Ti	me	Actual	Time	Actual
7.00	am	Pumping			Pumping			Pumping		Pumping
		Level			Level			Level		Level
1	Min	4.500 m	4 1/4	Hr	28.000 m	R		ry Readings		
2	Min	6.800 m	4 1/2	Hr	28.100 m	1	Min	16400 m		
3	Min	7.700 m	4 3/4	Hr	28. 200 m	2	Min	14.400 m		
4	Min	9.600 m	5	Hr	28.250m	3	Min	14.170 m		
5	Min	11.400 m	5 1/4	Hr	m	4	Min	13.95Um		
6	Min	12.300 m	5 1/2	Hr	m	5	Min	m		
7	Min	13.200 m	5 3/4	Hr	m	6.	Min	m		
8	Min	13.400 m	6	Hr	m	7	Min	13.000 m		
9	Min	13.450 m	6 1/4	Hr	m	8	Min	13.000 m		
10	Min	13 550 m	6 1/2	Hr	m	9	Min	13.000 m		
15	Min	13.700 m	6 3/4	Hr	m	10	Min	13:100 m		
20	Min	14,100 m	7	Hr	m	15	Min	i3.280 m	P2	
25	Min	19.500 m	7 1/4	Hr	m	20	Min	9,35 m		
30	Min	24,300 m	7 1/2	Hr	Ti.	25	Min	7.11 m		
35	Min	24780 m	7 3/4	Hr	m	30	Min	6-14 m		
40	Min	25040 m	8	Hr	m	35	Min	5 34 m		
50	Min	25330 m				40	Min	4.90 m		
1	Hr	25600 m				50	Min	1 17 m		
1 1/4	Hr	25750 m				1	Hr	2. 79 m		
1 1/2	Hr	25600 m				17	<u>,</u>	3 38		
1 3/4	Hr	25900 m				١.	2	2.10		
2	Hr	26050 m				13	1.	2.01		
2 1/4	Hr	26 800 m				12		2.7		
2 1/2	Hr	26.900 m						EVEL START		PPM
2 3/4	Hr	26.950m				SA	LTLE	EVEL FINISH		<u>PPM</u>
3	Hr	27.150m				2	1	255.		
3 1/3	Hr	27.350 m								
3 1/2	Hr									
3 3/2	Hr							SWL	1400	<u>M</u>
4	Hr	27.300 m				ļ				2.5
							TO	P OF SCREEN		M
		*								7) //
						<u> </u>	T	OTAL DEPTH	32:2.	M
						ļ			 	****
	<u>S'</u>	TART TIME	<u> </u>			ļ		FINISH TIME	-	
			<u> </u>			<u> </u>			<u> </u>	
	(COMMENTS	<u></u>							
1										

72-12.50 72-12.50



Appendix C: Water Quality Data and Laboratory Certificates.

Reference: PES18011 Appendices Date: July 2018
Site: Calingiri Copper Project Title: Hydrogeological Assessment Revision No: 1

Calingiri Copper Project																					
Caravel Minerals			Field Meas	uromonte																	
Date: 13 April 2018			i iciu ivieds	arements.				Gene	eral Chem	istry					Ma	jor Cations	s and Ani	ons			
Analyte	Ground Water Level	Temperature (°C)	Н	Dissolved Oxygen	Electrical Conductivity	Total Dissolved Solids	Н	Electrical Conductivity	Sodium Adsorption Ratio	Total Hardness as CaCO3	TDS	Calcium (Ca)	Magnesium (Mg)	Sodium (Na)	Potassium (K)	Chloride (Cl)	Sulphate (SO4)	Hydroxide Alkalinity as CaCQ	Carbonate Alkalinity as CaCQ	Bicarbonate Alkalinity as CaCQ	Total Alkalinity as CaCQ
Unit	(mbgl)	(°C)	pH Units	mg/L	(μS/cm)	(mg/L)	pH Units	(µS/cm)	-	• • • • • • • • • • • • • • • • • • • •	ng/L		j		T	mg L	ı/L			ıı	
LoR Assessment Levels ANZECC (2000) ¹		<u> </u>	-	•	-	•	-	1	0.01	1	10	1	1	1	1	1	1	1	1	1	1
Fresh Water ² : 99% Species Protection Level Fresh Water ² : 95% Species Protection Level Fresh Water ² : 90% Species Protection Level Fresh Water ² : 80% Species Protection Level		-	6.5 - 8.5 6.5 - 8.5 6.5 - 8.5 6.5 - 8.5	-	-	-	6.5 - 8.5 6.5 - 8.5 6.5 - 8.5 6.5 - 8.5		-	-	-	- - -	-	- - -	-	- - -	-	-	-	-	- - -
ADWG (2011) ³																					
Health Value (HV)	-	-	•	-	-	-	-	•			-	-	-	-	-	-	500	-	-	-	-
Aesthetic Value (AV)	-	-	6.5 - 8.5	>5	-	-	6.5 - 8.5	-			600	-	-	180	-	250	250	-	-	-	-
Surface Water	,,,,,,,, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,	ļ		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	······	·····	p		,	T	·		7	,	T	T				,,,,,,,,,, ,,,,,,,,,,,,,,,,,,,,,,,,,,	
Lake	-	-	-	-	-	-	8.03	20,700	33.9	2,100	13,400	57	476	3,570	128	7,400	529	<1	<1	315	315
Ground Water																					
CAWB001	2.00	24.3	4.77	7.5	5,980	3,300	6.84	5,870	15.9	569	3,820	20	126	874	35	1,700	185	<1	<1	32	32
CAWB002	5.30	24.1	5.15	7.5	2,950	1,700	6.88	2,820	10.2	270	1,830	9	60	385	14	795	104	<1	<1	17	17
CAWB003	4.27	23.7	4.71	5.0	8,950	4,850	5.14	8,700	15.3	1,120	5,660	15	263	1,180	46	2,720	315	<1	<1	5	5
CAWB005	1.40	23.5	5.72	5.8	8,120	4,600	5.65	7,920	16.4	985	5,150	12	232	1,180	41	2,460	282	<1	<1	5	5
CAWB006	3.01	24.1	5.58	4.9	8,560	4,750	5.50	8,410	16.6	918	5,470	10	217	1,160	39	2,720	299	<1	<1	7	7
CARC027	1.72	24.3	5.44	6.7	6,750	3,950	7.06	6,330	22.6	393	4,110	22	82	1,030	31	1,870	198	<1	<1	70	70
CARC028	0.00	23.8	6.01	6.3	7,650	4,600	6.50	7,770	18.2	956	5,050	20	220	1,290	47	2,420	258	<1	<1	30	30
Minimum Maximum	0.00 5.30	23.50 24.30	4.71 6.01	4.9 7.5	2,950 8,950	1,700 4,850	5.14 7.06	2,820 8,700	10.2 22.6	270 1,120	1,830 5,660	9 22	60 263	385 1,290	14 47	795 2,720	104 315	-	- -	5 70	5 70
Average Standard Deviation	2.53 1.80	23.97 0.31	5.34 0.49	6.2 1.1	6,994 2,058	3,964 1,139	6.22 0.78	6,831 2,054	16.5 3.7	744 330	4,441 1,337	15 5	171 81	1,014 308	36 11	2,098 697	234 76	-	-	24 23	24 23
						-	Guidelines for systems.				•	ological v	alue syste	ms and hi	ighly distu	ırbed ecos	ystems a	re availabl	e in ANZE	ECC and Al	RMCANZ (

3. NHMRC and ARMCANZ (2011). Australian Drinking Water Guidelines.

Calingiri Copper Project	Water	r Quality																					
Caravel Minerals			EP18	804748 - 23 Ap	oril 2018																		
Date: 13 April 2018					Discol	ed Metals										Nutrients					lo	nic Baland	20
			<u> </u>		Dissol	/ed Metals										Nutrients					10	nic Balanc	;e
Analyte	Aluminium	Arsenic	Cadmium	Chromium	Copper	Lead	Nickel	Selenium	Iron	Mercury	Zinc	Ammonia as N	Fluoride	Nitrite as N	Nitrate as N	Nitrite + Nitrate as N	Total Kjeldahl Nitrogen as N	Total Nitrogen as N	Reactive Phosphorus as P	Total Phosphorus as P	Total Anions	Total Cations	lonic Balance
Unit	0.010	0.004	0.0004	0.001	·	ng/L	0.004	0.01	0.05	0.0001	0.005	0.01	0.1	0.04	0.04	mg/L	T 04	T 0.4	1 004 1	0.01	me	pin	%
LoR Assessment Levels ANZECC (2000) ¹	0.010	0.001	0.0001	0.001	0.001	0.001	0.001	0.01	0.05	0.0001	0.005	0.01	0.1	0.01	0.01	0.01	0.1	0.1	0.01	0.01	0.01	0.01	0.01
Fresh Water ² : 99% Species Protection Level Fresh Water ² : 95% Species Protection Level Fresh Water ² : 90% Species Protection Level Fresh Water ² : 80% Species Protection Level Fresh Water ² : 80% Species Protection Level	0.027 0.055 0.08 0.15	0.008(V) 0.013(V) 0.042(V) 0.140(V)	0.00006 0.0002 0.0004 0.0008	0.00001(VI) 0.001(VI) 0.006(VI) 0.040(VI)	0.0010 - 0.0018 0.0025	0.001 - 0.0056 0.0094	0.008 0.011 0.013 0.017	0.005 0.011 0.018 0.034	-	0.00006 - 0.0019 0.0054	0.0024 0.008 0.015 0.031	0.32 0.9 1.43 2.3		-	0.017 0.7 3.4 170	-	-	-		-	- -	- -	- - -
ADWG (2011) ³																							
Health Value (HV)	-	0.01	0.002	0.05(VI)	-	-	0.2	0.01	-	-	-		-	0.91	11.3	-	-	-	-	-	-	-	-
Aesthetic Value (AV)	0.2	-	-	-	-	-	-	-	-	-	3	-	-	-		-	-	-	-	-	-	-	-
Surface Water		,		,		***************************************		, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	,				,	, ,		,	.	#****	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			,	
Lake	<0.01	<0.001	<0.0001	<0.001	<0.001	<0.001	<0.001	<0.01	<0.05	<0.0001	<0.005	0.36	0.2	<0.01	<0.01	<0.01	3.9	3.9	0.0	0.1	226	200	6.0
Ground Water																							
CAWB001	<0.01	<0.001	<0.0001	<0.001	0.003	<0.001	0.002	<0.01	<0.05	<0.0001	<0.005	0.06	0.3	<0.01	4.07	4.07	0.70	4.80	0.06	0.14	52.4	50.3	2.1
CAWB002	<0.01	<0.001	<0.0001	<0.001	0.002	<0.001	<0.001	<0.01	<0.05	<0.0001	<0.005	0.03	0.2	<0.01	12.30	12.30	2.80	15.10	0.02	<0.05	24.9	22.5	5.1
CAWB003	1.17	<0.001	<0.0001	0.002	0.005	<0.001	0.015	<0.01	0.75	<0.0001	0.065	0.04	0.4	<0.01	<0.01	<0.01	2.10	2.10	12.50	18.60	83.4	74.9	5.4
CAWB005	0.35	<0.001	<0.0001	<0.001	0.026	<0.001	0.007	<0.01	0.21	<0.0001	0.036	0.04	0.2	<0.01	0.88	0.88	0.30	1.20	0.02	0.04	75.4	72.1	2.2
CAWB006	0.02	<0.001	<0.0001	<0.001	0.030	<0.001	0.004	<0.01	<0.05	<0.0001	0.029	0.04	0.3	<0.01	1.53	1.53	0.40	1.90	1.74	6.68	83.1	69.8	8.7
CARC027	<0.01	<0.001	<0.0001	<0.001	0.017	<0.001	0.005	<0.01	<0.05	<0.0001	0.008	0.03	0.7	<0.01	0.80	0.80	0.20	1.00	0.13	0.13	58.3	53.4	4.3
CARC028	<0.01	<0.001	<0.0001	0.001	0.015	<0.001	0.006	<0.01	<0.05	<0.0001	0.011	0.03	0.6	<0.01	1.62	1.62	0.20	1.80	1.72	12.50	74.2	76.4	1.5
Minimum	0.02	-	-	0.001	0.002	-	0.002	-	0.21	-	0.008	0.03	0.2	-	0.80	0.80	0.20	1.00	0.02	0.04	-	-	-
Maximum	1.17	-	-	0.002	0.030	-	0.015	-	0.75	-	0.065	0.06	0.7	-	12.30	12.30	2.80	15.10	12.50	18.60	-	-	-
Average	0.51	-	-	0.002	0.014	-	0.007	-	0.48	-	0.030	0.04	0.4	-	3.53	3.53	0.96	3.99	2.31	6.35	-	-	-
Standard Deviation	0.59	-	-	0.001	0.011	-	0.005	-	0.38	-	0.023	0.01	0.2	-	4.46	4.46	1.05	5.06	4.56	7.81	-	-	-
Notes:	(2000).																						

Saac		Pend	LANGER STREET, STATE OF		THE RESERVE OF THE PARTY OF THE			Sample	38	Car				Sac y A	the contract of the con-	HUARTER STATE	Service of the One	The second second	CONTRACTOR STATE AS	COMPANY THE STATE OF THE STATE
Site			ragon Env	dronmen	ital Solutions			Mobile Phone:	Sugar Control	Car	el van der V		(carel@pendr el 0439-993-90	agonenvironmer 33	ital.com)					
Site	188540 22 53 73 73	Project Manager (PA			Carel van der Westhuize	n			inalyeis/re	port to:		· ·	rei#Inendron	nenvironmental			Envi	ronme	intal Scie	ntists and Engineers
	Calingiri	Job Numbe	er:		PES18011	6208.81		Copy li	wolce to:					nenvironmental						
For Laboratory (Results required by (date):		NA .			54,710		W. 1		ANA	LYSIS REQL	IRED	No.			46.0
Cooler Seal					Comments/Special Ha	andling/Storage	or Disposal		1											
Intact:		(95)	No	N/A	Quote: EP-014-14						1	13/14								
Sample Tempera	ature	\sim			See Notes. Please filter met		***	-	8											<u>Notes:</u> e.g. Highly contaminated samples, ext
Chilled	Part of the Control o	(Yes)	. No	. N/A	See (source, Please Tilles Rietz	a.s				1	Jan di									volume for QC or trace LOF
Sample Informat Lab ID	tion (5 = 8c	il, Sed = Sediment, R = Re				Contain	r Information	1 =	Dissolved											etc.
LAD ID	-	Sample ID	Matrix	Time	Date	Type / Code	Total	¥ ¥	å											
1	<u> </u>	CAWB001	Water		11-Apr-18		3	×	х											
	•	CAWB002	Water		11-Apr-18		3	×	×		l				+	- 		— <u> </u>		Instructions to ALS:
3	•	CAWB003	Water		11-Apr-18		3	×	×	 	-							ntal D	Division	Do not discard any sample without written
ų	•	CAWB005	Water		11-Apr-18	-	3	+ +	- 	 -					4	Perth	rk Orde	r Dofo		instruction.
5		CAWB006	Water		11-Apr-18		3	+	×	 					1				748	Additional instructions,
6		CARC027	Water		11-Apr-18		 	×	×						1	<u> </u>	ГС	רטנ	740	any, will follow on completion of these
7		CARC028	Water				3	_ ×	×	 					1					preliminary tests
8		LAKE	 		11-Apr-18		3	X	×	ļ					1				* 5	· · · · · · · · · · · · · · · · · · ·
- 0		CASS	10		94			•	*						T					
			-					1							†			, (i), (i)	-3. 2	
															t		順位		1 2 E l III	
								1	1						+ .	Telephor	ie: +61-8	-9406 13	in1	
								1	 	 					+					
						 		 	 						1					
						- 		<u> </u>									. 1	1	1	
																				
																		_		
			Reling	uished By:						۹		N :		eceived By	<u></u>	1,1				Manual at any and a
	_	er Westhuizen				Date:	11/04/2018	Name:		Var	WI	2		·	13	141	Q			Method of Shipment
	Pendragon i	Environmental Solutions				Time;		Of:			MI				11	2√L	M			Courier:
ume:						Date:		Name:			()					<u>~</u> ∪^.	<u> </u>	******		22 1 1 2 2 2 2 2
ter Container Codes:	P = Uproseco	and Disease N = N/2 - S-				Time:		Of:						***************************************			···			Other:
VOA Viel HCI Preser	wed; VS = VOA	Vial Substantic Preserved; SG = Su	sec; OKC = Nitric Pre Munic Preserved Amb	sterved ORC; SH ser Glass: H≖HC	= Sodium Hydroxide/Cd Preserved; S = S Spreserved Plastic; HS = HCl preserved S	iodium Hydroxide Pres Specializa bottle: 20	erved Plastic; AG = /	vmber Glass U	ripreserved;				A 1.4 1.			7 - 7 -	7.00			Drop off
Zinc Acetate Preserv	ed Bottle; E = E	DTA Preserved Sottles: ST < Sterile effected on all invoices an	Bottle; ASS/AMD *	Plastic Beg for Ac	of preserved Plastic; HS = HCl preserved S id Sulphate Solls; B = Unpreserved Bag.	-Learning Friedlik 25, 2	Orwanic LiezenAeg 5	anacc; ⊦ ≠ For	maidehyde Pre	served Glass;							ımber of E	Г		1 of 1



SAMPLE RECEIPT NOTIFICATION (SRN)

Work Order : EP1804748

Client : PENDRAGON ENVIRONMENTAL Laboratory : Environmental Division Perth

SOLUTIONS

Contact : MR CAREL VAN DER WESTHUIZEN Contact : Customer Services EP

Address : 310 NEWCASTLE STREET Address : 26 Rigali Way Wangara WA Australia

NORTHBRIDGE WESTERN 6065

AUSTRALIA 6003

E-mail : carel@pendragonenvironmental.co : ALSEnviro.Perth@alsglobal.com

m

Telephone : +61 08 9382 8286 Telephone : +61-8-9406 1301
Facsimile : +61 08 9382 8693 Facsimile : +61-8-9406 1399

Project : PES18011 Page : 1 of 3

 Order number
 :
 Quote number
 : EP2018PENENV0002 (EN/222/17)

 C-O-C number
 : -- QC Level
 : NEPM 2013 B3 & ALS QC Standard

Site : Calingiri

Sampler : Callingin

Dates

Date

Delivery Details

Mode of Delivery : Carrier Security Seal : Intact.

No. of coolers/boxes : 1 Temperature : 9.5 - Ice Bricks present

Receipt Detail : No. of samples received / analysed : 8 / 8

General Comments

• This report contains the following information:

- Sample Container(s)/Preservation Non-Compliances
- Summary of Sample(s) and Requested Analysis
- Proactive Holding Time Report
- Requested Deliverables
- Please see scanned COC for sample discrepencies: extra samples, samples not received etc.
- Please direct any queries related to sample condition / numbering / breakages to Sample Receipt (SamplesPerth@alsenviro.com)
- Analytical work for this work order will be conducted at ALS Environmental Perth.
- Please direct any turnaround / technical queries to the laboratory contact designated above.
- Sample Disposal Aqueous (3 weeks), Solid (2 months) from receipt of samples.
- pH analysis should be conducted within 6 hours of sampling.

: 13-Apr-2018 Issue Date

Page

2 of 3 EP1804748 Amendment 0 Work Order

: PENDRAGON ENVIRONMENTAL SOLUTIONS Client



Sample Container(s)/Preservation Non-Compliances

All comparisons are made against pretreatment/preservation AS, APHA, USEPA standards.

• No sample container / preservation non-compliance exists.

Summary of Sample(s) and Requested Analysis

Some items described below may be part of a laboratory process necessary for the execution of client requested

tasks. Packages may contain additional analyses, such as the determination of moisture content and preparation tasks, that are included in the package. If no sampling time is provided, the sampling time will default 00:00 on the date of sampling. If no sampling date is provided, the sampling date will be assumed by the laboratory and displayed in brackets without a time

Matrix: WATER

component

Laboratory sample	Client sampling date / time	Client sample ID	WATER - Extended	WATER- 11 Metals
EP1804748-001	11-Apr-2018 00:00	CAWB001	✓	✓
EP1804748-002	11-Apr-2018 00:00	CAWB002	✓	✓
EP1804748-003	11-Apr-2018 00:00	CAWB003	✓	✓
EP1804748-004	11-Apr-2018 00:00	CAWB005	✓	✓
EP1804748-005	11-Apr-2018 00:00	CAWB006	✓	✓
EP1804748-006	11-Apr-2018 00:00	CARC027	✓	✓
EP1804748-007	11-Apr-2018 00:00	CARC028	✓	1
EP1804748-008	11-Apr-2018 00:00	LAKE	1	1

Proactive Holding Time Report

The following table summarises breaches of recommended holding times that have occurred prior to samples/instructions being received at the laboratory.

Matrix: WATER

Evaluation: **x** = Holding time breach ; ✓ = Within holding time.

Method		Due for	Due for	Samples R	eceived	Instructions	Received
Client Sample ID(s)	Container	extraction	analysis	Date	Evaluation	Date	Evaluation
EA005-P: pH by PC	Titrator						
CARC027	Clear Plastic Bottle - Natural		11-Apr-2018	13-Apr-2018)£		
CARC028	Clear Plastic Bottle - Natural		11-Apr-2018	13-Apr-2018	*		
CAWB001	Clear Plastic Bottle - Natural		11-Apr-2018	13-Apr-2018	3c		
CAWB002	Clear Plastic Bottle - Natural		11-Apr-2018	13-Apr-2018	*		
CAWB003	Clear Plastic Bottle - Natural		11-Apr-2018	13-Apr-2018	*		
CAWB005	Clear Plastic Bottle - Natural		11-Apr-2018	13-Apr-2018	*		
CAWB006	Clear Plastic Bottle - Natural		11-Apr-2018	13-Apr-2018	*		
LAKE	Clear Plastic Bottle - Natural		11-Apr-2018	13-Apr-2018	*		

Suite B

Water S W-30

: 13-Apr-2018 Issue Date

Page

3 of 3 EP1804748 Amendment 0 Work Order

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS



Requested Deliverables

CADEL	1/ A NI	DED	WEST	TUIIフCI	м
CAREL	·VAN	DEK	VVES	I DUIZEI	v

- *AU Certificate of Analysis - NATA (COA) Email carel@pendragonenvironmental.co - *AU Interpretive QC Report - DEFAULT (Anon QCI Rep) (QCI) Email carel@pendragonenvironmental.co - *AU QC Report - DEFAULT (Anon QC Rep) - NATA (QC) Email carel@pendragonenvironmental.co - A4 - AU Sample Receipt Notification - Environmental HT (SRN) Email carel@pendragonenvironmental.co - A4 - AU Tax Invoice (INV) Email carel@pendragonenvironmental.co - Chain of Custody (CoC) (COC) Email carel@pendragonenvironmental.co - EDI Format - ENMRG (ENMRG) Email carel@pendragonenvironmental.co - EDI Format - ESDAT (ESDAT) Email carel@pendragonenvironmental.co - EDI Format - XTab (XTAB) Email carel@pendragonenvironmental.co



CERTIFICATE OF ANALYSIS

Work Order : EP1804748

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS

Contact : MR CAREL VAN DER WESTHUIZEN

Address : 310 NEWCASTLE STREET

NORTHBRIDGE WESTERN AUSTRALIA 6003

Telephone : +61 08 9382 8286

Project : PES18011

Order number

C-O-C number Sampler Site : Calingiri

: EN/222/17 Quote number No. of samples received

: 8 No. of samples analysed : 8 Page : 1 of 6

> Laboratory : Environmental Division Perth

Contact : Customer Services EP

Address : 26 Rigali Way Wangara WA Australia 6065

: 13-Apr-2018 11:30

Telephone : +61-8-9406 1301 **Date Samples Received**

Date Analysis Commenced : 13-Apr-2018

Accreditation Category

Issue Date : 23-Apr-2018 17:15



This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. This document shall not be reproduced, except in full.

This Certificate of Analysis contains the following information:

- General Comments
- Analytical Results

Additional information pertinent to this report will be found in the following separate attachments: Quality Control Report, QA/QC Compliance Assessment to assist with **Quality Review and Sample Receipt Notification.**

Signatories

Signatories

This document has been electronically signed by the authorized signatories below. Electronic signing is carried out in compliance with procedures specified in 21 CFR Part 11.

Cignatonoc	1 COMOTI	7 toor outlation outlogory
Canhuang Ke	Inorganics Supervisor	Perth Inorganics, Wangara, WA
Efua Wilson	Metals Chemist	Perth Inorganics, Wangara, WA
Indra Astuty	Instrument Chemist	Perth Inorganics, Wangara, WA
Jeremy Truong	Laboratory Manager	Perth Inorganics, Wangara, WA

Position

Page : 2 of 6 Work Order : EP1804748

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS

Project : PES18011

General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

When sampling time information is not provided by the client, sampling dates are shown without a time component. In these instances, the time component has been assumed by the laboratory for processing purposes.

Where a result is required to meet compliance limits the associated uncertainty must be considered. Refer to the ALS Contact for details.

Key: CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.

LOR = Limit of reporting

^ = This result is computed from individual analyte detections at or above the level of reporting

ø = ALS is not NATA accredited for these tests.

~ = Indicates an estimated value.


EA016: Calculated TDS is determined from Electrical conductivity using a conversion factor of 0.65.



Page : 3 of 6 Work Order : EP1804748

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS

Project : PES18011





Page : 4 of 6 Work Order : EP1804748

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS

Project : PES18011






Page : 5 of 6 Work Order : EP1804748

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS

Project : PES18011





Page : 6 of 6
Work Order : EP1804748

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS

Project : PES18011



Sub-Matrix: WATER (Matrix: WATER)		Clie	ent sample ID	CARC027	CARC028	LAKE	
	CI	ient sampli	ng date / time	11-Apr-2018 00:00	11-Apr-2018 00:00	11-Apr-2018 00:00	
Compound	CAS Number	LOR	Unit	EP1804748-006	EP1804748-007	EP1804748-008	
				Result	Result	Result	
EG035F: Dissolved Mercury by FI	MS						
Mercury	7439-97-6	0.0001	mg/L	<0.0001	<0.0001	<0.0001	
EK040P: Fluoride by PC Titrator							
Fluoride	16984-48-8	0.1	mg/L	0.7	0.6	0.2	
EK055G: Ammonia as N by Discre	ete Analyser						
Ammonia as N	7664-41-7	0.01	mg/L	0.03	0.03	0.36	
EK057G: Nitrite as N by Discrete	Analyser						
Nitrite as N	14797-65-0	0.01	mg/L	<0.01	<0.01	<0.01	
EK058G: Nitrate as N by Discrete	Analyser						
Nitrate as N	14797-55-8	0.01	mg/L	0.80	1.62	<0.01	
EK059G: Nitrite plus Nitrate as N	(NOx) by Discrete Ana	lvser					
Nitrite + Nitrate as N		0.01	mg/L	0.80	1.62	<0.01	
EK061G: Total Kjeldahl Nitrogen l	Bv Discrete Analyser						
Total Kjeldahl Nitrogen as N		0.1	mg/L	0.2	0.2	3.9	
EK062G: Total Nitrogen as N (TKI	N + NOx) by Discrete Ar	alvser					
^ Total Nitrogen as N		0.1	mg/L	1.0	1.8	3.9	
EK067G: Total Phosphorus as P b	ov Discrete Analyser						
Total Phosphorus as P		0.01	mg/L	0.13	12.5	0.13	
EK071G: Reactive Phosphorus as	P by discrete analyser						
Reactive Phosphorus as P	14265-44-2		mg/L	0.13	1.72	0.01	
EN055: Ionic Balance							
Total Anions		0.01	meq/L	58.3	74.2	226	
Total Cations		0.01	meq/L	53.4	76.4	200	
Ionic Balance		0.01	%	4.32	1.45	5.97	



QUALITY CONTROL REPORT

· EP1804748 Work Order

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS

Contact : MR CAREL VAN DER WESTHUIZEN

Address : 310 NEWCASTLE STREET

NORTHBRIDGE WESTERN AUSTRALIA 6003

Telephone : +61 08 9382 8286

: PES18011 Project

Order number

C-O-C number Sampler

Site : Calingiri : EN/222/17 Quote number

No. of samples received : 8 : 8 No. of samples analysed

Page : 1 of 7

Date Samples Received

Laboratory : Environmental Division Perth

: Customer Services EP Contact

Address : 26 Rigali Way Wangara WA Australia 6065

Telephone : +61-8-9406 1301

: 13-Apr-2018 **Date Analysis Commenced** : 13-Apr-2018

Issue Date : 23-Apr-2018



This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. This document shall not be reproduced, except in full. This Quality Control Report contains the following information:

- Laboratory Duplicate (DUP) Report; Relative Percentage Difference (RPD) and Acceptance Limits
- Method Blank (MB) and Laboratory Control Spike (LCS) Report; Recovery and Acceptance Limits
- Matrix Spike (MS) Report; Recovery and Acceptance Limits

Signatories

This document has been electronically signed by the authorized signatories below. Electronic signing is carried out in compliance with procedures specified in 21 CFR Part 11.

Signatories	Position	Accreditation Category
Canhuang Ke	Inorganics Supervisor	Perth Inorganics, Wangara, WA
Efua Wilson	Metals Chemist	Perth Inorganics, Wangara, WA
Indra Astuty	Instrument Chemist	Perth Inorganics, Wangara, WA
Jeremy Truong	Laboratory Manager	Perth Inorganics, Wangara, WA

Page : 2 of 7
Work Order : EP1804748

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS

Project : PES18011



General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis. Where the LOR of a reported result differs from standard LOR, this may be due to high

Key: Anonymous = Refers to samples which are not specifically part of this work order but formed part of the QC process lot

CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.

LOR = Limit of reporting

RPD = Relative Percentage Difference

= Indicates failed QC

Laboratory Duplicate (DUP) Report

The quality control term Laboratory Duplicate refers to a randomly selected intralaboratory split. Laboratory duplicates provide information regarding method precision and sample heterogeneity. The permitted ranges for the Relative Percent Deviation (RPD) of Laboratory Duplicates are specified in ALS Method QWI-EN/38 and are dependent on the magnitude of results in comparison to the level of reporting: Result < 10 times LOR: No Limit: Result between 10 and 20 times LOR: 0% - 50%: Result > 20 times LOR: 0% - 20%.

Sub-Matrix: WATER						Laboratory I	Duplicate (DUP) Report		
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	LOR	Unit	Original Result	Duplicate Result	RPD (%)	Recovery Limits (%)
EA005P: pH by PC	Titrator (QC Lot: 15765)	62)							
EP1804712-005	Anonymous	EA005-P: pH Value		0.01	pH Unit	7.64	7.65	0.131	0% - 20%
EP1804741-005	Anonymous	EA005-P: pH Value		0.01	pH Unit	6.66	6.66	0.00	0% - 20%
EA005P: pH by PC	Titrator (QC Lot: 15765)	65)							
EP1804821-008	Anonymous	EA005-P: pH Value		0.01	pH Unit	6.57	6.55	0.305	0% - 20%
EP1804748-008	LAKE	EA005-P: pH Value		0.01	pH Unit	8.03	8.10	0.868	0% - 20%
EA010P: Conductiv	ity by PC Titrator (QC L	_ot: 1576564)							
EP1804741-005	Anonymous	EA010-P: Electrical Conductivity @ 25°C		1	μS/cm	590	593	0.512	0% - 20%
EP1804748-008	LAKE	EA010-P: Electrical Conductivity @ 25°C		1	μS/cm	20700	20800	0.443	0% - 20%
ED037P: Alkalinity I	by PC Titrator (QC Lot:	1576563)							
EP1804741-005	Anonymous	ED037-P: Hydroxide Alkalinity as CaCO3	DMO-210-001	1	mg/L	<1	<1	0.00	No Limit
		ED037-P: Carbonate Alkalinity as CaCO3	3812-32-6	1	mg/L	<1	<1	0.00	No Limit
		ED037-P: Bicarbonate Alkalinity as CaCO3	71-52-3	1	mg/L	24	22	7.97	0% - 20%
		ED037-P: Total Alkalinity as CaCO3		1	mg/L	24	22	7.97	0% - 20%
EP1804748-008	LAKE	ED037-P: Hydroxide Alkalinity as CaCO3	DMO-210-001	1	mg/L	<1	<1	0.00	No Limit
		ED037-P: Carbonate Alkalinity as CaCO3	3812-32-6	1	mg/L	<1	<1	0.00	No Limit
		ED037-P: Bicarbonate Alkalinity as CaCO3	71-52-3	1	mg/L	315	325	3.26	0% - 20%
		ED037-P: Total Alkalinity as CaCO3		1	mg/L	315	325	3.26	0% - 20%
ED041G: Sulfate (Tu	urbidimetric) as SO4 2-	by DA (QC Lot: 1566804)							
EP1804748-007	CARC028	ED041G: Sulfate as SO4 - Turbidimetric	14808-79-8	1	mg/L	258	260	0.881	0% - 20%
EP1804740-002	Anonymous	ED041G: Sulfate as SO4 - Turbidimetric	14808-79-8	1	mg/L	280	275	1.73	0% - 20%
ED045G: Chloride b	y Discrete Analyser (Q	C Lot: 1566805)							
EP1804748-007	CARC028	ED045G: Chloride	16887-00-6	1	mg/L	2420	2460	1.49	0% - 20%
EP1804740-002	Anonymous	ED045G: Chloride	16887-00-6	1	mg/L	395	400	1.32	0% - 20%

Page : 3 of 7
Work Order : EP1804748

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS



Sub-Matrix: WATER						Laboratory	Duplicate (DUP) Report		
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	LOR	Unit	Original Result	Duplicate Result	RPD (%)	Recovery Limits (%)
ED093F: Dissolved	Major Cations (QC Lot	: 1578634) - continued							
EP1804741-004	Anonymous	ED093F: Calcium	7440-70-2	1	mg/L	116	117	1.08	0% - 20%
		ED093F: Magnesium	7439-95-4	1	mg/L	95	95	0.00	0% - 20%
		ED093F: Sodium	7440-23-5	1	mg/L	590	597	1.28	0% - 20%
		ED093F: Potassium	7440-09-7	1	mg/L	6	6	0.00	No Limit
EP1804748-004	CAWB005	ED093F: Calcium	7440-70-2	1	mg/L	12	12	0.00	0% - 50%
		ED093F: Magnesium	7439-95-4	1	mg/L	232	232	0.00	0% - 20%
		ED093F: Sodium	7440-23-5	1	mg/L	1180	1200	1.09	0% - 20%
		ED093F: Potassium	7440-09-7	1	mg/L	41	41	0.00	0% - 20%
G020F: Dissolved	Metals by ICP-MS (QC	Lot: 1578633)							
EP1804741-002	Anonymous	EG020A-F: Cadmium	7440-43-9	0.0001	mg/L	<0.0001	0.0001	0.00	No Limit
	-	EG020A-F: Arsenic	7440-38-2	0.001	mg/L	<0.001	<0.001	0.00	No Limit
		EG020A-F: Chromium	7440-47-3	0.001	mg/L	<0.001	<0.001	0.00	No Limit
		EG020A-F: Copper	7440-50-8	0.001	mg/L	<0.001	<0.001	0.00	No Limit
		EG020A-F: Lead	7439-92-1	0.001	mg/L	<0.001	<0.001	0.00	No Limit
		EG020A-F: Nickel	7440-02-0	0.001	mg/L	0.030	0.032	4.31	0% - 20%
		EG020A-F: Zinc	7440-66-6	0.005	mg/L	0.009	0.008	0.00	No Limit
		EG020A-F: Aluminium	7429-90-5	0.01	mg/L	<0.01	<0.01	0.00	No Limit
		EG020A-F: Selenium	7782-49-2	0.01	mg/L	<0.01	<0.01	0.00	No Limit
		EG020A-F: Iron	7439-89-6	0.05	mg/L	<0.05	<0.05	0.00	No Limit
EP1804752-005	Anonymous	EG020A-F: Cadmium	7440-43-9	0.0001	mg/L	<0.0001	<0.0001	0.00	No Limit
		EG020A-F: Arsenic	7440-38-2	0.001	mg/L	<0.001	<0.001	0.00	No Limit
		EG020A-F: Chromium	7440-47-3	0.001	mg/L	<0.001	<0.001	0.00	No Limit
		EG020A-F: Copper	7440-50-8	0.001	mg/L	0.006	0.006	0.00	No Limit
		EG020A-F: Lead	7439-92-1	0.001	mg/L	<0.001	<0.001	0.00	No Limit
		EG020A-F: Nickel	7440-02-0	0.001	mg/L	0.002	0.002	0.00	No Limit
		EG020A-F: Zinc	7440-66-6	0.005	mg/L	0.010	0.010	0.00	No Limit
		EG020A-F: Aluminium	7429-90-5	0.01	mg/L	0.02	0.02	0.00	No Limit
		EG020A-F: Selenium	7782-49-2	0.01	mg/L	<0.01	<0.01	0.00	No Limit
		EG020A-F: Iron	7439-89-6	0.05	mg/L	<0.05	<0.05	0.00	No Limit
G035F: Dissolved	Mercury by FIMS (QC I	Lot: 1578635)							
EP1804741-008	Anonymous	EG035F: Mercury	7439-97-6	0.0001	mg/L	<0.0001	<0.0001	0.00	No Limit
EP1804748-006	CARC027	EG035F: Mercury	7439-97-6	0.0001	mg/L	<0.0001	<0.0001	0.00	No Limit
	y PC Titrator (QC Lot:								1
EP1804690-009	Anonymous	EK040P: Fluoride	16984-48-8	0.1	mg/L	2.3	2.3	0.00	No Limit
EP1804741-005	Anonymous	EK040P: Fluoride	16984-48-8	0.1	mg/L	<0.1	<0.1	0.00	No Limit
	,		10004 40 0	V. 1	9, =	.0.1	-0.1	0.00	110 Ellilli
EP1804748-008	y PC Titrator (QC Lot: '	· · · · · · · · · · · · · · · · · · ·	16004 40 0	0.1	ma/l	0.2	0.2	0.00	No Limit
		EK040P: Fluoride	16984-48-8	0.1	mg/L	U.Z	0.2	0.00	NO LIMIT
	as N by Discrete Analy	ser (QC Lot: 1567025)							
EP1804745-002	Anonymous	EK055G: Ammonia as N	7664-41-7	0.01	mg/L	19.6	19.2	2.24	0% - 20%

Page : 4 of 7
Work Order : EP1804748

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS



Sub-Matrix: WATER						Laboratory L	Duplicate (DUP) Report		
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	LOR	Unit	Original Result	Duplicate Result	RPD (%)	Recovery Limits (%)
EK055G: Ammonia a	as N by Discrete Analy	yser (QC Lot: 1567025) - continued							
EP1804748-006	CARC027	EK055G: Ammonia as N	7664-41-7	0.01	mg/L	0.03	0.04	0.00	No Limit
EK057G: Nitrite as I	N by Discrete Analyse	r (QC Lot: 1566803)							
EP1804748-007	CARC028	EK057G: Nitrite as N	14797-65-0	0.01	mg/L	<0.01	<0.01	0.00	No Limit
EP1804740-002	Anonymous	EK057G: Nitrite as N	14797-65-0	0.01	mg/L	0.16	0.16	0.00	0% - 50%
EK059G: Nitrite plus	s Nitrate as N (NOx) b	y Discrete Analyser (QC Lot: 1567026)							
EP1804745-002	Anonymous	EK059G: Nitrite + Nitrate as N		0.01	mg/L	24.6	25.2	2.84	0% - 20%
EP1804748-006	CARC027	EK059G: Nitrite + Nitrate as N		0.01	mg/L	0.80	0.80	0.00	0% - 20%
EK061G: Total Kjeld	ahl Nitrogen By Discr	ete Analyser (QC Lot: 1578735)							
EP1804741-005	Anonymous	EK061G: Total Kjeldahl Nitrogen as N		0.1	mg/L	0.6	0.6	0.00	No Limit
EP1804745-003	Anonymous	EK061G: Total Kjeldahl Nitrogen as N		0.1	mg/L	9.2	9.2	0.00	0% - 20%
EK061G: Total Kjeld	ahl Nitrogen By Discr	ete Analyser (QC Lot: 1578737)							
EP1804748-008	LAKE	EK061G: Total Kjeldahl Nitrogen as N		0.1	mg/L	3.9	4.0	2.84	0% - 20%
EK067G: Total Phos	phorus as P by Discre	ete Analyser (QC Lot: 1578734)							
EP1804741-005	Anonymous	EK067G: Total Phosphorus as P		0.01	mg/L	0.03	0.02	51.1	No Limit
EP1804745-003	Anonymous	EK067G: Total Phosphorus as P		0.01	mg/L	0.04	0.05	0.00	No Limit
EK067G: Total Phos	phorus as P by Discre	ete Analyser (QC Lot: 1578736)							
EP1804776-004	Anonymous	EK067G: Total Phosphorus as P		0.01	mg/L	<0.01	0.02	0.00	No Limit
EP1804748-008	LAKE	EK067G: Total Phosphorus as P		0.01	mg/L	0.13	0.12	0.00	0% - 50%
EK071G: Reactive P	hosphorus as P by dis	screte analyser (QC Lot: 1566802)							
EP1804748-007	CARC028	EK071G: Reactive Phosphorus as P	14265-44-2	0.01	mg/L	1.72	1.72	0.00	0% - 20%
EP1804740-002	Anonymous	EK071G: Reactive Phosphorus as P	14265-44-2	0.01	mg/L	0.31	0.31	0.00	0% - 20%

Page : 5 of 7

Work Order : EP1804748

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS

Project : PES18011



Method Blank (MB) and Laboratory Control Spike (LCS) Report

The quality control term Method / Laboratory Blank refers to an analyte free matrix to which all reagents are added in the same volumes or proportions as used in standard sample preparation. The purpose of this QC parameter is to monitor potential laboratory contamination. The quality control term Laboratory Control Spike (LCS) refers to a certified reference material, or a known interference free matrix spiked with target analytes. The purpose of this QC parameter is to monitor method precision and accuracy independent of sample matrix. Dynamic Recovery Limits are based on statistical evaluation of processed LCS.

Sub-Matrix: WATER			Method Blank (MB)		Laboratory Control Spike (LC	S) Report	
			Report	Spike	Spike Recovery (%)	Recovery	Limits (%)
Method: Compound CAS Nur	nber LOR	Unit	Result	Concentration	LCS	Low	High
EA005P: pH by PC Titrator (QCLot: 1576562)							
EA005-P: pH Value		pH Unit		4 pH Unit	100	99	102
				7 pH Unit	99.8	99	102
EA005P: pH by PC Titrator (QCLot: 1576565)							
EA005-P: pH Value		pH Unit		4 pH Unit	100	99	102
				7 pH Unit	99.8	99	102
EA010P: Conductivity by PC Titrator (QCLot: 1576564)							
EA010-P: Electrical Conductivity @ 25°C	1	μS/cm	<1	24800 μS/cm	95.3	95	105
ED037P: Alkalinity by PC Titrator (QCLot: 1576563)							
ED037-P: Hydroxide Alkalinity as CaCO3 DMO-210	-00 1	mg/L	<1				
DIVIO-210	1		·				
ED037-P: Carbonate Alkalinity as CaCO3 3812-3		mg/L	<1				
ED037-P: Bicarbonate Alkalinity as CaCO3 71-5	2-3 1	mg/L	<1				
ED037-P: Total Alkalinity as CaCO3	1	mg/L	<1	20 mg/L	102	76	126
			<1	200 mg/L	96.4	90	106
ED041G: Sulfate (Turbidimetric) as SO4 2- by DA (QCLot: 1566804)							
ED041G: Sulfate as SO4 - Turbidimetric 14808-7	9-8 1	mg/L	<1	25 mg/L	105	89	113
		J	<1	100 mg/L	95.6	79	121
ED045G: Chloride by Discrete Analyser (QCLot: 1566805)							
ED045G: Chloride by Discrete Analyser (4025t: 1505655)	0-6 1	mg/L	<1	10 mg/L	104	84	120
EB0400. Official		9-=	<1	1000 mg/L	98.8	84	110
ED093F: Dissolved Major Cations (QCLot: 1578634)							I .
ED093F: Dissolved Major Cattoris (QCEOt. 1578654) FD093F: Calcium 7440-7	0-2 1	mg/L	<1	50 mg/L	95.1	91	109
ED093F: Magnesium 7439-9		mg/L	<1	50 mg/L	95.3	90	108
ED093F: Sodium 7440-2		mg/L	<1	50 mg/L	105	87	111
ED093F: Potassium 7440-0		mg/L	<1	50 mg/L	94.5	90	110
25 CONTINUES OF THE PROPERTY O					••		
EG020F: Dissolved Metals by ICP-MS (QCLot: 1578633) EG020A-F: Aluminium 7429-9	0-5 0.01	mg/L	<0.01	0.5 mg/L	97.9	84	120
		mg/L	<0.01	0.5 mg/L	97.3	84	120
EG020A-F: Arsenic 7440-3 EG020A-F: Cadmium 7440-4			<0.001	0.1 mg/L	96.7	86	120
EG020A-F: Cadmium 7440-4		mg/L	<0.001	0.1 mg/L	94.1	85	120
EG020A-F: Corporer 7440-5		mg/L	<0.001	0.1 mg/L	91.7	84	120
EG020A-F: Copper 7440-5		mg/L	<0.001	0.1 mg/L	96.1	85	120
EG020A-F: Nickel 7440-0		mg/L	<0.001	0.1 mg/L	101	84	120
EG020A-F: Nickel 7440-0		mg/L	<0.01	0.1 mg/L	98.2	88	120
EGUZUA-F. SEIEIIIUIII	0.01	ilig/∟	70.01	0.1 mg/L	30.2		120

Page : 6 of 7
Work Order : EP1804748

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS

Project : PES18011



Sub-Matrix: WATER			Method Blank (MB)		Laboratory Control Spike (LCS	S) Report	
			Report	Spike	Spike Recovery (%)	Recovery	Limits (%)
Method: Compound CAS Number	er LOR	Unit	Result	Concentration	LCS	Low	High
EG020F: Dissolved Metals by ICP-MS (QCLot: 1578633) - continued							
EG020A-F: Zinc 7440-66-	6 0.005	mg/L	<0.005	0.1 mg/L	101	89	120
EG020A-F: Iron 7439-89-	6 0.05	mg/L	<0.05	0.5 mg/L	114	84	120
EG035F: Dissolved Mercury by FIMS (QCLot: 1578635)							
EG035F: Mercury 7439-97-	6 0.0001	mg/L	<0.0001	0.01 mg/L	102	92	116
EK040P: Fluoride by PC Titrator (QCLot: 1576555)							
EK040P: Fluoride 16984-48-	8 0.1	mg/L	<0.1	5 mg/L	102	86	116
EK040P: Fluoride by PC Titrator (QCLot: 1576566)							
EK040P: Fluoride 16984-48-	8 0.1	mg/L	<0.1	5 mg/L	104	86	116
EK055G: Ammonia as N by Discrete Analyser (QCLot: 1567025)							
EK055G: Ammonia as N 7664-41	7 0.01	mg/L	<0.01	1 mg/L	99.6	87	115
EK057G: Nitrite as N by Discrete Analyser (QCLot: 1566803)							
EK057G: Nitrite as N 14797-65	0.01	mg/L	<0.01	0.5 mg/L	101	86	112
EK059G: Nitrite plus Nitrate as N (NOx) by Discrete Analyser (QCLo	: 1567026)						
EK059G: Nitrite + Nitrate as N	0.01	mg/L	<0.01	0.5 mg/L	101	92	112
EK061G: Total Kjeldahl Nitrogen By Discrete Analyser (QCLot: 15787	35)						
EK061G: Total Kjeldahl Nitrogen as N	- 0.1	mg/L	<0.1	10 mg/L	95.3	82	110
EK061G: Total Kjeldahl Nitrogen By Discrete Analyser (QCLot: 15787	37)						
EK061G: Total Kjeldahl Nitrogen as N	- 0.1	mg/L	<0.1	10 mg/L	89.0	82	110
EK067G: Total Phosphorus as P by Discrete Analyser (QCLot: 15787)	4)						
EK067G: Total Phosphorus as P	- 0.01	mg/L	<0.01	4.42 mg/L	92.2	70	130
EK067G: Total Phosphorus as P by Discrete Analyser (QCLot: 15787)	6)						
EK067G: Total Phosphorus as P	0.01	mg/L	<0.01	4.42 mg/L	92.6	70	130
EK071G: Reactive Phosphorus as P by discrete analyser (QCLot: 156	6802)						
EK071G: Reactive Phosphorus as P 14265-44	2 0.01	mg/L	<0.01	0.5 mg/L	104	87	115

Matrix Spike (MS) Report

The quality control term Matrix Spike (MS) refers to an intralaboratory split sample spiked with a representative set of target analytes. The purpose of this QC parameter is to monitor potential matrix effects on analyte recoveries. Static Recovery Limits as per laboratory Data Quality Objectives (DQOs). Ideal recovery ranges stated may be waived in the event of sample matrix interference.

Sub-Matrix: WATER				Ма	trix Spike (MS) Repor	t	
				Spike	SpikeRecovery(%)	Recovery Li	imits (%)
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	Concentration	MS	Low	High
ED041G: Sulfate (T	urbidimetric) as SO4 2- by DA (QCLot: 1566804)						
EP1804740-001	Anonymous	ED041G: Sulfate as SO4 - Turbidimetric	14808-79-8	100 mg/L	70.5	70	130
ED045G: Chloride l	by Discrete Analyser (QCLot: 1566805)						
EP1804740-001	Anonymous	ED045G: Chloride	16887-00-6	1000 mg/L	92.8	70	130

Page : 7 of 7
Work Order : EP1804748

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS



Sub-Matrix: WATER				M	atrix Spike (MS) Report		
				Spike	SpikeRecovery(%)	Recovery L	imits (%)
Laboratory sample ID	Client sample ID	Method: Compound	CAS Number	Concentration	MS	Low	High
EG020F: Dissolved	d Metals by ICP-MS (QCLot: 1578633)						
EP1804741-003	Anonymous	EG020A-F: Arsenic	7440-38-2	0.2 mg/L	100	70	130
		EG020A-F: Cadmium	7440-43-9	0.05 mg/L	98.1	70	130
		EG020A-F: Chromium	7440-47-3	0.2 mg/L	97.6	70	130
		EG020A-F: Copper	7440-50-8	0.2 mg/L	94.8	70	130
		EG020A-F: Lead	7439-92-1	0.2 mg/L	95.0	70	130
		EG020A-F: Nickel	7440-02-0	0.2 mg/L	103	70	130
		EG020A-F: Zinc	7440-66-6	0.2 mg/L	101	70	130
EG035F: Dissolved	d Mercury by FIMS (QCLot: 1578635)						
EP1804741-009	Anonymous	EG035F: Mercury	7439-97-6	0.01 mg/L	88.3	70	130
EK040P: Fluoride	by PC Titrator (QCLot: 1576555)						
EP1804690-007	Anonymous	EK040P: Fluoride	16984-48-8	49 mg/L	84.9	70	130
EK040P: Fluoride	by PC Titrator (QCLot: 1576566)						
EP1804779-001	Anonymous	EK040P: Fluoride	16984-48-8	4.9 mg/L	121	70	130
EK055G: Ammonia	a as N by Discrete Analyser (QCLot: 1567025)						
EP1804745-001	Anonymous	EK055G: Ammonia as N	7664-41-7	1 mg/L	# Not Determined	70	130
EK057G: Nitrite as	s N by Discrete Analyser (QCLot: 1566803)						
EP1804740-001	Anonymous	EK057G: Nitrite as N	14797-65-0	0.5 mg/L	106	70	130
EK059G: Nitrite pl	lus Nitrate as N (NOx) by Discrete Analyser (QCLot: 15	667026)					
EP1804745-001	Anonymous	EK059G: Nitrite + Nitrate as N		0.5 mg/L	# Not Determined	70	130
EK061G: Total Kje	Idahl Nitrogen By Discrete Analyser (QCLot: 1578735)						
EP1804741-006	Anonymous	EK061G: Total Kjeldahl Nitrogen as N		5 mg/L	99.8	70	130
EK061G: Total Kje	Idahl Nitrogen By Discrete Analyser (QCLot: 1578737)						
EP1804748-008	LAKE	EK061G: Total Kjeldahl Nitrogen as N		5 mg/L	101	70	130
EK067G: Total Pho	osphorus as P by Discrete Analyser (QCLot: 1578734)						
EP1804741-006	Anonymous	EK067G: Total Phosphorus as P		1 mg/L	98.3	70	130
EK067G: Total Pho	osphorus as P by Discrete Analyser (QCLot: 1578736)						
EP1804748-008	LAKE	EK067G: Total Phosphorus as P		1 mg/L	101	70	130
EK071G: Reactive	Phosphorus as P by discrete analyser (QCLot: 156680						
EP1804740-001	Anonymous	EK071G: Reactive Phosphorus as P	14265-44-2	0.5 mg/L	113	70	130



QA/QC Compliance Assessment to assist with Quality Review

Work Order : **EP1804748** Page : 1 of 9

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS Laboratory : Environmental Division Perth

 Contact
 : MR CAREL VAN DER WESTHUIZEN
 Telephone
 : +61-8-9406 1301

 Project
 : PES18011
 Date Samples Received
 : 13-Apr-2018

 Site
 : Calingiri
 Issue Date
 : 23-Apr-2018

Sampler :--- No. of samples received : 8
Order number : No. of samples analysed : 8

This report is automatically generated by the ALS LIMS through interpretation of the ALS Quality Control Report and several Quality Assurance parameters measured by ALS. This automated reporting highlights any non-conformances, facilitates faster and more accurate data validation and is designed to assist internal expert and external Auditor review. Many components of this report contribute to the overall DQO assessment and reporting for guideline compliance.

Brief method summaries and references are also provided to assist in traceability.

Summary of Outliers

Outliers: Quality Control Samples

This report highlights outliers flagged in the Quality Control (QC) Report.

- NO Method Blank value outliers occur.
- NO Duplicate outliers occur.
- NO Laboratory Control outliers occur.
- Matrix Spike outliers exist please see following pages for full details.
- For all regular sample matrices, NO surrogate recovery outliers occur.

Outliers: Analysis Holding Time Compliance

• Analysis Holding Time Outliers exist - please see following pages for full details.

Outliers: Frequency of Quality Control Samples

NO Quality Control Sample Frequency Outliers exist.

Page : 2 of 9 Work Order : EP1804748

Client PENDRAGON ENVIRONMENTAL SOLUTIONS

Project : PES18011

Outliers: Quality Control Samples

Duplicates, Method Blanks, Laboratory Control Samples and Matrix Spikes

Matrix: WATER

Compound Group Name	Laboratory Sample ID	Client Sample ID	Analyte	CAS Number	Data	Limits	Comment
Matrix Spike (MS) Recoveries							
EK055G: Ammonia as N by Discrete Analyser	EP1804745001	Anonymous	Ammonia as N	7664-41-7	Not		MS recovery not determined,
					Determined		background level greater than or
							equal to 4x spike level.
EK059G: Nitrite plus Nitrate as N (NOx) by Discrete A	r EP1804745001	Anonymous	Nitrite + Nitrate as N		Not		MS recovery not determined,
					Determined		background level greater than or
							equal to 4x spike level.

Outliers: Analysis Holding Time Compliance

Matrix: WATER

Wattik: WATER							
Method		E	extraction / Preparation			Analysis	
Container / Client Sample ID(s)		Date extracted	Due for extraction	Days	Date analysed	Due for analysis	Days
				overdue			overdue
EA005P: pH by PC Titrator							
Clear Plastic Bottle - Natural							
CAWB001,	CAWB002,				18-Apr-2018	11-Apr-2018	7
CAWB003,	CAWB005,						
CAWB006,	CARC027,						
CARC028,	LAKE						

Analysis Holding Time Compliance

If samples are identified below as having been analysed or extracted outside of recommended holding times, this should be taken into consideration when interpreting results.

This report summarizes extraction / preparation and analysis times and compares each with ALS recommended holding times (referencing USEPA SW 846, APHA, AS and NEPM) based on the sample container provided. Dates reported represent first date of extraction or analysis and preclude subsequent dilutions and reruns. A listing of breaches (if any) is provided herein.

Holding time for leachate methods (e.g. TCLP) vary according to the analytes reported. Assessment compares the leach date with the shortest analyte holding time for the equivalent soil method. These are: organics 14 days, mercury 28 days & other metals 180 days. A recorded breach does not guarantee a breach for all non-volatile parameters.

Holding times for <u>VOC in soils</u> vary according to analytes of interest. Vinyl Chloride and Styrene holding time is 7 days; others 14 days. A recorded breach does not guarantee a breach for all VOC analytes and should be verified in case the reported breach is a false positive <u>or</u> Vinyl Chloride and Styrene are not key analytes of interest/concern.

Matrix: WATER

Evaluation: × = Holding time breach ; ✓ = Wi	itnin nolaina l	time.
--	-----------------	-------

IVIALITA: WATER					Lvaluation	Holding time	breach, • - with	ir noluling time
Method		Sample Date	Ex	traction / Preparation			Analysis	
Container / Client Sample ID(s)			Date extracted	Due for extraction	Evaluation	Date analysed	Due for analysis	Evaluation
EA005P: pH by PC Titrator								
Clear Plastic Bottle - Natural (EA005-P)								
CAWB001,	CAWB002,	11-Apr-2018				18-Apr-2018	11-Apr-2018	×
CAWB003,	CAWB005,							
CAWB006,	CARC027,							
CARC028,	LAKE							

Page : 3 of 9
Work Order : EP1804748

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS



Matrix: WATER					Evaluation	n: × = Holding time	breach; ✓ = With	n holding tim
Method		Sample Date	E	xtraction / Preparation			Analysis	
Container / Client Sample ID(s)			Date extracted	Due for extraction	Evaluation	Date analysed	Due for analysis	Evaluation
EA006: Sodium Adsorption Ratio (SAR)								
Clear HDPE (U-T ORC) - Filtered; Lab-acidifie								
CAWB001,	CAWB002,	11-Apr-2018				19-Apr-2018	09-May-2018	✓
CAWB003,	CAWB005,							
CAWB006,	CARC027,							
CARC028,	LAKE							
EA010P: Conductivity by PC Titrator								
Clear Plastic Bottle - Natural (EA010-P)								
CAWB001,	CAWB002,	11-Apr-2018				18-Apr-2018	09-May-2018	✓
CAWB003,	CAWB005,							
CAWB006,	CARC027,							
CARC028,	LAKE							
EA065: Total Hardness as CaCO3								
Clear HDPE (U-T ORC) - Filtered; Lab-acidifie	d (ED093F)							
CAWB001,	CAWB002,	11-Apr-2018				19-Apr-2018	09-May-2018	✓
CAWB003,	CAWB005,							,
CAWB006,	CARC027,							
CARC028,	LAKE							
ED037P: Alkalinity by PC Titrator								
Clear Plastic Bottle - Natural (ED037-P)						I		
CAWB001,	CAWB002,	11-Apr-2018				18-Apr-2018	25-Apr-2018	✓
CAWB003,	CAWB005,							,
CAWB006,	CARC027,							
CARC028.	LAKE							
ED041G: Sulfate (Turbidimetric) as SO4 2- by								
Clear Plastic Bottle - Natural (ED041G)	y DA							
CAWB001,	CAWB002,	11-Apr-2018				13-Apr-2018	09-May-2018	1
CAWB003,	CAWB005,							,
CAWB006,	CARC027,							
l · · · · · · · · · · · · · · · · · · ·								
CARC028,	LAKE							
ED045G: Chloride by Discrete Analyser							I	
Clear Plastic Bottle - Natural (ED045G)	CAMPOOS	11-Apr-2018				13-Apr-2018	09-May-2018	
CAWB001,	CAWB002,	11-Apr-2016	_ 			13-Apr-2010	03-111ay-2010	✓
CAWB003,	CAWB005,							
CAWB006,	CARC027,							
CARC028,	LAKE							
ED093F: Dissolved Major Cations								
Clear HDPE (U-T ORC) - Filtered; Lab-acidifie						40.4	00 14- 0045	
CAWB001,	CAWB002,	11-Apr-2018				19-Apr-2018	09-May-2018	✓
CAWB003,	CAWB005,							
CAWB006,	CARC027,							
CARC028,	LAKE							

Page : 4 of 9 Work Order : EP1804748

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS



Matrix: WATER					Evaluation	n: × = Holding time	breach ; ✓ = With	in holding time
Method		Sample Date	Extraction / Preparation			Analysis		
Container / Client Sample ID(s)			Date extracted	Due for extraction	Evaluation	Date analysed	Due for analysis	Evaluation
EG020F: Dissolved Metals by ICP-MS								
Clear HDPE (U-T ORC) - Filtered; Lab-acidified (EG020								
CAWB001,	CAWB002,	11-Apr-2018				19-Apr-2018	08-Oct-2018	✓
CAWB003,	CAWB005,							
CAWB006,	CARC027,							
CARC028,	LAKE							
EG035F: Dissolved Mercury by FIMS								
Clear HDPE (U-T ORC) - Filtered; Lab-acidified (EG035								
CAWB001,	CAWB002,	11-Apr-2018				19-Apr-2018	09-May-2018	✓
CAWB003,	CAWB005,							
CAWB006,	CARC027,							
CARC028,	LAKE							
EK040P: Fluoride by PC Titrator								
Clear Plastic Bottle - Natural (EK040P)								
CAWB001,	CAWB002,	11-Apr-2018				18-Apr-2018	09-May-2018	✓
CAWB003,	CAWB005,							
CAWB006,	CARC027,							
CARC028,	LAKE							
EK055G: Ammonia as N by Discrete Analyser								
Clear Plastic Bottle - Sulfuric Acid (EK055G)								
CAWB001,	CAWB002,	11-Apr-2018				13-Apr-2018	09-May-2018	✓
CAWB003,	CAWB005,							
CAWB006,	CARC027,							
CARC028,	LAKE							
EK057G: Nitrite as N by Discrete Analyser								
Clear Plastic Bottle - Natural (EK057G)								
CAWB001,	CAWB002,	11-Apr-2018				13-Apr-2018	13-Apr-2018	✓
CAWB003,	CAWB005,							
CAWB006,	CARC027,							
CARC028,	LAKE							
EK059G: Nitrite plus Nitrate as N (NOx) by Discrete	Analyser							
Clear Plastic Bottle - Sulfuric Acid (EK059G)								
CAWB001,	CAWB002,	11-Apr-2018				13-Apr-2018	09-May-2018	✓
CAWB003,	CAWB005,							
CAWB006.	CARC027,							
CARC028,	LAKE							
EK061G: Total Kjeldahl Nitrogen By Discrete Analyse								
Clear Plastic Bottle - Sulfuric Acid (EK061G)	·	1						
CAWB001,	CAWB002,	11-Apr-2018	19-Apr-2018	09-May-2018	1	19-Apr-2018	09-May-2018	✓
CAWB001,	CAWB005,							,
CAWB003, CAWB006,	CARC027,							
CARC028,	LAKE							

Page : 5 of 9
Work Order : EP1804748

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS



Matrix: WATER					Evaluation	: × = Holding time	breach; ✓ = Withi	n holding time
Method		Sample Date	E	traction / Preparation			Analysis	
Container / Client Sample ID(s)			Date extracted	Due for extraction	Evaluation	Date analysed	Due for analysis	Evaluation
EK067G: Total Phosphorus as P by Dis	crete Analyser							
Clear Plastic Bottle - Sulfuric Acid (EK06	67G)							
CAWB001,	CAWB002,	11-Apr-2018	19-Apr-2018	09-May-2018	✓	19-Apr-2018	09-May-2018	✓
CAWB003,	CAWB005,							
CAWB006,	CARC027,							
CARC028,	LAKE							
EK071G: Reactive Phosphorus as P by	discrete analyser							
Clear Plastic Bottle - Natural (EK071G)								
CAWB001,	CAWB002,	11-Apr-2018				13-Apr-2018	13-Apr-2018	✓
CAWB003,	CAWB005,							
CAWB006,	CARC027,							
CARC028,	LAKE							

Page : 6 of 9 Work Order EP1804748

PENDRAGON ENVIRONMENTAL SOLUTIONS Client

PES18011 Project



Quality Control Parameter Frequency Compliance

The following report summarises the frequency of laboratory QC samples analysed within the analytical lot(s) in which the submitted sample(s) was(were) processed. Actual rate should be greater than or equal to the expected rate. A listing of breaches is provided in the Summary of Outliers.

Matrix: WATER				Evaluation	n: 🗴 = Quality Co	ntrol frequency i	not within specification; ✓ = Quality Control frequency within specification
Quality Control Sample Type		Сс	ount		Rate (%)		Quality Control Specification
Analytical Methods	Method	OC	Reaular	Actual	Expected	Evaluation	
Laboratory Duplicates (DUP)							
Alkalinity by PC Titrator	ED037-P	2	20	10.00	10.00	✓	NEPM 2013 B3 & ALS QC Standard
Ammonia as N by Discrete analyser	EK055G	2	20	10.00	10.00	✓	NEPM 2013 B3 & ALS QC Standard
Chloride by Discrete Analyser	ED045G	2	17	11.76	10.00	✓	NEPM 2013 B3 & ALS QC Standard
Conductivity by PC Titrator	EA010-P	2	20	10.00	10.00	✓	NEPM 2013 B3 & ALS QC Standard
Dissolved Mercury by FIMS	EG035F	2	13	15.38	10.00	✓	NEPM 2013 B3 & ALS QC Standard
Dissolved Metals by ICP-MS - Suite A	EG020A-F	2	20	10.00	10.00	✓	NEPM 2013 B3 & ALS QC Standard
Fluoride by PC Titrator	EK040P	3	24	12.50	10.00	✓	NEPM 2013 B3 & ALS QC Standard
Major Cations - Dissolved	ED093F	2	15	13.33	10.00	✓	NEPM 2013 B3 & ALS QC Standard
Nitrite and Nitrate as N (NOx) by Discrete Analyser	EK059G	2	20	10.00	10.00	✓	NEPM 2013 B3 & ALS QC Standard
Nitrite as N by Discrete Analyser	EK057G	2	15	13.33	10.00	✓	NEPM 2013 B3 & ALS QC Standard
pH by PC Titrator	EA005-P	4	37	10.81	10.00	✓	NEPM 2013 B3 & ALS QC Standard
Reactive Phosphorus as P-By Discrete Analyser	EK071G	2	12	16.67	10.00	✓	NEPM 2013 B3 & ALS QC Standard
Sulfate (Turbidimetric) as SO4 2- by Discrete Analyser	ED041G	2	17	11.76	10.00	✓	NEPM 2013 B3 & ALS QC Standard
Total Kjeldahl Nitrogen as N By Discrete Analyser	EK061G	3	28	10.71	10.00	✓	NEPM 2013 B3 & ALS QC Standard
Total Phosphorus as P By Discrete Analyser	EK067G	4	33	12.12	10.00	✓	NEPM 2013 B3 & ALS QC Standard
Laboratory Control Samples (LCS)							
Alkalinity by PC Titrator	ED037-P	2	20	10.00	10.00	✓	NEPM 2013 B3 & ALS QC Standard
Ammonia as N by Discrete analyser	EK055G	1	20	5.00	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Chloride by Discrete Analyser	ED045G	2	17	11.76	10.00	✓	NEPM 2013 B3 & ALS QC Standard
Conductivity by PC Titrator	EA010-P	1	20	5.00	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Dissolved Mercury by FIMS	EG035F	1	13	7.69	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Dissolved Metals by ICP-MS - Suite A	EG020A-F	1	20	5.00	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Fluoride by PC Titrator	EK040P	2	24	8.33	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Major Cations - Dissolved	ED093F	1	15	6.67	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Nitrite and Nitrate as N (NOx) by Discrete Analyser	EK059G	1	20	5.00	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Nitrite as N by Discrete Analyser	EK057G	1	15	6.67	5.00	✓	NEPM 2013 B3 & ALS QC Standard
pH by PC Titrator	EA005-P	4	37	10.81	10.00	✓	NEPM 2013 B3 & ALS QC Standard
Reactive Phosphorus as P-By Discrete Analyser	EK071G	1	12	8.33	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Sulfate (Turbidimetric) as SO4 2- by Discrete Analyser	ED041G	2	17	11.76	10.00	✓	NEPM 2013 B3 & ALS QC Standard
Total Kjeldahl Nitrogen as N By Discrete Analyser	EK061G	2	28	7.14	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Total Phosphorus as P By Discrete Analyser	EK067G	2	33	6.06	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Method Blanks (MB)							
Alkalinity by PC Titrator	ED037-P	1	20	5.00	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Ammonia as N by Discrete analyser	EK055G	1	20	5.00	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Chloride by Discrete Analyser	ED045G	1	17	5.88	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Conductivity by PC Titrator	EA010-P	1	20	5.00	5.00	✓	NEPM 2013 B3 & ALS QC Standard

Page : 7 of 9
Work Order : EP1804748

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS



Matrix: WATER				Evaluation	n: × = Quality Co	entrol frequency r	not within specification; ✓ = Quality Control frequency within specification
Quality Control Sample Type		Count		Rate (%)			Quality Control Specification
Analytical Methods	Method	QC	Reaular	Actual	Expected	Evaluation	
Method Blanks (MB) - Continued							
Dissolved Mercury by FIMS	EG035F	1	13	7.69	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Dissolved Metals by ICP-MS - Suite A	EG020A-F	1	20	5.00	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Fluoride by PC Titrator	EK040P	2	24	8.33	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Major Cations - Dissolved	ED093F	1	15	6.67	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Nitrite and Nitrate as N (NOx) by Discrete Analyser	EK059G	1	20	5.00	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Nitrite as N by Discrete Analyser	EK057G	1	15	6.67	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Reactive Phosphorus as P-By Discrete Analyser	EK071G	1	12	8.33	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Sulfate (Turbidimetric) as SO4 2- by Discrete Analyser	ED041G	1	17	5.88	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Total Kjeldahl Nitrogen as N By Discrete Analyser	EK061G	2	28	7.14	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Total Phosphorus as P By Discrete Analyser	EK067G	2	33	6.06	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Matrix Spikes (MS)							
Ammonia as N by Discrete analyser	EK055G	1	20	5.00	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Chloride by Discrete Analyser	ED045G	1	17	5.88	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Dissolved Mercury by FIMS	EG035F	1	13	7.69	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Dissolved Metals by ICP-MS - Suite A	EG020A-F	1	20	5.00	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Fluoride by PC Titrator	EK040P	2	24	8.33	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Nitrite and Nitrate as N (NOx) by Discrete Analyser	EK059G	1	20	5.00	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Nitrite as N by Discrete Analyser	EK057G	1	15	6.67	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Reactive Phosphorus as P-By Discrete Analyser	EK071G	1	12	8.33	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Sulfate (Turbidimetric) as SO4 2- by Discrete Analyser	ED041G	1	17	5.88	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Total Kjeldahl Nitrogen as N By Discrete Analyser	EK061G	2	28	7.14	5.00	✓	NEPM 2013 B3 & ALS QC Standard
Total Phosphorus as P By Discrete Analyser	EK067G	2	33	6.06	5.00	✓	NEPM 2013 B3 & ALS QC Standard

Page : 8 of 9
Work Order : EP1804748

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS

Project : PES18011



Brief Method Summaries

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the US EPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request. The following report provides brief descriptions of the analytical procedures employed for results reported in the Certificate of Analysis. Sources from which ALS methods have been developed are provided within the Method Descriptions.

Analytical Methods	Method	Matrix	Method Descriptions	
pH by PC Titrator	EA005-P	WATER	In house: Referenced to APHA 4500 H+ B. This procedure determines pH of water samples by automated ISE. This method is compliant with NEPM (2013) Schedule B(3)	
Conductivity by PC Titrator	EA010-P	WATER	In house: Referenced to APHA 2510 B. This procedure determines conductivity by automated ISE. This method is compliant with NEPM (2013) Schedule B(3)	
Calculated TDS (from Electrical Conductivity)	EA016	WATER	In house: Calculation from Electrical Conductivity (APHA 2510 B) using a conversion factor specified in the analytical report. This method is compliant with NEPM (2013) Schedule B(3)	
Alkalinity by PC Titrator	ED037-P	WATER	In house: Referenced to APHA 2320 B This procedure determines alkalinity by automated measurement (e.g. PC Titrate) using pH 4.5 for indicating the total alkalinity end-point. This method is compliant with NEPM (2013) Schedule B(3)	
Sulfate (Turbidimetric) as SO4 2- by Discrete Analyser	ED041G	WATER	In house: Referenced to APHA 4500-SO4. Dissolved sulfate is determined in a 0.45um filtered sample. Sulfate ions are converted to a barium sulfate suspension in an acetic acid medium with barium chloride. Light absorbance of the BaSO4 suspension is measured by a photometer and the SO4-2 concentration is determined by comparison of the reading with a standard curve. This method is compliant with NEPM (2013) Schedule B(3)	
Chloride by Discrete Analyser	ED045G	WATER	In house: Referenced to APHA 4500 CI - G.The thiocyanate ion is liberated from mercuric thiocyanate through sequestration of mercury by the chloride ion to form non-ionised mercuric chloride.in the presence of ferric ions the librated thiocynate forms highly-coloured ferric thiocynate which is measured at 480 nm APHA 21st edition seal method 2 017-1-L april 2003	
Major Cations - Dissolved	ED093F	WATER	In house: Referenced to APHA 3120 and 3125; USEPA SW 846 - 6010 and 6020; Cations are determined by either ICP-AES or ICP-MS techniques. This method is compliant with NEPM (2013) Schedule B(3) Sodium Adsorption Ratio is calculated from Ca, Mg and Na which determined by ALS in house method QWI-EN/ED093F. This method is compliant with NEPM (2013) Schedule B(3) Hardness parameters are calculated based on APHA 2340 B. This method is compliant with NEPM (2013) Schedule B(3)	
Dissolved Metals by ICP-MS - Suite A	EG020A-F	WATER	In house: Referenced to APHA 3125; USEPA SW846 - 6020, ALS QWI-EN/EG020. Samples are 0.45µm filtered prior to analysis. The ICPMS technique utilizes a highly efficient argon plasma to ionize selected elements. Ions are then passed into a high vacuum mass spectrometer, which separates the analytes based on their distinct mass to charge ratios prior to their measurement by a discrete dynode ion detector.	
Dissolved Mercury by FIMS	EG035F	WATER	In house: Referenced to AS 3550, APHA 3112 Hg - B (Flow-injection (SnCl2)(Cold Vapour generation) AAS) Samples are 0.45µm filtered prior to analysis. FIM-AAS is an automated flameless atomic absorption technique. A bromate/bromide reagent is used to oxidise any organic mercury compounds in the filtered sample. The ionic mercury is reduced online to atomic mercury vapour by SnCl2 which is then purged into a heated quartz cell. Quantification is by comparing absorbance against a calibration curve. This method is compliant with NEPM (2013) Schedule B(3)	

Page : 9 of 9 Work Order : EP1804748

Client : PENDRAGON ENVIRONMENTAL SOLUTIONS



Analytical Methods	Method	Matrix	Method Descriptions	
Fluoride by PC Titrator	EK040P	WATER	In house: Referenced to APHA 4500-F C: CDTA is added to the sample to provide a uniform ionic strength background, adjust pH, and break up complexes. Fluoride concentration is determined by either manual or automatic ISE measurement. This method is compliant with NEPM (2013) Schedule B(3)	
Ammonia as N by Discrete analyser	EK055G	WATER	In house: Referenced to APHA 4500-NH3 G Ammonia is determined by direct colorimetry by Discrete Analyser. This method is compliant with NEPM (2013) Schedule B(3)	
Nitrite as N by Discrete Analyser	EK057G	WATER	In house: Referenced to APHA 4500-NO2- B. Nitrite is determined by direct colourimetry by Discrete Analyser. This method is compliant with NEPM (2013) Schedule B(3)	
Nitrate as N by Discrete Analyser	EK058G	WATER	In house: Referenced to APHA 4500-NO3- F. Nitrate is reduced to nitrite by way of a chemical reduction followed by quantification by Discrete Analyser. Nitrite is determined seperately by direct colourimetry and result for Nitrate calculated as the difference between the two results. This method is compliant with NEPM (2013) Schedule B(3)	
Nitrite and Nitrate as N (NOx) by Discrete Analyser	EK059G	WATER	In house: Referenced to APHA 4500-NO3- F. Combined oxidised Nitrogen (NO2+NO3) is determined by Chemical Reduction and direct colourimetry by Discrete Analyser. This method is compliant with NEPM (2013) Schedule B(3)	
Total Kjeldahl Nitrogen as N By Discrete Analyser	EK061G	WATER	In house: Referenced to APHA 4500-Norg D (In house). An aliquot of sample is digested using a high temperature Kjeldahl digestion to convert nitrogenous compounds to ammonia. Ammonia is determined colorimetrically by discrete analyser. This method is compliant with NEPM (2013) Schedule B(3)	
Total Nitrogen as N (TKN + Nox) By Discrete Analyser	EK062G	WATER	In house: Referenced to APHA 4500-Norg / 4500-NO3 This method is compliant with NEPM (2013) Schedule B(3)	
Total Phosphorus as P By Discrete Analyser	EK067G	WATER	In house: Referenced to APHA 4500-P H, Jirka et al (1976), Zhang et al (2006). This procedure involves sulphuric acid digestion of a sample aliquot to break phosphorus down to orthophosphate. The orthophosphate reacts with ammonium molybdate and antimony potassium tartrate to form a complex which is then reduced and its concentration measured at 880nm using discrete analyser. This method is compliant with NEPM (2013) Schedule B(3)	
Reactive Phosphorus as P-By Discrete Analyser	EK071G	WATER	In house: Referenced to APHA 4500-P F Ammonium molybdate and potassium antimonyl tartrate reacts in acid medium with othophosphate to form a heteropoly acid -phosphomolybdic acid - which is reduced to intensely coloured molybdenum blue by ascorbic acid. Quantification is by Discrete Analyser. This method is compliant with NEPM (2013) Schedule B(3)	
Ionic Balance by PCT DA and Turbi SO4 DA	EN055 - PG	WATER	In house: Referenced to APHA 1030F. This method is compliant with NEPM (2013) Schedule B(3)	
Preparation Methods	Method	Matrix	Method Descriptions	
TKN/TP Digestion	EK061/EK067	WATER	In house: Referenced to APHA 4500 Norg - D; APHA 4500 P - H. This method is compliant with NEPM (2013) Schedule B(3)	